INCH POUND

MIL-C-3098/88E
5 May 1993
SUPERSEDING
MIL-C-3098/88D
9 November 1983


MILITARY SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR112/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirement for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-C-3098.

Pertinent characteristics: 5 to 20 MHz; fundamental; noncontrolled; series.



INCHES	mm
.001	.03
.002	.05
.008	.20
.017	.43
.150	3.81
.183	4.65
.192	4.88
.402	10.21
.435	11.05
.50	12.7
.530	13.46

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with MIL-C-3098.

FIGURE 1. Crystal unit - CR112/U.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:46Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Holder: HC-18/U (MIL-H-10056/9) or HC-43/U.

Dimensions, marking, and configuration: See figure 1.

Frequency range: 5 to 20 MHz, inclusive.

Capacitance, shunt: 7 pF, maximum.

Drive Level: 5.0 ±1.0 mW.

Frequency tolerance:

Operating temperature range: ±25 ppm.

Equivalent resistance:

Frequency range, inclusive MHz	Maximum resistance Ohms
5 to 7	50
7+ to 10	30
10+ to 15	25
15+ to 20	20

Mode of oscillation: Fundamental.

Operating temperature range: -55°C to +105°C, inclusive.

Shock: (specified pulse).

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Vibration: Method 201 of MIL-STD-202.

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Thermal shock:

Frequency change permitted. ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Aging:

Frequency change permitted: ±5 ppm.

NOTE: This crystal unit is identical to CR60A/U, except for the tighter frequency tolerance of ±25 ppm.

Revision letters are not used to denote changes due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:46Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR, MI, SM
Navy - SH
Air Force - 99
DLA - ES

Users activities:
Navy - AS, CG, MC, OS
Air Force - 17, 19

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5955-0678-20)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:46Z
Check the source to verify that this is the current version before use.