INCH-POUND
MIL-PRF-3098/90C
w/AMENDMENT1
24 June 2019
SUPERSEDING
MIL-PRF-3098/90C
7 August 2009

PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR114/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-3098.

Pertinent characteristics: 2.9 MHz to 3.85 MHz; fundamental; noncontrolled; series resonance.




FIGURE 1. Crystal unit - CR114/U.

AMSC N/A

FSC 5955

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:46Z
Check the source to verify that this is the current version before use.

Ltr	Inches		mm	
	Min	Max	Min	Max
A	---	.435	---	11.05
B	---	.402	---	10.21
C	---	.530	---	13.46
D	.120	.130	3.05	3.30
E	.184	.200	4.67	5.08
F	---	.150	---	3.81
G	---	.183	---	4.65
H	.038	.042	0.96	1.07

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with MIL-PRF-3098.

FIGURE 1. Crystal unit - CR114/U - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:46Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions, marking, and configuration: See figure 1.

Frequency range: 2.9 MHz to 3.85 MHz, inclusive.

Frequency tolerance:

Operating temperature range: ±0.005 percent.

Mode of oscillation: Fundamental.

Operating temperature range (noncontrolled): -55°C to +105°C, inclusive.

Capacitance, load: 32.0 pF ±.05 pF.

Resonance: Series.

Rated drive level: 1.0 mW, maximum.

Calibration values:

Resistance: 100 ohms.

Crystal current: 3.2 mA.

Capacitance, shunt: 7 pF, maximum.

Equivalent resistance: 300 ohms, maximum.

Shock: MIL-STD-202-213

Frequency change permitted: ±0.0005 percent.

Equivalent-resistance change permitted: ±15 percent.

Vibration: MIL-STD-202-204, test condition A; .10 inch (2.54 mm) double amplitude or 5 gravity units, whichever is less.

Frequency change permitted: ±0.0005 percent.

Equivalent-resistance change permitted: ±15 percent.

Unwanted modes: Minimum unwanted mode effective resistance shall be at least twice that of the main mode, or greater, over the operating temperature range -55°C to +105°C.

Aging:

Frequency change permitted: ±0.0005 percent.

Reference documents. In addition to MIL-PRF-3098, this document references the following:

MIL-STD-202-204
MIL-STD-202-213

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:46Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 84
DLA - CC

Review activities:
Air Force - 19

Preparing activity:
DLA - CC

(Project 5955-2019-002)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:46Z
Check the source to verify that this is the current version before use.