INCH-POUND
MIL-PRF-3098/92G
17 September 2014
SUPERSEDING
MIL-PRF-3098/92F
6 March 2013

PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR116/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-3098.

Pertinent characteristics: 50 MHz to 125 MHz; fifth mechanical overtone; noncontrolled; series resonance.




FIGURE 1. Crystal unit - CR116/U.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:47Z
Check the source to verify that this is the current version before use.

Ltr	Inches		mm	
	Min	Max	Min	Max
A	---	.402	---	10.21
B	---	.183	---	4.65
C	---	.435	---	11.05
D	.184	.200	4.67	5.08
E	---	.530	---	13.46
F	.50	---	12.7	---
G	---	.150	---	3.81
H	.015	.019	0.38	0.48

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with MIL-PRF-3098.

FIGURE 1. Type CR116/U, crystal unit - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:47Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Qualification inspection is not applicable for this specification sheet. Acceptance testing shall consist of screening, Group A and Group B inspection of MIL-PRF-3098.

Dimensions, marking, and configuration: See figure 1.

Frequency range: 50 MHz to 125 MHz, inclusive.

Capacitance, shunt: 4.5 pF, maximum.

Mode of oscillation: Fifth mechanical overtone.

Rated drive level: 1.0 mW, maximum.

Resonance: Series.

Calibration values:

Resistance: 40 ohms.

Resistor voltage drop: 0.28 volt.

Operating temperature range (noncontrolled): -55°C to +105°C, inclusive.

Frequency tolerance: ±25 ppm.

Equivalent resistance: 60 ohms, maximum.

Unwanted modes: The minimum unwanted mode effective resistance shall be at least three times that of the main mode, or 120 ohms, whichever is greater.

Shock:

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Vibration: Method 204, MIL-STD-202, test condition A.

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Thermal shock:

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Aging:

Frequency change permitted: ±5 ppm.

Reference documents. In addition to MIL-PRF-3098, this document references the following:

MIL-STD-202

The margins of this specification sheet are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:47Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Review activities:
Air Force - 99

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5955-2014-003)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:47Z
Check the source to verify that this is the current version before use.