The documentation and process conversion measures necessary to comply with this revision shall be completed by 1 August 2007.

INCH-POUND

MIL-PRF-19500/488D
1 May 2007
SUPERSEDING
MIL-PRF-19500/488C
16 July 1999

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, TRANSISTOR, NPN, SILICON, HIGH-POWER,
TYPES 2N5671 AND 2N5672,
JAN, JANTX, JANTXV, AND JANS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

* The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for NPN, silicon, high-power transistors. Four levels of product assurance are provided for each device type as specified in MIL-PRF-19500.

1.2 Physical dimensions. See figure 1 (similar to TO-3).

* 1.3 Maximum ratings. Unless otherwise specified, T_C = +25°C.

Types	P_T (1) T_A = +25°C	P_T (2) T_C = +25°C	$R_{\theta JC}$	V_{CBO}	V_{CEO}	V_{EBO}	I_C	I_B	T_{STG} and T_J
	W	W	°C/W	V dc	V dc	V dc	A dc	A dc	°C
2N5671	6.0	140	1.25	120	90	7.0	30	10	-65 to +200
2N5672	6.0	140	1.25	150	120	7.0	30	10	

(1) Derate linearly 34.2 mW/°C for T_A > +25°C.
(2) Derate linearly 800 mW/°C for T_C > +25°C.

1.4 Primary electrical characteristics at T_A = +25°C.


Limits	h_{FE1} V_{CE} = 2.0 V dc I_C = 15 A dc	$V_{CE(sat)1}$ I_C = 15 A dc I_B = 1.2 A dc	C_{obo} 100 kHz < f < 1 MHz V_{CB} = 10 V dc I_E = 0	$\|h_{fe}\|$ f = 5 MHz I_C = 2 A dc V_{CE} = 10 V dc	Pulse response t_{on}	Pulse response t_{off}
		V dc	pF		µs	µs
Min	20			10		
Max	100	0.75	900	40	0.5	1.5

* Comments, suggestions, or questions on this document should be addressed to Defense Supply Center, Columbus, ATTN: DSCC-VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dscc.dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://assist.daps.dla.mil/.

AMSC N/A

FSC 5961

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:26Z
Check the source to verify that this is the current version before use.



Symbol	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
CD		.875		22.23	
CH	.250	.450	6.35	11.43	
HT	.050	.135	1.27	3.43	
HR	.495	.525	12.57	13.34	
HR_1	.131	.188	3.33	4.78	
LD	.038	.043	0.97	1.09	7
LL	.312		7.92		
L_1		.050		1.27	
MHD	.151	.161	3.84	4.09	
MHS	1.177	1.197	29.90	30.40	
PS	.420	.440	10.67	11.18	4
PS_1	.205	.225	5.21	5.72	4
s_1	.655	.675	16.64	17.15	

NOTES:
1. Dimensions are in inches.
* 2. Millimeters are given for general information only.
3. Terminal 1, emitter; terminal 2,base; case, collector.
4. These dimensions should be measured at points .050-.055 inch (1.27-1.40 mm) below seating plane. When gauge is not used, measurement will be made at the seating plane.
5. The seating plane of the header shall be flat within .004 inch (0.10 mm) concave to .004 inch (0.10 mm) convex inside a .930 inch (23.62 mm) diameter circle on the center of the header and flat within .006 inch (0.15 mm) concave to .006 inch (0.15 mm) convex overall.
6. Collector shall be electrically connected to the case.
* 7. LD applies between L_1 and LL. Lead diameter shall not exceed twice LD within L_1.
* 8. In accordance with ASME Y14.5M, diameters are equivalent to ϕx symbology.

* FIGURE 1. Physical dimensions (similar to TO-3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:26Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

* 2.1 General. The documents listed in this section are specified in sections 3, 4, or 5 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3, 4, or 5 of this specification, whether or not they are listed.

2.2 Government documents.

* 2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

* DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

* DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 - Test Methods for Semiconductor Devices.

* (Copies of these documents are available online at http://assist.daps.dla.mil/quicksearch/ or http://assist.daps.dla.mil/ or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

* 3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturers list before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

3.4 Interface and physical dimensions. Interface and physical dimensions shall be as specified in MIL-PRF-19500, and on figure 1.

3.4.1 Lead finish. Lead finish shall be solderable in accordance with MIL-STD-750, MIL-PRF-19500, and herein.

3.5 Marking. Marking shall be in accordance with MIL-PRF-19500.

3.6 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in paragraph 1.3, 1.4, and table I herein.

3.7 Electrical test requirements. The electrical test requirements shall be as specified in table I.

3.8 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:26Z
Check the source to verify that this is the current version before use.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

* c. Conformance inspection (see 4.4 and tables I and II).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500 and as specified herein.

* 4.2.1 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not request the performance of table III tests, the tests specified in table III herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

* 4.3 Screening (JANS, JANTX, and JANTXV levels only). Screening shall be in accordance with MIL-PRF-19500, table E-IV, and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen (see table E-IV of MIL-PRF-19500)	Measurement	
	JANS level	JANTX and JANTXV levels
(1) 3c	Thermal impedance (see 4.3.2)	Thermal impedance (see 4.3.2)
9	I_{CEX1} and h_{FE1}	I_{CEX1}
11	I_{CEX1} and h_{FE1}; ΔI_{CEX1} = 100 percent of initial value or 2 mA dc, whichever is greater. Δh_{FE1} = ± 15 percent of initial value.	I_{CEX1} and h_{FE1}; ΔI_{CEX1} = 100 percent of initial value or 3 mA dc, whichever is greater.
12	See 4.3.1	See 4.3.1
13	Subgroups 2 and 3 of table I herein. ΔI_{CEX1} = 100 percent of initial value or 2 mA dc, whichever is greater. Δh_{FE1} = ± 15 percent of initial value.	Subgroup 2 of table I herein. ΔI_{CEX1} = 100 percent of initial value or 3 mA dc, whichever is greater. Δh_{FE1} = ± 25 percent of initial value.

(1) Shall be performed anytime after temperature cycling, screen 3a; and does not need to be repeated in screening requirements.

* 4.3.1 Power burn-in conditions. Power burn-in conditions are T_J = +187.5 ±12.5°C, $V_{CB} \geq$ 30 V dc, T_A = +35°C max. T_J measurement shall be in accordance with method 3100 of MIL-STD-750.

* 4.3.2 Thermal impedance. The thermal impedance measurements shall be performed in accordance with method 3131 of MIL-STD-750 using the guidelines in that method for determining I_M, I_H, t_H, t_{SW}, (and V_H where appropriate). Measurement delay time (t_{MD}) = 70 μs max. See table III, group E, subgroup 4 herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:26Z
Check the source to verify that this is the current version before use.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with table V of MIL-PRF-19500 and table I herein.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VIA (JANS) and table E-VIB (JAN, JANTX, and JANTXV) of MIL-PRF-19500 and 4.4.2.1 and 4.4.2.2 herein. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein. Delta measurements shall be in accordance with table II herein.

* 4.4.2.1 Group B inspection, (JANS) table E-VIA of MIL-PRF-19500.

Subgroup	Method	Conditions
B4	1037	$V_{CB} \geq 30$ V dc, for 2,000 cycles.
B5	1027	$V_{CB} \geq 30$ V dc, T_A = +125°C ±25°C for 96 hours; P_T = 6 W at T_A = +112°C or adjusted as required by the chosen T_A to give an average lot T_J = +275°C. Marking legibility requirement shall not apply.

* 4.4.2.2 Group B inspection, (JAN, JANTX, and JANTXV) table E-VIB of MIL-PRF-19500.

Subgroup	Method	Conditions
B3	1027	For eutectic die attach: $T_A \leq$ +35°C; adjust P_T to achieve T_J = +187.5°C ± 5°C, $V_{CB} \geq 30$ V dc
B3	1037	For solder die attach: $V_{CB} \geq 30$ V dc, 2,000 cycles.
B6	1032	T_A = +200°C.
B7	3053	Load condition C; (unclamped inductive lead, see figure 2); T_C = +25°C; Duty cycle ≤ 10 percent; R_S = 0.1 ohm; Test 1: $t_p \approx 150$ µs; R_{BB1} = 1Ω; V_{BB1} = 10 V dc max; R_{BB2} = 20Ω; V_{BB2} = 4 V dc; I_C = 30 A dc; V_{CC} = 10 V dc, L = 50µH, 0.1Ω Test 2: $t_p \approx 325$ µs; R_{BB1} = 40Ω; V_{BB1} = 10 V dc max; R_{BB2} = 20Ω; V_{BB2} = 4 V dc; I_C = 6.5 A dc; V_{CC} = 10 V dc, L = 500µH, 0.1Ω
B7		Electrical measurements: See table I, subgroup 2 herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:26Z
Check the source to verify that this is the current version before use.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VII of MIL-PRF-19500, and as follows. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein. Delta measurements shall be in accordance with table II herein.

	Subgroup	Method	Conditions
	C2	1056	Test condition B.
	C2	2036	Test condition A, weight = 10 lbs, application time = 15 seconds.
*	C5	3131	See 4.3.2, $R_{\theta JC}$ = 1.25°C/W.
	C6	1026	For eutectic die attach: $T_A \leq +35°C$; adjust P_T to achieve $T_J = +187.5°C \pm 5°C$, $V_{CB} \geq 30$ V dc
	C6	1037	For solder die attach: $V_{CB} \geq 30$ V dc, 6,000 cycles.

* 4.4.4 Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-IX of MIL-PRF-19500 and as specified in table III herein. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein. Delta measurements shall be in accordance with table II herein.

4.5 Methods of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:26Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical inspection	2071					
Subgroup 2						
Thermal impedance 2/	3131	See 4.3.2	$Z_{\theta JC}$			°C/W
Breakdown voltage, collector to emitter	3011	I_C = 200 mA dc; L = 15 mH; 30 Hz ≤ f ≤ 60 Hz, (see figure 3)	$V_{(BR)CEO}$			
2N5671				90		V dc
2N5672				120		V dc
Breakdown voltage, collector to emitter	3011	I_C = 200 mA dc; L = 15 mH; R_{BE} = 50 ohms; 30 Hz ≤ f ≤ 60 Hz (see figure 3)	$V_{(BR)CER}$			
2N5671				110		V dc
2N5672				140		V dc
Breakdown voltage, collector to emitter	3011	I_C = 200 mA dc; L = 2 mH; V_{BE} = -1.5 V dc; 30 Hz ≤ f ≤ 60 Hz (see figure 3)	$V_{(BR)CEX}$			
2N5671				120		V dc
2N5672				150		V dc
Emitter to base cutoff current	3061	Bias condition D; V_{EB} = 7.0 V dc	I_{EBO}		10	mA dc
Collector to emitter cutoff current	3041	Bias condition D; V_{CE} = 80 V dc	I_{CEO}		10	mA dc
Collector to emitter cutoff current	3041	Bias condition A; V_{BE} = 1.5 V dc	I_{CEX1}			
2N5671		V_{CE} = 110 V dc			12	mA dc
2N5672		V_{CE} = 135 V dc			10	mA dc
Collector to base cutoff current	3036	Bias condition D	I_{CBO}		25	mA dc
2N5671		V_{CE} = 120 V dc				
2N5672		V_{CE} = 150 V dc				
Forward-current transfer ratio	3076	V_{CE} = 2.0 V dc; I_C = 15 A dc; pulsed (see 4.5.1)	h_{FE1}	20	100	

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:26Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 2 - Continued						
Forward-current transfer ratio	3076	V_{CE} = 5.0 V dc; I_B = 20 A dc; pulsed (see 4.5.1)	h_{FE2}	20		
Collector to emitter voltage (saturated)	3071	I_C = 15 A dc; I_B = 1.2 A dc; pulsed (see 4.5.1)	V_{CE} (sat)1		0.75	V dc
Base emitter voltage (saturated)	3066	Test condition A; I_B = 1.2 A dc; I_C = 15 A dc; pulsed (see 4.5.1)	V_{BE}(sat)		1.5	V dc
Collector to emitter voltage (saturated)	3071	I_C = 30 A dc; I_B = 6 A dc; pulsed (see 4.5.1)	$V_{CE(sat)2}$		5.0	V dc
Subgroup 3						
High temperature operation:		T_A = +150°C				
Collector to emitter cutoff current	3041	Bias condition A; V_{BE} = -1.5 V dc;	I_{CEX2}			
2N5671		V_{CE} = 100 V dc			15	mA dc
2N5672		V_{CE} = 100 V dc			10	mA dc
Low temperature operation:		T_A = -65°C				
Forward-current transfer ratio	3076	V_{CE} = 2.0 V dc; I_C = 15 A dc; pulsed (see 4.5.1)	h_{FE3}	10		
Subgroup 4			$\lvert h_{fe} \rvert$	10	40	
Magnitude of small-signal short-circuit forward-current transfer ratio	3306	V_{CE} = 10 V dc; I_C = 2.0 A dc; f = 5.0 MHz				
Open circuit output capacitance	3236	V_{CB} = 10 V dc; I_E = 0; 100 kHz ≤ f ≤ 1 MHz	C_{obo}		900	pF

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:26Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 4 - Continued						
Pulse response:	3251	Test condition A; except test circuit and pulse requirements in accordance with figure 4.				
Turn-on time		V_{CC} = 30 V dc ± 2 V dc; I_C = 15 A dc; I_{B1} = 1.2 A dc	t_{on}		0.5	µs
Turn-off time		V_{CC} = 30 V dc ± 2 V dc; I_C = 15 A dc; I_{B1} = 1.2 A dc; I_{B2} = 1.2 A dc	t_{off}		1.5	µs
Subgroup 5						
Safe operating area (continuous dc)	3051	T_C = +25°C; t ≥ 1 s; 1 cycle; (see figure 5)				
Test 1		I_C = 5.8 A dc; V_{CE} = 24 V dc				
Test 2		I_C = 0.9 A dc; V_{CE} = 45 V dc				
Test 3		I_C = 30 A dc; V_{CE} = 4.67 V dc				
Test 4 2N5671 only		I_C = 0.19 A dc; V_{CE} = 90 V dc				
Test 5 2N5672 only		I_C = 0.11 A dc; V_{CE} = 120 V dc				

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:26Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Safe operating area (switching)	3053	Load condition B; (clamped inductive lead) (see figure 6); T_C = +25°C; Duty cycle ≤ 10 percent; t_p > 10 μs; R_S = 0.1 ohm; R_{BB1} = 1Ω; V_{BB1} = 10 V dc max; R_{BB2} = 20Ω; V_{BB2} = 4 V dc; I_C = 30 A dc; V_{CC} = 90 V dc (2N5671) and 120 V dc (2N5672); R_L ≤ 3.0 Ω (2N5671), 4.0 Ω (2N5672); L = 50 μH, 0.1 Ω; CR = 1N1186A; Clamp voltage = 90 V dc +0, -5 (2N5671); 120 V dc +0, -5 (2N5672). Device fails if clamp voltage is not reached.				
Electrical measurements Subgroups 6 and 7 Not applicable		See table I, subgroup 2 herein				

1/ For sampling plan, see MIL-PRF-19500.
2/ This test required for the following end-point measurements only:
Group B, subgroups 3, 4, and 5 (JANS).
Group B, subgroups 2 and 3 (JAN, JANTX, and JANTXV).
Group C, subgroup 2 and 6.
Group E, subgroup 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:26Z
Check the source to verify that this is the current version before use.

* TABLE II. Groups B, C, and E delta measurements. 1/ 2/ 3/ 4/

Step	Inspection	MIL-STD-750		Symbol	Limits		Unit
		Method	Conditions		Min	Max	
1.	Collector to emitter cutoff current 2N5671 2N5672	3041	Bias condition A; V_{BE} = -1.5 V dc; V_{CE} = 110 V dc V_{CE} = 135 V dc	ΔI_{CEX1}		100 percent of initial value or 3 mA dc, whichever is greater.	
2.	Forward-current transfer ratio	3076	V_{CE} = 2 V dc; I_C = 15 A dc; pulsed (see 4.5.1)	Δh_{FE1}		±25 percent change from previously measured value.	

1/ The delta measurements for group B, table E-VIA (JANS) of MIL-PRF-19500 are subgroups 4 and 5, see table II herein, steps 1 and 2.
2/ The delta measurements for group B, table E-VIB (JAN, JANTX, and JANTXV) of MIL-PRF-19500 are subgroups 3 and 6, see table II herein, steps 1 and 2.
3/ The delta measurements for group C, table E-VII of MIL-PRF-19500 are subgroup 6, see table II herein, steps 1 and 2.
4/ The delta measurements for group E, table E-IX of MIL-PRF-19500 are subgroups 1 and 2, see table II herein, steps 1 and 2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:26Z
Check the source to verify that this is the current version before use.

* TABLE III. Group E inspection (all quality levels) – for qualification or re-qualification only.

Inspection	MIL-STD-750		Sample plan
	Method	Conditions	
Subgroup 1			45 devices c = 0
Temperature cycling (air to air)	1051	Test condition C, 500 cycles.	
Hermetic seal Fine leak Gross leak	1071	 Test conditions G or H. Test conditions C or D.	
Electrical measurements		See table I, subgroup 2 and table II herein.	
Subgroup 2			45 devices c = 0
Blocking life	1048	Test temperature = +125°C; V_{CB} = 80 percent of rated; T = 1,000 hours.	
Electrical measurements		See table I, subgroup 2 and table II herein.	
Subgroup 4			Sample size N/A
Thermal impedance curves		See MIL-PRF-19500.	
Subgroup 6			3 devices
ESD	1020	Testing not required for class 3 listing. Testing is required for nonsensitive listing to prove capability.	
Subgroup 8			45 devices c = 0
Reverse stability	1033	Condition B.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:26Z
Check the source to verify that this is the current version before use.






FIGURE 2. Safe operating area for switching between saturation and cutoff (unclamped inductive load).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:26Z
Check the source to verify that this is the current version before use.






NOTE:

$V_{(BR)CEQ}$, $V_{(BR)CER}$, $V_{(BR)CEX}$, is acceptable when the trace falls to the right and above point "A" for type 2N5671. The trace shall fall to the right and above point "B" for type 2N5672.

FIGURE 3. $V_{(BR)CEO}$, $V_{(BR)CER}$, $V_{(BR)CEX}$, measurement circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:26Z
Check the source to verify that this is the current version before use.



NOTES:

1. The rise time (t_r) and fall time (t_f) of the applied pulse shall be each ≤ 20 ns; duty cycle ≤ 2 percent; generator source impedance shall be 50 ohms; pulse width = 20 μs.
2. Output sampling oscilloscope: Z_{in} ≥ 100 kΩ; C_{in} ≤ 50 pF; rise time ≤ 20 ns.

FIGURE 4. Pulse response test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:26Z
Check the source to verify that this is the current version before use.




FIGURE 5. Maximum safe operating area graph (continuous dc).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:26Z
Check the source to verify that this is the current version before use.




FIGURE 6. Safe operating area for switching between saturation and cutoff (clamped inductive load).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:26Z
Check the source to verify that this is the current version before use.

5. PACKAGING

* 5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL-PRF-19500 are applicable to this specification.)

* 6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

* 6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Packaging requirements (see 5.1).

c. Lead finish (see 3.4.1).

d. Product assurance level and type designator.

* 6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML 19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from Defense Supply Center, Columbus, ATTN: DSCC/VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil.

6.4 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - EC
Air Force - 11
NASA - NA
DLA - CC

Preparing activity:
DLA - CC

(Project 5961- 2006-025)

Review activities:
Army - AR, MI, SM
Navy - SH
Air Force - 13, 19, 99

* NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:26Z
Check the source to verify that this is the current version before use.