The documentation and process conversion measures necessary to comply with this revision shall be completed by 21 October 2000.

INCH-POUND

MIL-PRF-19500/545C(USAF)
21 July 2000
SUPERSEDING
MIL-PRF-19500/545B(USAF)
30 July 1999

PERFORMANCE SPECIFICATION

SEMICONDUCTOR DEVICE, TRANSISTOR, PNP, SILICON, POWER
TYPES 2N5151, 2N5153, 2N5151L, 2N5153L, 2N5151U3, AND 2N5153U3
JAN, JANTX, JANTXV, JANS, JANHC, AND JANKC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for PNP, silicon, power transistors for use in high-speed power-switching applications. Four levels of product assurance are provided for each encapsulated device type as specified in MIL-PRF-19500. Two levels of product assurance are provided for each unencapsulated device type.

1.2. Physical dimensions. See figure 1 (similar to T0-205), figures 2, 3, and 4 (JANHC and JANKC), and figure 5 (U3).

1.3. Maximum ratings.

Types	P_T T_A = +25°C	P_T T_C = +25°C	V_{CBO}	V_{CEO}	V_{EBO}	I_C	I_C (4), (5)	Reverse pulse (6) energy	Safe operating area	T_{stg} and T_J
	W	W	V dc	V dc	V dc	A dc	A dc	mj		°C
2N5151, L	1 (1)	11.8 (2)	100	80	5.5	2	10	15	See	-65 to
2N5153, L	1 (1)	11.8 (2)	100	80	5.5	2	10	15	figure 8	+ 200
2N5151U3	1.2 (3)	1.4	100	80	5.5	2	10	15	See	-65 to
2N5153U3	1.2 (3)	1.4	100	80	5.5	2	10	15	figure 8	+ 200

(1) Derate linearly 5.7 mW/°C for T_A > +25°C.
(2) Derate linearly 66.7 mW/°C for T_C > +25°C.
(3) Derate linearly 6.67 mW/°C for T_A > +25°C.
(4) Derate linearly 80 mW/°C for T_C > +25°C.
(5) This value applies for Pw ≤ 8.3 ms, duty cycle ≤ 1 percent.
(6) This rating is based on the capability of the transistors to operate safely in the unclamped inductive load energy test circuit of figure 7.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Defense Supply Center Columbus, ATTN: DSCC-VAC, 3990 East Broad Street, Columbus, OH 43216-5000, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5961

DISTRIBUTION STATEMENT. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

1.4. Primary electrical characteristics at T_C = +25°C.

Limits	h_{FE2} (1) V_{CE} = 5 V I_C = 2.5 A dc		$\|h_{fe}\|$ V_{CE} = 5 V I_C = 500 mA dc f = 10 MHz		$V_{CE(sat)2}$ (1) I_C = 5 A dc I_B = 500 mA dc	$V_{CE(sat)2}$ (1) I_C = 5 A dc I_B = 500 mA dc	C_{obo} V_{CB} = 10 V dc I_E = 0 f = 1 Mhz	$R_{\theta JA}$	$R_{\theta JC}$
	2N5151 (2)	2N5153 (2)	2N5151 (2)	2N5153 (2)					
					V dc	V dc	pF	°C/W	°C/W
Min	30	70	6	7					
Max (TO-205)	90	200			2.2	1.5	250	175	15
Max (U3)	90	200			2.2	1.5	250	150	12.5

(1) Pulsed (see 4.5.1)
(2) The limits specified apply to all package outlines unless otherwise stated.

2. APPLICABLE DOCUMENTS

2.1. General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in section 3 and 4 of this specification, whether or not they are listed.

2.2. Government documents.

2.2.1. Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATION

DEPARTMENT OF DEFENSE

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

STANDARD

DEPARTMENT OF DEFENSE


MIL-STD-750 - Test Methods for Semiconductor Devices.

(Unless otherwise indicated, copies of the above specifications, standards, and handbooks are available from the Defense Automated Printing Service, Building 4D (DPM-DODSSP), 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.3. Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

Symbol 11	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
CD	0.305	0.335	7.75	8.51	6
CH	0.240	0.260	6.10	6.60	
HD	0.335	0.370	8.51	9.40	
LC	0.200 TP		5.08 TP		7
LD	0.016	0.021	0.41	0.53	8, 9
LL	See notes 8, 9, 12, 13				
LU	0.016	0.019	0.041	0.48	8, 9
L_1	---	0.050	---	1.27	8, 9
L_2	0.250	---	6.35	---	8, 9
Q	---	0.050	---	1.27	6
TL	0.029	0.045	0.74	1.14	4, 5
TW	0.028	0.034	0.71	0.86	3
r	---	0.010	---	0.25	11
α	45° TP		45° TP		7
P	0.100		2.54		
Notes	1, 2, 10, 12, 15				




NOTES:

1. Dimension are in inches.
2. Metric equivalents are given for general information only.
3. Beyond r (radius) maximum, TW shall be held for a minimum length of 0.011 (.28 mm).
4. TL measured from maximum HD.
5. Outline in this zone is not controlled.
6. CD shall not vary more than 0.010 (0.25 mm) in zone P. This zone is controlled for automatic handling.
7. Leads at gauge plane 0.054 + 0.001 - 0.000 (1.37 + 0.03 - 0.00 mm) below seating plane shall be within 0.007 (0.18 mm) radius of true position (TP) at maximum material condition (MMC) relative to tab at MMC
8. LU applied between L_1 and L_2. LD applies between L_2 and LL minimum. Diameter is uncontrolled in L_1 and beyond LL minimum.
9. All three leads.
10. The collector shall be electrically and mechanically connected to the case.
11. r (radius) applies to both inside corners of tab.
12. In accordance with ANSI Y14.5M, diameters are equivalent to ∅x symbology.
13. For transistor types 2N5151 and 2N5153, LL is 0.5 (12.70 mm) minimum, and 0.75 (19.05 mm) maximum.
14. For transistor types 2N5151L and 2N5153L, LL is 1.5 (38.10 mm) minimum and 1.75 (44.45 mm) maximum.
15. Lead designation, depending on device type, shall be as follows:

Lead number	TO-205
1	Emitter
2	Base
3	Collector

FIGURE 1. Physical dimensions (T0-205)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.




Ltr	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
A	0.117	0.127	02.97	3.23	

NOTES:
1. Dimensions are in inches.
2. Metric equivalents (millimeters) are in parenthesis.
3. Metric equivalents are given for general information only.
4. Unless otherwise specified, tolerance is ± 0.005 (0.13 mm).
5. The physical characteristics of the die are;
   Thickness: 0.008 (0.20 mm) to .012 (0.30 mm), tolerance is ± 0.005 (0.13 mm).
   Top metal: Aluminum, 40,000 Å minimum, 50
   Back metal: Gold 2,500 Å minimum, 3,000 Å nominal.
   Back side: Collector.
   Bonding pad:
      B = 0.015 (0.38 mm) x 0.0072 (1.83 mm).
      E = 0.015 (0.38 mm) x 0.0060 (1.52 mm).

FIGURE 2. JANHCA and JANKCA die dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.




Ltr	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
A	0.1		2.54		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ± 0.005 (0.13 mm).
4. The physical characteristics of the die are;
   Thickness: 0.0078 (0.198 mm) nominal, tolerance is ± 0.005 (0.13 mm).
   Top metal: Aluminum, 25,000 Å minimum, 33
   Back metal: Gold 1,500 Å minimum, 2,500 Å nominal.
   Back side: Collector.
   Bonding pad: 0.012 (0.305 mm) min. x 0.030 (0.761 mm) min.

FIGURE 3. JANHCB and JANKCB die dimensions.


Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.



1. Chip size..... 0.128 x 0.128 inches ±0.002 inches
2. Chip thickness.....0.010 ± 0.0015 inches nominal
3. Top metal.....Aluminum 30,000 minimum, 33,000Å nominal
4. Back metal.....A. Al/Ti/Ni/Ag15k /2kÅ/7kÅ/7kÅmin.18kÅ/3kÅ/10kÅ/10kÅ nom.
   B. Gold 2,500Å minimum, 3,000Å nominal
5. Backside.....Collector
6. Bonding pad.....B = 0.052 x 0.012 inches, E = 0.084 x 0.012 inches

FIGURE 4. JANHC and JANKC C-version die dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.



Symbol	Dimensions			
	Millimeters		Inches	
	Min	Max	Min	Max
A	2.82	3.10	0.111	0.122
B	7.39	7.65	0.291	0.301
C	10.03	10.29	0.395	0.405
D	7.14	7.39	0.281	0.291
E	5.59	5.84	0.220	0.230
F	2.92	3.18	0.115	0.125
G	2.29	2.54	0.09	0.100
H	3.68	3.94	0.145	0.155
I	1.85 TYP.	-	0.073 TYP.	-
J	2.11 TYP.	-	0.083 TYP.	-
K	0.13 TYP.		0.005 TYP.	-
L	0.38 TYP.	-	0.015 TYP.	-

NOTES:

1. Dimensions are in millimeters.
2. Inch-pond equivalents are given for general information only.

SCHEMATIC




FIGURE 5. Physical dimensions and configuration for SMD.5

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1. General. The requirements for acquiring the product described herein shall consist of this document and MIL-PRF-19500.

3.2. Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturers' (QML) list before contract award (see 4.2 and 6.3).

3.3. Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

3.4. Interface requirements and physical dimensions. The Interface requirements and physical dimensions shall be as specified in MIL-PRF-19500 and figure 1 (TO-205), figures 2, 3, and 4 for JANHC and JANKC, figure 5 for U3 herein.

3.4.1. Current density. Current density of internal conductors shall be as specified in MIL-PRF-19500.

3.4.2. Lead finish. Lead finish shall be solderable as defined in MIL-PRF-19500, MIL-STD-750, and herein. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

3.5. Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4, and table I herein.

3.6. Electrical test requirements. The electrical test requirements shall be the subgroups specified in table I herein.

3.7. Marking. Marking shall be in accordance with MIL-PRF-19500.

3.8. Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4. VERIFICATION

4.1. Classification of Inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4).

4.2. Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500 and herein.

4.2.1. JANHC and JANKC qualification. JANHC and JANKC qualification inspection shall be in accordance with MIL-PRF-19500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

4.3. Screening (JANS, JANTX, and JANTXV levels only). Screening shall be in accordance with table IV of MIL-PRF-19500 and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen (see table IV of MIL-PRF-19500	Measurement	
	JANS levels	JANTX and JANTXV levels
1a 1b	Not Required Required	Not Required Required for JANTXV only
2	Optional	Optional
3a 3b 3c	Required Not applicable Thermal response (see 4.5.3)	Required Not applicable Thermal response (see 4.5.3)
4	Required	Optional
5	Required	Not applicable
6	Required	Not applicable
7a and 7b	Required	Required
8	Required	Not required
9	I_{CES1} and h_{FE2}	Not applicable
10	48 hours minimum	48 hours minimum
11	I_{CES1} and h_{FE2}; ΔI_{CES1} = 100 percent of initial value or100 nA dc, whichever is greater. Δh_{FE2} = ± 20 percent.	I_{CES1} and h_{FE2}
12	See 4.3.2	See 4.3.2
13	Subgroup 2 of table I herein; ΔI_{CES1} = 100 percent of initial value or 100 nA dc, whichever is greater. Δh_{FE2} = ± 20 percent.	Subgroup 2 of table I herein; ΔI_{CES1} = 100 percent of initial value or 100 nA dc, whichever is greater. Δh_{FE2} = ± 20 percent.
14a and 14b	Optional	Optional
15	Required	Not required
16	Required	Not required

4.3.1. Screening (JANHC and JANKC). Screening of JANHC and JANKC die shall be in accordance with MIL-PRF-19500. As a minimum, die shall be 100-percent probed to insure compliance with group A, subgroup 2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

4.3.2. Power burn-in conditions. Power burn-in conditions are as follows: V_{CB} = 10 - 30 Vdc T_A = Room ambient as defined in the general requirements of MIL-STD-750, paragraph 4.5. Power shall be applied to the device to achieve a Junction temperature, T_J=135 °C minimum and a minimum P_D = 75% of P_T maximum rated as defined
in paragraph 1.3.

4.4. Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500.

4.4.1. Group A inspection. Group A inspection shall be conducted in accordance with MIL-PRF-19500 and table I herein. Electrical measurements (end-points) shall be in accordance with the inspections of table I, subgroup 2 herein.

4.4.2. Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in table VIa of MIL-PRF-19500 (JANS) and 4.4.2.1 herein. Electrical measurements (end-points) shall be in accordance with group A, subgroup 2 herein. Delta measurements shall be in accordance with table II herein. See 4.4.2.2 herein and table VIb of MIL-PRF-19500 for JAN, JANTX, and JANTXV group B testing. Electrical measurements (end-points) requirements shall be in accordance with group A, subgroup 2 herein. Delta measurements shall be in accordance with table II herein.

4.4.2.1. Group B inspection table VIa (JANS) of MIL-PRF-19500.

Subgroup	Method	Conditions
B4	1037	V_{CB} = 40 V dc ± 1 V.
B5	1027	V_{CB} = 10 V dc; T_A = +125°C ±25°C for 96 hours with P_T adjusted according to the chosen T_A to give T_J = +275°C minimum. Optionally the test may be performed for a minimum of 216 hours with P_T adjusted to achieve a T_J = +225°C minimum;
sample		size = 45, c = 0. In this case the ambient temperature shall be adjusted such that a minimum 75% of maximum rated P_T (see1.3) is applied to the device under test. (Note: If a failure occurs, resubmission shall be at the test conditions of the original sample.)
B5	2037	Test condition A (Al - Au die interconnects only).
B6	3131	Forward voltage drop, emitter to base diode only (see 4.5.2).

4.4.2.2. Group B inspection, table VIb (JAN, JANTX and, JANTXV) of MIL-PRF-19500.

Subgroup	Method	Conditions
B3	1027	For eutectic die attach: V_{CB} = 10 percent of V_{CBO} (min) (see 1.3); $T_A \leq$ +35° C (max); adjust P_T to achieve T_J = +150°C (min).
B3	1037	For solder die attach: V_{CB} = 10 percent of V_{CBO} (min) (see 1.3) 2,000 cycles.
B5	3131	See 4.5.2

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

4.4.3. Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table VII of MIL-PRF-19500 and as follows. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein. Delta measurements shall be in accordance with table II herein. Delta measurements shall be in accordance with table II herein.

Subgroup	Method	Conditions
C2	2036	Test condition E.
C6	1026	1,000 hours, $V_{CB} \geq 10$ V dc, $T_J = +150°C$ minimum; $T_A \leq +35°C$.

4.4.4. Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup testing in table IX of MIL-PRF-19500. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein. Delta measurements shall be in accordance with table II herein.

Subgroup	Method	Condition	Sampling plan
E1	1051	500 cycles	45 devices, c = 0
E2	1039	Condition A: 500 hours	45 devices, c = 0
E3		Not applicable	
E4	3131	$R_{\theta JC}$ = 15°C/W maximum (TO-205) $R_{\theta JC}$ = 12.5°C/W maximum (U3) (See 4.5.2)	22 devices, c = 0 (See 4.5.2) 22 devices, c = 0 (See 4.5.2)
E5		Not applicable	

4.5. Methods of examination and test. Methods of examination and test shall be as specified in the appropriate tables and as follows.

4.5.1. Pulse measurements. Conditions for pulse measurements shall be as specified in section 4 of MIL-STD-750.

4.5.2. Thermal resistance. Thermal resistance measurements shall be conducted in accordance with method 3131 of MIL-STD-750. The following details shall apply:

a. Collector current magnitude during power application shall be 500 mA dc.

b. Collector to emitter voltage magnitude shall be 10 V dc.

c. Reference temperature measuring point shall be the case.

d. Reference temperature measuring point shall be within the range $+25°C \leq T_R \leq +35°C$. The chosen reference temperature shall be recorded before the test is started.

e. Mounting arrangement shall be with heat sink to case.

f. Maximum limit of $R_{\theta JC}$ shall be 15.0°C/W for (TO-205) and 12.5°C/W for (U3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

4.5.3. Thermal response (ΔV_{BE} measurements). The ΔV_{BE} measurements shall be performed in accordance with MIL-STD-750, method 3131. The ΔV_{BE} conditions (I_H and V_H) and maximum limit shall be derived by each vendor. The chosen ΔV_{BE} measurement and conditions for each device in the qualification lot shall be submitted in the qualification report and a thermal response curve shall be plotted. The chosen ΔV_{BE} shall be considered final after the manufacturer has had the opportunity to test five consecutive lots. One-hundred percent safe operating area (SOA) testing may be performed in lieu of thermal response testing herein provided that the appropriate conditions of temperature, time, current, and voltage to achieve die attach integrity are approved by the qualifying activity. The following parameter measurements shall apply:

a. I_M measurement ..... 10 mA.
b. V_{CE} measurement voltage ..... 16 V (same as V_H).
c. I_H collector heating current ..... 1 A minimum.
d. V_H collector-emitter heating voltage ..... 16 V minimum.
e. t_H heating time ..... 10 ms.
f. t_{MD} measurement delay time ..... 50 µs.
g. t_{SW} sample window time ..... 10 µs maximum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical inspection	2071					
Subgroup 2						
Breakdown voltage, collector to emitter	3011	Bias condition D, I_C = 100 mA dc; I_B = 0, pulsed (see 4.5.1)	$V_{(BR)CEO}$	80		V dc
Collector to emitter cutoff current	3041	Bias condition C, V_{CE} = 60 V dc; V_{BE} = 0	I_{CES1}		1.0	µA dc
Collector to emitter cutoff current	3041	Bias condition C, V_{CE} = 100 V dc; V_{BE} = 0	I_{CES2}		1.0	mA dc
Collector to emitter cutoff current	3041	Bias condition D, V_{CE} = 40 V dc; I_B = 0	I_{CEO}		50	µA dc
Emitter to base cutoff current	3061	Bias condition D, V_{EB} = 4 V dc; I_C = 0	I_{EBO1}		1.0	µA dc
Emitter to base cutoff current	3061	Bias condition D, V_{EB} = 5.5 V dc; I_C = 0	I_{EBO2}		1.0	mA dc
Forward current transfer ratio	3076	V_{CE} = 5 V dc; I_C = 50 mA dc pulsed (see 4.5.1)	h_{FE1}			
2N5151 2/				20		
2N5153				50		
Forward current transfer ratio	3076	V_{CE} = 5 V dc; I_C = 2.5 A dc pulsed (see 4.5.1)	h_{FE2}			
2N5151 2/				30	90	
2N5153				70	200	
Forward current transfer ratio	3076	V_{CE} = 5 V dc; I_C = 5 A dc pulsed (see 4.5.1)	h_{FE3}			
2N5151 2/				20		
2N5153				40		
Base-emitter voltage (non-saturated)	3066	Test condition B, V_{CE} = 5 V dc; I_C = 2.5 A dc, pulsed (see 4.5.1)	V_{BE}		1.45	V dc|
Base-emitter saturation voltage	3066	Test condition A, I_C = 2.5 A dc; I_B = 250 mA dc, pulsed (see 4.5.1)	$V_{BE(sat)1}$		1.45	V dc
Base-emitter saturation voltage	3066	Test condition A, I_C = 5 A dc; I_B = 500 mA dc; pulsed (see 4.5.1)	$V_{BE(sat)2}$		2.2	V dc

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 2 - Continued						
Collector-emitter saturation voltage	3071	I_C = 2.5 A dc; I_B = 250 mA dc, pulsed (see 4.5.1)	$V_{CE(sat)1}$		0.75	V dc
Collector-emitter saturation voltage	3071	I_C = 5 A dc; I_B = 500 mA dc, pulsed (see 4.5.1)	$V_{CE(sat)2}$		1.5	V dc
Subgroup 3						
High temperature operation:		T_C = +150°C				
Collector to emitter cutoff current	3041	Bias condition A, V_{CE} = 60 V dc; V_{BE} = +2 V dc	I_{CEX}		500	µA dc
Low temperature operation		T_C = -55°C				
Forward - current transfer ratio	3076	V_{CE} = 5 V dc; I_C = 2.5 A dc; pulsed (see 4.5.1)	h_{FE4}			
2N5151 2/ 2N5153				15 25		
Subgroup 4						
Common-emitter, small- signal, short-circuit, forward-current transfer ratio	3206	V_{CE} = 5 V dc; I_C = 100 mA dc; f = 1 KHz	h_{fe}			
2N5151 2/ 2N5153				20 50		
Magnitude of common- emitter, small-signal short-circuit, forward-current, transfer ratio	3306	V_{CE} = 5 V dc; I_C = 500 mA dc, f = 10 MHz	$\|h_{fe}\|$			
2N5151 2/ 2N5153				6 7		
Open-circuit output capacitance	3236	V_{CB} = 10 V dc; I_E = 0, f = 1 MHz	C_{obo}		250	pf
Switching time		I_C = 5 A dc; I_{B1} = 500 mA dc	t_{on}		0.5	µs
		I_{B2} = -500 mA dc	t_s		1.4	µs
		$V_{BE(off)}$ = 3.7 V dc	t_f		0.5	µs
		R_L = 6 Ω, (see figure 4)	t_{off}		1.5	µs

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

TABLE I, Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 5						
Safe operating area (D.C.)	3051	Pre-pulse condition for each test: V_{CE} = 0; I_C = 0; T_C = +25°C Pulse condition for each test: t_p = 1 sec. 1 cycle. T_C = +25°C, (see figure 6)				
Test # 1		V_{CE} = 5.8 V dc; I_C = 2 A dc				
Test # 2		V_{CE} = 32 V dc; I_C = 340 mA dc				
Test # 3		V_{CE} = 80 V dc; I_C = 20 mA dc				
Safe operating area (unclamped inductive)		T_C = +25°C; R_{BB1} = 10 Ω; R_{BB2} = 100 Ω; L = 0.3 mH; RL = 0.1 Ω; V_{CC} = 10 V dc; V_{BB1} = 10 V dc; V_{BB2} = 4 V dc; I_{CM} = 10 A dc (see figure 5)				
End point electrical measurements		See table I, Subgroup 2				
Subgroups 6 and 7						
Not applicable						

1/ For sampling plan, see MIL-PRF-19500
2/ The units specified apply to all package outlines unless otherwise stated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

TABLE II. Groups B, C and E delta electrical measurements. 3/ 4/ 5/ 6/

Steps	Inspection 1/, 2/	MIL-STD-750		Symbol	Limits		Unit
		Method	Conditions		Min	Max	
1.	Forward - current transfer ratio	3076	I_C = 2.5 V dc; V_{CE} = 5 V dc, Pulsed (see 4.5.1)	Δh_{FE2}	± 20 percent change from initial reading.		
2.	Thermal response 7/	3131	See 4.5.3	ΔV_{BE}			

1/ See MIL-PRF-19500 for sampling plan.

2/ Devices which exceed the group A limits for this test shall not be acceptable.

3/ The delta measurements for table VIa (JANS) of MIL-PRF-19500 are as follows:

a. Subgroup 3, see table II herein, step 2.

b. Subgroups 4 and 5, see table II herein, step 2.

4/ The delta measurements for table VIb (JANTX and JANTXV) of MIL-PRF-19500 are as follows:

a. Subgroup 2, see table II herein, step 1.

b. Subgroups 3 and 6, see table II herein, step 1.

5/ The delta measurements for table VII of MIL-PRF-19500 are as follows:

a. Subgroup 6, see table II herein, step 1.


6/ The delta measurements for table IX of MIL-PRF-19500 are as follows:

a. Subgroup 1, see table II herein, step 1.

b. Subgroup 2, see table II herein, step 1.

7/ Safe operating area (SOA) testing may be performed in lieu of thermal response testing herein provided that appropriate conditions of temperature, time, current, and voltage to achieve die attach integrity are submitted to the qualifying activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.



NOTES:

1. V_{gen} is -30 pulse (from 0 V) into a 50 ohm termination.
2. The V_{gen} waveform is supplied by a generator with the following characteristics: $t_r \leq 15$ ns, $t_f = 15$ ns, $Z_{OUT} = 50$ ohm, duty cycle ≤ 2 percent.
3. Waveforms are monitored on an oscilloscope with the following characteristics: $t_r \leq 15$ ns, $R_{IN} \geq 10$ MΩ, $C_{IN} \leq 11.5$ pF.
4. Resistors shall be noninductive types.
5. The dc power supplies may require additional bypassing in order to minimize ringing.
6. An equivalent circuit may be used.

FIGURE 6. Switching time test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

R_{BB1} = 10 Ω
R_{BB2} = 100 Ω
L = 0.3 mH
R_L = 0.1 Ω
V_{CC} = 10 V dc
I_C = 10 nA
V_{BB1} = 10 V dc
V_{BB2} = 4 V dc




FIGURE 7. Unclamped inductive load energy test circuit.




FIGURE 8. Maximum safe operating area.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1. Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of material is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Points' packaging activity within the Military Department or Defense Agency, or within the Military Departments' System Command. Packaging data retrieval is available from the managing Military Departments' or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1. Intended use. The notes specified in MIL-PRF-19500 are applicable to this specification.

6.2. Acquisition requirements. Acquisition documents must specify the following:

a. Issue of DODISS to be cited in the solicitation (see 2.2.1).

b. The lead finish as specified (see 3.4.2).

c. Type designation and quality assurance level.

-

c. Packaging requirements (see 5.1).

e. For die acquisition, the JANHC or JANKC letter version shall be specified (see figures 2, 3, and 4).

6.3. Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturer's QML-19500 whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or purchase orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from Defense Supply Center Columbus, DSCC-VQE, Columbus, OH 43216.

6.4. Suppliers of JANHC and JANKC die. The qualified JANHC and JANKC suppliers with the applicable letter version (example JANHCA2N5151) will be identified on the QML.

JANHC and JANKC ordering information			
PIN	Manufacturer		
	33178	34156	43611
2N5151 2N5153	JANHCA2N5151 JANHCA2N5153	JANHCB2N5151 JANHCB2N5153	JANHCC2N5151 JANHCC2N5153
2N5151 2N5153	JANKCA2N5151 JANKCA2N5153	JANKCB2N5151 JANKCB2N5153	JANHCC2N5151 JANHCC2N5153

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Air Force - 11
NASA - NA
DLA - CC

Preparing activity:
DLA - CC

(Project 5961-2263)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-PRF-19500/545C	2. DOCUMENT DATE (YYMMDD) 000721

3. DOCUMENT TITLE
SEMICONDUCTOR DEVICE, TRANSISTOR, PNP, SILICON, POWER, TYPES 2N5151, 2N5153, 2N5151L, 2N5153L, 2N5151U3, 2N5153U3 JAN, JANTX, JANTXV, JANS, JANHC, AND JANKC.

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) Commercial DSN FAX EMAIL	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. Point of contact: Alan Barone,	b. TELEPHONE Commercial 614-692-0510	DSN 850-0510	FAX 614-692-6939	EMAIL alan_barone@dscc.dla.mil
c. ADDRESS : Defense Supply Center Columbus, ATTN: DSCC-VAC, 3990 East Broad Street, Columbus, OH 43216-5000	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** Defense Standardization Program Office (DLSC-LM) 8725 John J. Kingman, Suite 2533, Fort Belvoir, VA 22060-6221 Telephone (703) 767-6888 DSN 427-68880			

DD Form 1426, Feb 1999 (EG) Previous editions are obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.