The documentation and process conversion measures necessary to comply with this revision shall be completed by 3 February 2006.

INCH-POUND
MIL-PRF-19500/586G
3 November 2005
SUPERSEDING
MIL-PRF-19500/586F
17 October 2003

* PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, DIODE, SILICON, SCHOTTKY BARRIER, HERMETIC,
TYPES 1N5819-1, 1N5819UR-1, 1N6761-1, AND 1N6761UR-1,
JAN, JANTX, JANTXV, JANS, JANHC, AND JANKC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

* The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for silicon, Schottky barrier diodes. Four levels of product assurance are provided for each encapsulated device types as specified in MIL-PRF-19500, and two levels of product assurance are provided for unencapsulated devices.

1.2 Physical dimensions. See figure 1 (DO-41), figure 2 (DO-213AB), and figure 3 (JANC die) dimensions.

* 1.3 Maximum ratings. T_A = +25°C (unless otherwise specified).

Types	V_{RWM} (1)	$I_{O(PCB)}$ (2) T_A = 55°C	I_{FSM}	T_{STG}	T_J (3)	Max $R_{\Theta JL}$ (2)	Max $R_{\Theta JEC}$ (2)	Max $R_{\Theta JA}$
	V (pk)	A dc	A dc	°C	°C	°C/W	°C/W	°C/W
1N5819-1	45	1.0	25	-65 to +150	-65 to +125	70		220
1N5819UR-1	45	1.0	25				40	220
1N6761-1	100	1.0	25		-65 to +150	70		220
1N6761UR-1	100	1.0	25				40	220

(1) See figures 4, 5, 6, and 7 for derating curves and for effects of V_R on T_J. T_A = +75°C for both axial and MELF (UR) on printed circuit board (PCB), PCB = FR4 - .0625 inch (1.59 mm) 1-layer 1-Oz Cu, horizontal, in still air, pads for (UR) = .061 inch (1.55 mm) x .105 inch (2.67 mm); pads for axial = .092 inch (2.34 mm) diameter, strip = .030 inch (0.76 mm) x 1 inch (25.4 mm) long, lead length L ≤ .187 inch (≤ 4.75 mm); $R_{\Theta JA}$ with a defined PCB thermal resistance condition included, is measured at I_O = 1A.
(2) For thermal impedance see figures 8 and 9.
(3) The maximum T_J depends on the voltage applied.

* Comments, suggestions, or questions on this document should be addressed to Defense Supply Center, Columbus, ATTN: DSCC-VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dscc.dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://assist.daps.dla.mil.

AMSC N/A FSC 5961

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:44Z
Check the source to verify that this is the current version before use.

* 1.4 Primary electrical characteristics. Unless otherwise specified, primary electrical characteristics at T_A = +25°C.

Types	Max V_{F1} I_F = 0.1 A	Max V_{F2} I_F = 1.0 A	Max V_{F3} I_F = 3.1 A	Max I_{RM} @ V_{RWM} pulsed method (see 4.5.1)		Max C_T V_R = 5 V dc
				T_J = +25°C I_{RM1}	T_J = +100°C I_{RM2}	
	V (pk)	V (pk)	V (pk)	µA	mA	pF
1N5819-1	0.34	0.49	0.80	50	5.0	70
1N5819UR-1	0.34	0.49	0.80	50	5.0	70
1N6761-1	0.38	0.69	NA	100	12.0	70
1N6761UR-1	0.38	0.69	NA	100	12.0	70

2. APPLICABLE DOCUMENTS

* 2.1 General. The documents listed in this section are specified in sections 3, 4, or 5 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3, 4, or 5 of this specification, whether or not they are listed.

2.2 Government documents.

* 2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

* DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

* DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 - Test Methods for Semiconductor Devices.

* (Copies of these documents are available online at http://assist.daps.dla.mil/quicksearch/ or http://assist.daps.dla.mil or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.


3. REQUIREMENTS

* 3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

* 3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturers list before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:44Z
Check the source to verify that this is the current version before use.




Symbol	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
BD	.080	.107	2.03	2.72	3
BL	.160	.205	4.06	5.21	3
LD	.028	.034	0.71	0.86	
LL	1.000		25.40		
LL_1		.050		1.27	4

NOTES:
1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. Package contour optional within cylinder of diameter BD and length BL. Slugs, if any, shall not be included within this cylinder, but shall not be subject to the minimum limit of BD.
4. Lead diameter not controlled in this zone to allow for flash, lead finish build-up, and minor irregularities other than slugs.
5. In accordance with ASME Y14.5M, diameters are equivalent to Φx symbology.

Types 1N5819-1 and 1N6761-1

* FIGURE 1. Physical dimensions (DO-41).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:44Z
Check the source to verify that this is the current version before use.




Symbol	Dimensions			
	Inches		Millimeters	
	Min	Max	Min	Max
BD	.094	.105	2.39	2.67
BL	.189	.205	4.80	5.21
ECT	.016	.022	0.41	0.56
S	.001		0.03	

NOTES:
1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. In accordance with ASME Y14.5M, diameters are equivalent to Φx symbology.

Types 1N5819UR-1, and 1N6761UR-1

* FIGURE 2. Physical dimensions (DO-213AB).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:44Z
Check the source to verify that this is the current version before use.



BACKSIDE IS CATHODE

Symbol	Dimensions			
	Inches		Millimeters	
	Min	Max	Min	Max
A	.035	.039	0.89	0.99
B	.031	.033	0.79	0.84

Design data

Metallization:
Top: (Anode) .....AL
Back: (Cathode).....Au

AL thickness .....25,000 Å min
Gold thickness.....4,000 Å min
Chip thickness .....10 Mils ± 2 Mils

FIGURE 3. JANC (A-version) die dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:44Z
Check the source to verify that this is the current version before use.

* 3.4 Interface and physical dimensions. Interface and physical dimensions shall be as specified in MIL-PRF-19500, and on figures 1, 2, and 3.

3.4.1 Lead material and finish. Lead material shall be copper clad steel with a minimum of 50 percent copper by weight. Lead finish shall be solderable in accordance with MIL-PRF-19500, MIL-STD-750, and herein. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

* 3.4.2 Diode construction. All devices shall be metallurgically bonded, double plug construction in accordance with the requirements of MIL-PRF-19500. All glass diodes shall be designed with sufficient thermal compensation in the axial direction to optimize tensile and compressive stresses. Dimensional analysis is required of all materials used to achieve axial thermal compensation. Dimensional tolerances and corresponding coefficient of thermal expansion (CTE) shall be documented on the DSCC Design and Construction Form 36D and shall be approved by the qualifying activity to maintain qualification. Dimensional tolerances shall be sufficiently tight enough to prevent excessive stresses due to the inherent CTE mismatch. The UR version shall be structurally identical to the non-UR versions except for end-cap lead attachment.

* 3.5 Marking. Marking shall be in accordance with MIL-PRF-19500. Manufacturer's identification and date code shall be marked on the devices. Initial container package marking shall be in accordance with MIL-PRF-19500. The polarity shall be indicated with a contrasting color band to denote the cathode end. The prefixes JAN, JANTX, JANTXV, and JANS may be abbreviated as J, JX, JV, and JS respectively. Manufacturer's identification and date code shall be marked on the devices. The part number may be reduced to J5819, JX5819, JV5819, or JS5819. Color coding shall not be permitted for part numbering.

* 3.5.1 UR devices. For 'UR' version devices only, all marking, except polarity may be omitted from the body, but shall be retained on the initial container. Polarity marking of 'UR' devices shall consist as a minimum, a band or 3 contrasting dots around the periphery of the cathode.

3.6 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4, and table I.

3.7 Electrical test requirements. The electrical test requirements shall be as specified in table I herein.

3.8 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4. VERIFICATION

* 4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4 and tables I and II).

* 4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500 and as specified herein.

* 4.2.1 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not require the performance of table II tests, the tests specified in table II herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:44Z
Check the source to verify that this is the current version before use.

* 4.2.1.1 Group E thermal impedance. Each supplier shall submit a thermal impedance ($Z_{\Theta JX}$) histogram of the entire qualification lot. The histogram data shall be taken prior to the removal of devices that are atypical for thermal impedance. Thermal impedance curves (from $Z_{\Theta JX}$ test pulse time to $R_{\Theta JX}$ minimum steady-state time) of the best device in the qual lot and the worst device in the qual lot (that meets the supplier proposed screening limit), or from the thermal grouping, shall be submitted. The optimal test conditions and proposed initial thermal impedance screening limit shall be provided in the qualification report. Data indicating how the optimal test conditions were derived for $Z_{\Theta JX}$ shall also be submitted. The proposed specification maximum thermal impedance curve shall be submitted. The qualifying activity may approve a different $Z_{\Theta JX}$ limit not to exceed the specification's thermal curve for conformance inspection end-point measurements as applicable. Equivalent data, procedures, or statistical process control plans may be used for part, or all, of the above requirements. The approved thermal impedance conditions and limit for $Z_{\Theta JX}$ shall be used by the supplier in screening and table I, subgroup 2. The approved thermal resistance conditions for $R_{\Theta JX}$ shall be used by the supplier for conformance inspection. For product families with similar thermal characteristics based on the same physical and thermal die, package, and construction combination (thermal grouping), the supplier may use the same thermal impedance curves.

4.2.2 JANHC and JANKC devices. Qualification for devices shall be in accordance with MIL-PRF-19500. This testing may be performed on a TO-5 package in lieu of the DO-41 axial leaded package.

* 4.3 Screening (JAN, JANTX, JANTXV, and JANS levels only). Screening shall be in accordance with table IV of MIL-PRF-19500, and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen (see table IV of MIL-PRF-19500)	Measurement	
	JANS level	JANTXV and JANTX level
1a 1b	Required Required	Not required Required (JANTXV only)
2	Not required	Not required
3a 3b (1) 3c	Required Not applicable Required (see 4.3.3)	Required Not applicable Required (see 4.3.3)
4, 5, 6, and 7a	Not applicable	Not applicable
7b	Optional	Optional
8	Required	
9	I_{R1} and V_{F2}	Not applicable
(2) 10	T_A = +100°C; V_{RWM} = 100 V(pk), 1N6761; T_A = +110°C; V_{RWM} =45 V(pk), 1N5819, I_O = 0, half sine wave, f = 60 Hz	T_A = +100°C; V_{RWM} = 100 V(pk), 1N6761; T_A = +110°C; V_{RWM} =45 V(pk), 1N5819, I_O = 0, half sine wave, f = 60 Hz
11	$\Delta I_{R1} \leq$ 100 percent of initial reading or .02 mA, whichever is greater. $\Delta V_{F2} \leq \pm$ 50 mV dc.	I_{R1} and V_{F2}
12	See 4.3.2	See 4.3.2
13	Subgroup 2 of table I herein; $\Delta I_{R1} \leq$ 100 percent of initial reading or .02 mA, whichever is greater; $\Delta V_{F2} \leq \pm$ 50 mV dc.	Subgroup 2 of table I herein; $\Delta I_{R1} \leq$ 100 percent of initial reading or .02 mA, whichever is greater; $\Delta V_{F2} \leq \pm$ 50 mV dc.
14a (3) 14b	Not applicable Required	Not applicable Required
15	Required	Not Required
16	Required	Not Required

See notes on next page

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:44Z
Check the source to verify that this is the current version before use.

(1) Thermal impedance shall be performed any time after sealing provided temperature cycling is performed in accordance with table IV of MIL-PRF-19500, screen 3 prior to this thermal test.
(2) Junction temperature (T_J) is not to exceed 115°C at V_{RWM}. T_J is affected by the device mounting thermal resistance when parasitic power is generated by the temperature dependent leakage current. Until this leakage becomes significant near thermal runaway, T_J remains approximately equal to T_A or T_J for I_O = 0.
(3) For clear glass diodes, the gross leak test may be performed any time after temperature cycling.

4.3.1 Screening (JANHC or JANKC). Screening of die shall be in accordance with "Discrete Semiconductor Die/Chip Lot Acceptance" appendix G of MIL-PRF-19500 and die shall be 100-percent probed in accordance with table I, subgroup 2.

* 4.3.1.1 JAN testing. JAN level product will have temperature cycling and thermal impedance testing performed in accordance with MIL-PRF-19500, JANTX level screening level requirements.

* 4.3.2 Burn-in conditions. Burn-in conditions are as follows: I_F = 1.0 A dc (min), adjust I_F or T_A to achieve T_J = 100°C min. Mounting and test conditions shall be in accordance with method 1038 of MIL-STD-750, test condition B.

* 4.3.3 Thermal impedance. The thermal impedance measurements shall be performed in accordance with method 3101 or 4081 of MIL-STD-750 using the guidelines in that method for determining I_M, I_H, t_H, t_{SW}. Measurement delay time (t_{MD}) = 70 μs max. See group E, subgroup 4 herein.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with table V of MIL-PRF-19500, and table I herein.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in table VIa (JANS), and table VIb (JAN, JANTX, and JANTXV) of MIL-PRF-19500. Electrical measurements (end-points) shall be in accordance with the applicable inspections of table I, subgroup 2 herein.

* 4.4.2.1 Group B inspection, table VIa (JANS) of MIL-PRF-19500.

Subgroup	Method	Condition
B3	1056	0°C to 100°C, 25 cycles, n = 22, c = 0.
B3	1051	-55°C to 150°C, 100 cycles, n = 22, c = 0.
B3	4066	I_{FSM} = 25 A(pk), condition A, I_O = 1.0 A; T_A = room ambient as defined in the general requirements of MIL-STD-750; 5 surges of 8.3 ms each at 1 minute intervals.
* B3	2101	Decap analysis; scribe and break only.
B4	1037	I_F = 1.0 A; T_A = room ambient as defined in the general requirements of MIL-STD-750; t_{on} = t_{off} = 3 minutes minimum for 2,000 cycles.
B5	1027	I_F = 1 A dc (minimum), adjust I_F or T_A to achieve T_J = 125°C (minimum).
B6	4081	See 4.3.3; $R_{\Theta JL}$ and $R_{\Theta JEC}$ only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:44Z
Check the source to verify that this is the current version before use.

4.4.2.2 Group B inspection, table VIb (JAN, JANTX, and JANTXV of MIL-PRF-19500).

Subgroup	Method	Condition
B2	1056	0°C to 100°C, 10 cycles, n = 22, c = 0.
B2	1051	-55°C to 150°C, 25 cycles, n = 22, c = 0.
B2	4066	I_{FSM} = 25 A(pk), condition A, I_O = 1.0 A; T_A = room ambient as defined in the general requirements of MIL-STD-750 (see 4.5); 5 surges of 8.3 ms each at 1 minute intervals.
B3	1027	I_F = 1 A dc (minimum), adjust I_F or T_A to achieve T_J = 125°C minimum,
B4	2101	Decap analysis; scribe and break only.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table VII of MIL-PRF-19500. Electrical measurements (end-points) shall be in accordance with the applicable inspections of table I, subgroup 2 herein.

* 4.4.3.1 Group C inspection, table VII of MIL-PRF-19500.

Subgroup	Method	Condition
C2	1056	0°C to + 100°C, 10 cycles.
C2	1051	-55°C to + 150°C, 25 cycles.
C2	2036	Tension: Test condition A; weight = 10 pounds; t = 15 s. Lead fatigue: Test condition E; weight 1 pounds. NOTE: Neither tension nor lead fatigue are applicable for UR devices.
* C5	4081	See 4.3.3; $R_{\Theta JL}$ and $R_{\Theta JEC}$ only.
C6	1027	I_F = 1 A dc (minimum), adjust I_F or T_A to achieve T_J = +125°C minimum.

4.4.4 Group E inspection. Group E inspection shall be conducted in accordance with table IX of MIL-PRF-19500 and the conditions for subgroup testing in table II herein. Electrical measurements (end-points) shall be in accordance with the applicable inspections of table I, subgroup 2 herein.

4.5 Methods of inspection. Methods of inspection shall be as specified in the appropriate tables as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

* 4.5.2 Free air power burn-in and life tests. The use of a current limiting or ballast resistor is permitted provided that each device under test still sees the full P_t (minimum) and that the minimum applied voltage, where applicable, is maintained through-out the burn-in period. Method 3100 of MIL-STD-750 shall be used to measure T_J.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:44Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical examination	2071					
Subgroup 2						
Thermal impedance	3101	See 4.3.3	$Z_{\Theta JX}$			°C/W
Forward voltage	4011	I_F = .1 A (pk) pulsed (see 4.5.1)	V_{F1}			
1N5819-1, 1N5819UR-1					0.34	V dc
1N6761-1, 1N6761UR-1					0.38	V dc
Forward voltage	4011	I_F = 1.0 A (pk) pulsed (see 4.5.1)	V_{F2}			
1N5819-1, 1N5819UR-1					0.49	V dc
1N6761-1, 1N6761UR-1					0.69	V dc
Forward voltage 1N5819-1, 1N5819UR-1	4011	I_{FM} = 3.1 A (pk) pulsed (see 4.5.1)	V_{F3}		0.80	V dc
Reverse current leakage	4016	Pulse method	I_{R1}			
1N5819-1, 1N5819UR-1		V_{RM} = 45 V (pk)			50	µA
1N6761-1, 1N6761UR-1		V_{RM} = 100 V (pk)			100	µA
Subgroup 3						
High temperature operation:		T_A = +100°C				
Reverse current leakage	4016	Pulse method (see 4.5.1)				
1N5819-1, 1N5819UR-1		V_{RM} = 45 V (pk)	I_{R2}		5.0	mA
		V_{RM} = 40 V (pk)	I_{R3}		4.5	mA
		V_{RM} = 35 V (pk)	I_{R4}		4.0	mA
		V_{RM} = 24 V (pk)	I_{R5}		3.5	mA
		V_{RM} = 12 V (pk)	I_{R6}		2.5	mA
		V_{RM} = 6 V (pk)	I_{R7}		2.0	mA
1N6761-1, 1N6761UR-1		V_{RM} = 100 V (pk)	I_{R2}		12.0	mA
		V_{RM} = 50 V (pk)	I_{R3}		5.0	mA
		V_{RM} = 25 V (pk)	I_{R4}		3.5	mA
		V_{RM} = 12 V (pk)	I_{R5}		2.5	mA

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:44Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection. – Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 3 - Continued						
Forward voltage	4011	Pulse method (see 4.5.1) I_F = 1.0 A (pk)	V_{F4}			
1N5819-1, 1N5819UR-1					0.45	V dc
1N6761-1, 1N6761UR-1					0.64	V dc
Low temperature operation:		T_A = -55°C				
Forward voltage	4011	Pulse method (see 4.5.1) I_F = 1.0 A (pk)	V_{F5}			
1N5819-1, 1N5819UR-1					0.65	V dc
1N6761-1, 1N6761UR-1					0.80	V dc
Reverse current leakage	4016	Pulse method (see 4.5.1)	I_{R5}			
1N5819-1, 1N5819UR-1		V_{RM} = 45 V (pk)			200	µA
1N6761-1, 1N6761UR-1		V_{RM} = 90 V (pk)			400	µA
Subgroup 4						
Capacitance	4001	V_R = 5 V dc, .01 ≤ f ≤ 1 MHz, V_{SIG} = 15 mV p-p	C_T		70	pF

1/ For sampling plan, see MIL-PRF-19500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:44Z
Check the source to verify that this is the current version before use.

* TABLE II. Group E inspection (all quality levels) for qualification and re-qualification.

Inspection	MIL-STD-750		Sampling plan
	Method	Conditions	
Subgroup 1			n = 22, c = 0
Thermal shock	1056	100 cycles 0°C to 100°C	
Temperature cycling	1051	500 cycles -65°C to 150°C	
Hermetic seal	1071	Test condition E	
Electrical measurement		See table I, subgroup 2	
Subgroup 2			n = 22, c = 0
Blocking life	1048	1,000 hours	
Electrical measurement		See table I, subgroup 2	
Subgroup 4			Sample size N/A
Thermal impedance curves		See 4.2.1.1	
Subgroup 5			
Not applicable			
Subgroup 6			n = 3, c =0
ESD	1020		
Subgroup 8			n = 45
Resistance to glass cracking	1057	Test condition B. Test to destruction or 25 cycles max whichever comes first.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:44Z
Check the source to verify that this is the current version before use.





FIGURE 4. Derating for 1N5819-1 (DO-41).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:44Z
Check the source to verify that this is the current version before use.



The curve for V_R =6V coincides with the curve for V_R =12V.

FIGURE 5. Derating for 1N5819UR-1 (DO-213AB).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:44Z
Check the source to verify that this is the current version before use.




FIGURE 6. Derating for 1N6761-1 (DO-41).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:44Z
Check the source to verify that this is the current version before use.





FIGURE 7. Derating for 1N6761UR-1 (DO-213AB).


Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:44Z
Check the source to verify that this is the current version before use.



$R_{\Theta JL}$ = 70°C/W.
$Z_{\Theta JX}$ = 10°C/W maximum at t_H = 10ms.

* FIGURE 8. Thermal impedance for 1N5819-1 and 1N6761-1 (DO-41).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:44Z
Check the source to verify that this is the current version before use.



$R_{\theta JEC}$ = 40°C/W.
$Z_{\Theta JX}$ = 10°C/W maximum at t_H = 10ms.

* FIGURE 9. Thermal impedance for 1N5819UR-1 and 1N6761UR-1 (DO-213AB).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:44Z
Check the source to verify that this is the current version before use.

5. PACKAGING

* 5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The notes specified in MIL-PRF-19500 are applicable to this specification.

* 6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Packaging requirements (see 5.1).

c. Lead finish (see 3.4.1).

d. Product assurance level and type designator.

* 6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML-19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from Defense Supply Center, Columbus, ATTN: DSCC/VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil.

* 6.4 Suppliers of die. The qualified JANHC and JANKC suppliers with the applicable letter version (example JANHCA1N5819) will be identified on the QML.

PIN	Manufacturer
	43611
1N5819	JANHCA1N5819, JANKCA1N5819
1N6761	JANHCA1N6761, JANKCA1N6761

6.5 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:44Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 11
NASA - NA
DLA - CC

Review activities:
Army - AR, MI, SM
Navy - AS, MC
Air Force - 19, 99

Preparing activity:
DLA - CC

(Project 5961-2945)

* NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:44Z
Check the source to verify that this is the current version before use.