The documentation and process conversion measures necessary to comply with this amendment shall be completed by 30 January 2002.

INCH-POUND

MIL-PRF-19500/676A
AMENDMENT 2
30 October 2001
SUPESEDING
AMENDMENT 1
14 September 2001

PERFORMANCE SPECIFICATION

SEMICONDUCTOR DEVICE, FIELD EFFECT RADIATION HARDENED
(TOTAL DOSE AND SINGLE EVENT EFFECTS)
TRANSISTORS, N-CHANNEL, SILICON TYPES 2N7465T3 AND 2N7466T3 AND U3 SUFFIXES
JANTXVR AND JANSR

This amendment forms a part of MIL-PRF-19500/676A, dated 20 February 2001, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

* 1.4, max $r_{DS(on)}$ (2) column, T_J = +25°C column, delete "1.2" and "1.6" respectively and substitute "1.39" and "1.77" respectively.

* 1.4, max $r_{DS(on)}$ (2) column, T_J = +150°C column, delete "2.7" and "3.6" respectively and substitute "3.0" and "3.9" respectively.

PAGE 11

* TABLE I, subgroup 2, static drain to source on-state resistance test (first occurrence), limits max column, delete "1.2" and "1.6" respectively and substitute "1.39" and "1.77" respectively.

* TABLE I, subgroup 2, static drain to source on-state resistance test (second occurrence), limits max column, delete "1.22" and "1.62" respectively and substitute "1.52" and "1.9" respectively.

PAGE 12

* TABLE I, subgroup 3, static drain to source on-state resistance, limits max column, delete "2.4" and "3.12" respectively and substitute "2.64" and "3.76" respectively.

* TABLE I, subgroup 4, forward transconductance test, limits min column, delete "1.8" and "1.5" respectively and substitute "0.5" and "0.4" respectively.

* TABLE I, subgroup 4, switching time test, turn-on delay time, 2N7466, limits max column, delete "20" and substitute "25".

  TABLE I, subgroup 4, switching time test, rise time step, limits max column, delete "40" and "27" respectively and substitute "75" and "65" respectively.

PAGE 13

* TABLE I, subgroup 4, fall time test, 2N7466, limits max column, delete "50" and substitute "63".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:43Z
Check the source to verify that this is the current version before use.

* TABLE I, subgroup 7, delete and substitute:

"

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 7						
Gate charge	3471	Condition B				
On-state gate charge			$Q_{G(on)}$			
2N7465					31	nC
2N7466					30	nC
Gate to source charge			Q_{GS}			
2N7465					8.5	nC
2N7466					8	nC
Gate to drain charge			Q_{GD}			
2N7465					20	nC
2N7466					18	nC
Reverse recovery time		di/dt ≤ 100A/µs, V_{DD} ≤ 50 V, $I_D = I_{D1}$	t_{rr}			
2N7465					350	nC
2N7466					400	nC

"

PAGE 15

* TABLE II, static drain to source on-state voltage, preirradiation limits, max column, delete "4.08" and "4.48" respectively and substitute "4.726" and "4.956" respectively.

* TABLE II, static drain to source on-state voltage, post irradiation limits, max column, delete "4.08" and "4.48" respectively and substitute "4.726" and "4.956" respectively.

The margins of this amendment are marked with an asterisk to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - CR
Navy - NW
Air Force - 11
NASA - NA
DLA - CC

Review activities:
Army - MI

Preparing activity:
DLA - CC

(Project 5961-2549)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:43Z
Check the source to verify that this is the current version before use.