
INCH-POUND
MIL-DTL-52525/14D
5 August 2019
SUPERSEDING
MIL-DTL-52525/14C
20 November 2008

DETAIL SPECIFICATION SHEET

# FITTINGS, HOSE CRIMP TYPE, SPLIT-FLANGE 45 DEGREE BENT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-52525.




| Part or Identifying Number (PIN) | Hose | | Tube dash no. | flange head | | A inches (mm) | B inches (mm) |
|---|---|---|---|---|---|---|---|
| | Dash no | ID inches (mm) | | Dash no. | size inches (mm) | | |
| M52525/14-12-12 | -12 | .750 (19.05) | -12 | -12 | .750 (19.05) | 5.62 (142.75) | 1.94 (49.28) |
| M52525/14-16-16 | -16 | 1.000 (25.40) | -16 | -16 | 1.000 (25.40) | 5.79 (147.07) | 2.03 (51.56) |
| M52525/14-20-20 | -20 | 1.250 (31.75) | -20 | -20 | 1.250 (31.75) | 7.77 (197.36) | 3.00 (76.20) |
| M52525/14-24-24 | -24 | 1.500 (38.10) | -24 | -24 | 1.500 (38.10) | 8.83 (224.28) | 2.87 (72.90) |

See notes at end of figure.

FIGURE 1. Fitting, screw-on to 4-bolt split-flange, 45° bent tube.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:22Z
Check the source to verify that this is the current version before use.

| PIN | C inches (mm) | F inches (mm) |
|---|---|---|
| M52525/14-12-12 | 1.625 (41.28) | 1.00 (25.40) |
| M52525/14-16-16 | 2.000 (50.80) | 1.06 (26.92) |
| M52525/14-20-20 | 2.625 (66.68) | 1.19 (30.23) |
| M52525/14-24-24 | 2.875 (73.03) | 1.44 (36.58) |

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. All dimensions not shown shall be in accordance with SAE-J516 and SAE-J518-1 or -2 as applicable.
4. SAE-J516 type, for use with SAE-J517, type 100RE hose (formerly SAE-J517, type 100R10 hose), coupled to part using SAE-J518-1 or -2 split-flange type.

FIGURE 1. Fitting, screw-on to 4-bolt split-flange, 45° bent tube - Continued.

ENGINEERING DATA:

NOTE: SAE-J517, type 100R10 hoses have been discontinued by SAE. Use SAE-J517 hoses specified in table I. The “RE” designator at the end of the hose type “100RE” is a MIL-DTL-52471 term used to indicate a hose type that has been discontinued and to use an SAE-J517 replacement hose.

TABLE I. Hose type 100RE to SAE replacement. 1/

| 100R10 hose dash size | SAE-J517 replacement | Operating pressure psi | SAE MPa | 100RE MPa |
|---|---|---|---|---|
| -12 | SAE J517 100R13-12 | 5000 | 35 | 34.5 |
| -16 | SAE J517 100R13-16 | 4000 | 35 | 27.6 |
| -20 | SAE J517 100R12-20 | 3000 | 21 | 20.7 |
| -24 | SAE J517 100R12-24 | 2500 | 17.5 | 17.2 |

1/ If the SAE-J517 hose does not meet system requirements chose an SAE-J517 hose with pressure requirements at or above pressure requirements specified in this specification.

REQUIREMENTS:

The fittings described herein are for use with hose in accordance with SAE-J517 and hose assemblies in accordance with MIL-DTL-52471/3.

Fittings shall be as specified on figure 1 and in tables II and III.

If fittings are to be used on an oxygen hose see MIL-DTL-52525.

Materials and finishes shall be in accordance with MIL-DTL-52525 and in table II.

Finish. Finishes shall be in accordance with table I. All plating’s shall be capable of meeting 96-hour salt spray test in accordance with ASTM B117. The fittings shall show no evidence of red corrosion after 96 hours of salt spray. Fluid passages, other openings, and internal threads shall not be subject to the plating thickness requirement and may have bare areas provided they are protected with a light film of oil.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:22Z
Check the source to verify that this is the current version before use.

TABLE II. Material and finish identification codes. 1/ 2/

| PIN code material/plating finish | Material | Plating finish |
|---|---|---|
| A | Aluminum alloy 6061 or 7075 | Anodize in accordance with MIL-A-8625, type II. |
| AN | | Anodize in accordance with MIL-A-8625, type II and NAVAIR trivalent chromium pretreatment (TCP) in accordance with MIL-DTL-81706, type II, class 1A. TCP Applied after anodizing. |
| BN | | Bare aluminum with NAVAIR TCP in accordance with MIL-DTL-81706, type II, class 1A. |
| C | Steel 2/ | Cadmium plating in accordance with SAE-AMS-C-81562, type II, class 3 or SAE-AMS-QQ-P-416, type II, class 2. 1/ 5/ 8/ |
| YC | Chrome-molybdenum steel alloy 4130 | Cadmium plating in accordance with SAE-AMS-C-81562, type II, class 3 or SAE-AMS-QQ-P-416, type II, class 2. 1/ 5/ 8/ |
| G | Steel 2/ | Zinc plating with colorless passivate in accordance with ASTM B633, type VI, Fe/Zn 8. 3/ |
| YG | Chrome-molybdenum steel alloy 4130 | |
| H | Steel 2/ | Zinc phosphate finish in accordance MIL-DTL-16232, type Z, class1. |
| YH | Chrome-molybdenum steel alloy 4130 | |
| J | Steel 2/ | Zinc plating with a colored chromate conversion in accordance with ASTM B633; type II or III, Fe/Zn 8, or ASTM B695, type II, class 8. 3/ 5// |
| YJ | Chrome-molybdenum steel alloy 4130 | |
| K | Nickel-copper alloy UNS N04400 | No additional finish. |
| M | High-chromium nickel alloy UNS N06690 | No additional finish. |
| N | Steel 2/ | Zinc-aluminum in accordance with ASTM F1136/F1136M, grade 3, NC. 4/ |
| YA | Chrome-molybdenum steel alloy 4130 | |
| YN | | Zinc-nickel in accordance with SAE-AMS2417, type 2, grade B. 4/ 7/. |
| P | Steel 2/ | Zinc plating with colorless passivate in accordance with ASTM B633, type V, Fe/Zn 8. 3/ |
| YP | Chrome-molybdenum steel alloy 4130 | |
| S | Corrosion resistant steel | No additional finish. Passivation in accordance with SAE-AMS2700, type 6 or 7. |
| T | Titanium | Anodize in accordance with SAE-AMS2488, type 2. 6/ 9/ |
| TF | | Fluoride phosphate in accordance with SAE-AMS2486. 6/ 9/ |
| U | Steel 2/ | Zinc-aluminum in accordance with ASTM F1136/F1136M, grade 3, NC. 4/ |
| V | | Zinc-nickel in accordance with SAE-AMS2417, type 2, grade B. 4/ 7/. |
| W | Steel 2/ | Any zinc plating above. 3/ 5/ |
| YW | Chrome-molybdenum steel alloy 4130 | |
| Z | Steel | Zinc plating in accordance with ASTM B695, type II, class 8. 3/ 5/ |

1/ Embrittlement test need not be run.
2/ All steels except 4130.
3/ Not for use in aircraft. Requires approval from the Program Office for all applications. Zinc-plated materials should be avoided in hydraulic systems with water-glycol fluids. Reference ASTM MNL37 - Fuels and Lubricants Handbook.
4/ Hexavalent chromium free. Finish shall be RoHS compliant.
5/ These finishes have a chromate conversion coating or chromic acid rinse which includes hexavalent chromium and are not recommended.
6/ A pretreatment, a modification of the fluoride treatment, or a post treatment shall be applied so the final color of the fittings shall be similar to SAE-AMS-STD-595 colors 36076 through 36293.
7/ The zinc-nickel alloy plate shall contain 12% to 16% nickel. The coating thickness shall be 315µ inches (8µm) minimum.
8/ Cadmium shall not be used in oxygen or potable water systems. Cadmium is prohibited from use in NAVSEA-owned shipboard systems in accordance with the requirements of T9070-AL-DPC-020/077-2, unless otherwise approved by NAVSEA.
9/ Titanium shall not be used in oxygen or potable water systems.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:22Z
Check the source to verify that this is the current version before use.


Maximum operating pressure shall be as specified in table III. Maximum operating pressures are for low carbon steel fittings consult manufacturer for values on other materials.

TABLE III. Maximum operating pressures of fittings. 1/

| SAE dash size | Hose ID ref inches (mm) | psi | MPa |
|---|---|---|---|
| -12 | .750 (19.05) | 5000 | 34.5 |
| -16 | 1.000 (25.40) | 4000 | 27.6 |
| -20 | 1.250 (31.75) | 3000 | 20.7 |
| -24 | 1.500 (38.10) | 2500 | 17.2 |

1/ Metric equivalents are given for information only.

PIN: The PIN consists of the letter “M” the specification sheet number, a dash, a number for hose size, a dash, a number for tube size, a dash, a number for flange, and a material finish designator.




PIN example: M52525/14-12-12A, describes a 45° split flange for a .750 inch (19.05 mm) hose, with a .750 inch (19.05 mm) flange, aluminum with an anodized finish.

To the users of this document, it is recommended that the use of carbon steel material with cadmium plating be used only when the other materials and finishes specified in this document cannot meet performance requirements.

Cadmium is prohibited from use in NAVSEA-owned shipboard systems in accordance with the requirements of T9070-AL-DPC-020/077-2, unless otherwise approved by NAVSEA.

Class I and II ozone depleting substances (ODS) shall not be used in MIL-DTL-52525/14 or any referenced procedures.

Referenced documents shall be of the issue in effect on date of invitations for bid.

Color identification. Color identification shall be in accordance with SAE-AS4841.

Marking shall include the manufacturer’s name or trademark, size, and hose identifier 100R10. Location of marking is optional.

Harmonization to SAE-J516 and J518-1 or -2 cross reference PIN‘s in table IV is for reference only. SAE style fittings may not have the same material/finish as required by MIL-DTL-52525 and legacy with MIL-DTL-52471.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:22Z
Check the source to verify that this is the current version before use.

TABLE IV. Harmonization to SAE-J516 and SAE-J518-1 and -2 flange cross reference PIN. 1/

| PIN | SAE PIN | SAE J518-1 PIN Flange head only | SAE J518-2 PIN Flange head only |
|---|---|---|---|
| M52525/14-12-12 | SAE J516 12-12 F392276EE | N/A | SAE J518 -12-1162 |
| M52525/14-16-16 | SAE J516 16-16 F392276EE | N/A | SAE J518 -16-1162 |
| M52525/14-20-20 | SAE J516 20-20 F392276EE | SAE J518 -20-1161 | |
| M52525/14-24-24 | SAE J516 24-24 F392276EE | SAE J518 -24-1161 | |

1/ Material and finish designators are omitted from PIN's, see table I and SAE-J846.
2/ EE at the end of the PIN indicates SAE 100R10 has been discontinued, see table I.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue, due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-52525, this document references the following:

| | | |
|---|---|---|
| MIL-A-8625 | SAE-AMS-STD-595/36081 | SAE-AMS-C-81562 |
| MIL-DTL-16232 | SAE-AMS-STD-595/36099 | SAE-AMS-QQ-P-416 |
| MIL-DTL-52471 | SAE-AMS-STD-595/36118 | SAE-AMS2417 |
| MIL-DTL-52471/3 | SAE-AMS-STD-595/36134 | SAE-AMS2488 |
| MIL-DTL-52525/16 | SAE-AMS-STD-595/36152 | SAE-AMS2486 |
| MIL-DTL-52525/17 | SAE-AMS-STD-595/36170 | SAE-AMS2700 |
| MIL-DTL-81706 | SAE-AMS-STD-595/36173 | SAE-AS4841 |
| ASTM B117 | SAE-AMS-STD-595/36176 | SAE-J516 |
| ASTM B633 | SAE-AMS-STD-595/36231 | SAE-J517 |
| ASTM B695 | SAE-AMS-STD-595/36251 | SAE-J518-1 |
| ASTM F1136/F1136M | SAE-AMS-STD-595/36270 | SAE-J518-2 |
| ASTM MNL37 | SAE-AMS-STD-595/36280 | SAE-J846 |
| SAE-AMS-STD-595/36076 | SAE-AMS-STD-595/36293 | T9070-AL-DPC-020/077-2 |

CONCLUDING MATERIAL

Custodians:
Army - AT
Navy - SH
Air Force - 71
DLA - CC

Preparing activity:
DLA - CC

(Project 4730-2019-064)

Review activities:
Army - CR4
Navy - AS, CG, SA, YD

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:22Z
Check the source to verify that this is the current version before use.