METRIC


MIL-DTL-55302/161D
w/AMENDMENT 2
6 March 2023
SUPERSEDING
w/AMENDMENT 1
20 July 2011

DETAIL SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES, RECEPTACLE, 160 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS, 2.54 MM X 1.27 MM OFFSET GRID, METRIC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-55302.



NOTE: Dimensions are in millimeters.

FIGURE 1. Connector receptacle.

AMSC N/A FSC 5935

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.

TERMINAL STYLES





REF FEMALE CONTACTS	REF MALE CONTACTS
J. STRAIGHT DIP SOLDER 	P. STRAIGHT DIP SOLDER 
T. STRAIGHT DIP SOLDER  1.6 (.064 IN) P.C. BOARD	U. STRAIGHT DIP SOLDER  1.6 (.064 IN) P.C. BOARD

FIGURE 2. Connector termination styles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.

TERMINAL STYLES






REF FEMALE CONTACTS	REF MALE CONTACTS
N. STRAIGHT DIP SOLDER  2.4 (.094 IN) P.C. BOARD	Z. STRAIGHT DIP SOLDER  2.4 (.094 IN) P.C. BOARD
V. STRAIGHT DIP SOLDER  3.2 (.125 IN) P.C. BOARD	W. STRAIGHT DIP SOLDER  3.2 (.125 IN) P.C. BOARD


FIGURE 2. Connector termination styles – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.

TERMINAL STYLES

REF FEMALE CONTACTS	REF MALE CONTACTS
G. WRAP POST	Q. WRAP POST






NOTES:
1. Dimensions are in millimeters.
2. This is a metric design.
3. Unless otherwise specified, tolerance is ± 0.10 millimeter.
4. These connectors mate with MIL-DTL-55302/164.
5. See table I for mating.
6. Contact identification may be located adjacent to cavity on face or side and may be rotated 180°.
7. Insulator bodies are not to be bonded or affixed in any way such that the front removal feature of this assembly would be defeated.

FIGURE 2. Connector termination styles – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.

MOUNTING DIMENSIONS

FOR MOUNTING STYLES B
MOTHER BOARD APPLICATION



NOTE: Dimensions are in millimeters.

FIGURE 3. Mounting styles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Design and construction:

Dimensions and configuration: See figures 1 through 3.

Mating references: See table I.

TABLE I. Mating references.

Type	Will only mate with (see note)	Locking method
B	P,U,W	None

NOTE: These connectors mate with MIL-DTL-55302/164.

Material:

Insulators: Diallyl phthalate in accordance with ASTM D5948.

Guides and hardware: Brass in accordance with ASTM B36/B36M, ASTM B16/B16M, ASTM B124/B124M, ASTM B453/B453M, or ASTM B455; nickel plated in accordance with SAE AMS-QQ-N-290 or AISI 300 series stainless steel or equivalent in accordance with ASTM A582/A582M, passivated in accordance with SAE AMS2700.

Plating: Plating in accordance with MIL-DTL-55302 or as noted below.

Mating surface (pin and wire): Gold in accordance with MIL-DTL-45204 or equivalent as approved by the qualifying and preparing activities, class 1, type II, grade C, over nickel in accordance with SAE AMS-QQ-N-290, 30-150 microinches.

Terminations: Solderable areas (including crimp barrels and wire wrap terminations) shall be gold in accordance with MIL-DTL-45204 or equivalent as approved by the qualifying and preparing activities, type III, grade A, 10 µin. (0.254 µm) minimum thickness or gold in accordance with MIL-DTL-45204 or equivalent as approved by the qualifying and preparing activities , type II, grade C, class 00 (0.51 µm) over nickel in accordance with SAE AMS-QQ-N-290, 30 to 150 microinches thick. Solderable areas must meet the requirements of MIL-STD-202, method 208.

All other surfaces: Gold in accordance with MIL-DTL-45204 or equivalent as approved by the qualifying and preparing activities , type II, code C, 5 µin. (0.127 µm) minimum thickness over nickel in accordance with SAE AMS-QQ-N-290, 30-150 microinches.

Contact identification: See figure 1.

Contact separation forces:

Minimum force: 0.14 newton (0.50 ounce) with a 0.5800 millimeter (.0228 inch) +0.005, -0.00 diameter pin after being cycled 3 times.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.

Note: Steel pin test surface roughness to be 0.025-0.25 micron rms.

Unmating: The maximum force of a connector assembly shall not exceed 0.53 newton (1.90 ounces) multiplied by the number of contact positions.

Mating: The maximum force of a connector assembly shall not exceed 0.70 newton (2.5 ounces) multiplied by the number of contact positions.

Contact retention minimum: functional value 22.2 newtons (5 pounds); destructive test 35.3 newtons (8 pounds) maximum design and qualification value.

Contact rating: 5 amperes per line.


Durability: 2,000 cycles minimum.

Dielectric withstanding voltage:

Sea level: 1,400 V ac rms test.
High altitude: 300 V ac rms test.

Keying: Rotation of guides, 6 positions each, 36 possible combinations.

Connector Part or Identifying Number (PIN):



Amendment notations. The margins of this specification are marked with vertical lines to indicate where modifications from this amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-DTL-55302, this document references the following:

MIL-DTL-55302/164
MIL-DTL-45204
MIL-STD-202
ASTM A582/A582M
ASTM B16/B16M
ASTM B36/B36M
ASTM B124/B124M
ASTM B453/B453M
ASTM B455
ASTM D5948
SAE AMS-QQ-N-290
SAE AMS2700

CONCLUDING MATERIAL

Custodians:
Army – CR
DLA – CC

Preparing activity:
DLA – CC

(Project 5935-2023-019)

Review activities:
Army – AR, AT, AV, CR4, MI

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsible can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.