INCH-POUND


MIL-PRF-55339/54B
w/AMENDMENT 2
01 February 2023
SUPERSEDING
MIL-PRF-55339/54B
w/AMENDMENT 1
01 October 2017

PERFORMANCE SPECIFICATION

ADAPTER, CONNECTOR, ELECTRICAL, COAXIAL, RADIO FREQUENCY,
(BETWEEN SERIES SMA TO N)

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall
consist of this specification sheet and MIL-PRF-55339.



NOTES:
1. Dimensions are in inches.
2. Unless otherwise specified, tolerance is ± .015 (0.38 mm).
3. All undimensioned pictorial configurations are for reference purposes only.
4. Interfaces shall be in accordance with MIL-STD-348.

FIGURE 1. General configuration.

AMSC N/A FSC 5935

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:08Z
Check the source to verify that this is the current version before use.

ENGINEERING DATA:

Nominal impedance: 50 ohms.

Frequency range: 18 GHz.

Voltage range: 355 V rms at sea level, 85 V rms at 70,000 feet.

Operating temperature range: -65°C to +165°C.

REQUIREMENTS:

Dimensions and configuration: See MIL-STD-348 and figure 1.

Inspection conditions: For each test of threaded coupling connectors where the test is performed on mated pairs, the pairs shall be torqued to 7 to 10 inch-pounds.

Permeability: Less than 2.0, air = 1.0.

Seal:

Pressurized: Not applicable.

Weatherproof: Not applicable.

Insulation resistance: 5,000 megohms, minimum.

VSWR:

1.06 + .005 F (GHz); dc to 12.4 GHz.

.83 + .023 F (GHz); 12.4 to 18 GHz.

RF leakage: -65 dB, minimum, 2 to 3 GHz.

RF insertion loss: .18 dB, maximum, at 9 GHz.

Dielectric withstanding voltage: 1,000 V rms at sea level, minimum.

Contact resistance (milliohms, maximum):

Contact	Initial	After environmental
Center	4.1 1/	6.0
Outer	2.2	Not applicable

1/ Two center contacts must be mated to the center conductor under test, therefore doubling “center contact” resistance.

Vibration, high frequency: Interruptions, 1 µs maximum. MIL-STD-202-204, test condition D.

Shock: MIL-STD-202-213, test condition I.

Thermal shock: MIL-STD-202-107, test condition C.

Moisture resistance: 200 megohms, minimum, MIL-STD-202-106 within 5 minutes after removal from humidity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:08Z
Check the source to verify that this is the current version before use.

Corona level:

Voltage: 375 V, minimum, at 70,000 feet minimum.

RF high potential withstanding voltage:

RF voltage: 1,000 V rms, minimum at 5 MHz minimum.

Salt spray: MIL-STD-202-101, test condition B.

Center contact retention:

Axial force: 6 pounds, minimum.

Torque: Not applicable.

Force to engage and disengage:

	Series N	Series SMA
Longitudinal force:	Not applicable	Not applicable
Torque: (inch-pounds, maximum)	6.0	2.0

Coupling proof torque: 15 inch-pounds, minimum.

Durability: 500 cycles, minimum at 12 cycles per minute, maximum.

Coupling mechanism retention force: 60 pounds, minimum.

Group qualification: See table I.

MARKING: As specified in MIL-PRF-55339. See Figure 1.

Part or Identifying Number (PIN). M55339/54-30001
M55339/54-40001

TABLE I. Group qualification.

Group	Submission and qualification of any of the following connectors	Qualifies the following connectors
1	M55339/54-30001 M55339/54-30002 M55339/54-30004	M55339/54-30001 M55339/54-30002 M55339/54-30003 M55339/54-30004

Amendment notations. The margins of this specification are marked with vertical lines to indicate notifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:08Z
Check the source to verify that this is the current version before use.

Referenced documents: In addition to MIL-PRF-55339, this document references the following:

MIL-STD-202-101
MIL-STD-202-106
MIL-STD-202-107
MIL-STD-202-204
MIL-STD-202-213
MIL-STD-348

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA – CC

Preparing activity:
DLA - CC

(Project 5935-2023-011)

Review activities:
Army - AR, AT, EA
Navy - AS, MC, OS
Air Force – 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:08Z
Check the source to verify that this is the current version before use.