MIL-C-81309D
AMENDMENT 3
25 September 1986
SUPERSEDING
~~AMENDMENT~~ 2
3 November 1983

MILITARY SPECIFICATION

CORROSION PREVENTIVE COMPOUNDS, WATER DISPLACING, ULTRA-THIN FILM

This amendment forms a part of Military Specification MIL-C-81309D, dated 26 July 1982, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

*2.1.1 Federal: Add "VV-L-800 - Lubricating Oil, General Purpose Preservative (Water-Displacing, Low Temperature)."

2.1.1 Military: Add "MIL-C-81302 - Cleaning Compound, Solvent, Trichlorotrifluoroethane."

*2.1.1 Military: Delete "MIL-L-17672."

PAGE 4

3.5.2, line 2: Change "13" to "16:"

3.5.4: Delete in its entirety and substitute:

"3.5.4 Propellant. The propellant shall consist of either carbon dioxide dissolved in type II material of MIL-C-81302 or a mixture of trichlorotrifluoroethane and chlorodifluoromethane."

PAGE 5

*Table 1, Requirements column, entry 11: Delete in its entirety and add the following:

"No evidence of sedimentation."

PAGE 6

4.3.1, line 5: Change "13" to "16."

AMSC N/A FSC 8030

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:11Z
Check the source to verify that this is the current version before use.

PAGE 13

*4.10.11.1 Delete in its entirety and add the following:

"4.10.11.1 Test procedure. Combine 5ml of the compound and 15ml of lubricating oil conforming to VV-L-800 in a 40ml cone-shaped centrifuge tube. Shake by hand until the mixture appears homogeneous. Place the tube in a beaker and heat in an explosion-proof oven at 76.7° ±1.1°C (170° ±2°F) for 15 minutes. There shall be no sedimentation or evidence of chemical precipitation or reaction after the 15 minutes 76.7°C (170°F) temperature inspection or after 24 hours at 25° ±2.8°C (77° ±5°F) (see table I). A slight separation of liquid shall be acceptable."

PAGE 14

4.10.13.2, line 3: Change "13" to "16."

PAGE 15

5.1.2, first sentence: Delete in its entirety and substitute:

"The containers shall conform to class 4, type IX of PPP-C-96 with valve opening diameter suitable for the specified valve."

PAGE 16

5.3, front face, last line: Change "13" to "16."

The margin of this amendment is marked with an asterisk to indicate where a modification from the previous amendment was made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in the notation. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notation and relationship to the last previous amendment.

Custodians:
Army - EA
Navy - AS
Air Force - 99

Review Activities:
Army - MR
Navy - OS, YD
Air Force - 84
Other Agencies - DS

User Activities:
Army - AT, ER, ME
Navy - CG

Preparing Activity:
Navy - AS
(Project No. 8030-0552)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:11Z
Check the source to verify that this is the current version before use.