MILITARY SPECIFICATION

RAILWAY CAR, FLAT, 56-1/2-INCH GAGE, HEAVY DUTY

140-TON CAPACITY, DOMESTIC SERVICE

This amendment forms a part of Military Specification MIL-R-52968C(ME), dated 20 August 1982 and is approved for use by the US Army Mobility Equipment Research and Development Command, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1.1, before "SPECIFICATIONS", "MILITARY" add:

"FEDERAL

TT-E-489 - Enamel, Alkyd, Gloss, (For Exterior and Interior Surfaces)."

Delete "MIL-P-3320" in its entirety and substitute:

"MIL-P-53044 - Painting and Marking: Freight and Maintenance Cars Railway Motive Power and Work Equipment."

PAGE 2

Add new paragraph:

"2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

AMSC N/A FSC 2220

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:43Z
Check the source to verify that this is the current version before use.

"ME

13226E7053	- Coupling Link.
13226E7054	- Claw Hook.
13226E7055	- Sling Hook.
13226E7056	- Shackle.
13226E7057	- Master Ring."

PAGE 6

3.11.1, delete paragraph in its entirety and substitute:

"3.11.1 Tank securement system. The securement system shall be of the latest AAR approved 48 chain tiedown system with end hook configuration. The system shall consist of these components: steel anchoring channels, coupling link conforming to drawing 13226E7053, load binder, compression unit, coupling link (same as above), claw hook conforming to drawing 13226E7054, 1/2-inch alloy steel chain, and a sling hook conforming to drawing 13226E7055. Four extra complete tiedown assemblies to be used as spares shall be provided with each car. Four channels shall be flush-mounted parallel along the entire length of the car. The bolster area may be excluded. The heavy-duty anchoring devices shall move freely in the channels, with the ability to be locked at positions in maximum of three-inch increments along the full length of the channels. The anchoring device shall remain in the channels when not in use. The securement devices shall be designed to have a minimum breaking strength of not less than 50,000 pounds. The construction shall be such that one man can position anchors and chain assembly without special tools. Each chain tie-down and anchoring device shall be permanently fixed to the flatcar. A complete set of shackles and masterlinks conforming to drawings 13226E7056 and 13226E7057 and sufficient to secure two M1 tanks to the flatcar shall also be provided with the car."

PAGE 9

3.17, delete in its entirety and substitute:

"3.17 Painting and marking. Painting and marking shall conform to MIL-P-53044, color 14064, with these exceptions: (1) Stencilling shall be done with AAR approved white paint or other AAR approved material and must be of a consistency to thoroughly cover black background and provide a sharp contrast that will remain legible for a minimum period of 96 months. (2) Trucks shall be painted with a light application of TT-E-489 to attain 0.5 mils minimum dry film thickness that will not prevent detection of flaws or cracks in ordinary inspection. (3) Handgrabs and sill steps shall be painted safety yellow. (4) "JACK HERE" and "LIFT HERE" stencils shall be applied at the appropriate place. (5) The deck and side sills shall be stencilled to show the location of both the single and two tank configurations and their corresponding anchor locations. A color-coding system shall be used to clearly indicate the above for both the M1 tank (white) and the M60 tank (yellow). (6) The deck shall be stencilled to

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:43Z
Check the source to verify that this is the current version before use.

show the correct pedestal locations for both 20 and 40 foot containers. Substitute systems affording equal protection are acceptable if approved by the Government. Reporting marks shall be DODX in lieu of USAX as specified in MIL-P-53044 and the words US Army shall not be applied. Stencilling on ends of car will include but not be limited to identificatin of couplers, wheels, end-of-car cushioning, springs and snubbers. Additional markings shall be in accordance with AAR's Section L - Lettering and Marking of Cars, as applicable. Car numbers conforming to MIL-P-53044 shall be applied and shall be provided by the contracting officer. Decals shall be applied to the side sills when furnished (see 6.7)."

3.17.1, lines 3 and 5, delete "ml" and substitute "mils".

PAGE 12

4.5.2.7, delete in its entirety and add:

"4.5.2.7 Cargo securement system. The cargo securement system's ability to restrain two M1 tanks and ANSI/ISO containers shall be demonstrated. Nonconformance to 3.11, 3.11.1, 3.11.2 and AAR requirements shall constitute failure of this test."

PAGE 13

6.10, delete in its entirety.

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 2220-A196

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:43Z
Check the source to verify that this is the current version before use.