MIL-S-60502A(MU)
AMENDMENT 3
3 August 1973
SUPERSEDING
AMENDMENT 2
25 January 1973

MILITARY SPECIFICATION

STOP PREAMPLIFIER: 10540715

This amendment forms a part of Military Specification MIL-S-60502A(MU), dated 18 June 1970.

Paragraph 2.1: Add Military Specification "MIL-P-46843 - Printed Circuit Assemblies, Design and Production of".

Paragraph 3.3: Add "and MIL-P-46843".

Paragraph 3.3.1: Add after MIL-F-13926 "and MIL-P-46843".

Paragraph 3.7.1: Delete paragraph and substitute:

Pulse response.- The amplifier shall generate the responses of 3.7.2 across a 240 ± 1% ohm resistor connected between Pins B and E of P_1 with a constant input pulse width of 40 ± 2 nanoseconds applied to P_2 (Figure 2).

Paragraph 3.7.2: Delete paragraph and substitute:

Input thresholds.- The input threshold of the amplifier shall be controlled by applying to Pin C of P_1 an initiation pulse of 1.25 ± 0.25 V amplitude, and 0.5 ± 0.1 uSEC (Figure 3).

Add paragraph 3.7.2.1.a as follows:

3.7.2.1.a Low gain response.- At 2 uSEC after the application of the initiation pulse described in paragraph 3.7.2, and with the application of an input pulse of 30 mV amplitude as described in paragraph 3.7.1, the output voltage pulse across the 240 ohm resistor as described in paragraph 3.7.1 could be zero, but must be less than 1.5 V.

Add paragraph 3.7.2.1b as follows:

3.7.2.1b Low gain response.- At 3.5 uSEC after the application of the initiation pulse as described in paragraph 3.7.2 and with an input pulse amplitude of 43 ± 10 mV, the signal ovserved across the 240 ohm resistor described in paragraph 3.7.1 shall have a pulse width between 15 and 60 nSEC, measured at the 50% points (Figure I). For an input voltage amplitude of 60 ± 1% mV, the output pulse width shall be less than 150 nanoseconds:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:39Z
Check the source to verify that this is the current version before use.

Add paragraph 3.7.2.1c as follows:

3.7.2.1.c Low gain response.- At a point 10 ± 1 uSEC after the application of an initiation pulse as described in paragraph 3.7.2 and with an input signal amplitude of 2.2 ± 1.2 mV meeting the requirements of paragraph 3.7.2 applied to P_2, the output pulse amplitude measured across the 240 ohm resistor shall be 1.5 volts minimum.

Paragraph 4.3.4: Delete paragraph and substitute: "Certification.- Certification shall include test data and results for the characteristics specified below. Certification shall be provided prior to performing final acceptance inspection, and remain in effect throughout the performance of the contract. This does not relieve the contractor from inspection throughout the contract production, including recording data and results therefrom. Recorded data and results shall be made available to the Government upon request. A new certification shall be required whenever any change(s) occur in materials, manufacturing processes and techniques previously certified. Exception to the above may be provided by certificate of compliance (COC) for those items for which the contractor cannot obtain recorded data, i.e., off the shelf items. This exception shall not apply without prior approval by Frankford Arsenal. Request for approval shall include item name, part number, identification of supplier, and justification for exception; and shall be forwarded to Commander, Frankford Arsenal, ATTN: SARFA-Q4000.

CHARACTERISTIC	TEST DATA TO COMPLY WITH
Cleaning	3.3.1.9
Drying	3.3.1.10
Coating, insulating compound	3.3.1.11.2"

Paragraph 4.4.1, TABLE III, NO. 303: Add "MIL-P-46843."

* Paragraph 4.6.2, second sentence: Delete "Procedure II" and substitute "Procedure I".

* Paragraph 4.6.3, fourth sentence: Delete and substitute "The vibration test shall be performed in accordance with Figure 514-1 Curve C of MIL-STD-810 except double amplitude shall not exceed .036 inch."

Paragraph 4.6.4.1: Delete and substitute:

"Pulse resonse and input threshold.- Using pulse generator (Item 1 of 4.5.3), apply the pulses specified in 3.7.1 at a repetition rate which allows for convenient monitoring of the output on an oscilloscope. The requirements of paragraph 3.7.1 and 3.7.2 shall be met."

Figure 1: Delete "100 nSEC max". Also, delete "A = 1.5 min" and substitute "A".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:39Z
Check the source to verify that this is the current version before use.

* The margin of this specification is marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue."

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1240-A529

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:39Z
Check the source to verify that this is the current version before use.