NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/245D(IH)
20 December 2023
SUPERSEDING
MIL-DTL-3628/245C(IH)
6 July 2023

DETAIL SPECIFICATION SHEET

BADGE, NATIONAL SECURITY AGENCY


This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3628.



.

BASE



PIERCED

DEVICE



ASSEMBLED

AMSC N/A

FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:20Z
Check the source to verify that this is the current version before use.

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIALS:
BASE: Red Brass 85/15 (UNS Alloy No. C-230)
DEVICE: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH:
BASE: Epoxy resin (Floating epoxy): 24K Gold Plated Mirror-like Polished and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 6.
SIX-POINTED STAR: Nickle Plated Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16.
DEVICE: Epoxy resin (Stoning epoxy) 24K Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.

DIMENSIONS:
BASE:
DIAMETER:
-1 : 2 inches (REF)
-2: 1 -1/2 inches (REF)
THICKNESS (At thickest point):
-1 : 0.075 ± 0.010 inch
-2: 0.075 ± 0.010 inch
DEVICE:
HEIGHT:
-1 : 27/32 inch (REF)
-2: 5/8 inch (REF)
WIDTH:
-1: 13/16 inch(REF)
-2: 19/32 inch(REF)
THICKNESS (At thickest point):
-1 : 0.075 ± 0.010 inch
-2: 0.075 ± 0.010 inch
ASSEMBLED THICKNESS(At thickest point):
0.150 ± 0.010 inch

ATTACHING DEVICE:
1. The attaching device shall be prongs and wing-type clutch.

2. Three prongs shall be located on the reverse on 1-3/4 inches diameter circle for -1. Three prongs shall be located on the reverse on 1-1/4 inches diameter circle for -2. The prongs shall be spaced 120 degrees apart with the bottom prong located on the vertical center line 1/8 inch from the bottom.

3. -1 and -2 device may be attached to the base either by swedging or by riveting.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:20Z
Check the source to verify that this is the current version before use.

EPOXY: Epoxy resin shall be applied to the Badge as indicated above and shall match TIOH Hard Enamel Color Chip Numbers listed below. If hard enamel is used, then the material will be Gilding Metal 95/5 (UNS Alloy C-210).

Enamel Chip Number	Location
Red #1	Left to right 2nd & 4th Stripes on Device Shield, And Center Stripe on Device Shield
Blue #20	Center Sphere of Base around 6-pointed star
White #28	Designation Band & 1st & 3rd Stripes of Device Shield
Blue #33	Horizontal Bar of Shield under Eagle's Head

EPOXY:

1. Epoxy shall be floating on the base center sphere around the six-pointed star and the designation band. Epoxy shall be stoned on the device shield.

2. For epoxy placement, see attached manufacturing drawing, B-5-217

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. BASE: The base for -1 and -2 shall be two-tone gold and nickel plated. The outer and inner ring and letters in the designation band will be gold plated. The six-pointed star will be raised faceted, modelled and nickel plated. The star must be below the level of the designation band. The designation band will be filled with White #28 epoxy and floated. The background of the base will be filled with Blue # 20 floating epoxy. The device area on the base shall be slightly recessed for the device to be attached in a nested manner.

3. DEVICE: The shield for -1 and -2 shall be raised and modeled as the highest point of the device to allow for stoning. The shield for -2 will have three (3) stripes with red in the center. The eagle shall be fully modeled but lower than the shield. The eagle device shall be pierced as indicated for -1 and -2.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

.

Review activities:
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-2024-020)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:20Z
Check the source to verify that this is the current version before use.