NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/245E(IH)
12 August 2024
SUPERSEDING
MIL-DTL-3628/245D(IH)
20 December 2023

DETAIL SPECIFICATION SHEET

BADGE, IDENTIFICATION, NATIONAL SECURITY AGENCY


This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3628.

.



BASE



PIERCED

DEVICE



ASSEMBLED

AMSC N/A

FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:20Z
Check the source to verify that this is the current version before use.

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIALS:
BASE: Red Brass 85/15 (UNS Alloy No. C-230)
DEVICE: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH:
BASE: Epoxy resin (Floating epoxy): 24K Gold Plated Mirror-like Polished and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 6.
SIX-POINTED STAR: Nickle Plated Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16.
DEVICE: Epoxy resin (Stoning epoxy) 24K Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.

DIMENSIONS:
BASE:
DIAMETER:
-1 : 2 inches (REF)
-2: 1 -1/2 inches (REF)
THICKNESS (At thickest point):
-1 : 0.075 ± 0.010 inch
-2: 0.075 ± 0.010 inch
DEVICE:
HEIGHT:
-1 : 27/32 inch (REF)
-2: 5/8 inch (REF)
WIDTH:
-1: 13/16 inch (REF)
-2: 19/32 inch (REF)
THICKNESS (At thickest point):
-1 : 0.075 ± 0.010 inch
-2: 0.075 ± 0.010 inch
ASSEMBLED THICKNESS (At thickest point):
0.150 ± 0.010 inch

ATTACHING DEVICE:
1. The attaching device shall be prongs and wing-type clutch.

2. Three prongs shall be located on the reverse on 1-3/4 inches diameter circle for -1. Three prongs shall be located on the reverse on 1-1/4 inches diameter circle for -2. The prongs shall be spaced 120 degrees apart with the bottom prong located on the vertical center line 1/8 inch from the bottom.

3. -1 and -2 device may be attached to the base either by swedging or by riveting.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:20Z
Check the source to verify that this is the current version before use.

EPOXY: Epoxy resin shall be applied to the Badge as indicated above and shall match TIOH Hard Enamel Color Chip Numbers listed below. If hard enamel is used, then the material will be Gilding Metal 95/5 (UNS Alloy C-210).

Enamel Chip Number	Location
Red #1	-1: 2nd & 4th Stripes on Device Shield. -2: Center Stripe on Device Shield
Blue #20	Center Sphere of Base around 6-pointed star
White #28	-1: Designation Band and 1st, 3rd & 5th Stripes on Device Shield. -2: Designation Band and 1st and 3rd Stripes on Device Shield
Blue #33	Horizontal Bar of Shield under Eagle's Head

EPOXY:

1. Epoxy shall be floating on the base center sphere around the six-pointed star and the designation band. Epoxy shall be stoned on the device shield.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The shield for -1 has 5 stripes; the shield for -2 has 3 stripes. The stripes for both shields shall be epoxied alternating white and red, beginning with white and ending with white.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-2024-256)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:20Z
Check the source to verify that this is the current version before use.