MILITARY SPECIFICATION

INDICATOR, TEMPERATURE, ELECTRICAL RESISTANCE, MULTI-FUNCTION, -70° TO +150°C

This amendment forms a part of Military Specification MIL-I-6669C, dated 22 December 1972, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

3.1: Delete and substitute:

"3.1 Preproduction. The indicator furnished under this specification shall be a product which has been tested and has passed the preproduction tests specified."

PAGE 5

4.4: Delete and substitute:

"4.4 TEST METHODS".

4.4.1: Delete and substitute:

"4.4.1 PREPRODUCTION TESTS".

4.4.1.4: Delete and substitute:

"4.4.1.4 Sealing. When a mass spectrometer, or an equivalent quantitative measuring device of at least equal sensitivity is used, the total leak rate of the indicator shall not exceed one micron cubic foot per hour."

4.4.1.6: Delete in its entirety.

PAGE 6

*Table II: Delete and replace with new Table II.

PAGE 7

Following 4.4.2.8 add:

"4.4.2.9 Fogging. The indicator shall be placed in a 71° ±2°C controlled ambient temperature for a minimum of 1 hour. At the end of this period and while still at this temperature, an ice cube shall be rubbed on the indicator glass face for 1 minute ±5 seconds. The glass should be dried immediately (do not use compressed air).

FSC 6685

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:18Z
Check the source to verify that this is the current version before use.

6.4: Delete and substitute:

"6.4 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue."

Custodians:
Air Force - 99
Navy - AS

Review Activity:
DLA - GS

Preparing activity:
Air Force - 82

(Project 6685-0688)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:18Z
Check the source to verify that this is the current version before use.

TABLE II Test Tolerances

Test Point	Test Resistance	Scale Error at Room Temp	Reduced Voltage	Scale Error at Low Temp	Scale Error at High Temp	Scale Error at Room Temp After Vibration
°C	Ohms	Tol ±°C	Tol ±°C	Tol ±°C	Tol ±°C	Tol ±°C
-70	68.27	4.4 (5.0)	3.0 (3.0)	6.6 (6.6)	6.6 (6.6)	6.6 (6.6)
-30	80.56	4.4 (4.4)	3.0 (3.0)	6.6 (6.6)	6.6 (6.6)	6.6 (6.6)
0	90.38	4.4 (4.4)	2.0 (2.0)	6.6 (6.6)	6.6 (6.6)	6.6 (6.6)
+30	100.91	4.4 (4.4)	2.0 (2.0)	6.6 (6.6)	6.6 (6.6)	6.6 (6.6)
80	120.36	4.4 (4.4)	2.0 (2.0)	6.6 (6.6)	6.6 (6.6)	6.6 (6.6)
120	137.78	4.4 (4.4)	3.0 (3.0)	6.6 (6.6)	6.6 (6.6)	6.6 (6.6)
150	151.91	4.4 (5.0)	3.0 (3.0)	6.6 (6.6)	6.6 (6.6)	6.6 (6.6)

Test Point	Test Resistance	Scale Error at Room Temp after Open and Short Circuit	Scale Error With Bulb Lead Resistance	Extreme Temperature Exposure		
				Scale Error at Low Temp	Scale Error at Room Temp After Low Temp	Scale Error at Room Temp After High Temp
°C	Ohms	Tol ±°C	Tol ±°C	Tol ±°C	Tol ±°C	Tol ±°C
-70	68.27	6.6 (6.6)	3.0 (3)	9.5 (6.6)	6.6 (4.4)	6.6 (4.4)
-30	80.56	6.6 (6.6)	3.0 (3)	9.5 (6.6)	6.6 (4.4)	6.6 (4.4)
0	90.38	6.6 (6.6)	3.0 (3)	7.5 (6.6)	6.6 (4.4)	6.6 (4.4)
+30	100.91	6.6 (6.6)	3.0 (3)	7.5 (6.6)	6.6 (4.4)	6.6 (4.4)
80	120.36	6.6 (6.6)	3.0 (3)	7.5 (6.6)	6.6 (4.4)	6.6 (4.4)
120	137.78	6.6 (6.6)	3.0 (3)	9.5 (6.6)	6.6 (4.4)	6.6 (4.4)
150	151.91	6.6 (6.6)	3.0 (3)	9.5 (6.6)	6.6 (4.4)	6.6 (4.4)

Source: https://assist.dla.mil -- Downloaded: 2026-01-17T07:18Z
Check the source to verify that this is the current version before use.