INCH-POUND

MIL-PRF-24308/23D
23 March 1998
SUPERSEDING
MIL-PRF-24308/23C
2 December 1996

PERFORMANCE SPECIFICATION SHEET

CONNECTORS, ELECTRIC, RECTANGULAR, NONENVIRONMENTAL, MINIATURE,
POLARIZED SHELL, RACK AND PANEL,SOCKET CONTACTS
PRINTED WIRING BOARD TERMINATION TYPES

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein
shall consist of this specification and MIL-PRF-24308.

REQUIREMENTS:

The connectors shall conform to the design standards (MS standards) indicated in table I.

TABLE I. Design standards. 1/

Part or Identifying Number (PIN)	Shell size	Shell MS number	Insert MS number	Contact 1/	
				Mating end 2/	PWB tail
M24308/23-1	1	MS14058-1	MS18273-1	Size 20	Straight
M24308/23-2	2	MS14058-2	MS18274-1	Size 20	Straight
M24308/23-3	3	MS14058-3	MS18275-1	Size 20	Straight
M24308/23-4	4	MS14058-4	MS18276-1	Size 20	Straight
M24308/23-5	5	MS14058-5	MS18277-1	Size 20	Straight
M24308/23-7	1	MS14058-7	MS18273-1	Size 20	Straight
M24308/23-8	2	MS14058-8	MS18274-1	Size 20	Straight
M24308/23-9	3	MS14058-9	MS18275-1	Size 20	Straight
M24308/23-10	4	MS14058-10	MS18276-1	Size 20	Straight
M24308/23-11	5	MS14058-11	MS18277-1	Size 20	Straight
M24308/23-13	1	MS14058-13	MS18273-1	Size 20	Straight
M24308/23-14	2	MS14058-14	MS18274-1	Size 20	Straight
M24308/23-15	3	MS14058-15	MS18275-1	Size 20	Straight
M24308/23-16	4	MS14058-16	MS18276-1	Size 20	Straight
M24308/23-17	5	MS14058-17	MS18277-1	Size 20	Straight
M24308/23-19	1	MS14058-19	MS18273-1	Size 20	Straight
M24308/23-20	2	MS14058-20	MS18274-1	Size 20	Straight
M24308/23-21	3	MS14058-21	MS18275-1	Size 20	Straight
M24308/23-22	4	MS14058-22	MS18276-1	Size 20	Straight
M24308/23-23	5	MS14058-23	MS18277-1	Size 20	Straight
M24308/23-25	1	MS14058-25	MS18273-1	Size 20	Rt angle

See footnotes at end of table.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:10Z
Check the source to verify that this is the current version before use.

TABLE I. Design standards - Continued.

Part or Identifying Number (PIN)	Shell size	Shell MS number	Insert MS number	Contact 1/	
				Mating end 2/	PWB tail
M24308/23-26	2	MS14058-26	MS18274-1	Size 20	Rt angle
M24308/23-27	3	MS14058-27	MS18275-1	Size 20	Rt angle
M24308/23-28	4	MS14058-28	MS18276-1	Size 20	Rt angle
M24308/23-29	5	MS14058-29	MS18277-1	Size 20	Rt angle
M24308/23-31	1	MS14058-31	MS18273-1	Size 20	Rt angle
M24308/23-32	2	MS14058-32	MS18274-1	Size 20	Rt angle
M24308/23-33	3	MS14058-33	MS18275-1	Size 20	Rt angle
M24308/23-34	4	MS14058-34	MS18276-1	Size 20	Rt angle
M24308/23-35	5	MS14058-35	MS18277-1	Size 20	Rt angle
M24308/23-37	1	MS14058-37	MS18273-1	Size 20	Rt angle
M24308/23-38	2	MS14058-38	MS18274-1	Size 20	Rt angle
M24308/23-39	3	MS14058-39	MS18275-1	Size 20	Rt angle
M24308/23-40	4	MS14058-40	MS18276-1	Size 20	Rt angle
M24308/23-41	5	MS14058-41	MS18277-1	Size 20	Rt angle
M24308/23-43	1	MS14058-43	MS18273-1	Size 20	Rt angle
M24308/23-44	2	MS14058-44	MS18274-1	Size 20	Rt angle
M24308/23-45	3	MS14058-45	MS18275-1	Size 20	Rt angle
M24308/23-46	4	MS14058-46	MS18276-1	Size 20	Rt angle
M24308/23-47	5	MS14058-47	MS18277-1	Size 20	Rt angle
M24308/23-49	1	MS14058-49	MS18273-1	Size 20	Rt angle
M24308/23-50	2	MS14058-50	MS18274-1	Size 20	Rt angle
M24308/23-51	3	MS14058-51	MS18275-1	Size 20	Rt angle
M24308/23-52	4	MS14058-52	MS18276-1	Size 20	Rt angle
M24308/23-53	5	MS14058-53	MS18277-1	Size 20	Rt angle
M24308/23-55	1	MS14058-55	MS18273-1	Size 20	Rt angle
M24308/23-56	2	MS14058-56	MS18274-1	Size 20	Rt angle
M24308/23-57	3	MS14058-57	MS18275-1	Size 20	Rt angle
M24308/23-58	4	MS14058-58	MS18276-1	Size 20	Rt angle
M24308/23-59	5	MS14058-59	MS18277-1	Size 20	Rt angle
M24308/23-61	1	MS14058-61	MS18273-2	Size 22	Straight
* M24308/23-62	2	MS14058-62	MS18274-2	Size 22	Straight
M24308/23-63	3	MS14058-63	MS18275-2	Size 22	Straight
M24308/23-64	4	MS14058-64	MS18276-2	Size 22	Straight
M24308/23-65	5	MS14058-65	MS18277-2	Size 22	Straight
M24308/23-67	1	MS14058-67	MS18273-2	Size 22	Straight
M24308/23-68	2	MS14058-68	MS18274-2	Size 22	Straight
M24308/23-69	3	MS14058-69	MS18275-2	Size 22	Straight
M24308/23-70	4	MS14058-70	MS18276-2	Size 22	Straight
M24308/23-71	5	MS14058-71	MS18277-2	Size 22	Straight
M24308/23-73	1	MS14058-73	MS18273-2	Size 22	Rt angle
M24308/23-74	2	MS14058-74	MS18274-2	Size 22	Rt angle
M24308/23-75	3	MS14058-75	MS18275-2	Size 22	Rt angle
M24308/23-76	4	MS14058-76	MS18276-2	Size 22	Rt angle
M24308/23-77	5	MS14058-77	MS18277-2	Size 22	Rt angle

1/ These socket contacts are in accordance with MS14058 for connection to printed circuit boards.
2/ Socket contact shall accommodate .041/.039 inch (1.04/.99 mm) diameter pin.

NOTE: Qualification by similarity: Qualification of connectors of one shell size of one configuration with a specific printed wiring tail length and diameter shall qualify all connectors of the same shell size and configuration with all other printed wiring tail lengths and diameters.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:10Z
Check the source to verify that this is the current version before use.

PIN: Consists of the letter M, the basic number of the specifications sheet, and a dash number compiled from the code.

PIN example: M24308/23 -90 F

Specification sheet number

Dash sheet number from table I

Finish: Cadmium = F
No suffix letter = cadmium or zinc
P = Passivated steel

The margins of this specification are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA

Preparing activity:
DLA - CC

Review activities:
Army - AT, AV, CR-4, MI
Navy - AS, CG, MC, SH
Air Force - 99

(Project: 5935-4123-01)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:10Z
Check the source to verify that this is the current version before use.