INCH-POUND

MIL-DTL-24308/23F
25 June 2007
SUPERSEDING
MIL-DTL-24308/23E
4 April 2001

DETAIL SPECIFICATION SHEET

# CONNECTORS, ELECTRIC, RECTANGULAR, NONENVIRONMENTAL, MINIATURE, POLARIZED SHELL, RACK AND PANEL,SOCKET CONTACTS PRINTED WIRING BOARD TERMINATION TYPES

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-24308





FIGURE 1. Shell, receptacle, printed wiring board type.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:10Z
Check the source to verify that this is the current version before use.







FIGURE 1. Shell, receptacle, printed wiring board – Continued.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:10Z
Check the source to verify that this is the current version before use.




CONFIGURATION 4 - RIGHT ANGLE TAILS

FIGURE 1. Shell, receptacle, printed wiring board – Continued.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:10Z
Check the source to verify that this is the current version before use.

Dimensions and configurations

| Shell Size | A | B | C | D | E | F | G | H | J | K | L |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 1.228 (31.19) 1.198 (30.43) | .648 (16.46) .638 (16.21) | .989 (25.12) .979 (24.87) | .316 (8.03) .306 (7.77) | .509 (12.93) .479 (12.17) | .439 (11.15) .419 (10.64) | .248 (6.30) .238 (6.05) | .769 (19.53) .749 (19.02) | .432 (10.97) .412 (10.46) | .060 (1.52) .035 (0.89) | .040 (1.02) .020 (0.51) |
| 2 | 1.556 (39.52) 1.526 (38.76) | .976 (24.79) .966 (24.54) | 1.317 (33.45) 1.307 (33.20) | .316 (8.03) .306 (7.77) | .509 (12.93) .479 (12.17) | .439 (11.15) .419 (10.64) | .248 (6.30) .238 (6.05) | 1.093 (27.76) 1.073 (27.25) | .432 (10.97) .412 (10.46) | .060 (1.52) .035 (0.89) | .040 (1.02) .020 (0.51) |
| 3 | 2.103 (53.42) 2.073 (52.65) | 1.516 (38.51) 1.506 (38.25) | 1.857 (47.17) 1.847 (46.91) | .316 (8.03) .306 (7.77) | .509 (12.93) .479 (12.17) | .439 (11.15) .419 (10.64) | .248 (6.30) .238 (6.05) | 1.635 (41.53) 1.615) (41.02) | .432 (10.97) .412 (10.46) | .060 (1.52) .035 (0.89) | .049 (1.24) .029 (0.74) |
| 4 | 2.744 (69.70) 2.714 (68.94) | 2.164 (54.97) 2.154 (54.71) | 2.505 (63.63) 2.495 (63.37) | .316 (8.03) .306 (7.77) | .509 (12.93) .479 (12.17) | .439 (11.15) .419 (10.64) | .248 (6.30) .238 (6.05) | 2.282 (57.96) 2.262 (57.45) | .432 (10.97) .412 (10.46) | .060 (1.52) .035 (0.89) | .049 (1.24) .029 (0.74) |
| 5 | 2.650 (67.31) 2.620 (66.55) | 2.069 (52.55) 2.059 (52.30 | 2.411 (61.24) 2.401 (60.99) | .428 (10.87) .418 (10.62) | .620 (15.75) .590 (14.00) | .439 (11.15) .419 (10.64) | .248 (6.30) .238 (6.05) | 2.188 (55.58) 2.168 (55.07) | .544 (13.82) .524 (13.31) | .060 (1.52) .035 (0.89) | .049 (1.24) .029 (0.74) |

Application data and dimensions.

| Applicable dash number M24308/23 | Applicable Configurations | Applicable board thickness | Nominal pin diameter | M | N |
|---|---|---|---|---|---|
| -1 through –5 (See note 16) | 1 and 2 | .094 (2.39 mm) | .030 (0.76 mm) | .185 (4.70 mm) .130 (3.30 mm) | .033 (0.84 mm) .027 (.027 mm) |
| -7 through –11 (See note 16) | 1 and 2 | .125 (3.18 mm) | .030 (0.76 mm) | .210 (5.33 mm) .155 (3.94 mm) | .033 (0.84 mm) .027 (.027 mm) |
| -13 through –17 (See note 16) | 1 and 2 | .094 (2.39 mm) | .040 (1.02 mm) | .185 (4.70 mm) .130 (3.30 mm) | .043 (1.09 mm) .037 (0.94 mm) |
| -19 through –23 (See note 16) | 1 and 2 | .125 (3.18 mm) | .040 (1.02 mm) | .210 (5.33 mm) .155 (3.94 mm) | .043 (1.09 mm) .037 (0.94 mm) |
| -25 through –29 (See note 16) | 1 and 3 | .062 (1.57 mm) | .030 (0.76 mm) | .154 (3.91 mm) .099 (2.51 mm) | .033 (0.84 mm) .027 (.027 mm) |
| -31 through –35 (See note 16) | 1 and 3 | .094 (2.39 mm) | .030 (0.76 mm) | .185 (4.70 mm) .130 (3.30 mm) | .033 (0.84 mm) .027 (.027 mm) |
| -37 through –41 (See note 16) | 1 and 3 | .062 (1.57 mm) | .040 (1.02 mm) | .154 (3.91 mm) .099 (2.51 mm) | .043 (1.09 mm) .037 (0.94 mm) |
| -43 through –47 (See note 16) | 1 and 3 | .094 (2.39 mm) | .040 (1.02 mm) | .185 (4.70 mm) .130 (3.30 mm) | .043 (1.09 mm) .037 (0.94 mm) |
| -49 through –53 (See note 16) | 1 and 3 | .125 (3.18 mm) | .030 (0.76 mm) | .210 (5.33 mm) .155 (3.94 mm) | .033 (0.84 mm) .027 (.027 mm) |
| -55 through –59 (See note 16) | 1 and 3 | .125 (3.18 mm) | .040 (1.02 mm) | .210 (5.33 mm) .155 (3.94 mm) | .043 (1.09 mm) .037 (0.94 mm) |
| -61 through –65 (See note 16) | 1 and 2 | .094 (2.39 mm) | .020 (0.51 mm) | .185 (4.70 mm) .130 (3.30 mm) | .023 (0.58 mm) .017 (0.43 mm) |
| -67 through –71 (See note 16) | 1 and 2 | .125 (3.18 mm) | .020 (0.51 mm) | .320 (8.13 mm) .275 (6.99 mm) | .023 (0.58 mm) .017 (0.43 mm) |
| -73 through –77 (See note 16) | 1 and 4 | .062 (1.57 mm) | .020 (0.51 mm) | .154 (3.91 mm) .099 (2.51 mm) | .023 (0.58 mm) .017 (0.43 mm) |

FIGURE 1. Shell, receptacle, printed wiring board type - Continued.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:10Z
Check the source to verify that this is the current version before use.

| Inches | mm | Inches | mm | Inches | mm |
|---|---|---|---|---|---|
| .005 | 0.13 | .092 | 2.34 | .247 | 6.27 |
| .010 | 0.25 | .097 | 2.46 | .251 | 6.38 |
| .015 | 0.38 | .103 | 2.62 | .283 | 7.19 |
| .030 | 0.76 | .112 | 2.84 | .302 | 7.67 |
| .040 | 1.02 | .115 | 2.92 | .340 | 8.64 |
| .041 | 1.04 | .120 | 3.05 | .395 | 10.03 |
| .062 | 1.57 | .125 | 3.18 | .484 | 12.29 |
| .065 | 1.65 | .135 | 3.43 | .507 | 12.88 |
| .070 | 1.78 | .149 | 3.78 | .594 | 15.09 |

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Socket contact shall accommodate .041/.039 (1.04/0.99 mm) diameter pin for size 20 contacts and .0305/.0295 (.775/.749 mm) diameter pin for size 22D contacts.
4. Point of electrical engagement. Use .0393/,0390 (1.00/0.99 mm) diameter square ended test pin.
5. Applicable insert patterns see MIL-DTL-24308, appendix A.
6. Copyright notice. All information disclosed in this military specification sheet which is or may be copyrighted by ITT Cannon Electric is reproduced herein with the expressed permission of the copyright owner.
7. The 90 ° bracket shall be one piece flame resistant glass-filled nylon, polyester or two piece metal and nylon of which the metal pieces shall be coated with a material in accordance with IPC-CC-830.
8. The 90 ° bracket shall be furnished as an integral part of the connector assembly.
9. Spacers will be supplied with connectors (not attached to the connector).
10. Layout shown for reference only to locate $C_L$. See applicable insert arrangement.
11. Requirement for contact retention shall be 3.5 lbs. for right angle printed circuit board mount connectors. Connectors may be fastened to board for test.
12. Unless otherwise specified, tolerance is ± .010 inch (0.25 mm).
13. In the event of a conflict between the text of this specification sheet and the references cited herein, the text of this specification sheet shall take precedence.
14. Referenced Governments documents of the issue listed in ASSIST Online database at http://assist.daps.dla.mil/ specified in the solicitation form a part of this standard to the extent specified herein.
15. Indentation on the ends of the termination side of the shell, for the purpose of securing the insulator in the shell, is permitted. This may result in the “F” dimension being undersized in these areas. However the “F” dimension shall be maintained for the remainder of the connector.
16. For classes M, N and D use table I for applicable dash numbers.

FIGURE 1. Shell, receptacle, printed wiring board type - Continued.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:10Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

The connectors shall conform to figure 1 and the specification Part or Identifying Numbers (PIN) indicated in table I.

TABLE I. Design standards. 1/

| PIN Class G | PIN Class M | PIN Class N | PIN Class D | Shell size | Shell detail configurations | Insert arrangement reference number 2/ | Contact | |
|---|---|---|---|---|---|---|---|---|
| | | | | | | | Mating end | PWB tail |
| M24308/23-1 | M24308/23-101 | M24308/23-201 | M24308/23-301 | 1 | 1 and 2 | A-1-1 | Size 20 | Straight |
| M24308/23-2 | M24308/23-102 | M24308/23-202 | M24308/23-302 | 2 | 1 and 2 | A-2-1 | Size 20 | Straight |
| M24308/23-3 | M24308/23-103 | M24308/23-203 | M24308/23-303 | 3 | 1 and 2 | A-3-1 | Size 20 | Straight |
| M24308/23-4 | M24308/23-104 | M24308/23-204 | M24308/23-304 | 4 | 1 and 2 | A-4-1 | Size 20 | Straight |
| M24308/23-5 | M24308/23-105 | M24308/23-205 | M24308/23-305 | 5 | 1 and 2 | A-5-1 | Size 20 | Straight |
| M24308/23-7 | M24308/23-107 | M24308/23-207 | M24308/23-307 | 1 | 1 and 2 | A-1-1 | Size 20 | Straight |
| M24308/23-8 | M24308/23-108 | M24308/23-208 | M24308/23-308 | 2 | 1 and 2 | A-2-1 | Size 20 | Straight |
| M24308/23-9 | M24308/23-109 | M24308/23-209 | M24308/23-309 | 3 | 1 and 2 | A-3-1 | Size 20 | Straight |
| M24308/23-10 | M24308/23-110 | M24308/23-210 | M24308/23-310 | 4 | 1 and 2 | A-4-1 | Size 20 | Straight |
| M24308/23-11 | M24308/23-111 | M24308/23-211 | M24308/23-311 | 5 | 1 and 2 | A-5-1 | Size 20 | Straight |
| M24308/23-13 | M24308/23-113 | M24308/23-213 | M24308/23-313 | 1 | 1 and 2 | A-1-1 | Size 20 | Straight |
| M24308/23-14 | M24308/23-114 | M24308/23-214 | M24308/23-314 | 2 | 1 and 2 | A-2-1 | Size 20 | Straight |
| M24308/23-15 | M24308/23-115 | M24308/23-215 | M24308/23-315 | 3 | 1 and 2 | A-3-1 | Size 20 | Straight |
| M24308/23-16 | M24308/23-116 | M24308/23-216 | M24308/23-316 | 4 | 1 and 2 | A-4-1 | Size 20 | Straight |
| M24308/23-17 | M24308/23-117 | M24308/23-217 | M24308/23-317 | 5 | 1 and 2 | A-5-1 | Size 20 | Straight |
| M24308/23-19 | M24308/23-119 | M24308/23-219 | M24308/23-319 | 1 | 1 and 2 | A-1-1 | Size 20 | Straight |
| M24308/23-20 | M24308/23-120 | M24308/23-220 | M24308/23-320 | 2 | 1 and 2 | A-2-1 | Size 20 | Straight |
| M24308/23-21 | M24308/23-121 | M24308/23-221 | M24308/23-321 | 3 | 1 and 2 | A-3-1 | Size 20 | Straight |
| M24308/23-22 | M24308/23-122 | M24308/23-222 | M24308/23-322 | 4 | 1 and 2 | A-4-1 | Size 20 | Straight |
| M24308/23-23 | M24308/23-123 | M24308/23-223 | M24308/23-323 | 5 | 1 and 2 | A-5-1 | Size 20 | Straight |
| M24308/23-25 | M24308/23-125 | M24308/23-225 | M24308/23-325 | 1 | 1 and 3 | A-1-1 | Size 20 | Rt Angle |
| M24308/23-26 | M24308/23-126 | M24308/23-226 | M24308/23-326 | 2 | 1 and 3 | A-2-1 | Size 20 | Rt Angle |
| M24308/23-27 | M24308/23-127 | M24308/23-227 | M24308/23-327 | 3 | 1 and 3 | A-3-1 | Size 20 | Rt Angle |
| M24308/23-28 | M24308/23-128 | M24308/23-228 | M24308/23-328 | 4 | 1 and 3 | A-4-1 | Size 20 | Rt Angle |
| M24308/23-29 | M24308/23-129 | M24308/23-229 | M24308/23-329 | 5 | 1 and 3 | A-5-1 | Size 20 | Rt Angle |
| M24308/23-31 | M24308/23-131 | M24308/23-231 | M24308/23-331 | 1 | 1 and 3 | A-1-1 | Size 20 | Rt Angle |
| M24308/23-32 | M24308/23-132 | M24308/23-232 | M24308/23-332 | 2 | 1 and 3 | A-2-1 | Size 20 | Rt Angle |
| M24308/23-33 | M24308/23-133 | M24308/23-233 | M24308/23-333 | 3 | 1 and 3 | A-3-1 | Size 20 | Rt Angle |
| M24308/23-34 | M24308/23-134 | M24308/23-234 | M24308/23-334 | 4 | 1 and 3 | A-4-1 | Size 20 | Rt Angle |
| M24308/23-35 | M24308/23-135 | M24308/23-235 | M24308/23-335 | 5 | 1 and 3 | A-5-1 | Size 20 | Rt Angle |
| M24308/23-37 | M24308/23-137 | M24308/23-237 | M24308/23-337 | 1 | 1 and 3 | A-1-1 | Size 20 | Rt Angle |
| M24308/23-38 | M24308/23-138 | M24308/23-238 | M24308/23-338 | 2 | 1 and 3 | A-2-1 | Size 20 | Rt Angle |
| M24308/23-39 | M24308/23-139 | M24308/23-239 | M24308/23-339 | 3 | 1 and 3 | A-3-1 | Size 20 | Rt Angle |
| M24308/23-40 | M24308/23-140 | M24308/23-240 | M24308/23-340 | 4 | 1 and 3 | A-4-1 | Size 20 | Rt Angle |
| M24308/23-41 | M24308/23-141 | M24308/23-241 | M24308/23-341 | 5 | 1 and 3 | A-5-1 | Size 20 | Rt Angle |
| M24308/23-43 | M24308/23-143 | M24308/23-243 | M24308/23-343 | 1 | 1 and 3 | A-1-1 | Size 20 | Rt Angle |
| M24308/23-44 | M24308/23-144 | M24308/23-244 | M24308/23-344 | 2 | 1 and 3 | A-2-1 | Size 20 | Rt Angle |
| M24308/23-45 | M24308/23-145 | M24308/23-245 | M24308/23-345 | 3 | 1 and 3 | A-3-1 | Size 20 | Rt Angle |
| M24308/23-46 | M24308/23-146 | M24308/23-246 | M24308/23-346 | 4 | 1 and 3 | A-4-1 | Size 20 | Rt Angle |
| M24308/23-47 | M24308/23-147 | M24308/23-247 | M24308/23-347 | 5 | 1 and 3 | A-5-1 | Size 20 | Rt Angle |

See footnotes at end of table.

TABLE I. Design standards - Continued.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:10Z
Check the source to verify that this is the current version before use.

| PIN Class G | PIN Class M | PIN Class N | PIN Class D | Shell size | Shell detail configurations | Insert arrangement reference number 1/ | Contact | |
|---|---|---|---|---|---|---|---|---|
| | | | | | | | Mating end | PWB tail |
| M24308/23-49 | M24308/23-149 | M24308/23-249 | M24308/23-349 | 1 | 1 and 3 | A-1-1 | Size 20 | Rt Angle |
| M24308/23-50 | M24308/23-150 | M24308/23-250 | M24308/23-350 | 2 | 1 and 3 | A-2-1 | Size 20 | Rt Angle |
| M24308/23-51 | M24308/23-151 | M24308/23-251 | M24308/23-351 | 3 | 1 and 3 | A-3-1 | Size 20 | Rt Angle |
| M24308/23-52 | M24308/23-152 | M24308/23-252 | M24308/23-352 | 4 | 1 and 3 | A-4-1 | Size 20 | Rt Angle |
| M24308/23-53 | M24308/23-153 | M24308/23-253 | M24308/23-353 | 5 | 1 and 3 | A-5-1 | Size 20 | Rt Angle |
| M24308/23-55 | M24308/23-155 | M24308/23-255 | M24308/23-355 | 1 | 1 and 3 | A-1-1 | Size 20 | Rt Angle |
| M24308/23-56 | M24308/23-156 | M24308/23-256 | M24308/23-356 | 2 | 1 and 3 | A-2-1 | Size 20 | Rt Angle |
| M24308/23-57 | M24308/23-157 | M24308/23-257 | M24308/23-357 | 3 | 1 and 3 | A-3-1 | Size 20 | Rt Angle |
| M24308/23-58 | M24308/23-158 | M24308/23-258 | M24308/23-358 | 4 | 1 and 3 | A-4-1 | Size 20 | Rt Angle |
| M24308/23-59 | M24308/23-159 | M24308/23-259 | M24308/23-359 | 5 | 1 and 3 | A-5-1 | Size 20 | Rt Angle |
| M24308/23-61 | M24308/23-161 | M24308/23-261 | M24308/23-361 | 1 | 1 and 2 | A-1-2 | Size 22 | Straight |
| M24308/23-62 | M24308/23-162 | M24308/23-262 | M24308/23-362 | 2 | 1 and 2 | A-2-2 | Size 22 | Straight |
| M24308/23-63 | M24308/23-163 | M24308/23-263 | M24308/23-363 | 3 | 1 and 2 | A-3-2 | Size 22 | Straight |
| M24308/23-64 | M24308/23-164 | M24308/23-264 | M24308/23-364 | 4 | 1 and 2 | A-4-2 | Size 22 | Straight |
| M24308/23-65 | M24308/23-165 | M24308/23-265 | M24308/23-3 65 | 5 | 1 and 2 | A-5-2 | Size 22 | Straight |
| M24308/23-67 | M24308/23-167 | M24308/23-267 | M24308/23-367 | 1 | 1 and 2 | A-1-2 | Size 22 | Straight |
| M24308/23-68 | M24308/23-168 | M24308/23-268 | M24308/23-368 | 2 | 1 and 2 | A-2-2 | Size 22 | Straight |
| M24308/23-69 | M24308/23-169 | M24308/23-269 | M24308/23-369 | 3 | 1 and 2 | A-3-2 | Size 22 | Straight |
| M24308/23-70 | M24308/23-170 | M24308/23-270 | M24308/23-370 | 4 | 1 and 2 | A-4-2 | Size 22 | Straight |
| M24308/23-71 | M24308/23-171 | M24308/23-271 | M24308/23-371 | 5 | 1 and 2 | A-5-2 | Size 22 | Straight |
| M24308/23-73 | M24308/23-173 | M24308/23-273 | M24308/23-373 | 1 | 1 and 4 | A-1-2 | Size 22 | Rt Angle |
| M24308/23-74 | M24308/23-174 | M24308/23-274 | M24308/23-374 | 2 | 1 and 4 | A-2-2 | Size 22 | Rt Angle |
| M24308/23-75 | M24308/23-175 | M24308/23-275 | M24308/23-375 | 3 | 1 and 4 | A-3-2 | Size 22 | Rt Angle |
| M24308/23-76 | M24308/23-176 | M24308/23-276 | M24308/23-376 | 4 | 1 and 4 | A-4-2 | Size 22 | Rt Angle |
| M24308/23-77 | M24308/23-177 | M24308/23-277 | M24308/23-377 | 5 | 1 and 4 | A-5-2 | Size 22 | Rt Angle |

1/ These connectors mate with connectors specified in MIL-DTL-24308/3, MIL-DTL-24308/4, MIL-DTL-24308/6, and MIL-DTL-24308/24.

2/ For insert arrangements see MIL-DTL-24308, Appendix A.

NOTE: Qualification by similarity: Qualification of connectors of one shell size of one configuration with a specific printed wiring tail length and diameter shall qualify all connectors of the same shell size and configuration with all other printed wiring tail lengths and diameters.

Contact retention: Not applicable.

PIN: Consists of the letter M, the basic number of the specifications sheet, and a dash number compiled from the code.

PIN example: M24308/23 -50 F

Specification sheet number

Dash sheet number from table I

Finish: For class G and N:

F = Cadmium
Z = zinc (See MIL-DTL-24308 for disposition of stock for “No suffix” finish)
P = Passivated steel

For class M:

Class M connectors have a gold finish, no suffix is required.

For class D:

Class D connectors have a nickel finish, no suffix is required.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:10Z
Check the source to verify that this is the current version before use.

Reference documents. In addition to MIL-DTL-24308, this document references the following:

MIL-DTL-24308/3
MIL-DTL-24308/4
MIL-DTL-24308/6
MIL-DTL-24308/24
IPC-CC-830

CHANGES FROM PREVIOUS ISSUE: The margins of this specification are marked with vertical lines to indicate where changes from previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 11
NASA - NA
DLA - CC

Preparing activity:
DLA - CC

(Project: 5935-4795-000)

Review activities:
Army - AT, AV, CR4, MI
Navy - AS, CG, MC, SH
Air Force - 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil .



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:10Z
Check the source to verify that this is the current version before use.