MILITARY SPECIFICATION SHEET

CONNECTORS, ELECTRIC, RECTANGULAR, NONENVIRONMENTAL, MINIATURE, POLARIZED SHELL, RACK AND PANEL, PIN CONTACTS, PRINTED WIRING BOARD TERMINATION TYPES

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the connectors described herein shall consist of this document and the latest issue of Specification MIL-C-24308.

The connectors shall conform to the design standards (MS Nos.) indicated in TABLE I.

TABLE I. Design standards.

Part Number	Shell Size	Shell MS No.	Insert MS No.	Contact 1/	
				Mating end 2/	PWB tail
M24308/24 - 1	1	MS14059 - 1	MS18273-1	Size 20	Straight
M24308/24 - 2	2	MS14059 - 2	MS18274-1	Size 20	Straight
M24308/24 - 3	3	MS14059 - 3	MS18275-1	Size 20	Straight
M24308/24 - 4	4	MS14059 - 4	MS18276-1	Size 20	Straight
M24308/24 - 5	5	MS14059 - 5	MS18277-1	Size 20	Straight
M24308/24 - 7	1	MS14059 - 7	MS18273-1	Size 20	Straight
M24308/24 - 8	2	MS14059 - 8	MS18274-1	Size 20	Straight
M24308/24 - 9	3	MS14059 - 9	MS18275-1	Size 20	Straight
M24308/24 -10	4	MS14059 -10	MS18276-1	Size 20	Straight
M24308/24 -11	5	MS14059 -11	MS18277-1	Size 20	Straight
M24308/24 -13	1	MS14059 -13	MS18273-1	Size 20	Straight
M24308/24 -14	2	MS14059 -14	MS18274-1	Size 20	Straight
M24308/24 -15	3	MS14059 -15	MS18275-1	Size 20	Straight
M24308/24 -16	4	MS14059 -16	MS18276-1	Size 20	Straight
M24308/24 -17	5	MS14059 -17	MS18277-1	Size 20	Straight
M24308/24 -19	1	MS14059 -19	MS18273-1	Size 20	Straight
M24308/24 -20	2	MS14059 -20	MS18274-1	Size 20	Straight
M24308/24 -21	3	MS14059 -21	MS18275-1	Size 20	Straight
M24308/24 -22	4	MS14059 -22	MS18276-1	Size 20	Straight
M24308/24 -23	5	MS14059 -23	MS18277-1	Size 20	Straight
M24308/24 -25	1	MS14059 -25	MS18273-1	Size 20	Rt angle
M24308/24 -26	2	MS14059 -26	MS18274-1	Size 20	Rt angle
M24308/24 -27	3	MS14059 -27	MS18275-1	Size 20	Rt angle
M24308/24 -28	4	MS14059 -28	MS18276-1	Size 20	Rt angle
M24308/24 -29	5	MS14059 -29	MS18277-1	Size 20	Rt angle
M24308/24 -31	1	MS14059 -31	MS18273-1	Size 20	Rt angle
M24308/24 -32	2	MS14059 -32	MS18274-1	Size 20	Rt angle

See footnote at end of table.

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:11Z
Check the source to verify that this is the current version before use.

TABLE I. Design standards. - Continued

Part Number	Shell Size	Shell MS No.	Insert MS No.	Contact 1/	
				Mating end 2/	PWB tail
M24308/24 -33	3	MS14059 -33	MS18275-1	Size 20	Rt angle
M24308/24 -34	4	MS14059 -34	MS18276-1	Size 20	Rt angle
M24308/24 -35	5	MS14059 -35	MS18277-1	Size 20	Rt angle
M24308/24 -37	1	MS14059 -37	MS18273-1	Size 20	Rt angle
M24308/24 -38	2	MS14059 -38	MS18274-1	Size 20	Rt angle
M24308/24 -39	3	MS14059 -39	MS18275-1	Size 20	Rt angle
M24308/24 -40	4	MS14059 -40	MS18276-1	Size 20	Rt angle
M24308/24 -41	5	MS14059 -41	MS18277-1	Size 20	Rt angle
M24308/24 -43	1	MS14059 -43	MS18273-1	Size 20	Rt angle
M24308/24 -44	2	MS14059 -44	MS18274-1	Size 20	Rt angle
M24308/24 -45	3	MS14059 -45	MS18275-1	Size 20	Rt angle
M24308/24 -46	4	MS14059 -46	MS18276-1	Size 20	Rt angle
M24308/24 -47	5	MS14059 -47	MS18277-1	Size 20	Rt angle
M24308/24 -49	1	MS14059 -49	MS18273-1	Size 20	Rt angle
M24308/24 -50	2	MS14059 -50	MS18274-1	Size 20	Rt angle
M24308/24 -51	3	MS14059 -51	MS18275-1	Size 20	Rt angle
M24308/24 -52	4	MS14059 -52	MS18276-1	Size 20	Rt angle
M24308/24 -53	5	MS14059 -53	MS18277-1	Size 20	Rt angle
M24308/24 -55	1	MS14059 -55	MS18273-1	Size 20	Rt angle
M24308/24 -56	2	MS14059 -56	MS18274-1	Size 20	Rt angle
M24308/24 -57	3	MS14059 -57	MS18275-1	Size 20	Rt angle
M24308/24 -58	4	MS14059 -58	MS18276-1	Size 20	Rt angle
M24308/24 -59	5	MS14059 -59	MS18277-1	Size 20	Rt angle

1/ These pin contacts are in accordance with MS14059 for connection to printed circuit boards.

2/ Pin contact mating end shall be .041/.039 inch (1.04/.99 mm)

NOTE: 1. Qualification by similarity: Qualification of connectors of one shell size of one configuration with a specific printed wiring tail length and diameter shall qualify all connectors of the same shell size and configuration with all other printed wiring tail lengths and diameters.

Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - MI, AV
Navy - AS
Air Force - 11, 99
DSA - ES

User activities:
Army - ME, AT
Navy - CG, MC, SH

Agent:
DSA - ES

Preparing activity:
Navy - EC

(Project 5935-3386-11)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:11Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-24308/24B	CONNECTORS, ELECTRIC, RECTANGULAR, NONENVIRONMENTAL, MINIATURE, POLARIZED SHELL, RACK AND PANEL, PIN CONTACTS, PRINTED WIRING BOARD TERMINATION TYPES

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*:
3b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:11Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY
Naval Electronic Systems Command
Washington, DC 20363

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, DC 20363
ATTN: ELEX 8111

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:11Z
Check the source to verify that this is the current version before use.