MILITARY SPECIFICATION SHEET

CONNECTORS, ELECTRIC, RECTANGULAR, NONENVIRONMENTAL, MINIATURE, POLARIZED SHELL, RACK AND PANEL, PIN CONTACTS, PRINTED WIRING BOARD TERMINATION TYPES

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation. MIL-C-24308.

REQUIREMENTS:

The connectors shall conform to the design standards (MS numbers) indicated in table I

TABLE I. Design standards

Part or Identifying Number (PIN)	Shell size	Shell MS number	Insert MS number	Contact 1/	
				Mating end 2/	PWB tail
M24308/24-1	1	MS14059-1	MS18273-1	Size 20	Straight
M24308/24-2	2	MS14059-2	MS18274-1	Size 20	Straight
M24308/24-3	3	MS14059-3	MS18275-1	Size 20	Straight
M24308/24-4	4	MS14059-4	MS18276-1	Size 20	Straight
M24308/24-5	5	MS14059-5	MS18277-1	Size 20	Straight
M24308/24-7	1	MS14059-7	MS18273-1	Size 20	Straight
M24308/24-8	2	MS14059-8	MS18274-1	Size 20	Straight
M24308/24-9	3	MS14059-9	MS18275-1	Size 20	Straight
M24308/24-10	4	MS14059-10	MS18276-1	Size 20	Straight
M24308/24-11	5	MS14059-11	MS18277-1	Size 20	Straight
M24308/24-13	1	MS14059-13	MS18273-1	Size 20	Straight
M24308/24-14	2	MS14059-14	MS18274-1	Size 20	Straight
M24308/24-15	3	MS14059-15	MS18275-1	Size 20	Straight
M24308/24-16	4	MS14059-16	MS18276-1	Size 20	Straight
M24308/24-17	5	MS14059-17	MS18277-1	Size 20	Straight
M24308/24-19	1	MS14059-19	MS18273-1	Size 20	Straight
M24308/24-20	2	MS14059-20	MS18274-1	Size 20	Straight
M24308/24-21	3	MS14059-21	MS18275-1	Size 20	Straight
M24308/24-22	4	MS14059-22	MS18276-1	Size 20	Straight
M24308/24-23	5	MS14059-23	MS18277-1	Size 20	Straight
M24308/24-25	1	MS14059-25	MS18273-1	Size 20	Rt angle

See footnotes at end of table.

© denotes changes

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:11Z
Check the source to verify that this is the current version before use.

© TABLE I. Design standards - Continued

PIN	Shell size	Shell MS number	Insert MS number	Contact 1/	
				Mating end 2/	PWB tail
M24308/24-26	2	MS14059-26	MS18274-1	Size 20	Rt angle
M24308/24-27	3	MS14059-27	MS18275-1	Size 20	Rt angle
M24308/24-28	4	MS14059-28	MS18276-1	Size 20	Rt angle
M24308/24-29	5	MS14059-29	MS18277-1	Size 20	Rt angle
M24308/24-31	1	MS14059-31	MS18273-1	Size 20	Rt angle
M24308/24-32	2	MS14059-32	MS18274-1	Size 20	Rt angle
M24308/24-33	3	MS14059-33	MS18275-1	Size 20	Rt angle
M24308/24-34	4	MS14059-34	MS18276-1	Size 20	Rt angle
M24308/24-35	5	MS14059-35	MS18277-1	Size 20	Rt angle
M24308/24-37	1	MS14059-37	MS18273-1	Size 20	Rt angle
M24308/24-38	2	MS14059-38	MS18274-1	Size 20	Rt angle
M24308/24-39	3	MS14059-39	MS18275-1	Size 20	Rt angle
M24308/24-40	4	MS14059-40	MS18276-1	Size 20	Rt angle
M24308/24-41	5	MS14059-41	MS18277-1	Size 20	Rt angle
M24308/24-43	1	MS14059-43	MS18273-1	Size 20	Rt angle
M24308/24-44	2	MS14059-44	MS18274-1	Size 20	Rt angle
M24308/24-45	3	MS14059-45	MS18275-1	Size 20	Rt angle
M24308/24-46	4	MS14059-46	MS18276-1	Size 20	Rt angle
M24308/24-47	5	MS14059-47	MS18277-1	Size 20	Rt angle
M24308/24-49	1	MS14059-49	MS18273-1	Size 20	Rt angle
M24308/24-50	2	MS14059-50	MS18274-1	Size 20	Rt angle
M24308/24-51	3	MS14059-51	MS18275-1	Size 20	Rt angle
M24308/24-52	4	MS14059-52	MS18276-1	Size 20	Rt angle
M24308/24-53	5	MS14059-53	MS18277-1	Size 20	Rt angle
M24308/24-55	1	MS14059-55	MS18273-1	Size 20	Rt angle
M24308/24-56	2	MS14059-56	MS18274-1	Size 20	Rt angle
M24308/24-57	3	MS14059-57	MS18275-1	Size 20	Rt angle
M24308/24-58	4	MS14059-58	MS18276-1	Size 20	Rt angle
M24308/24-59	5	MS14059-59	MS18277-1	Size 20	Rt angle
M24308/23-61	1	MS14059-61	MS18273-2	Size 22	Straight
M24308/23-62	2	MS14059-62	MS18274-2	Size 22	Straight
M24308/23-63	3	MS14059-63	MS18275-2	Size 22	Straight
M24308/23-64	4	MS14059-64	MS18276-2	Size 22	Straight
M24308/23-65	5	MS14059-65	MS18277-2	Size 22	Straight
M24308/23-67	1	MS14059-67	MS18273-2	Size 22	Straight
M24308/23-68	2	MS14059-68	MS18274-2	Size 22	Straight
M24308/23-69	3	MS14059-69	MS18275-2	Size 22	Straight
M24308/23-70	4	MS14059-70	MS18276-2	Size 22	Straight
M24308/23-71	5	MS14059-71	MS18277-2	Size 22	Straight
M24308/23-73	1	MS14059-73	MS18273-2	Size 22	Rt angle
M24308/23-74	2	MS14059-74	MS18274-2	Size 22	Rt angle
M24308/23-75	3	MS14059-75	MS18275-2	Size 22	Rt angle
M24308/23-76	4	MS14059-76	MS18276-2	Size 22	Rt angle
M24308/23-77	5	MS14059-77	MS18277-2	Size 22	Rt angle

1/ These pin contacts are in accordance with MS14059 for connection to printed circuit boards.
2/ Pin contact mating end shall be .041/.039 inch (1.04/.99 mm).

NOTE: Qualification by similarity. Qualification of connectors of one shell size of one configuration with a specific printed wiring tail length and diameter shall qualify all connectors of the same shell size and configuration with all other printed wiring tail lengths and diameters.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:11Z
Check the source to verify that this is the current version before use.

© PIN Consists of the letter M, the basic number of the specification sheet, and a dash number compiled from the code.

PIN example M24308/24 -87 F

Specification sheet number

Dash sheet number from table I

Finish. Cadmium = F
No suffix letter = cadmium or zinc.

Custodians
Army - CR
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AV, MI
Navy - AS
Air Force - 11, 99
DLA - ES

User activities
Army - AT, ME
Navy - CG, MC, SH

Preparing activity
Navy - EC

Agent
DLA - ES

(Project 5935-3672-03)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:11Z
Check the source to verify that this is the current version before use.