INCH-POUND
MIL-PRF-24308/24D
2 December 1996
SUPERSEDING
MIL-C-24308/24C
26 January 1989

PERFORMANCE SPECIFICATION
CONNECTORS, ELECTRIC, RECTANGULAR, NONENVIRONMENTAL, MINIATURE, POLARIZED SHELL, RACK AND PANEL,SOCKET CONTACTS PRINTED WIRING BOARD TERMINATION TYPES

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-PRF-24308 listed in that issue of the Department of Defense Index of Specification and Standards (DoDISS).

REQUIREMENTS:

The connectors shall conform to the design standards (MS standards) indicated in table I.

TABLE I. Design standards.

Part or identifying number (PIN)	Shell size	Shell MS number	Insert MS number	Contact 1/	
				Mating end 2/	PWB tail
M24308/24-1	1	MS14059-1	MS18273-1	Size 20	Straight
M24308/24-2	2	MS14059-2	MS18274-1	Size 20	Straight
M24308/24-3	3	MS14059-3	MS18275-1	Size 20	Straight
M24308/24-4	4	MS14059-4	MS18276-1	Size 20	Straight
M24308/24-5	5	MS14059-5	MS18277-1	Size 20	Straight
M24308/24-7	1	MS14059-7	MS18273-1	Size 20	Straight
M24308/24-8	2	MS14059-8	MS18274-1	Size 20	Straight
M24308/24-9	3	MS14059-9	MS18275-1	Size 20	Straight
M24308/24-10	4	MS14059-10	MS18276-1	Size 20	Straight
M24308/24-11	5	MS14059-11	MS18277-1	Size 20	Straight
M24308/24-13	1	MS14059-13	MS18273-1	Size 20	Straight
M24308/24-14	2	MS14059-14	MS18274-1	Size 20	Straight
M24308/24-15	3	MS14059-15	MS18275-1	Size 20	Straight
M24308/24-16	4	MS14059-16	MS18276-1	Size 20	Straight
M24308/24-17	5	MS14059-17	MS18277-1	Size 20	Straight
M24308/24-19	1	MS14059-19	MS18273-1	Size 20	Straight
M24308/24-20	2	MS14059-20	MS18274-1	Size 20	Straight
M24308/24-21	3	MS14059-21	MS18275-1	Size 20	Straight
M24308/24-22	4	MS14059-22	MS18276-1	Size 20	Straight
M24308/24-24	5	MS14059-24	MS18277-1	Size 20	Straight
M24308/24-25	1	MS14059-25	MS18273-1	Size 20	Rt angle

See footnotes at end of table.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:11Z
Check the source to verify that this is the current version before use.

TABLE I. Design standards - Continued.

Part or identifying number (PIN)	Shell size	Shell MS number	Insert MS number	Contact 1/	
				Mating end 2/	PWB tail
M24308/24-26	2	MS14059-26	MS18274-1	Size 20	Rt angle
M24308/24-27	3	MS14059-27	MS18275-1	Size 20	Rt angle
M24308/24-28	4	MS14059-28	MS18276-1	Size 20	Rt angle
M24308/24-29	5	MS14059-29	MS18277-1	Size 20	Rt angle
M24308/24-31	1	MS14059-31	MS18273-1	Size 20	Rt angle
M24308/24-32	2	MS14059-32	MS18274-1	Size 20	Rt angle
M24308/24-33	3	MS14059-33	MS18275-1	Size 20	Rt angle
M24308/24-34	4	MS14059-34	MS18276-1	Size 20	Rt angle
M24308/24-35	5	MS14059-35	MS18277-1	Size 20	Rt angle
M24308/24-37	1	MS14059-37	MS18273-1	Size 20	Rt angle
M24308/24-38	2	MS14059-38	MS18274-1	Size 20	Rt angle
M24308/24-39	3	MS14059-39	MS18275-1	Size 20	Rt angle
M24308/24-40	4	MS14059-40	MS18276-1	Size 20	Rt angle
M24308/24-41	5	MS14059-41	MS18277-1	Size 20	Rt angle
M24308/24-43	1	MS14059-43	MS18273-1	Size 20	Rt angle
M24308/24-44	2	MS14059-44	MS18274-1	Size 20	Rt angle
M24308/24-45	3	MS14059-45	MS18275-1	Size 20	Rt angle
M24308/24-46	4	MS14059-46	MS18276-1	Size 20	Rt angle
M24308/24-47	5	MS14059-47	MS18277-1	Size 20	Rt angle
M24308/24-49	1	MS14059-49	MS18273-1	Size 20	Rt angle
M24308/24-50	2	MS14059-50	MS18274-1	Size 20	Rt angle
M24308/24-51	3	MS14059-51	MS18275-1	Size 20	Rt angle
M24308/24-52	4	MS14059-52	MS18276-1	Size 20	Rt angle
M24308/24-53	5	MS14059-53	MS18277-1	Size 20	Rt angle
M24308/24-55	1	MS14059-55	MS18273-1	Size 20	Rt angle
M24308/24-56	2	MS14059-56	MS18274-1	Size 20	Rt angle
M24308/24-57	3	MS14059-57	MS18275-1	Size 20	Rt angle
M24308/24-58	4	MS14059-58	MS18276-1	Size 20	Rt angle
M24308/24-59	5	MS14059-59	MS18277-1	Size 20	Rt angle
M24308/24-61	1	MS14059-61	MS18273-2	Size 20	Straight
M24308/24-62	2	MS14059-62	MS18274-2	Size 20	Straight
M24308/24-63	3	MS14059-63	MS18275-2	Size 20	Straight
M24308/24-64	4	MS14059-64	MS18276-2	Size 20	Straight
M24308/24-65	5	MS14059-65	MS18277-2	Size 20	Straight
M24308/24-67	1	MS14059-67	MS18273-2	Size 20	Straight
M24308/24-68	2	MS14059-68	MS18274-2	Size 20	Straight
M24308/24-69	3	MS14059-69	MS18275-2	Size 20	Straight
M24308/24-70	4	MS14059-70	MS18276-2	Size 20	Straight
M24308/24-71	5	MS14059-71	MS18277-2	Size 20	Straight
M24308/24-73	1	MS14059-73	MS18273-2	Size 20	Rt angle
M24308/24-74	2	MS14059-74	MS18274-2	Size 20	Rt angle
M24308/24-75	3	MS14059-75	MS18275-2	Size 20	Rt angle
M24308/24-76	4	MS14059-76	MS18276-2	Size 20	Rt angle
M24308/24-77	5	MS14059-77	MS18277-2	Size 20	Rt angle

1/ These socket contacts are in accordance with MS14059 for connection to printed circuit boards.
2/ Pin contact shall be .041/.039 inch (1.04/.99 mm) diameter pin.

NOTE: Qualification by similarity: Qualification of connectors of one shell size of one configuration with a specific printed wiring tail length and diameter shall qualify all connectors of the same shell size and configuration with all other printed wiring tail lengths and diameters.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:11Z
Check the source to verify that this is the current version before use.

PIN: Consists of the letter M, the basic number of the specifications sheet, and a dash number compiled from the code.

PIN example: M24308/24 -87 F

Specification sheet number

Dash sheet number from table I

Finish: Cadmium =F
No suffix letter = cadmium or zinc

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AV, MI, AT, ME
Navy - AS, CG, MC, SH
Air Force - 99

Preparing activity:
DLA - ES

(Project: 5935-4075-11)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:11Z
Check the source to verify that this is the current version before use.