INCH- POUND

MIL-DTL-24308/26K
25 June 2007
SUPERSEDING
MIL-DTL-24308/26J
19 July 2000

DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRIC, RECTANGULAR, MINIATURE, POLARIZED SHELL, RACK AND PANEL, SCREW-LOCK ASSEMBLY, FEMALE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-24308.



Inches	mm
.015	0.38
.030	0.76
.032	0.81
.107	2.72
.112	2.84
.120	3.05
.155	3.94
.188	4.78
.216	5.49
.219	5.56

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are in parentheses.
3. Metric equivalents are given for information only.
4. When a connector using the alternate method of securing the shell (tab type) is front mounted, one flat washer shall be used as a spacer between the mounting surface and the connector.

FIGURE 1. Dimensions and configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:13Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Material: Cold rolled steel or corrosion resistant steel in accordance with ASTM-A582/A582M.

Finish: Cold rolled steel - Yellow chromate over cadmium in accordance with SAE-AMS-QQ-P-416, or yellow chromate over zinc in accordance with ASTM B633.

Corrosion resistant steel - Shall be passivated in accordance with SAE-AMS-2700.

Qualification requirements: See MIL-DTL-24308/25.

Part or Identifying Number (PIN) example: M24308/26 - 1F

(See table I)

F - Cadmium
P - Passivated stainless steel
Z- Zinc

(See MIL-DTL-24308 for disposition of stock for “No suffix” finish)

TABLE I. Dash number.

Dash no.	A ±.015
-1	.312
-2	.625

Changes from previous issue: The margins of this specification are marked with vertical lines to indicate where changes from previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Referenced documents. In addition to MIL-DTL-24308, this document references the following:

MIL-DTL-24308/25
ASTM A582/A582M
ASTM B633
SAE-AMS-QQ-P-416
SAE-AMS-2700

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:13Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 11
NASA - NA
DLA - CC

Review activities:
Army - AT, AV, CR4, MI
Navy - AS, CG, MC, SH
Air Force - 99

Preparing activity:
DLA - CC

(Project 5935-2006-030)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:13Z
Check the source to verify that this is the current version before use.