INCH-POUND

MIL-C-24308/9E
26 January 1989
SUPERSEDING
MIL-C-24308/9D
28 January 1985

MILITARY SPECIFICATION SHEET

CONNECTORS, ELECTRIC, RECTANGULAR, MINIATURE, POLARIZED SHELL, RACK AND PANEL, PLUG, PIN CONTACTS, HERMETIC, CLASS H AND K

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-C-24308.

REQUIREMENTS.

The connectors shall conform to the design standards (MS numbers) indicated in table I.

TABLE I. Design standards. 1/

Part or Identifying Number (PIN) class H	PIN number class K	Shell size	Shell MS number	Insert MS number	Contact terminals	
					Solder cup	Eyelet
M24308/9-1	M24308/9-21	1	MS18272-1	MS18273-1	MS18281-4	
M24308/9-2	M24308/9-22	2	MS18272-2	MS18274-1	MS18281-4	
M24308/9-3	M24308/9-23	3	MS18272-3	MS18275-1	MS18281-4	
M24308/9-4	M24308/9-24	4	MS18272-4	MS18276-1	MS18281-4	
M24308/9-5	M24308/9-25	5	MS18272-5	MS18277-1	MS18281-4	
M24308/9-6	M24308/9-26	1	MS18272-1	MS18273-1		MS18281-3
M24308/9-7	M24308/9-27	2	MS18272-2	MS18274-1		MS18281-3
M24308/9-8	M24308/9-28	3	MS18272-3	MS18275-1		MS18281-3
M24308/9-9	M24308/9-29	4	MS18272-4	MS18276-1		MS18281-3
M24308/9-10	M24308/9-30	5	MS18272-5	MS18277-1		MS18281-3
M24308/9-11	M24308/9-31	1	MS18272-6	MS18273-1	MS18281-4	
M24308/9-12	M24308/9-32	2	MS18272-7	MS18274-1	MS18281-4	
M24308/9-13	M24308/9-33	3	MS18272-8	MS18275-1	MS18281-4	
M24308/9-14	M24308/9-34	4	MS18272-9	MS18276-1	MS18281-4	
M24308/9-15	M24308/9-35	5	MS18272-10	MS18277-1	MS18281-4	
M24308/9-16	M24306/9-36	1	MS18272-6	MS18273-1		MS18281-3
M24308/9-17	M24308/9-37	2	MS18272-7	MS18274-1		MS18281-3
M24308/9-18	M24308/9-38	3	MS18272-8	MS18275-1		MS18281-3
M24308/9-19	M24308/9-39	4	MS18272-9	MS18276-1		MS18281-3
M24308/9-20	M24308/9-40	5	MS18272-10	MS18277-1		MS18281-3

1/ These connectors mate with connectors specified in MIL-C-24308/1, MIL-C-24308/2, and MIL-C-24308/23

(E) denotes changes

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:08Z
Check the source to verify that this is the current version before use.

(E)PIN Consists of the letter M, the basic number of the specification sheet, and a dash number compiled from the code

PIN example M24308/9 -10 F

Specification sheet number

Dash sheet number from table I

Finish. For class H:
F = Cadmium.
No suffix = Cadmium or zinc.
For class K.
Class K connectors have a nickel finish, no suffix is required.

CONCLUDING MATERIAL

Custodians.
Army - CR
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AV, MI
Navy - AS, SH
Air Force - 11, 99
DLA - ES

User activities
Army - ME
Navy - CG, MC

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5935-3672-01)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:08Z
Check the source to verify that this is the current version before use.