MILITARY STANDARD

AUTOMATED ENGINEERING
DOCUMENT PREPARATION SYSTEM

NETWORKS

TO ALL HOLDERS OF MIL-STD-35-35(MI)

1. The following pages of MIL-STD-35-35(MI) have been revised and supersede the pages listed:

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
v	14 February 1975	v	19 November 1973
vi	14 February 1975	vi	19 November 1973
vii	14 February 1975	vii	19 November 1973
viii	14 February 1975	viii	19 November 1973
ix	14 February 1975	ix	19 November 1973
	14 February 1975	x through xii	19 November 1973
5	14 February 1975	5	19 November 1973
6	14 February 1975	6	19 November 1973
7	14 February 1975	7	19 November 1973
8	14 February 1975	8	19 November 1973
9	14 February 1975	9 through 14	19 November 1973
15	14 February 1975	15	19 November 1973
16	14 February 1975	16	19 November 1973
17	14 February 1975	17	19 November 1973
18	14 February 1975	18 through 20	19 November 1973
43	19 November 1973	Reprinted without change	
44	14 February 1975	44 through 48	19 November 1973
49	14 February 1975	49	19 November 1973
50	19 November 1973	Reprinted without change	
51	19 November 1973	Reprinted without change	
52	14 February 1975	52	19 November 1973
111	14 February 1975	111 through 122	19 November 1973
123	19 November 1973	Reprinted without change	
124	14 February 1975	124	19 November 1973 A-
125	19 November 1973	Reprinted without change	
126	14 February 1975	126	19 November 1973
127	19 November 1973	Reprinted without change	
128	14 February 1975	128	19 November 1973
129	14 February 1975	129 and 130	19 November 1973
133	14 February 1975	133 through 146	19 November 1973
157	14 February 1975	157 through 160	19 November 1973

2. Retain this notice page and insert before the Table of Contents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

3. Holders of MIL-STD-35-35(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or cancelled.

Custodians:
Army-MI

Review Activities:
Army-AT
Army-AV
Army-EL
Ariny-ME
Army-MR
Amy- SG
Army-WC

User Activity:
Army-MU

Preparing Activity:
Army-MI
Project EDS-0081

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE OF CONTENTS

SECTION	TITLE	PAGE
1.0	Pulse Forming Networks	1
l.l	Specification Title Index	3-4
1.2	Specification Requirements Instructions	5
1.2.1	General	5
1.2.2	Approved Item Name Code	6
1.2.3	Figure Number	6
1.2.4	Dimensions	7
1.2.5	Tabulation	7
1.2.6	Deleted	
1.2.7	Deleted	
1.2.8	Deleted	
1.2.9	Applicable Documents	7
	NOTE : Paragraphs 1.2.10 through 1.2.19 have been deleted.	
1.2.20	Circuit Diagram Configuration	9
1.2.21	Type Package	9
1.2.22	Mounting Means	9
1.2.23	Number of Sections	15
1.2.24	Wiring	15
1.2.25	Weight	16
1.2.26	Component Part Reliability	16
1.2.27	Mean Time Between Failure	16

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE OF CONTENTS (CONT)

SECTION	TITLE	PAGE
1.2.28	Operating Temperature Range	
1.2.29	Maximum Operating Temperature	16
1.2.30	Nonoperating (Storage) Temperature Range	16
1.2.31	Life Expectancy	17
1.2.32	Altitude	17
1.2.33	Terminal Types	17
1.2.33.1	Terminal Type and Specification	17
1.2.33.2	Deleted	
1.2.33.3	Deleted	
1.2.34	Connector Types	18
1.2.34.1	Connector Type and Specification	18
1.2.34.2	Deleted	
1.2.34.3	Deleted	
1.2.35	Deleted	
1.2.36	Pulse Repetition Frequency	18
1.2.37	Pulse Duration	18
1.2.38	Peak Working Voltage	18
1.2.39	Supply Voltage	18
1.2.40	Operating Voltage	18
1.2.41	Charging Voltage	18

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE OF CONTENTS (CONT)

SECTION	TITLE	PAGE
1.2.42	Load, Source, and/or Charging Reactor Impedance	21
1.2.43	Impedance	21
1.2.43.1	Test Methods	21
1.2.43.2	Requirements	21
1.2.44	Waveshape	22
1.2.44.1	Test Methods	22
1.2.44.2	Requirements	22
1.2.45	Corona Discharge	25
1.2.45.1	Test Methods	25
1.2.45.2	Requirements	25
1.2.46	Dissipation Factor	26
1.2.46.1	Test Methods	26
1.2.46.2	Requirements	26
1.2.47	Flashpoint of Impregnant or Potting Compound	27
1.2.47.1	Test Methods	27
1.2.47.2	Requirements	27
1.2.48	Reliability Screening (Life, Conditioning)	28
1.2.48.1	Test Methods	28
1.2.48.2	Requirements	28

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE OF CONTENTS (CONT)

SECTION	TITLE	PAGE
1.2.49	High Temperature	29
1.2.49.1	Test Methods	29
1.2.49.2	Requirements	30
1.2.50	Low Temperature	30
1.2.50.1	Test Methods	30
1.2.50.2	Requirements	31
1.2.51	Altitude	32
1.2.51.1	Test Methods	32
1.2.51.2	Requirements	32
1.2.52	Strength of Mounting Means	33
1.2.52.!	Test Methods	33
1.2.52.2	Requirements	34
1.2.53	Dielectric Withstanding Volts	34
1.2.53.1	Sea Level	34
1.2.53.2	Reduced Barometric Pressure	34
1.2.54	Insulation Resistance	35
1.2.54.1	Test Methods	35
1.2.54.2	Requirements	36

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE OF CONTENTS (CONT)

SECTION	TITLE	PAGE
1.2.55	Seal	36
1.2.55.1	Test Methods	36
1.2.55.2	Requirements	38
1.2.56	Fungus	38
1.2.56.1	Test Methods	38
1.2.56.2	Requirements	39
1.2.57	Resistance to Solvents	39
1.2.57.1	Test Methods	39
1.2.57.2	Requirements	40
1.2.58	Radiographic	40
1.2.59	Environmental Test Methods and Requirements	41
1.2.59.1	Test Methods	42
1.2.59.2	Requirements	42
1.2.59.3	Electrical and Mechanical Limits	42
1.2.60	Humidity	43
1.2.60.1	Test Methods	43
1.2.60.2	Requirements	43
	Specification Requirements	49

Supersedes page ix of 19 November 1973

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE OF CONTENTS (CONT)

SECTION	TITLE	PAGE
Table I.	Mounting Hardware Table	123
Table II.	Deleted	
Table III.	Deleted	
Table IV.	Wiring Table	125
Table V.	Terminal Table	126
Table VI.	Terminal Hardware Table	127
Table VII.	Deleted	
Table VIII.	Deleted	
Table IX.	Deleted	
Table X.	Waveshape Characteristics Table	130
Table XI.	Dielectric Withstanding Voltage Table	131
Table XII.	Insulation Resistance Table	132
1.3	Configuration and Drawings	147
1.3.1	Figure Titles vs Figure Numbers	149
1.3.2	Legend Index	151
	Figures Ø65-Ø1-1 thru Ø65-Ø2-2	153-156

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

SECTION 1.2

SPECIFICATION REQUIREMENTS INSTRUCTIONS

1.2.1 General

The purpose of these instructions is to establish the procedures to be followed, and the format to be used, for submission of requirements to obtain a computer generated procurement document.

The requester will find it impossible to complete an SRS using only this dash numbered part of MIL-STD-35. Information which is standard for all generic families has been included in the master document at the issuance of MXL-STD-35C. This information is not repeated for each dash numbered part. The following list contains the subjects which are pertinent to every family unless otherwise excepted.

General Description of AEDPS
Part Numering
Specification Requirements Sheet
Writing Methodology
Mandatory Specification Requirements
General Specification Requirements
Dimensions and Drawings
Applicable Documents
Materials
Finishes
Inspections
Single and Multi-Item Specification (Tabulation)
Sources
Search
General Instructions for SRL
Tables A through S

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

1.2.2 Approved Item Name Code

The item name code for a network, to be entered on the SRS with Code 1007, is selected from the Item Name Code column of the following list.

Approved Item Name	Item Name Code
Network, Pulse Forming	60769
Unapproved Names	77777

1.2.3 Figure Number

Code 1009 must show the figure number selected from Section 1.3.

1.2.4 Dimensions

MIL-STD-35 must be used in conjunction with this dash numbered part to completely delineate the dimensions for a network.

The figures and corresponding legends, representing different configurations of networks, are located at the end of Section 1.3. The figure number (representing the selected figure) is mandatory and shall be entered on the SRS with Code 1009. The figure legends in this document (AA, AB, AC, etc.) representing dimensions shall be employed with corresponding legends in Table A of MIL-STD-35.

The remaining instructions for dimensioning networks are located in MIL-STD-35.

1.2.5 Tabulation

The explanation of, and the instructions for using tabulation are found in MIL-STD-35. Candidates for tabulation for this part are the dimensional codes shown in Table A of MIL-STD-35 and the following.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABULATION CANDIDATES FOR NETWORKS

Characteristic Code	Title
	Frequency (pulses per second)
1606	Average
1608	Minimum
1610	Maximum
1612	Pulse Duration (nanoseconds)
1614	Peak Working Voltage (de)
	Impedance (ohms)
1617	Load
1619	Source
1621	Charging reactor
2201, 2202, 2203, 2204	Terminal Type

NOTE : Paragraphs 1.2.6, 1.2.7, and 1.2.8 have been deleted.

1.2.9 Applicable Documents

In addition to the documents contained in the Applicable Document List of MIL-STD-35, the documents that follow shall be entered on the SRS with appropriate codes from Table B of MIL-STD-35.

Document	Code	Related Subject
ASTM 092-57	3336	Flashpoint of Impregnant or Potting Compound
MIL-STD-810	2708	High Temperature
	2728	Low Temperature
	2730	Low Temperature
	2760	Altitude
	2762	Altitude
	4755	Fungus
MIL-STD-202	1374	Insulation Resistance
	1378	Insulation Resistance
	3206	Insulation Resistance
	3211	Insulation Resistance
	3216	Insulation Resistance

Supersedes page 7 of 19 November 1973

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

Document	Code	Related Subject
MIL-STD-202 (Cont)	3221	
	3226	
	3231	
	1393	Moisture Resistance
	1411	Terminal Strength
	1412	
	1413	
	1414	
	1415	
	1416	
	1428	Random Vibration
	1429	
	1448	High Frequency Vibration
	1467	Low Frequency Vibration
	1488	High Impact Shock
	1504	Specified Pulse Shock
	1660	Capacitance
	2784	Explosion
	2904	Flammability
	2919	Random Vibration
	2932	Acceleration
	4353	Dielectric Withstanding Voltage
	4357	(Sea Level)
	4361	
	4365	
	4369	
	4373	
	4377	
	4381	
	4385	
	4389	
	4865	
	4354	Dielectric Withstanding Voltage
	4359	(Reduced Pressure)
	4362	
	4366	
	4370	Dielectric Withstanding Voltage
	4374	(Reduced Pressure)
	4378	
	4382	
	4386	
	4390	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

Document	Code	Related Subject
MIL-STD-202 (Cont)	4886	
	4889	
	4666	Solderability
	4691	Resistance to Soldering Heat
	4715	Thermal Shock
	4737	Seal
	4772	Salt Spray
	4790	Humidity
	4793	
	4811	Immersion
	4830	Resistance to Solvents
	4831	

NOTE : Paragraphs 1.2.10 through 1.2.19 have been deleted.

1.2.20 Circuit Diagram Configuration

It is mandatory that the electrical circuit configuration be specified on the SRS by selecting the applicable circuit from Figure Ø65-Ø2-1 or Ø65-Ø2-2 and writing the type under the selected circuit configuration with Code 1570 or 1571.

1.2.21 Type Package

The type package may be specified on the SRS by selecting one of the following and writing it in with Code 1562:

Hermetically sealed
Encapsulated
Encased

1.2.22 Mounting Means

Mounting means may be specified on the SRS by selecting one of the following and writing it in with Code 1564:

Bracket
Threaded stud
Threaded insert

Supersedes pages 9 through 14 of 19 November 1973

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

In addition, mounting hardware may be specified by the use, as applicable, of Tables I, II, and III. Codes 2090 through 2109 are used to specify the configuration of the hardware. All lines need not be used, but each line started must be completed. For example, if no screw is needed, Codes 2090 through 2093 are not used, but if a washer, Code 2094, is needed, Code 2094 through 2097 must be used with applicable values. Typical type values are: slot head or philips for screws, flat or insulating or split lock for washers, hexagonal for nut, and bar for clamp. Size values are typically 6-32 for threaded parts, number 6 or inner diameter in inches and width in inches for a clamp. The length/thickness and quantity are entered with applicable codes. Tables II and III are used in the same way. If a specification is not to be referenced, or finish thickness is not specified, three dashes (---) may be entered on the SRS with the applicable code to complete the line.

1.2.23 Number of Sections

The number of sections in the network may be specified on the SRS by writing in the number with Code 1568.

1.2.24 Wiring

Wiring may be specified on the SRS with codes from Table IV "Wiring Table" (located before the appendices) to generate a table. The function column provides capability to specify from one to five signal nomenclatures. The input and output columns provide the capability to specify the input and/or output connector and pin number for the signal specified.

To generate this table, write in the signal nomenclatures with Code 3101, 3104, 3107, 3110, 3113 and/or 3116; write in the input connector and pin number, if required, for each signal nomenclature specified with Code 3102, 3105, 3108, 3111, 3114 and/or 3117; and write in the output connector and pin number, if required, for each signal nomenclature specified with Code 3103, 3106, 3109, 3112, 3115, and/or 3118. An example of SRS entries for a 28 volts DC function which requires specifying both input and output connectors and for a command function which requires specifying only output connectors is as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

Code	Value
3101	28 VOLTS DC
3102	J1-1
3103	J2-l0
3104	COMMAND
3105	---
3106	J36-5

1.2.25 Weight

Weight of the network may be specified on the SRS by writing in one of the following maximum values: (pounds) with Code 1572, (ounces) with Code 1574, or (grams) with Code 1576.

1.2.26 Component Part Reliability

Established reliability parts shall be used when applicable. When this requirement is applicable, enter an "X" with Code 1577.

1.2.27 Mean Time Between Failure

The mean time between failure design parameter may be specified on the SRS by writing in the value (hours) with Code 1579.

1.2.28 Operating Temperature Range

Operating temperature range may be specified on the SRS by writing in the values (degrees Celsius) for the minimum and the maximum temperature with Code 1578 and 1580; it is mandatory that both extremes be specified.

1.2.29 Maximum Operating Temperature

Maximum operating temperature may be specified on the SRS by writing the value (degrees Celsius) with Code 1581.

1.2.30 Nonoperating (Storage) Temperature Range

The nonoperating (storage) temperature range may be specified on the SRS by writing in the values (degrees Celsius) for the minimum and maximum temperatures with Codes 1582 and 1583; it is mandatory that both extremes be specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

1.2.31 Life Expectancy

Life expectancy may be specified on the SRS by writing in the value (hours) minimum with Code 1584.

1.2.32 Altitude

Maximum operating or nonoperating altitude may be specified on the SRS by writing in the value (feet) with Code 1586 for operating or with Code 1588 for nonoperating.

1.2.33 Terminals Types

Terminal types may be specified on the SRS with codes from Table V, "Terminal Table." If all terminals are of the same type, use the codes in Column 4. Use the codes in Column 1 for input terminals; use the codes in Column 2 for output terminals; and use the codes in Column 3 for ground terminals.

In addition, terminal hardware is specified by the use of applicable codes from Table VI located ahead of the appendices. Codes 2145 through 2160 are used to specify the configuration of the terminal. All items, or lines, need not be used.

1.2.33.1 Terminal Type and Specification

a. Type. Select one of the following and write in with appropriate codes from Table V (Codes 2201, 2202, 2203, and/or 2204):

Lug
Threaded stud
Threaded insert
Screw
Wire hook
Pin

If a type other than one of those listed is required, write in the type nomenclature with appropriate codes from Table V.

When a specification is required for the terminal type selected, write in the specification number with appropriate code from Table V (Codes 2211, 2212, 2213, and/or 2214). (See 1.2.9)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

1.2.34 Connector Types

Connector types may be specified on the SRS with one or more of the following.

1 .2.34.1 Connector Type and Specification

Write in the wording required with Code 1592. When a specification is required, write in the specification number with Code 1594 (see 1.2.9).

1.2.36 Pulse Repetition Frequency

Pulse repetition frequency may be specified on the SRS with one of the following: Write in the number of pulses per second (average) with Code 1606 (minimum) with Code 1608, and (maximum) with Code 1610; or-write in the number of pulses per second (minimum) with Code 1608 and (maximum) with Code 1610; or write in the number of pulses per second (average) with Code 1606.

1.2.37 Pulse Duration

Pulse duration may be specified on the SRS by writing in the value (microseconds) nominal with Code 1612.

1.2.38 Peak Working Voltage

Peak working voltage may be specified on the SRS by writing in the value (volts DC) with Code 1614.

1.2.39 Supply Voltage

Supply voltage may be specified on the SRS by writing in the value (volts DC) nominal with Code 1616.

1.2.40 Operating Voltaqe

Operating voltage may be specified on the SRS with one or both of the following: Write in the charging reactor voltage (volts DC) maximum with Code 1618; and/or write in the pulse transformer voltage (volts DC) maximum with Code 1620.

1.2.41 Charglnq Voltage

Charging voltage may be specified on the SRS by writing in the value (volts DC) nominal with Code 1622.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

1.2.60 Humidity

1 .2.60.1 Test Methods

The test method for humidity may be specified on the SRS by using one of the following:

a. For testing in accordance with the specification referenced with Code 1006, enter an "X" with Code 4787.

b. For exceptions to the test method of the specification referenced with Code 1006, complete the sentence with Code 4788. The exceptions stated must be limited to 189 characters,. including punctuation and spaces.

c. For testing in accordance with MIL-STD-202, Method 103, it is mandatory to write in the test condition letter with Code 4790 and complete the sentence (write-in limited to 189 characters, including punctuation and spaces) with Code 4793, to specify points of application of polarizing voltage.

One or more of the following may also be used. Complete the sentence with Code 4791, to specify measurements after conditioning; with Code 4794, to specify final measurements at high humidity; with Code 4795, to specify final measurements after drying period (each write-in limited to 189 characters, including punctuation and spaces). Write in the minimum time period with Code 4792, to specify the duration of application of polarizing voltage (i.e., 2 hours, 15 minutes, etc). Write in the value (volts DC) nominal with Code 4804 to specify the polarizing voltage.

If a Test Method Code is used, a Requirement Code must also be used. Do not use a combination of Codes 4784 and 4796 (see 1.2.59).

1 .2.60.2 Requirements

Requirements for humidity may be specified on the SRS by using one of the following:

a. For requirements in accordance with the requirements of the specification referenced with Code 1006, enter an "X" with Code 4796.

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

b. For exceptions to the requirements of the specification referenced with Code 1006, complete the sentence with Code 4797. The exceptions stated must be limited to 189 characters, including punctuation and spaces.

c. For detailed requirements, it is mandatory to enter an "X" with Code 4798, to specify that there shall be no evidence of physical damage, or degradation of performance.

If Code 4791 is used, it is mandatory to complete the sentence with Code 4806, to specify requirements after conditioning; if Code 4794 is used, it is mandatory to complete the sentence with Code 4800, to specify requirements after test and at high humidity; if Code 4795 is used, it is mandatory to complete the sentence with Code 4801, to specify requirements after test and drying period (each write-in limited to 189 characters, including punctuation and spaces).

When the insulation resistance requirement is applicable, enter an "X" with Code 4799. Review Table XII to ensure that the value (megohms) minimum requirement has been specified. (See 1.2.54.2)

Custodians:
Army-MI

Review Activities:
Army-AT
Army-AV
Army-EL
Army-ME
Army-MP
Army-SG
Army-WC

User Activity:
Army-MU

Preparing Activity:
Army-MI
Project EDS-0081

Supersedes pages 44 through 48 of 19 November 1973

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS

SEE MIL-STD-35 FOR EXANPLE OF VALUE FILL-IN.

REF, PARA	CHARACTERISTIC NAME	CHARACTERISTIC CODE
1.2.1	Enter on the SRS, requirements from MIL-STD-35. NOTE : Reference paragraphs 1.2.12 through 1.2.19 have been deleted. These characteristic names and codes are now contained in MIL-STD-35.	
1.2.20	*Circuit Diagram Configuration Select type from Figure 065-02-1	1570
	or	
	Select type from Figure 065-02-2	1571

* INDICATES MANDATORY REQUIREMENT

Supersedes pages 49 of 19 November 1973

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS

SEE MIL-STD-35 FOR EXAMPLE OF VALUE FILL-IN.

REF , PARA ,	CHARACTERISTIC NAME	CHARACTERISTIC CODE
1.2.21	Type Package (Select one if required)	1562
	Hermetically sealed	
	Encapsulated	
	Encased	
1.2.22	Mounting Means (Select one if required)	1564
	Bracket	
	or	
	Threaded stud	
	or	
	Threaded insert	
	Mounting hardware (Enter applicable codes and values on SRS from Tables I, II, and III)	
1.2.23	Number of Sections	1568
1.2.24	Wiring (Enter applicable codes and values on SRS from Table IV)	
1.2.25	Weight (Select one and enter value)	
	Pounds max	1572
	or	

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS

SEE MIL-STD-35 FOR EXANPLE OF VALUE FILL-IN.

REF , PARA,	CHARACTERISTIC NAME	CHARACTERISTIC CODE
1.2.25 Cont	Ounces max	1574
	or	
	Grams max	1576
1.2.26	Established reliability parts shall be used	1577
1.2.27	Network designed for MTBF of (hours)	1579
.2.28	Operating Temperature Range	
	*Min (deg C)	1578
	*Max (deg C)	1580
.2.29	Maximum Operating Temperature	
	*Max (deg C)	1581
.2.30	Nonoperating (storage) Temperature Range	
	*Min (deg C)	1582
	*Max (deg C)	1583
.2.31	Life Expectancy (hours) min	1584
.2.32	Altitude	
	Max Operating (feed)	1586
	or	
	Max Nonoperating (feet)	1588

“INDICATES MANDATORY REQUIREMENT
Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS

SEE MIL-STD-35 FOR EXAMPLE OF VALUE FILL-IN.

REF. PARA,	CHARACTERISTIC NAME	CHARACTERISTIC CODE
1.2.33	Terminals (Enter applicable codes and values on SRS from Table V)	
	Terminal hardware (Enter applicable codes and values on SRS from Table VI)	
1.2.34.1	Connector Type	1592
	Connector specification	1594
	Electrical Characteristics	
1.2.36	Pulse repetition frequency	
	Average (pulses per second)	1606
	Min (pulses per second)	1608
	Max (pulses per second)	1610

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS

SEE MIL-STD-35 FOR EXAMPLE OF VALUE FILL-IN.

REF, PARA,	CHARACTERISTIC NAME	CHARACTERISTIC CODE
1.2.60.1 Cont	Duration of application of polarizing voltage shall be	4792
	Final measurements at high humidity shall be .	4794
	Polarizing voltage (volts DC)	4804
1.2.60.2	Requirement (Select one) (Mandatory if either Code 4787, 4788, or 4790 is selected)	
	Requirements per Specification shown with Code 1006	4796
	or	
	Requirements per Specification shown with Code 1006 except .	4797
	or	
	Requirements as follows:	
	*No evidence of physical damage or degradation of performance	4798
	Insulation resistance per Table XII	4799
	Requirements at high humidity shall be .	4800
	Requirements after drying shall be — "	4801

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE I. MOUNTING HARDWARE TABLE

(See 1.2.22)

ITEM	TYPE		SIZE		LENGTH/THICKNESS		QUANTITY	
	Code	Value	Code	Value	Code	Value	Code	Value
Screw	2090		2091		2902		2093	
Washer	2094		2095		2096		2097	
Washer	2098		2099		2100		2101	
Nut	2102		2103		2104		2105	
Clamp	2106		2107		2108		2109	

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE II. DELETED

TABLE III. DELETED

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE IV. WIRING TABLE

(See 1.2.24)

FUNCTION		INPUT TERMINAL		OUTPUT TERMINAL	
Code	Value	Code	Value	Code	Value
3101		3102		3103	
3104		3105		3106	
3107		3108		3109	
3110		3111		3112	
3113		3114		3115	
3116		3117		3118	

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE V. TERMINAL TABLE

(See 1.2.33)

TERMINAL	Column 1		Column 2		Column 3		Column 4	
	INPUT TERMINAL		OUTPUT TERMINAL		GROUND TERMINAL		ALL	
	Code	Value	Code	Value	Code	Value	Code	Value
Terminal Type (Select one) Lug Threaded stud Threaded insert Screw Wire hook Pin Other (write in)	2201		2202		2203		2204	
Terminal Type Specification	2211		2212		2213		2214	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE VI. TERMINAL HARDWARE TABLE

(See 1.2.33)

ITEM	TYPE		SIZE		LENGTH/THICKNESS		QUANTITY	
	Code	Value	Code	Value	Code	Value	Code	Value
Washer	2145		2146		2147		2148	
Washer	2149		2150		2151		2152	
Screw	2153		2154		2155		2156	
Nut	2157		2158		2159		2160	

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE VII. DELETED

TABLE VIII. DELETED

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE IX. DELETED

TABLE X. WAVESHAPE CHARACTERISTICS TABLE

(See 1.2.44)

CHARACTERISTIC	Column 1		Column 2		Column 3		Column 4		Column 5	
	OUTPUT PULSE		PULSE TRANSFORMER		PULSE FORMING NETWORK		LONG PULSE NETWORK		SHORT PULSE NETWORK	
	Code	Value	Code	Value	Code	Value	Code	Value	Code	Value
Pulse Duration										
Nom (microseconds)	2501		2502		2503		2504		2505	
Min (microseconds)	2511		2512		2513		2514		2515	
Max (microseconds)	2521		2522		2523		2524		2525	
Percent Ripple										
Max (percent)	2531		2532		2533		2534		2535	
Pulse Rise Time										
Min (microseconds)	2551		2552		2553		2554		2555	
Max (microseconds)	2561		2562		2563		2564		2565	
Pulse Decay Time										
Min (microseconds)	2581		2582		2583		2584		2585	
Max (microseconds)	2591		2592		2593		2594		2595	
Characteristic Impedance										
Nom (ohms)	2601		2602		2603		2604		2605	
Min (ohms)	2611		2612		2613		2614		2615	
Max (ohms)	2621		2622		2623		2624		2625	
Pulse Amplitude										
Min (volts)	2631		2632		2633		2634		2635	
Max (volts)	2641		2642		2643		2644		2645	
Duty Cycle										
Nom (percent)	2651		2652		2653		2654		2655	
Min (percent)	2661		2662		2663		2664		2665	
Max (percent)	2671		2672		2673		2674		2675	
Pulse Droop										
Max (percent)	2681		2682		2683		2684		2685	

Supersedes pages 129 and 130 of 19 November 1973

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

APPENDIX A

DIMENSION CHARACTERISTICS

NOTE: The Dimension Characteristic Table now appears as Table A in MIL-STD-35.

APPENDIX B

APPLICABLE DOCUMENTS

NOTE: The Applicable Documents Table now appears as Table B in MIL-STD-35.

Supersedes pages 133 through 146 of 19 November 1973

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

THIS PAGE INTENTIONALLY

LEFT BLANK

Supersedes pages 157 through 160 of 19 November 1973

*U.S. GOVERNMENT PRINTING OFFICE:1975-603-127/1050

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.