INCH-POUND
MS90556J
21 November 2012
SUPERSEDING
MS90556H
20 November 2008

DETAIL SPECIFICATION SHEET

CONNECTOR, PLUG, ELECTRICAL, STRAIGHT, CLASS L

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-22992.




FIGURE 1. Plug.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.





FIGURE 1. Plug – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm	Inches	mm	Inches	mm
.001	0.03	.030	0.76	.130	3.30	.381	9.68
.002	0.05	.031	0.79	.135	3.43	.750	19.05
.005	0.13	.062	1.57	.142	3.61	1.060	26.92
.008	0.20	.067	1.70	.187	4.75	1.120	28.45
.010	0.25	.094	2.39	.312	7.92	2.000	51.00
.014	0.36	.101	2.57	.375	9.53		
.022	0.56	.120	3.05	.380	9.65		

FIGURE 1. Plug – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.

Shell size	B ± .047			C ± .016	D ± .005	J thread start ± .031	M thread
	Phase	Neutral	Ground				
28	.196 (4.98)	.078 (1.98)	.078 (1.98)	1.370 (34.80)	1.557 (39.55)	1.062 (26.97)	.164-32UNC
32	.196 (4.98)	.078 (1.98)	.078 (1.98)	1.370 (34.80)	1.557 (39.55)	1.062 (26.97)	.164-32UNC
44	.196 (4.98)	.078 (1.98)	.547 (13.89)	1.589 (40.36)	1.776 (45.11)	1.281 (32.54)	.250-28UNC
48	.196 (4.98)	.078 (1.98)	.547 (13.89)	1.589 (40.36)	1.776 (45.11)	1.281 (32.54)	.250-28UNC
52	.196 (4.98)	.078 (1.98)	.547 (13.89)	1.589 (40.36)	1.776 (45.11)	1.281 (32.54)	.250-28UNC

Shell size	A thread Class 2B	Q dia max	Z ± .47	AA dia + .006 - .005	XX dia + .001 - .010	YY dia + .010 - .010	ZZ ± .035 free length
28	2.000-1428P-2857L	2.312 (58.72)	1.422 (36.12)	1.672 (42.47)	1.522 (38.66)	1.370 (34.80)	.562 (14.27)
32	2.250-1428P-2857L	2.562 (65.07)	1.422 (36.12)	1.922 (48.82)	1.772 (45.01)	1.620 (41.15)	.562 (14.27)
44	3.000-1428P-2857L	3.531 (89.69)	1.625 (41.28)	2.672 (67.87)	2.522 (64.06)	2.296 (58.32)	.672 (17.07)
48	3.250-1428P-2857L	3.782 (96.06)	1.625 (41.28)	2.891 (73.43)	2.725 (69.22)	2.551 (64.80)	.672 (17.07)
52	3.500-1428P-2857L	4.016 (102.01)	1.625 (41.28)	3.141 (79.78)	2.975 (75.57)	2.801 (71.15)	.672 (17.07)

FIGURE 1. Plug – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.

Shell size	MM dia	BB dia	CC dia min	EE dia	FF dia	Packing preformed (See SAE-AS29513)
28	1.685 (42.80) 1.674 (42.52)	1.539 (39.09) 1.531 (38.89)	1.405 (35.69)	1.693 (43.00) 1.687 (42.85)	1.776 (45.11) 1.765 (44.83)	MS29513-128
32	1.935 (49.15) 1.924 (48.87)	1.789 (45.44) 1.781 (45.24)	1.655 (42.04)	1.943 (49.35) 1.937 (49.20)	2.026 (51.46) 2.015 (51.18)	MS29513-132
44	2.685 (68.20) 2.674 (67.92)	2.539 (64.49) 2.531 (64.29)	2.405 (61.09)	2.693 (68.40) 2.687 (68.25)	2.776 (70.51) 2.765 (70.23)	MS29513-144
48	2.935 (74.55) 2.924 (74.27)	2.789 (70.84) 2.781 (70.64)	2.655 (67.44)	2.943 (74.75) 2.937 (74.60)	3.026 (76.86) 3.015 (76.58)	MS29513-148
52	3.185 (80.90) 3.174 (80.62)	3.039 (77.19) 3.031 (76.99)	2.905 (73.79)	3.193 (81.10) 3.187 (80.95)	3.276 (83.21) 3.265 (82.93)	MS29513-151

FIGURE 1. Plug – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.

Shell size	HH thread	Hex socket head size	JJ dia	KK thread	
				Size	Mod minor dia
28	164-32UNC-2B	9/64	.198 (5.03) .187 (4.75)	.164-32UNC-2B	.143 (3.63) .137 (3.48)
32	.164-32UNC-2B	9/64	.198 (5.03) .187 (4.75)	.164-32UNC-2B	.143 (3.63) .137 (3.48)
44	.250-28UNF-2B	3/16	.286 (7.26) .275 (6.99)	.250-28UNF-2B	.229 (5.82) .223 (5.66)
48	.250-28UNF-2B	3/16	.286 (7.26) .275 (6.99)	.250-28UNF-2B	.229 (5.82) .223 (5.66)
52	.250-28UNF-2B	3/16	.286 (7.26) .275 (6.99)	.250-28UNF-2B	.229 (5.82) .223 (5.66)

NOTES.
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ± .016 (0.41 mm).
4. Mates with receptacles shown on MS90555.
5. Inserts and contacts are removable.
6. Normal key position. For alternate key positions, see figure 2.

FIGURE 1. Plug – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.

TABLE I. U diameter by contact size. 1/ 2/

Contact size	U diameter (metric equivalents in parentheses)
4/0	.614 / .624 (15.60/15.85)
2/0	.520 / .530 (13.21/13.46)
1/0	.471 / .481 (11.96/12.22)
4	.339 / .349 (8.61/8.86)
6	.292 / .302 (7.42/7.67)

1/ Dimensions are in inches.
2/ Metric equivalents are given for information only.

TABLE II. Accessory interface dimensions. 1/ 2/

Shell size	Arrangement no.	E Cable range	H +.001 -.010	L Max free length	N dia +.011 -.020
28	-02, -04 -03, -05, -06 -07, -12 -13	.844 (21.44)/ .719 (18.26) .969 (24.61)/ .844 (21.44) 1.047 (26.59)/ .922 (23.42) 1.130 (28.70)/ 1.005 (25.52)	1.750 (44.45)	8.188 (207.98)	2.000 (50.80)
32	-02, -04 -03, -05, -12 -07 -13 -06	.969 (24.61)/ .844 (21.44) 1.130 (28.70)/ 1.005 (25.53) 1.259 (31.98)/ 1.135 (28.83) 1.342 (34.09)/ 1.217 (30.91) 1.047 (26.59)/ .992 (25.2)	1.750 (44.45)	8.188 (207.98)	2.000 (50.80)

See notes at end of table

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.

TABLE II. Accessory interface dimensions – Continued. 1/ 2/

Shell size	Arrangement no.	E Cable range	H +.001 -.010	L max free length	N dia +.011 -.020
44	-02, -04	1.312(33.32)/ 1.187(30.15)	2.250 (57.15)	10.172 (258.37)	2.500 (63.50)
	-03, -05	1.438(36.53)/ 1.313(33.35)			
	-12	1.516(38.51)/ 1.391(35.33)			
	-13	1.672(42.47)/ 1.547(39.29)			
	-06	1.375(34.93)/ 1.250(31.75)			
	-51	1.734(44.04)/ 1.609(40.87)			
	-52 1/	1.525(38.74)/ 1.435(36.45)			
	-56 1/ 2/	1.135(28.82)/ 1.065(27.05)			
48	-13	2.000(50.80)/ 1.867(47.42)	2.750 (69.85)	10.734 (272.64)	2.953 (75.01)
52	-02	1.703(43.26)/ 1.558(39.57)	2.875 (73.03)	11.109 (282.17)	3.250 (82.55)
	-12	2.328(59.13)/ 2.183(55.45)			
	-13	2.453(62.31)/ 2.308(58.62)			
	-06	1.797(45.64)/ 1.652(41.96)			

See notes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.

TABLE II. Accessory interface dimensions – Continued. 1/ 2/

Shell size	Arrangement no.	G thread class 2 left hand	K approx. free length	DD dia basic	GG dia	LL	NN
28	-02, -04 -03, -05, -06 -07, -12 -13	1.8750-16UN	6.688 (169.88) 7.188 (182.58)	2.104 (53.44)	2.439 (61.95) 2.428 (61.67)	.417 (10.59) .406 (10.31)	.338 (8.59) .322 (8.18)
32	-02, -04 -03, -05, -12 -07 -13 -06	1.870-16UN	7.188 (182.58) 7.188 (182.58) 8.188 (207.98) 8.688 (220.68) 7.188 (182.58)	2.354 (59.79)	2.689 (68.30) 2.678 (68.02)	.417 (10.59) .406 (10.31)	.338 (8.59) .322 (8.18)
44	-02, -04 -03, -05 -12 -13 -06 -51 -52 3/ -56 3/ 4/	2.3125-16UNS	10.688 (271.48) 9.688 (246.08) 10.688 (271.48) 12.688 (322.28) 9.688 (246.08) 11.688 (296.88) 11.188 (284.18) 7.188 (182.58)	3.156 (80.16)	3.667 (93.14) 3.646 (92.61)	.605 (15.37) .594 (15.09)	.526 (13.36) .510 (12.95)

See notes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.

TABLE II. Accessory interface dimensions – Continued. 1/ 2/

Shell size	Arrangement no.	G Thread class 2 left hand	K approx. free length	DD dia basic	GG dia	LL	NN
48	-13	2.7500-16UN	14.188 (360.38)	3.406 (86.51)	3.917 (99.49) 3.896 (98.96)	.605 (15.37) .594 (15.09)	.526 (13.36) .510 (12.95)
52	-02 -12 -13 -06	3.0000-16UN	13.688 (347.68) 17.188 (436.58) 18.188 (461.98) 13.688 (347.68)	3.656 (92.86)	4.167 (105.84) 4.146 (105.31)	.605 (15.37) .594 (15.09)	.526 (13.36) .510 (12.95)

1/ Dimensions are in inches.
2/ Metric equivalents are given for information only.
3/ Arrangements 44-52 and 44-56 are for stub cable applications only; they are not to be used in a cable assembly.
4/ Arrangement 44-56 to include 4 each MS3348-1-6L contact bushings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.

TABLE III. Insert arrangements, crimp bushings, and contacts.

Insert arrangement	Contacts 1/		Cable conductors 1/		Contact bushing required	
	Quantity	Size	Quantity	Size	Quantity	PIN MS3348-
28-02	2	6	2	8	2	6-8L
	2	6	2	8	2	6-8L
28-04	1	6 (G)	2	10 (G)	---	---
	3	6	3	8	3	6-8L
28-06	1	4 (G)	3	12 (G)	1	4-8L
	3	6	3	8	---	---
28-07	1	4 (G)	3	10 (G)	4	4-5L
	4	6	4	8	4	6-8L
28-12	1	6 (G)	4	12 (G)	---	---
32-02	2	4	2	6	2	4-6L
	2	4	2	6	2	4-6L
32-04	2	6 (G)	2	10 (G)	2	4-10L
	2	4	2	4	---	---
32-05	2	6 (G)	2	8 (G)	2	6-8L
	3	4	3	6	3	4-6L
32-06	1	4 (G)	3	12 (G)	1	4-8L
	4	4	4	6	4	4-6L
32-12	1	6 (G)	4	12 (G)	---	---
44-02	2	1/0	2	2	2	1-2L
	2	1/0	2	2	2	1-2L
44-04	2	4 (G)	2	6 (G)	2	4-6L
	2	1/0	2	1	---	---
44-05	2	4 (G)	2	5 (G)	2	4-5L
	3	1/0	3	2	3	1-2L
44-06	3	6 (G)	3	8 (G)	3	6-8L
	4	1/0	4	2	4	1-2L
44-12	4	6 (G)	4	9 (G)	4	6-9L
	4	1/0	4	1	---	---
44-13	4	6 (G)	4	8 (G)	4	6-8L
	3	1/0	3	2	3	1-2L
44-52	1	1/0 (G)	1	2 (G)	1	1-2L
	3	1/0	3	6	3	1-6L
44-56	1	1/0 (G)	1	6 (G)	1	1-6L
52-02	2	4/0	2	2/0	2	4/0-2/0L
	3	4/0	3	2/0	3	4/0-2/0L
52-06	3	4 (G)	3	5 (G)	3	4-5L

1/ (G) designates grounding.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1 and tables I, II, III and IV.

Mating: See MS90555 for mating receptacle.

Inserts and contacts: Removable.

For final installation: Contacts will be assembled in all insert holes.

Shell and nut finish: See MIL-DTL-22992.

Normal key position: See figure 1.

Alternate key position: See figure 2.

Insert arrangements: See MS90565, MS90567, MS14054, MS14055 and MS14057.

Cover: In accordance with MS90564. Cover shall be attached to cap screw on body.


Crimp bushings: Shall be supplied with contact crimp bushings in accordance with SAE-AS39029/112 and table III herein.

Cable sealing gland: In accordance with MS23747. Shall be supplied with each connector.


Cable grip: In accordance with MS90561. Shall be supplied with each connector.

Pin contacts: In accordance with SAE-AS39029/48.

Part or Identifying Number (PIN) example:



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.



Finish N (nongrounding assemblies)

Shell size	Shell main key positions 2 wire, 28 V dc
28	N (105°)
32	N (105°)
44	N (105°)
48	N (105°)
52	N (105°)

FIGURE 2. Alternate key positions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.

TABLE IV. Finishes, conductive (grounding assemblies).

Shell size	Shell main key position						
	60 Hz and 400 Hz (see note 1)						
	1∅			3∅			3∅ (see note 2)
	2 wire		3 wire	4 wire			3 wire
	120 V	240 V	120/240 V	120/208 V	240/416 V	277/480 V	450/480 V
28	4 (120°)	5 (135°)	4 (120°)	4 (120°)	5 (135°)	6 (150°)	---
32	4 (120°)	5 (135°)	4 (120°)	4 (120°)	5 (135°)	6 (150°)	---
44	4 (120°)	---	4 (120°)	4 (120°)	5 (135°)	6 (150°)	1 (60°)
48	---	---	4 (120°)	4 (120°)	5 (135°)	6 (150°)	---
52	---	---	4 (120°)	4 (120°)	5 (135°)	6 (150°)	---

NOTES:
1. Discrimination of 60 Hz and 400 Hz assemblies is accomplished by alternate positioning of inserts. See applicable insert drawing for keying.
2. For Navy ground support equipment use only.
3. Shell main key positions 2 and 3 are not used.

FIGURE 2. Alternate key position – Continued.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-22992, this document references the following:

MS14054
MS14055
MS14057
MS23747
MS90555
MS90561
MS90564
MS90565
MS90567
SAE-AS29513
SAE-AS39029/48
SAE-AS39029/112

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – EC
Air Force – 85
DLA – CC

Preparing activity:
DLA – CC

Review activities:
Army – AT, AV, CR4, MI
Navy – AS, CG, MC, OS, SH
Air Force – 13, 19, 99

Project 5935–2012-190)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.