# COMMERCIAL ITEM DESCRIPTION

## WRENCH, ANGLE, DOUBLE HEAD, OPEN END, 15° AND 60° HEADS

The General Services Administration has authorized the use of this commercial item description in lieu of Federal Specification GGG-W-636.

This commercial item description covers wrenches suitable for hexagonal and square-headed bolts and nuts, assigned National Stock Numbers (NSN's) as listed below.

Salient characteristics:

| | |
|---|---|
| Material: | Steel, Rockwell C hardness of 40 minimum, 55 maximum. |
| Finish: | Chromium plated. Both faces of each head shall be bright and shall have a maximum roughness height value of 30 microinches (A.A.). |
| Marking: | Marked in a plain and permanent manner with wrench opening size on the faces or on the handle as close to the heads as practicable and with manufacturer's name or trademark. |
| Wrench opening: | Sized to pass the gaging requirements of Federal Standard No. 346. |
| Chamfer: | Tips chamfered or rounded to eliminate burrs. |

| National Stock Number | Wrench opening (distance across flats) (Inches) | Head width (maximum) (Inches) | Head thickness (maximum) (Inches) | Overall length (minimum) (Inches) | Test load (minimum) (In/lb) |
|---|---|---|---|---|---|
| 5120-00-289-8209 | 1/2 | 1-1/16 | 1/4 | 5 | 100 |
| 5120-00-293-1796 | 11/16 | 1-7/16 | 19/64 | 6-3/8 | 300 |
| 5120-00-293-0053 | 3/4 | 1-37/64 | 21/64 | 7 | 500 |
| 5120-00-184-8652 | 13/16 | 1-39/64 | 19/64 | 7-1/2 | 700 |
| 5120-00-184-8653 | 7/8 | 1-15/16 | 19/64 | 7-7/8 | 825 |
| 5120-00-184-8654 | 15/16 | 1-15/16 | 19/64 | 8-5/8 | 900 |
| 5120-00-293-1794 | 1 | 2-7/64 | 21/64 | 9-3/8 | 1,700 |
| 5120-00-293-2136 | 1-1/16 | 2-7/64 | 21/64 | 9-7/8 | 1,700 |
| 5120-00-595-9017 | 1-1/8 | 2-19/64 | 23/64 | 10-3/4 | 2,250 |
| 5120-00-293-1795 | 1-1/4 | 2-1/2 | 23/64 | 11 | 2,500 |
| 5120-00-289-8212 | 1-1/2 | 3 | 27/64 | 12-1/2 | 3,800 |





FIGURE 1. Wrench, angle

Workmanship. Wrench shall be free from rust, burrs, fins, nodules, and other defects which may impair serviceability, durability, or appearance. The edges and corners of the wrench shall be clearly defined and smoothly finished.

The issue of Federal Standard 346 in effect on the date of the solicitation shall be used to determine compliance with stated requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:13Z
Check the source to verify that this is the current version before use.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Recovered materials. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Preservation, packaging, packing, and marking. The preservation (when applicable), packaging, and packing shall be in accordance with normal commercial practice and shall assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with the National Motor Freight Classification and Uniform Freight Classification. Marking shall be as specified in the contract or order.

Federal standards are available from General Services Administration, Specification Sales, Building 197 (Washington Navy Yard), Washington, DC 20407.



GSA DC-81004888

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:13Z
Check the source to verify that this is the current version before use.