A-A-247
October 22, 1979

COMMERCIAL ITEM DESCRIPTION

FASTENER
(PRONG TYPE)

The General Services Administration has authorized the use of this commercial item description in lieu of Federal Specification FF-F-101.

Salient characteristics:

Fastener and its accompanying washer shall be made from a corrosion resistant metal.
Head shall be perpendicular to the prongs and of the diameter appropriate to that size, as indicated in table I.
Short prong shall be between 1/16 and 1/8 inch shorter than the long prong length indicated for each size in table I.
Washers shall be round and serviceable with the size fastener indicated.
The fasteners shall be of sufficient quality to be bent 25 times at a single point on the prong without cracking or breaking.
The procurement documents shall specify size from those listed in table I, as well as whether or not washers are required.

Workmanship. Fasteners and washers shall have a smooth finish, free from any defects which may injure the user or damage paper. They must be clean and free from oil.

TABLE I

Fasteners (in inches)					Washers
Commercial size number	Long prong length ± 1/16	Width ± 1/64	Thickness ± 0.001	Head diameter ± 1/32	Commercial size number
1	3/8	7/64	0.012	10/32	1
2	1/2	7/64	0.012	10/32	1
3	3/4	1/8	0.012	10/32	1
4	1	1/8	0.012	13/32	1
5	1-1/4	3/16	0.016	15/32	2
6	1-1/2	3/16	0.016	15/32	2
7	2	3/16	0.016	15/32	2
8	3	3/16	0.016	15/32	2
9	4	3/16	0.016	15/32	2

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Recovered materials. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. The fasteners shall be packaged in accordance with normal commercial practice and packed in fiberboard boxes that assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with National Motor Freight Classification and Uniform Freight Classification. Shipping containers shall be marked as specified in the contract or order.

FSC 7510

GSA DC-81002472

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:06Z
Check the source to verify that this is the current version before use.