COMMERCIAL ITEM DESCRIPTION

DATING STAMP
(TIME LEGEND)

The General Services Administration has authorized the use of this commercial item description in lieu of Federal Specification ZZ-R-1414.

Salient characteristics:

General. Each stamp shall have a suitable handle and a metal base with a circular die in two parts; the outer part rotating around the fixed inner part. The inner part of the die shall have a fixed legend and a mortise for removable type. Each stamp shall be accompanied by a set of removable type, a tweezer for handling the type, and a box with compartments for storing the type.

Removable Date Type. The removable type shall consist of "day" type, using separate type for the numerals "1" through "31"; "month" type, should be using the first three letters of each month as abbreviations; "year" type, using separate type for 9 consecutive four numeral year-dates, beginning with the year of the contract order; and separate type for the legends "A.M." and "P.M.". The type body shall be at least 5/16 inch thick with characters raised in relief at least 1/32 inch. The printed height of the characters shall be 9/64 inch $\pm$ 1/64 inch, or as stated in the procurement documents.

Fixed time legend. The fixed legend characters shall be raised in relief at least 1/32 inch from a rubber body that is at least 5/16 inch thick. The inner part of the die shall have a fixed legend consisting of an arrow centered over the legend "RECEIVED" or "DISPATCHED" and the name or other designation of the using activity: both to be specified in the procurement documents. The mortise shall accommodate the removable type to indicate the date and "A.M." or "P.M.". The outer part of the die shall have a time legend within a border of two concentric circles. The time legend shall be graduated and numbered for the hours "1" through "12." Each hour shall be graduated at 1/4-hour intervals.

Performance. Each stamp shall produce clear, distinct, sharp single impressions of equal intensity, with no closing of characters. The removable type shall not become dislodged when the stamp is dropped from desktop height. The base shall have both visual and mechanical locking indexing means for pointing the arrow to a desired time without sight of the die. The overall diameter of the die shall be specified in the procurement documents. The synthetic and/or natural rubbers used in this stamp shall be of sufficient hardness and durability to ensure useability over the entire 9-year lifetime of the stamp. The front of the inner die shall be readily identifiable. Metal components shall be coated or treated to prevent corrosion. When specified in the procurement documents, a replica of the legend shall be fixed to the front of the stamp base.

Workmanship. The base and handle shall have a smooth finish to prevent injury to the user.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Recovered materials. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. The stamps shall be packaged in accordance with normal commercial practice and packed in fiberboard boxes that will assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with National Motor Freight Classification and Uniform Freight Classification. Shipping containers shall be marked as specified in the contract or order.

FSC 7520

GSA DC-01004172

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:09Z
Check the source to verify that this is the current version before use.