A-A-67
February 7, 1980

COMMERCIAL ITEM DESCRIPTION

PUNCH, PAPER, HAND-HELD (2-INCH REACH)

The General Services Administration has authorized the use of this commercial item description in lieu of Federal Specification GGG-P-846.

This commercial item description covers two sizes of hand-held paper punches with 2-inch reach that are suitable for light-duty office use. The punch shall consist of jaws, a plunger and die, and two plier type handles held together by a rivet or a bolt and nut and connected by a spring.

Salient characteristics:

Sizes. Size I punches shall punch a hole 1/8 inch in diameter; size II punches shall punch a hole 3/16 inch in diameter.

The punches shall have salient characteristics equal to those of the following products, as well as possessing the listed salient characteristics.

a) P.J. Mieth Manufacturing Company, Model #464A, for either size.

b) McGill Metal Products, Model Utility #301 for size I, #302 for size II.

c) Bonney-Vehslage Tool Company, Model #12 Standard for either size.

Jaws. The jaws shall permit hole punching at least 2 inches from the paper edge.

Die and plunger. The die and plunger shall be hardened tool steel or any other suitable commercially used material. Filing, grinding, and cutting of the hardened surface shall be in accordance with the manufacturer's commercial practice.

Handles. The handles shall be curved to fit the hand in accordance with the manufacturer's commercial practice. The handles shall be malleable iron casting, heavy gauged steel, or any other suitable commercially used material. The handle grips shall be smooth, knurled, or plastic-coated.

Spring. A spring (helical compression type or equivalent) shall keep the punch jaws in the open position when not in use. The spring shall be strong enough to sustain repeated compressions during use and resilient enough to return the jaws to the open position after use; the spring shall not hamper the use of the punch.

Performance. The punch shall punch through five sheets of bond paper with a force of not more than 45 lb and shall clear afterward under the action of the spring. The punched hole shall be clean and sharp and within 1/64 inch of the specified hole diameter.

Workmanship. The punch shall be free of any defects that may affect its serviceability or appearance. Exposed surfaces shall be smooth, without any sharp edges, burrs, scales, fins, or nodules. Metal parts shall be rendered corrosion-resistant by any suitable surface treatment.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Recovered materials. The manufacturer shall utilize recovered materials to the maximum extent practicable.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:04Z
Check the source to verify that this is the current version before use.

Packaging, packing, and marking. The punches shall be packaged in accordance with normal commercial practice and packed in fiberboard boxes that will assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with National Motor Freight Classification and Uniform Freight Classification. Marking shall be as specified in the contract or order.

Notes:

The following features may be included with the punches but are not required: Depth gauge, nose cover, clipping receptacle, and finger ring.

The purchaser shall specify the size paper punch required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:04Z
Check the source to verify that this is the current version before use.