[Metric]
A-A-1022B
March 05, 1996
Superseding
A-A-1022A
Dated June 16, 1989

COMMERCIAL ITEM DESCRIPTION
TRIMMER, PAPER, DROP KNIFE

The General Services Administration has authorized the use of this commercial item description by all federal agencies.

1. Scope: This commercial item description covers paper trimmers that are intended to be used for cutting single and multiple sheets of various types of paper.

2. Classification:

Size:	I. 30.48 cm (12") x 30.48 cm (12")
	II. 38.10 cm (15") x 38.10 cm (15")
	III. 45.72 cm (18") x 45.72 cm (18")
	IV. 60.96 cm (24") x 60.96 cm (24")
	V. 76.20 cm (30") x 76.20 cm (30")

3. Salient Characteristics:

3.1 The trimmer shall be portable, right-hand operated and designed to have a horizontal, rigid, slow burning or non-flammable cutting table which will not warp or crack with age or typical use. The cutting table shall be marked with a grid of 12.7 mm (.5") squares.

3.2 The trimmer shall have a blade stop to prevent the movable blade from rotating beyond its useful stroke and be permanently fixed in position so that impact will not damage the function of the element and be stable when used on a flat surface and not mar the surface on which it rests.

3.3 The trimmer shall have cutting blades with hardened edges capable of maintaining sharpness for the term of warranty or a minimum of one year.

3.4 The trimmer shall have an arm stop to prevent the movable blade from dropping below the locking point and a device which will lock the movable blade in the down position.

Beneficial comments, recommendations, additions, deletions, clarification's, etc. and any data which may improve this document should be sent to General Services Administration, Federal Supply Service, Engineering Branch, 26 Federal Plaza, New York, NY 10278.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:11Z
Check the source to verify that this is the current version before use.

3.5 The locking device shall be located on the trimmer so that it cannot fail or be pushed under the blade and shall not in any way constitute a hazard to the user. It shall have strong durable springs located in a manner which will preclude injury to the operator should breakage occur.

3.6 The trimmers shall be designed so that the movable blade shall not fall from the raised position under its own weight, have a mechanism for adjusting the contact between blades, have all wood, plywood, and particle board surfaces protected by enamel, paint, shellac, varnish, or lacquer.

3.7 The trimmers shall have a red colored safety guard placed along the stationary blade. The safety guard shall prevent the operator from cutting or injuring their fingers when using the trimmer. The handle shall be no shorter than 101.6 mm (4 inches) to allow for a secure, safe grasp while in use and to ensure for the proper functioning of the trimmer in accordance with the prescribed performance requirements.

3.8 The trimmer shall have a ruling guide located across the top front, perpendicular to the movable blade. The ruling guide shall be graduated in 2.54 cm (inches), 1.27 cm (1/2 inch), 6.35 mm (1/4 inch), and 3.18 mm (1/8 inch) measuring rule shall be accurate ±.008 mm (±.030 inch).

3.9 Trimmers shall be permanently marked with the manufacturer's name or trademark according to standard commercial practice. Placement of these permanent markings shall be at the option of the manufacturer, provided they are prominently displayed.

3.10 Plastic, if used as a cutting table material, shall be in compliance with UL Standard 94 HB. Certification of compliance shall be maintained by the contractor and shall be supplied to the Government, upon request.

3.11 Corrosion Resistance. All metal parts shall be resistant to corrosion. The metal cutting surface of the table, however, shall be anodized, plated, finished with baked enamel, or subjected to a bluing process. The ground blade edge (only) shall not be required to exhibit corrosion resistant treatment. Contractor shall provide a manufacturer's chemical certification of corrosion resistance upon request by the Government.

3.12 Workmanship. Except for the edges of the cutting blades, the trimmer shall be free of sharp edges. The trimmer shall also be free of any defects which affect appearance or impair serviceability (including, but not limited to superfluous coating of any kind, burrs, scratches, or discoloration). Also, the trimmer shall not exhibit evidence of deformity (including, but not limited to cracking, warping, or visible stress marks) after testing as prescribed in Paragraphs 4.3 and 4.4. Minor color variations present as result of recycled polystyrene plastic will be acceptable.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T08:11Z
Check the source to verify that this is the current version before use.

4. **Regulatory Requirements:** The offeror/contractor is encouraged to use recovered material to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4.1 Certification: The contractor shall certify that if polystyrene is used in the manufacture of the item, it shall contain a minimum of 25 percent Postconsumer Recovered Materials in accordance with Title 40 Code of Federal Regulations Part 247, Comprehensive Guideline for Procurement of Products Containing Recovered Materials; final rule. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provision of the contract.

5. **Quality Assurance Requirements:**

5.1 Contractor Certification. The contractor shall certify and maintain substantial evidence that the product offered meets the salient characteristics of this commercial item description, and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provision of the contract.

5.2 Examination & Testing

5.2.1 Suppliers are encouraged to use quality control (QC) techniques that exhibits control over their processes (e.g. Statistical process Controls). These techniques shall ensure quality levels equal to, or greater than, those cited in the applicable technical document or herein. For those product characteristics which are controlled by such a method, requirements for end item inspection or test may be considered to have been met.

5.2.2 End item inspection / testing may be used by the offeror, or the Government representative, as a means to determine the effectiveness of the inprocess quality controls. While inprocess controls shall not be substituted for end item performance testing, they may be used for visual and dimensional sampling.

5.2.3 For those characteristics for which there are no such controls, or for end item performance test, lot by lot sampling for inspection/shall be required. The sample unit shall be one trimmer. Sampling shall be in accordance with the American National Standards Institute (ANSI) / American Society of Quality Control (ASQC) ANSI/ASQC Z1.4 1993, Sampling Procedures and Tables for Inspection by Attributes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:11Z
Check the source to verify that this is the current version before use.

5.2.4 For visual and dimensional inspections the level shall be S-3 with an Acceptable Quality Level (AQL) of 4.0 Percent Defective. For performance testing the level shall be S-1, with an Acceptable Quality Level of 4.0 percent defective. The supplier must provide objective evidence (test and inspection records) that the presented material meets the requirements of this Commercial Item Description.

5.3 Testing.

5.3.1 Sampling for Design Test: Samples shall be taken from the first ten(10) manufactured. At the beginning of the contract cycle or when the design is modified, design testing shall be performed. Design tests shall include all Operational and Performance Tests.

5.3.2 Routine Testing During The Contract Period: During the contract, lot testing shall be performed. Performance test variation is such: "Each cutting operation shall be performed ten(10) times. At least nine(9) of the cuts shall leave the edges straight and clean". Rigidity tests may be performed periodically at the discretion of the Government.

5.3.4 Rigidity Test. Place a 30 kg (66.15 lb.) mass in the center of the cutting table. The mass shall contact 250 sq. cm ± 13 sq. cm (38.74 sq. in ± 2.01 sq. in.) of the table's surface. The body shall not deflect more than 5 mm (0.196 in.).

5.4 Performance Tests.

5.4.1 9.07 kilogram(20-lb.), Book Paper, Chemical Pulp, (Weight Basis, 17x22-500). This test shall demonstrate the capacity of the trimmer to consistently cut ten(10) sheets of 20.828 cm x 27.94 cm (8-1/2" x 11") 9.07 kilogram (20-lb.) bond paper at one time, leaving the cut edges straight and clean. The cutting shall be performed along an edge at least 27.94 cm(11") long. The cutting shall be performed 100 times. At least 95 of the cuts shall leave the edges straight and clean. In addition, the trimmer shall not exhibit evidence of deformity(See Section 3) after the tests. Examination shall be by the naked eye, only.

5.4.2 36.28 kilogram(80-lb.)- Book Paper, Chemical Pulp, (Weight Basis, 25 x 38 -500). This test shall demonstrate the capability of the trimmer to consistently cut four(4) sheets of 36.28 kilogram(80-lb.), Book Paper, leaving the cut edges straight and clean. The cutting hall be performed along an edge at least 27.94 cm(11") long. The cutting shall be performed 100 times. At least 95 of the cuts shall leave the edges straight and clean. In addition, the trimmer shall not exhibit evidence of deformity after the tests. Examination shall be by the naked eye, only.

6. Packaging:

6.1 Preservation, packing and marking shall be as specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:11Z
Check the source to verify that this is the current version before use.

7. **Notes:**

7.1 Applicable Documents: The issue of the referenced documents in effect on the date of the solicitation for offers or request for proposals shall be used to determine conformance with the requirements of this commercial item description.

7.1.1 Federal Acquisition Regulation (FAR) may be obtained from the Superintendent of Documents, Government Printing Office, Washington. DC 20402.

7.1.2 Application for copies of (ANSI) Z1.1, Z1.2, Z1.3 and (ASQC) B.1, B.2 and B.3 may be obtained from the American Society for Quality Control. PO Box 3005, 611 E. Wisconsin Avenue, Milwaukee, WI 53201-4606.

7.1.3 Copies of Industry Standard: UL Standard No. 94 are available from Underwriters Laboratories, Inc.; Attn: Publication Stock; 333 Pfingsten Road; Northbrook, IL 60062.

7.2 National Stock Number Listing:

Trimmer, Paper, Drop

7520-00-163-2568
7520-00-224-7620
7520-00-224-7621
7520-00-282-2137
7520-00-634-4675

MILITARY INTERESTS:

NONE: DoD has no registered interest in revisions and amendments to this Commercial Item Description until further notice.

Preparing Activity:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2020-10-25T08:11Z
Check the source to verify that this is the current version before use.