INCH-POUND

A-A-52079B
19 March 2009
SUPERSEDING
A-A-52079A
30 June 1993

# COMMERCIAL ITEM DESCRIPTION

# MANTLE, ILLUMINATING (GASOLINE LANTERN)

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE. This commercial item description (CID) covers one type of mantle for fuel burning lanterns.

2. SALIENT CHARACTERISTICS

2.1 Design. The mantel shall be commercial, knitted, soft-type. When the mantle is laid flat its dimensions shall approximate 2.87 inches long by 2.25 inches wide with a tolerance of ± 0.25 inches.

2.2 Mantle. The mantle shall be made from a chemically treated seamless knitted rayon tubing. The closed end of the mantle shall be formed by gathering or pleating the tube and sewing with chemically treated cotton thread. The resulting bag shall be turned so that the end is on the inside. The top section of the mantle shall be treated with a chemical solution or material selection to provide hardness and increase the strength and abrasion resistance of this section of the mantle after ignition. Approximately half of this treated band shall be turned in, to form a double thickness. A drawstring shall be threaded around and through the top or head hardened section of the mantle for fastening the mantle to the mantle holder of the lantern.

2.2.1 Seamless knitted tubing. The seamless knitted tubing shall be knit from 150 denier, 42 filament, bright rayon yarn (or equal) using duplex weave.

2.2.2 Instructions. Mantle installation instructions shall be included with each unit pack.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to: STDZNMGT@dla.mil or Defense Supply Center Richmond (DSCR), ATTN: DSCR-VEB, 8000 Jefferson Davis Highway, Richmond, VA 23297-5616.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

## 3. REGULATORY REQUIREMENTS

3.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

## 4. PRODUCT CONFORMANCE PROVISIONS

4.1 Product conformance. The products provided shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The government reserves the right to require proof of such conformance.

4.2 Bid sample. Ten mantles shall be submitted for bid sample testing.

4.2.1 Bid sample performance test. Two mantles shall be installed and prepared in a commercial lantern according to mantle manufacturers instructions prior to lantern operation. The lantern shall then be lit per the manufactures instructions. The lantern shall be operated for 30 minutes, turned off, and allowed to cool for 30 minutes. This operation shall be repeated five times. The other mantle shall be installed and ignited (in pairs of two) in the same manner except they will be ignited only one time. All mantles shall be examined for broken threads and holes. The first set of mantles will be tested for light output. The light output shall be a minimum of 150 candle power.

4.3 Metric product. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in FED-STD-376, "Preferred Metric Units for General Use by the Federal Government", and all other requirements of this CID are met. If a product is manufactured to a metric dimension and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable. The contracting officer has the option of accepting or rejecting the product.

4.4 Market acceptability. The product offered must have been previously sold either to the government or on the commercial market.

## 5. PACKAGING

5.1 Preservation, packing, and marking. Preservation, packing, and marking shall be as specified in the acquisition order (see 6.3(b)).

## 6. NOTES

6.1 Intended use. The mantle is intended for use with a single or double mantle fuel burning lantern.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

6.2 Sources of documents.

6.2.1 FAR. The FAR may be obtained from the Superintendent of Documents, P.O. Box 371954, Pittsburgh, PA 15250-7954. Electronic copies of FAR documents may be obtained from http://www.arnet.gov/far/.

6.2.2 Federal standards. Copies of federal standards may be obtained from General Services Administration, Federal Supply Service, Specification Section, 470 East L'Enfant Plaza SW, Suite 8100, Washington, DC 20407. Electronic copies of federal standards may be obtained from http://assist.daps.dla.mil/.

6.3 Ordering data. The acquisition order should specify the following information:

a. CID document number and revision.
b. Preservation, packing, and marking (see 5.1).

6.4 Subject term (key word) listing.

fuel
knitted
rayon
tubing
yarn

MILITARY INTERESTS:

Custodians:
Army - GL
Navy - CG
Air Force - 99

Review Activity:
Army - CR4

CIVIL AGENCY
COORDINATING ACTIVITY:

GSA - FAS

Preparing Activity:
DLA - GS2

(Project 6260-2009-003)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST database at http://assist.daps.dla.mil/.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.