INCH-POUND

A-A-52087
December 10, 1990

COMMERCIAL ITEM DESCRIPTION

GLOVE INSERTS, COLD WEATHER, LIGHTWEIGHT

The General Services Administration has authorized the use of this commercial item description.

1. CLASSIFICATION

1.1 Classification. This commercial item description covers glove inserts in the following sizes as specified (see 5.2).

Small
Medium/Large
Extra Large

2. SALIENT CHARACTERISTICS

2.1 Description. The gloves inserts shall be of an ambidextrous design with knitted hands, fingers, and thumbs. All parts of the gloves except the cuffs shall be knit seamless with a plain (jersey) stitch. The cuffs shall be knit seamless with a mock rib with an elastic yarn laid in every other course and two elastic yarns inserted around the edge of the cuff. The two elastic yarns shall be overedged stitched twice around and overlapped not less than 1/4 inch. The gloves shall be knit with one end of yarn as specified in 2.2, and shall be made on a fully automatic, 84 needle, 13 cut flat bed knitting machine.

2.2 Material.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be addressed to: Commander, U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-IRT, Natick, MA 01760-5019.

AMSC N/A FSC 8415

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.

2.2.1 Yarn. The yarn for knitting the gloves shall be a 55 percent acrylic, 25 percent wool, and 20 percent hollow-core polyester blend. Acrylic staple, wool, and polyester staple shall be mixed, carded, spun, and twisted into a 2/24 count yarn with 10.5 turns per inch for the singles and 5.5 turns per inch for the ply. The acrylic shall be 3 denier 4-1/2 inches staple. The wool shall be virgin fleece not lower in grade than 54's U.S. Standard. The polyester shall be 5.5 denier, 12 to 18 percent void, 4-1/2 inches staple.

2.2.2 Elastic yarn. The elastic yarn for every other course of the cuff shall be made of spandex 210 denier (nominal size) with an inner and outer covering of 100 denier, 2 ply stretch nylon yarn.

2.3 Color. The color of all parts of the finished glove shall be Brown 436. The dyed glove inserts shall conform to the standard sample for shade and shall show good fastness to laundering and perspiration when tested in accordance with test methods 5614 and 5680 of FED-STD-191.

2.4 Dimensions. The dimensions of the finished gloves shall be as specified in table I.

TABLE I. Finished glove measurements (inches)

	Size			
Characteristic	Small	Medium/Large	Extra Large	Tolerance
Cuff length	3	3-1/4	3-3/8	± 1/8
Cuff width	3	3-1/4	3-3/8	± 1/8
Palm width 1/	3-7/8	4	4-1/8	± 1/8
Thumb length 2/	2-1/8	2-1/4	2-3/8	± 1/8
First finger length 2/	2-1/2	2-3/4	3	± 1/8
Second finger length 2/	2-3/4	3	3-1/4	± 1/8
Third finger length 2/	2-5/8	3	3-1/4	± 1/8
Fourth finger length 2/	1-7/8	2-1/8	2-1/4	± 1/8
Thumb width	1-1/4	1-1/4	1-1/4	± 1/16
First finger width	1-1/16	1-1/8	1-1/4	± 1/16
Second finger width	1-1/16	1-1/8	1-1/4	± 1/16
Third finger width	1-1/16	1-1/8	1-1/4	± 1/16
Fourth finger width	1	1-1/16	1-1/8	± 1/16
Overall length 3/	9	10-1/4	11-1/2	± 1/4

1/ Measured from thumb crotch and across the palm

2/ Measured from tip of finger to base of finger

3/ Measured from tip of middle finger to bottom of cuff

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.

2.5 Label. Each glove insert shall have a combination size, care, and identification marking conforming to type III or IV, class 4 of DDD-L-20, except that the color of the marking medium shall be white. The marking shall be applied to either the cuff (1/2 ± 1/16 inch down from the overedging), or to the palm area (1/2 ± 1/16 from the cuff). The marking shall be clearly legible and show good fastness to laundering when tested as specified in DDD-L-20. The marking legend and size of characters shall be as follows:

Size (minimum 1/2 inch)
Nomenclature (minimum 1/4 inch)
Contract number (minimum 1/4 inch)
National stock number (minimum 1/4 inch)
Contractor's name (minimum 1/4 inch)
Wool Products Labeling Act information (minimum 1/4 inch)

3. QUALITY ASSURANCE

3.1 Certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics and requirements of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery, and thereafter as may be otherwise provided for under the provisions of the contract.

3.2 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

3.3 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

3.4 End item visual examination. Each lot of glove inserts shall be examined for consumer type defects, defined as follows:

Defects in design, construction, or workmanship; any variation in size or color in gloves of a pair; any component full, tight, or twisted; open seam; any hole, needle chew, cut or tear, or any spot or stain clearly noticeable; elastic yarn not laid in every other course; not specified number of elastic yarns inserted around top edge of cuff; elastic yarns not overedged twice around and overlapped less than 1/4 inch; not properly mated; not labeled as specified.

The lot size shall be expressed in units of one glove. The sample unit shall be one glove, and the selection shall be by pairs. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 6.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.

3.4 End item dimensional examination. The gloves shall be examined for conformance to the dimensions specified in table I. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of one glove. The sample unit shall be one glove and the selection shall be by pairs. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4. PACKAGING

4.1 Packaging. Ten pairs of glove inserts of one size only shall be neatly stacked in a bundle and securely tied with tape or twine.

4.2 Packing. One hundred twenty pairs of glove inserts (twelve bundles) of one size only shall be packed in a fiberboard shipping container conforming to RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Inside dimensions of each shipping container shall approximate 22 inches in length, 10 inches in width, and 6-1/2 inches in depth. Four ounces of flaked napthalene shall be uniformly distributed throughout the contents of each shipping container. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to A-A-203. Each container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

4.3 Palletization. When specified (see 5.2), gloves packed as specified shall be palletized in accordance with load type Ia of MIL-STD-147.

4.4 Marking. In addition to any special marking required by the contract or purchase order, bundles, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129.

5. NOTES

5.1 Intended use. The glove inserts are to be worn for added warmth with the glove shells covered by MIL-G-44419, Gloves, Men's and Women's, Intermediate Cold/Wet.

5.2 Ordering data. Acquisition documents must specify the following:

a. Title, number, and date of this document.
b. Size required (see 1.1).
c. When palletization is required (see 4.3).

5.3 Source for Government documents. Copies of Military and Federal documents are available from:

Standardization Documents Order Desk
Building 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

Source: https://assist.dla.mil -- Downloaded: 202640-26T09:06Z
Check the source to verify that this is the currentversion before use.

MILITARY INTERESTS:

Custodians

Army - GL
Navy - NU
Air Force - 99

Review Activities

Army - MD
Air Force - 11, 82
DLA - CT

User Activities

Navy - MC
Air Force - 45

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

(Project 8415-0785)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.