INCH-POUND

A-A-52087A
22 July 1992
Superseding
A-A-52087
10 Dec. 1990

COMMERCIAL ITEM DESCRIPTION

GLOVE INSERTS (COLD WEATHER)

The General Services Administration has authorized the use of this Commercial Item Description.

Abstract. This description covers the requirements for glove inserts which are intended for use by all Military services.

Classification. The glove inserts shall be in the following sizes:

Small, Medium, Large

SALIENT CHARACTERISTICS

*Description. The glove inserts shall be ambidextrous design with knitted hands, fingers and thumbs. All parts of the glove insert with the exception of the cuffs shall be knit seamless with a plain (jersey) stitch. The cuffs shall be knit seamless with a mock rib with an elastic yarn laid in every other course and two elastic yarns inserted around the edge of the cuff. The two elastic yarns shall be overedged stitched twice around and overlapped not less than 1/4 inch. The gloves inserts shall be knit with one end of yarn as specified and shall be made on a fully automatic, 84 needle (Per Side), 13 cut flat bed knitting machine.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Personnel Support Center, Clothing and Textiles Directorate, Attn: DPSC-FSSD, 2800 South 20th Street, Philadelphia, PA 19101-8419, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8415

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.

MATERIAL.

*Yarn. The yarn for knitting the gloves shall be a 55% acrylic, 25% wool, and 20% hollow-core polyester blend. Acrylic staple, wool, and polyester staple shall be blended, spun, and twisted into a 2/24 worsted count yarn with 10.5 turns per inch for the singles and 5.5 turns per inch for the ply. The acrylic shall be 3 denier 4-1/2 inches nominal staple. The wool shall be virgin fleece not lower in grade than 54's U.S. standard. The polyester shall be 5.5 denier, 12 to 18% void, 4-1/2 inches nominal staple.

Elastic yarn. The elastic yarn for every other course of the cuff shall be made of spandex 210 denier (nominal size) with an inner and outer covering of 100 denier, 2 ply stretch nylon yarn.

*Color. The color of all parts of the finished glove shall approximate Brown 436. The dyed glove inserts shall conform to the standard sample for shade and shall show good fastness to laundering and perspiration when tested in accordance with test methods 5614 and 5680 of FED-STD-191.

*Dimensions. The dimensions of the finished gloves shall be as specified in Table I. In addition, the glove insert shall be constructed so that the thumb length shall be 85-90% of the middle finger length, the third finger shall be approximately 90% of the middle finger length, and the fourth finger length shall be approximately 72% of the middle finger length.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.

TABLE I. Finished gloves measurements (inches)

Characteristic	Size			
	Small	Medium	Large	Tolerance
Cuff length (Min.) 1/	3	3	3	- 3/8
Palm width 2/	3-7/8	4	4-7/8	± 1/4
Palm length 3/	3-1/2	4-1/2	5	± 3/16
Middle finger width 4/	1-1/16	1-1/8	1-1/4	± 1/8
Middle finger length 4/	2-3/4	3	3-1/4	± 3/16
Index finger length 5/	2-1/2	2-3/4	3	± 3/16

NOTE: All measurements shall be taken on glove inserts laid flat in a relaxed position.

1/ From top end of mock rib knit to the lower edge, including overedge hem.

2/ From thumb crotch horizontally across the palm.

3/ From crotch between index and middle finger down to top edge of mock rib knit at wrist.

4/ Horizontal at crotch from one side to the other side.

5/ From center of fingertip to the center of finger base, at crotch level.

*Weight. The weight of the finished glove inserts shall be as follows:

Insert Size	Ounces/Dozen Pair (Minimum)
Small	14
Medium	15
Large	17

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.

Label. Each glove shall have a combination identification, size and instruction label described as type VI, class 14 of DDD-L-20. The color of the label shall be approximately 1-1/2 inches wide and 1-1/4 inches long. The width shall be sewn onto the outside of the insert at the hem of the back hand. The label shall show colorfastness to laundering and contain the following information:

GLOVE INSERT
CW LIGHTWEIGHT
NSN
SIZE
CONTRACT NO.
NAME OF CONTRACTOR

On the underside of the label:
Machine or hand wash
in warm water with
mild soap/detergent
DO NOT TUMBLE DRY OR BLEACH

*Instruction slip. A printed slip of thin paper containing instructions as indicated below shall be inserted in one glove insert out of every pair:

Instructions
Glove Inserts, Cold Weather, Lightweight

Only wear these gloves inserts with gloves, Men's and women's intermediate cold/wet, MIL-C-44419. The glove inserts can be worn on either right or left hand. Remove the inserts when they become damp from perspiration and replace them with a dry pair of inserts to keep hands warm.

*Fitting. The following schedule dictates the appropriate size insert to be worn with gloves, men's/women's intermediate cold/wet:

Glove insert	Intermediate cold/wet glove shell
Small	Size 1 or 2
Medium	Size 3 or 4
Large	Size 5

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.

*CLEANING

*Field Laundry. The glove insert shall be laundered utilizing formula II of FM 10-280 and air dry. DO NOT TUMBLE DRY OR BLEACH.

*Machine/hand laundry. Use permanent press wash cycle or hand wash using warm water (90 degrees F) and mild laundry detergent or soap and air dry. DO NOT TUMBLE DRY OR USE BLEACH.

QUALITY ASSURANCE

*Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices. The government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for, under the provisions of the contract. Reliance on contractor QA systems shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the government for acceptance comply with all requirements of the contract.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

End item visual examination. Each lot of glove inserts shall be examined for consumer type defects, defined as follows:

*Defects in design, construction, or workmanship; any variation in size or color in gloves of a pair; any component full, tight, or twisted; any hole, needle chew, cut or tear, or any spot or stain clearly noticeable; elastic yarn not laid in every other course; not specified number of elastic yarns inserted around top edge of cuff; elastic yarns not overedged twice around and overlapped less than 1/4 inch; not properly mated; not labeled as specified.

The lot size shall be expressed in units of one glove. The sample unit shall be one glove, and the selection shall be by pairs.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:06Z
Check the source to verify that this is the current version before use.

End item dimensional examination. The glove inserts shall be examined for conformance to the dimensions specified in Table I. The lot size shall be expressed in units of one glove insert. The sample unit shall be one glove insert and the selection shall be by pairs. Any glove insert not within the specified tolerance shall be classified a defect.

PACKAGING

Packaging. Ten pairs of glove inserts of one size only shall be neatly stacked in a bundle and securely tied with tape or twine.

Packing. One hundred twenty pairs of glove inserts (twelve bundles) of one size only shall be packed in a fiberboard shipping container conforming to RSC-L, Type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Inside dimensions of each shipping container shall approximate 22 inches in length, 10 inches in width, and 6-1/2 inches in depth. Four ounces of flaked naphthalene shall be uniformly distributed throughout the contents of each shipping container. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to A-A-203. Each container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

Palletization. Gloves packed as specified shall be palletized in accordance with load type Ia of MIL-STD-147.

Marking. In addition to any special marking required by the contact or purchase order, bundles, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129.

NOTES

Intended use. The glove inserts are to be worn for added warmth with the glove shells covered by MIL-G-44419, Gloves, Men's and Women's, Intermediate Cold/Wet.

Ordering data. Acquisition documents must specify the following:

a. Title, number, and date of this document.
b. Size required.
c. When palletization is required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.

Source for Government documents. Copies of Military and Federal documents are available from:

Standardization Documents Order desk
Building 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

Custodian:
Army - GL
Navy - NU
Air Force - 99
Coast Guard - CG

Review Activity:
Army - MD
Air Force - 11, 82, 45

User Activities:
Navy - MC

Civil Agency Coordinating Activity
GSA - FSS

Preparing Activity
DLA - CT

Project No. 8415-0868

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER A-A-52087A	2. DOCUMENT DATE (YYMMDD) 920722

3. DOCUMENT TITLE
Glove Inserts (Cold Weather)

4. NATURE OF CHANGE (*Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.*)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (*Last, First, Middle Initial*)	b. ORGANIZATION	
c. ADDRESS (*Include Zip Code*)	d. TELEPHONE (*Include Area Code*) (1) Commercial (2) AUTOVON (*If applicable*)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME DLA-CT	b. TELEPHONE (*Include Area Code*) (1) Commercial (215) 737-8105	(2) AUTOVON 444-8105
c. ADDRESS (*Include Zip Code*) 2800 South 20th Street Philadelphia, PA 19101-8419	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 83 *Previous editions are obsolete.*

Source: https://assist.dla.mil -- Downloaded: 202640-26T09:06Z
Check the source to verify that this is the current version before use.