[METRIC]
A-A-52100A
19 June 1998
SUPERSEDING
A-A-52100
3 April 1991

COMMERCIAL ITEM DESCRIPTION

SPOT REMOVER (FOR REMOVAL OF OIL AND GREASE FROM CLOTHING)

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE. This commercial item description (CID) covers one type of spot remover to be used as an aid for removing oil and grease stains from washable fabrics, including permanent press, by application to the stains prior to washing.

2. SALIENT CHARACTERISTICS

2.1 Aliphatic petroleum distillate. The spot remover shall contain 94.5 ± 0.5 percent by weight of an aliphatic petroleum distillate conforming to Type II of P-D-680.

2.2 Nonionic surfactant. The nonionic surfactant contained in the spot remover shall be 5.5 ± 0.5 percent by weight of an oil soluble surface active agent. It shall be prepared by the ethoxylation of petroleum derived linear alcohols in the C_{11} to C_{15} range and shall contain an average of 5 moles of ethylene oxide. It shall have a molecular weight of 400 ± 5.

2.3 Chlorinated solvents. The spot remover shall not contain any chlorinated solvents. The spot remover shall not exhibit a “positive” result when tested as follows:

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data which may improve this document should be sent by letter to: Defense Supply Center Richmond (DSCR), ATTN: DSCR-VBD, 8000 Jefferson Davis Highway, Richmond, VA 23297-5610.

AMSC N/A FSC 6850

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.

a. Adjust a Bunsen burner to give a colorless flame. Heat a piece of copper wire in the flame and plunge it into ethyl alcohol. Reheat wire in flame watching flame color. When the wire itself imparts no color to the flame, it is clean. Repeat as necessary to ensure a clean wire. Cool wire.

b. Dip the cool, clean wire into the spot remover. While observing closely, insert the wire into the edge of the flame.

c. A green color imparted to the flame, sometimes only a momentary flash, is due to volatilization of copper chloride and is considered a “positive” test for chlorinated solvents.

2.4 Nonvolatile matter. The spot remover shall contain a maximum 5.4 ± 0.5 percent by weight of nonvolatile matter at 95 °C ± 1 °C when tested as follows:

a. Weigh to the nearest 0.1 milligram (mg) a 10 milliliter sample of the spot remover placed into a tared, low-form, weighing bottle (70 millimeter (mm) inside diameter and 33 mm in height). Place bottle containing sample on a billowing steam bath for 1 hour. Remove from steam bath and place in a forced air circulating oven at 95 °C ± 1 °C for 15 minutes. Remove from the oven, place glass stopper on bottle, cool in a desiccator, and weigh the nonvolatile matter to nearest 0.1 mg. Calculate the nonvolatile matter percentage as follows:

$$\text{Percent matter nonvolatile at 95 °C} = \frac{B}{A} \times 100$$

Where A = Weight of sample before 95 °C conditioning and
B = Weight of nonvolatile matter after 95 °C conditioning

2.5 Flash point. The spot remover shall have a minimum flash point of 60 °C when tested in accordance with ASTM D 56.

2.6 Odor. The spot remover shall have a mild odor, essentially that of Stoddard solvent.

3. REGULATORY REQUIREMENTS

3.1 Labeling, packaging and marking. Material shall be labeled, packed and marked in accordance with Title 49, Code of Federal Regulations (CFR), Parts 100 to 185.

3.2 Recycled materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practical, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4. QUALITY ASSURANCE PROVISIONS

4.1 Product conformance. The product provided shall meet the salient characteristics of this commercial item description; conform to the producer’s own drawings, specifications, standards,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.

and quality assurance practices; and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

4.2 Market acceptability. The item offered must have been sold to the government or commercial market.

5. PACKAGING. Preservation, packing, and marking shall be as specified in the contract or order.

6. NOTES. This section contains information of a general or explanatory nature which is helpful, but is not mandatory.

6.1 Source of documents.

6.1.1 Copies of federal documents referenced in this CID may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

6.1.2 ASTM Standards are available from the American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.

6.2. Ordering data. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Unit and quantity required.
c. Packaging requirements.

6.3 National stock numbers (NSNs). The following NSNs correspond to this CID: 6850-01-015-7939 and 6850-01-039-7940. These may not be the only NSNs associated with this document.

CIVIL AGENCY COORDINATING ACTIVITY:
GSA - 10FTE

MILITARY INTERESTS:

Custodians:
Air Force - 68
Army - GL

Preparing Activity:
DLA - GS

(Project 6850-1187)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.