MIL-C-43742B
3 March 1981
SUPERSEDING
MIL-C-43742A
7 November 1975

MILITARY SPECIFICATION

COVER, WATER CANTEEN, LC-2

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type and size canteen cover fabricated from nylon cloth, nylon webbing and acrylic pile liner material.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

V-T-285	-	Thread, Polyester
UU-P-268	-	Paper, Kraft, Wrapping
DDD-L-20	-	Label: for Clothing, Equipage and Tentage (General Use)
PPP-B-636	-	Boxes, Shipping, Fiberboard

MILITARY

MIL-W-4088	-	Webbing, Textile, Woven Nylon
MIL-T-5038	-	Tape, Textile and Webbing, Textile, Reinforcing, Nylon

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Laboratories, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8465

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

MIL-C-7219 - Cloth, Duck, Nylon
MIL-H-9890 - Hardware, Individual Load Carrying Equipment: and Hardware, Miscellaneous
MIL-F-10884 - Fasteners, Snap
MIL-E-20652/1- Eyelets, Metallic, Rolled Flange Type; and Eyelet Washer
MIL-F-21840 - Fastener Tapes, Hook and Pile, Synthetic
MIL-W-27265 - Webbing, Textile, Woven Nylon, Impregnated
MIL-C-43103 - Canteen, Water, Plastic, with Screw Cap
MIL-C-43251 - Cloth, Pile, Acrylic Fiber Pile
MIL-C-43761 - Cup, Water Canteen, w/Wire Handle, Corrosion-Resisting Steel

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads
MIL-STD-1188 - Commercial Packaging of Supplies and Equipment
MS 27980 - Fasteners, Snap, Style 2 (Regular Wire Spring Clamp Type)

DRAWINGS

U.S. ARMY NATICK RESEARCH AND DEVELOPMENT LABORATORIES

2-2-30 - Cover Water Canteen, LC-2; Assembly, Details, and Sections
2-2-31 - Cover Water Canteen, LC-2; Details A
2-2-32 - Cover Water Canteen, LC-2; Details B

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Samples.

3.1.1 Guide sample. Guide samples of the end item, when furnished, are solely for guidance and information to the contractor (see 6.3). Variations from this specification may appear in the sample, in which case this specification shall govern.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

3.1.2 First article. When specified (see 6.2), the contractor shall furnish a sample for the first article inspection and approval (see 4.3 and 6.4).

3.2 Materials (see 6.6).

3.2.1 Cloth, duck, nylon. The 7.25 oz. nylon duck cloth shall be Olive Green 106, water repellent treated, conforming to type III, class 3 of MIL-C-7219.

* 3.2.2 Cloth, pile, acrylic fiber pile. The lining cloth shall be acrylic knit pile, color Green conforming to class 1 of MIL-C-43251, except that the requirements for color matching, dullness, and colorfastness shall not apply.

* 3.2.3 Webbing, nylon 3/4, 1-1/4 and 2-1/4-inch widths. The 3/4-inch type Ia, 1-1/4-inch type III, and 2-1/4-inch type VIIIc webbing before treatment, shall conform to class 2 of MIL-W-4088. The webbing shall be dyed Olive Drab 7 to match the standard sample (see 6.3).

3.2.3.1 Resin treatment. The webbing shall be resin impregnated to conform to class R of MIL-W-27265.

3.2.4 Tape, nylon. The nylon binding tape shall be dyed Olive Drab 7 and shall conform to type III, 1 inch width of MIL-T-5038.

* 3.2.5 Thread, polyester. The polyester thread shall conform to type I, class 1, subclass B of V-T-285. Sizes shall be as follows:

For attaching piece "A", piece "B", body reinforcement, flap reinforcements and side and bottom closing.	Size F
For pocket, pocket flap, attaching lining to body and bottom, bartacking and binding.	Size E

3.2.5.1 Color. The thread shall be dyed Olive Drab S-1 (C.A. 66022) and shall show fastness to weathering equal to or better than the standard sample (see 6.3). If no standard sample is available, the thread shall show good fastness to weathering.

3.2.6 Fastener tape, hook and pile, nylon. The hook and pile fastener tape shall be dyed shade Olive Green 106, and shall conform to type II, class 1, 5/8 inch of MIL-F-21840.

3.2.7 Keeper with slide. The keeper with slide shall be steel, black, and shall conform to type X of MIL-H-9890.

3.2.8 Fasteners, snap. The snap fasteners shall conform to style 2, finish 2, size 1 of MIL-F-10884, and shall be Part Numbers MS 27980-1B (Button), -6B (Socket), -7B (Stud), and -8B (Eyelet) of MS 27980.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

3.2.9 Eyelet, aluminum, black. The black enameled aluminum eyelet shall conform to Dash No. ABE 131 of MIL-E-20652/1.

3.3 Construction. The construction shall conform in all respects to the drawings listed in section 2 and as specified herein.

* 3.3.1 Stitches, seams and stitchings. All stitching, except bartacking, shall conform to FED-STD-751 as follows:

For attaching piece "A", piece "B", body reinforcement, flap reinforcements and bottom closing.	Type 301, 6 to 8 stitches per inch
For pocket, pocket flap, attaching lining to body and bottom, and for binding. (As an option the stitching for attaching the bottom lining to the bottom may be type 401, 8 to 10 stitches per inch).	Type 301, 8 to 10 stitches per inch

* 3.3.1.1 Automatic stitching. Automatic machines may be used to perform any of the stitch patterns provided the requirements for the stitch pattern, stitches per inch, and size and type of thread are met; and at least three tying, overlapping or backstitches are used to secure the ends of stitching.

3.3.1.2 Lubrication of thread. There shall be no lubrication of the thread prior to or during sewing (see 4.4.1.1).

* 3.3.1.3 Type 301 stitching. Ends of all stitching shall be backstitched or overstitched not less than 1 inch (1/2 inch for box stitching) except where ends are turned under or caught in other seams or stitching. Thread tensions shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread or excessively tight stitching resulting in puckering of the materials sewn. The lock shall be imbedded in the materials sewn.

3.3.1.3.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during stitching the stitching shall be repaired by restarting the stitching a minimum of 1 inch (1/2 inch on box-stitching) back of the end of the stitching. 1/

* b. Thread breaks, or two or more consecutive skipped or runoff stitches noted during inspection of the item (in-process or end item), shall be repaired by overstitching. The stitching shall start a minimum of 1 inch in back of the defective area (1/2 inch on box-stitching), continue over the defective area and continue a minimum of 1 inch (1/2 inch on box-stitching) beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and restitching in the required manner. 1/

1/ When making the above repairs the ends of the stitching are not required to be backstitched.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

* 3.3.1.4 Type 401 stitching. Thread tension shall be maintained so that there will be no loose stitching. All repairs shall be in accordance with 3.3.1.3.1.a and 3.3.1.3.1.b.

3.3.1.5 Bartacking. Bartacking shall be 1/2 ± 1/16 inch in length, 1/8 ± 1/32 inch in width and shall contain 28 stitches. Bartacks shall be free from thread breaks and loose stitching.

3.3.1.6 Thread ends. All thread ends shall be trimmed to 1/4 inch maximum length.

* 3.3.2 Setting of snap fasteners. A hole shall be prepunched through the materials to receive the button and eyelet components of the snap fasteners. The hole shall be smaller than the outside diameter of the button and eyelet barrels so that the barrel must be forced through the hole. The hole shall not be punched in the setting operation with the button or eyelet barrel. The fasteners shall be securely clinched without cutting the adjacent materials and no more than three splits shall occur in the button or eyelet barrels.

* 3.3.3 Eyelets, aluminum. A hole shall be prepunched through the nylon duck and acrylic fiber pile cloth before inserting the eyelet barrel. The prepunched hole for receiving the eyelet shall be smaller than the outside diameter of the barrel of the eyelet so that the eyelet barrel must be forced through the hole. The eyelet shall be installed using score setting dies conforming to J. C. Rhodes, Part Number 1-KW-1KL and 101Y-1 KLOM or Stimpson Company, Part Number A2744-7 score or equal (see 6.5). The eyelets shall be securely set in a manner that will prevent detachment from, or cutting of, the adjacent material. The scored side of the eyelet shall be on the inside of the assembly.

3.3.4 Location marks. Location marks shall not be drilled. Printed markings shall not be more than 1/32-inch in width.

3.4 Repairs. Repairs such as mends, darns, patches or splices are not permitted on the canteen covers.

* 3.5 Replacement of defective components. During the spreading, cutting and manufacturing process, components having material defects or damages that are classified as defects in 4.4.3.1, shall be removed from production and replaced with non-defective and properly matched components.

3.6 Marking. The identification marking shall be applied in the location shown on Drawings 2-2-30 and 2-2-31 and shall conform to type IV, class 5 of DDD-L-20. The letters "US" shall be applied in the size characters and in the location indicated on Drawing 2-2-31 and shall conform to type IV, class 9 of DDD-L-20. Fastness of the class 9 marking shall be as specified for class 5 marking.

Source: https://assist.dla.mil -- Downloaded: 20261O-21T22:12Z
Check the source to verify that this is the current version before use.

3.7 Workmanship. The finished cover shall conform to the quality of product established by this specification. The occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Certificate of compliance. Where certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

* 4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.3.1, 4.4.3.2 and 4.4.3.3. The presence of any defect shall be cause for rejection of the first article.

* 4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

* 4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.1.1 Certification. The contractor shall furnish a certificate of compliance for the requirement in 3.3.1.2 prohibiting use of thread lubricants.

* 4.4.2 In-process inspection. Inspection shall be made at any point or during any phase of the manufacturing process to determine whether cut lengths, cut parts, markings for location of components, and location of assembled component parts are in accordance with specified requirements. In addition, inspection shall be made to determine that prepunched holes for receiving eyelets and snap fasteners, are smaller than the outside diameter of the hardware barrel. Whenever nonconformance is noted, corrections shall be made to the parts affected and lot in process. Components which cannot be corrected shall be removed from production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

* 4.4.3 End item examination. The classification of defects found during examination shall be in accordance with the lists in 4.4.3.1, 4.4.3.3 and as specified in 4.4.3.2. The sample unit for these examinations shall be one completely fabricated cover. The lot size shall be expressed in units of one cover. The inspection level and acceptable quality level (AQL) for these examinations shall be in accordance with 4.4.3.4.

4.4.3.1 Visual examination.

Examine	Defect	Classification Major	Classification Minor
Cloth, nylon duck	Any hole, cut or tear, smash, broken or missing yarns, or open place.	X	
	Shade bar, fine or coarse filling bar.		X
Cloth, acrylic fiber knit	Any cut, hole, or tear.	X	
Webbing and tape	Frayed or scalloped edge; not firmly and tightly woven.	X	
	Any hole cut or tear.	X	
Hardware (general)	Broken or malformed, corroded areas, burrs or sharp edges.	X	
	Finish omitted or not as specified: - on brass components		X
	- on steel components	X	
	Finish not uniform or partially missing.		X
	Any required component improperly installed causing failure to serve intended purpose.	X	
Snap fasteners	Any fastener not functioning properly, i.e., fails to snap closed, provide a secure closure or to open freely.	X	
	NOTE: The fasteners shall be snapped and unsnapped twice to determine whether parts of fastener separate freely and also effect a secure closure.		
	Clinched excessively tight, cutting adjacent material.	X	
	Clinched loosely, permitting any component to rotate freely but not to the degree that any component can be expected to become detached during use.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Hardware (general) (cont'd)			
Snap fasteners (cont'd)	Clinched loosely to the degree that components can be expected to become detached during use.	X	
NOTE:	Incomplete roll of end of button or eyelet barrel is evidence of improper and insecure clinching.		
	Incorrect style.	X	
	More than three splits in eyelet or button barrels.		X
Pocket and pocket flap	Omitted, not as specified, or not in specified location.	X	
	Pocket darts omitted.		X
Body reinforcement	Omitted, not as specified, or not in specified location.	X	
Eyelet, aluminum	Insecurely clinched.	X	
	Clinched excessively tight, cutting fabric.	X	
	Not set with scored setting.		X
	Scored side on outside.	X	
Open seam	1/2 inch or less.		X
	More than 1/2 inch.	X	
NOTE:	A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more consecutive skipped or runoff stitches occur. On double stitched seams, a seam shall be considered open when either one or both sides of the seam are open.		
Raw edge (except on closing and bottom seams inside cover)	More than 1/2 inch when securely caught in stitching.		X
NOTE:	Raw edges not securely caught in stitching shall be classified as open seams.		

Source: https://assist.dla.mil -- Downloaded: 20261010-21T22:12Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Run-off (see open seam)			
Seam and stitch type	Wrong seam or stitch type.	X	
Stitch tension	Loose, resulting in loose bobbin or top thread.		X
	Excessively tight, resulting in puckering of fabric.		X
Stitches per inch	One stitch less than minimum specified.		X
	Two or more stitches less than minimum specified.	X	
	One or more stitches in excess of maximum specified.		X
	NOTE: Variation in the number of stitches per inch, caused by the operator speeding up the machine and pulling the fabric in order to sew over thick places, or in turning corners shall be classified as follows: (a) Within the minor defect classification - no defect (b) Within the major defect classification - minor defect.		
Thread breaks, skipped stitches or runoffs	Not overstitched as specified.		X
	NOTE: On all types of stitching thread breaks or two or more consecutive skipped or run-off stitches not overstitched shall be classified as open seams.		
Stitching ends (When not caught in other seams or stitching)	Not secured as specified.		X
Bartacks	Any bartack omitted.	X	
	Loose stitching, incomplete or broken.		X

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:12Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Rows of stitching	Any row missing except on box-stitching	X	
	On box stitching:		
	- One row of stitching omitted.		X
	- Two or more rows of stitching omitted.	X	
Components and assembly	Any component or required operation omitted (unless otherwise classified herein).	X	
	Mend, darn, patch or splice.	X	
	Needle chew.	X	
Cleanness	Grease or oil stains clearly noticeable.		X
	Thread ends not trimmed as specified.		X
Location markings	Drilled.	X	
	Printed marking more than 1/32 inch in width.		X
Binding	Loosely applied but not exposing raw edge of material.		X
	Loosely applied exposing raw edge of material.	X	
	Ends of binding not securely caught in closing seam.		X
Marking	Omitted, incorrect, illegible, misplaced, or size of characters not as specified.		X

* 4.4.3.2 Dimensional examination. The cover shall be examined for compliance with all dimensions specified on the drawings and herein including stitch margins and gauge. Any dimension not within the specified tolerance shall be considered a defect.

* 4.4.3.3 Examination for fit of cover. The finished cover shall be examined for the defects listed below.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:12Z
Check the source to verify that this is the current version before use.

Examine		Defect
Fit of canteen and cup in cover	NOTE:	Fit examination shall be performed with a standard plastic water canteen manufactured in accordance with MIL-C-43103, and with a standard corrosion-resistant steel canteen cup manufactured in accordance with MIL-C-43761. The bottom section of the canteen shall be inserted in the cup, and the assembled canteen and cup shall be inserted into the cover. To determine whether canteen and cup fit in cover, the inspector shall ease the cup and canteen into the cover without effort and shall close flaps by snapping fasteners into a closed position. Cover too small; assembled canteen and cup fails to fit into cover. Cover flaps short, causing failure of snap fasteners to effect a smooth and secure closure.

* 4.4.3.4 Inspection level and AQL. Inspection levels and AQLs (expressed in defects per hundred units) shall be as follows:

Examine	Inspection level	AQL
For defects applicable to 4.4.3.1	II	2.5 Major 15.0 Total, major and minor defects combined
For defects applicable to 4.4.3.2	S-3	4.0 one class
For defects applicable to 4.4.3.3	S-3	0.65 one class

* 4.4.4 Packaging inspection. An examination shall be made to determine that the preservation, packing and marking comply with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully packaged except that it shall not be palletized and need not be closed. Examination of closure defects listed below shall be made on shipping containers fully packaged. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

Examine	Defect
Marking (exterior and unit packs)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or not as specified.
Workmanship	Inadequate application of components, such as: incomplete closure of container flap, improper taping, loose strapping or inadequate stapling. Bulged or distorted container.
Content	Number of bundles per container is more or less than required. Number of covers per bundle is more or less than required. 1/

1/ For this defect, two bundles from each shipping container in the sample shall be examined.

4.4.5 Examination for palletization. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the end item inspection lot. The inspection level shall be S-1 and the AQL shall be 6.5 defects per hundred units.

Examine	Defect
Finished dimensions	Length, width or height exceeds specified maximum requirement.
Palletization	Interlocking of loads not as specified. Pallet pattern not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

5.1.1 Level A. Each canteen cover shall be smoothed out flat. The flaps shall be fastened and keepers and pocket closed. Ten canteen covers shall be stacked one on top of another with the flaps alternated end for end and facing downward, except the flaps of the top cover shall face upward. The bundle shall then be securely tied with cotton tape or twine.

* 5.1.2 Commercial. The canteen covers shall be preserved in accordance with MIL-STD-1188.

5.2 Packing. Packing shall be level A, B or Commercial as specified (see 6.2).

* 5.2.1 Level A packing. One hundred and eighty canteen covers, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Level A unit packs shall be packed flat, three in length, three in width and two in depth. Inside dimensions of each shipping container shall approximate 24 inches in length, 21 inches in width and 12-1/2 inches in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on the top and bottom with a sheet of 30 pound minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V and reinforced as specified in the appendix of the container specification, except the inspection shall be in accordance with 4.4.4.

* 5.2.2 Level B packing. One hundred and eighty canteen covers, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Level A unit packs shall be packed flat, three in length, three in width and two in depth. Inside dimensions of each shipping container shall approximate 24 inches in length, 21 inches in width and 12-1/2 inches in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on the top and bottom with a sheet of 30 pound minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. Each shipping container shall be closed in accordance with method II as specified in the appendix of the container specification, except the inspection shall be in accordance with 4.4.4.

* 5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of the container specification, except the inspection shall be in accordance with 4.4.4.

* 5.2.3 Commercial packing. Canteen covers, preserved as specified in 5.1, shall be packed in accordance with MIL-STD-1188.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

5.3 Palletization. When specified (see 6.2), canteen covers, packed as specified in 5.2, shall be palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. If the container is of a size which does not conform to any of the patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

* 5.4 Marking. In addition to any special marking required by the contract, unit packs, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or MIL-STD-1188, as applicable. Each unit pack shall have attached a manila colored paper shipping tag for the identification information.

6. NOTES

6.1 Intended use. The canteen cover is designed as a carrier for a one quart nominal capacity water canteen and cup. The cover has a small pocket attached for carrying water purification tablets and is also equipped with metal keepers for attaching the cover to an individual equipment belt for carrying purposes.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) First article. When first article sample is required (see 3.1.2, 4.3 and 6.4).
* (c) Selection of the applicable levels of preservation and packing (see 5.1 and 5.2).
(d) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
(e) When palletization is not required (see 5.3).

6.3 Samples. For access to samples, address the procuring activity issuing the invitation for bids.

6.4 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of DAR 7-104.55. The first article should be a preproduction sample. consisting of one finished cover. The contracting officer should include specific instructions in all procurement instruments regarding arrangement for inspection and approval of the first article.

6.5 Sources of supply. Sources of supply for the score setting eyelet die specified in 3.3.3 is J.C. Rhodes & Co., Box B-962, New Bedford, MA 02745 and Stimpson Company, Inc., Bayport, NY 11705.

6.6 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

6.7 International standardization agreements. Certain provisions of this specification are the subject of international standardization agreement number STANAG 2311. When amendment, revision, or cancellation of this specification is proposed which will affect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels including departmental standardization offices, if required.

* 6.8 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - NU

Review activities:

Army - MD
Navy - AS
DLA - CT

User activity:

Navy - MC

Preparing activity:

Army - GL

Project No. 8465-0820

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-43742B Cover, Water Canteen, LC-2

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.