MIL-C-43745B
9 March 1981
SUPERSEDING
MIL-C-43745A
17 December 1975

MILITARY SPECIFICATION

CASE, FIELD, FIRST AID DRESSING-UNMOUNTED MAGNETIC COMPASS, LC-1

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type and size of case fabricated from nylon duck, with metallic hardware.

2. APPLICABLE DOCUMENTS

* 2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

V-T-285	-	Thread, Polyester
UU-P-268	-	Paper, Kraft, Wrapping
DDD-L-20	-	Label: for Clothing, Equipage and Tentage (General Use)
PPP-B-636	-	Boxes, Shipping, Fiberboard

MILITARY

MIL-W-4088	-	Webbing, Textile, Woven Nylon
MIL-T-5038	-	Tape, Textile and Webbing, Textile, Reinforcing, Nylon

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Laboratories, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8465

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

MIL-C-7219 - Cloth, Duck, Nylon
MIL-H-9890 - Hardware, Individual Load Carrying Equipment: and Hardware, Miscellaneous
MIL-F-10884 - Fasteners, Snap
MIL-E-20652/1- Eyelets, Metallic, Rolled Flange Type; and Eyelet Washer
MIL-E-20652/3- Eyelets, Metallic, Telescopic Type
MIL-W-27265 = Webbing, Textile, Woven Nylon Impregnated

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads
MIL-STD-1188 - Commercial Packaging of Supplies and Equipment

DRAWING

U.S. ARMY NATICK RESEARCH AND DEVELOPMENT LABORATORIES

2-2-29 - Case, Field, First Aid Dressing-Unmounted Magnetic Compass, LC-1; Illustration, Assembly and Details

(Copies of specifications, standards and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

* 3.1 Guide sample. Guide samples of the end item, when furnished, are solely for guidance and information to the contractor (see 6.3). Variations from the specification may appear in the sample, in which case the specification shall govern.

3.2 First article. When specified (see 6.2), the contractor shall furnish a sample for first article inspection and approval (see 4.3 and 6.4).

* 3.3 Materials (see 6.5).

3.3.1 Cloth, nylon. The nylon cloth shall be Olive Green 106 conforming to type III, class 3 of MIL-C-7219.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

3.3.2 Tape, nylon. The nylon binding tape shall conform to type III, 1 inch wide of MIL-T-5038 and shall be dyed Olive Drab 7.

* 3.3.3 Webbing, nylon. The nylon webbing, before treatment, shall be Olive Drab 7 conforming to type VIIIC, class 2 of MIL-W-4088.

3.3.3.1 Treatment. The nylon webbing shall be resin impregnated to conform to class R of MIL-W-27265.

3.3.4 Thread, polyester. The polyester thread shall conform to type I, class 1, subclass B, size E of V-T-285.

3.3.4.1 Color. The thread shall be dyed Olive Drab S-1 (C.A. 66022) and shall show fastness to weathering equal to or better than the standard sample (see 6.3). When no standard sample is available, the thread shall show "good" fastness to weathering.

3.3.5 Keeper with slide. The keeper with slide shall conform to type X of MIL-H-9890.

3.3.6 Fastener, snap. The snap fastener shall conform to style 2, finish 2 of MIL-F-10884. The female component shall be the socket with a 24 line size, size 1 button and the male component shall be the stud with size 1 eyelet.

3.3.7 Eyelet and washer. The eyelet and washer shall conform to dash numbers BBE 117 and BBW 101 respectively, of MIL-E-20652/1; or as an alternate, eyelet and washer conforming to dash numbers BBT 307 and BBT 308 respectively, of MIL-E-20652/3 may be used.

3.4 Construction. The construction shall conform in all respects to Drawing 2-2-29 and as specified herein.

* 3.4.1 Stitching, machine. All stitching, except bartacking, shall conform to FED-STD-751, type 301 with 8 to 10 stitches per inch.

3.4.1.1 Type 301 stitching. Ends of all stitching shall be backstitched or overstitched 1/2 inch minimum except where ends are turned under in a hem or held down by other stitching. Thread tensions shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread, or excessively tight stitching resulting in puckering of the materials sewn. The lock shall be embedded in the materials sewn.

* 3.4.1.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during stitching, the stitching shall be repaired by restarting the stitching a minimum of 1/2 inch back of the end of the stitching. 1/

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

b. Thread breaks, or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1/2 inch in back of the defective area, continue over the defective area and continue a minimum of 1/2 inch beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching without damaging the materials and restitching in the required manner. 1/

1/ When making the above repairs, the ends of the stitching are not required to be backstitched.

3.4.1.2 Bartacking. Unless otherwise specified, bartacking shall be 1/2 ± 1/16 inch in length, 1/8 ± 1/32 inch in width and shall contain 28 stitches. Bartacking shall be free from thread breaks and loose stitching.

3.4.1.3 Automatic stitching. Automatic machines may be used to perform any of the required stitch patterns provided the requirements for the stitch pattern, stitches per inch, size and type of thread are met; and at least three or more tying, overlapping or back stitches are used to secure the ends of the stitching.

3.4.1.4 Lubrication of thread. There shall be no lubrication of the thread prior to or during sewing (see 4.4.1.1).

3.4.1.5 Thread ends. All thread ends shall be trimmed to a length of not more than 1/4 inch.

* 3.4.2 Setting of snap fasteners. A hole shall be prepunched thru the materials before insertion of the button barrel of the female component and the eyelet barrel of the male component. The hole shall be smaller than the outside diameter of the button barrel or the eyelet barrel, as applicable, so that the barrel must be forced through the hole. The hole shall not be punched in the setting operation with the button or eyelet barrel. The fastener components shall be securely clinched without cutting the adjacent materials and no more than three splits shall occur in the button or eyelet barrels.

3.4.3 Setting of eyelet. A hole shall be prepunched before insertion of the barrel of the eyelet. The hole shall be smaller than the outside diameter of the eyelet barrel so that the barrel must be forced through the hole. The eyelet shall be securely clinched in a manner that will prevent detachment from or cutting of the adjacent material and shall be clinched without splitting.

3.4.4 Fusing of nylon tape and webbing ends. All ends of nylon tape and webbing shall be fused. The apparatus used to fuse the tape and webbing ends shall be capable of providing sufficient heat to provide a smooth edge with the cut ends of the tape and webbing yarns all fused together.

3.4.5 Location marks. Location marks shall not be drilled except for locating the eyelet and snap fastener.

* 3.4.6 Repairs. Except as otherwise specified herein, repairs such as mends, darns or patches are not allowed to be made to the case.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

* 3.4.7 Replacement of defective components. During the spreading, cutting and manufacturing process, components having material defects or damages that are classified as defects in 4.4.3.1 shall be removed from production and replaced with non-defective and properly matched components.

3.5 Marking. The identification marking shall be applied in the location shown on the drawing and shall conform to type IV, class 5 of DDD-L-20. The letters "US" shall be applied in the location and in the size characters indicated on the drawing and shall conform to type IV, class 9 of DDD-L-20. Fastness of the class 9 marking shall be as specified for class 5 marking.

3.6 Workmanship. The finished case shall conform to the quality of product established by this specification. The occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Certificate of compliance. Where certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3)
b. Quality conformance inspection (see 4.4)

* 4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.3.1, 4.4.3.2 and 4.4.3.3. The presence of any defect shall be cause for rejection of the first article.

* 4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

* 4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

* 4.4.1.1 Certification. The contractor shall furnish a certificate of compliance for the thread lubrication requirement specified in 3.4.1.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

* 4.4.2 In-process inspection. In-process inspection shall be made to ascertain that the following conform to the specified requirements. Whenever nonconformance is noted, corrections shall be made to the parts affected and lot in-process. Parts which cannot be corrected shall be removed from production.

Requirement	Requirement reference
Cut dimension of body and reinforcement	Drawing 2-2-29
Size of prepunched holes for snap fastener and eyelet	3.4.2 and 3.4.3

4.4.2.1 Examination of sub-assembly prior to attachment of binding tape. The sub-assembly shall be examined for frayed edges prior to attachment of the binding tape. The inspection level shall be S-3 and the acceptable quality level shall be 6.5 defects per hundred units. Any edge frayed a depth of 1/8 inch or more shall be considered a defect.

4.4.3 End item examination. The classification of defects found during examination shall be in accordance with the list shown in 4.4.3.1 and as specified in 4.4.3.2 and 4.4.3.3. The sample unit for these examinations shall be one finished case. The inspection levels and acceptable quality levels (AQLs) shall be as specified in 4.4.3.4.

* 4.4.3.1 Visual examination.

Examine	Defect	Classification Major	Minor
Cloth	Any hole, cut, tear or abrasion.	X	
	Smash, open place, broken or missing yarn or multiple floats.	X	
Webbing and tape	Ends not fused or not fused as specified, i.e., yarn ends not fused together or not smooth.		X
	Frayed or scalloped edges; not firmly and tightly woven.	X	
Hardware:			
General	Broken or malformed failing to serve intended purpose, protective finish omitted or not as specified; corroded area, burr or sharp edge.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Hardware: (cont'd)			
Keeper	Slide component of keeper jams in open, partly closed, or closed position.	X	
NOTE:	Check operation of keeper by fully opening and closing.		
Snap fastener	Fastener not functioning properly, i.e., fails to snap closed, to provide a secure closure, or to open freely.	X	
NOTE:	The fastener shall be snapped and unsnapped twice to determine whether parts of fastener separate freely and also effect a secure closure.		
	Clinched excessively tight, cutting adjacent material.	X	
	Clinched loosely, permitting any component to rotate freely but not to the degree that any component can be expected to become detached during use.		X
	Clinched loosely to the degree that components can be expected to become detached during use.	X	
NOTE:	Incomplete roll of end of button or eyelet barrel is evidence of improper and insecure clinching.		
	Incorrect style	X	
	More than three splits in eyelet or button barrels.		X
Eyelet	Clinched excessively tight, cutting adjacent material.	X	
	Insecurely clinched to a degree that eyelet may be detached from material.	X	
	Loosely clinched, permitting eyelet to rotate freely within the hole.		X
	Washer omitted or on outside of case.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Seams and stitching:			
Open seams	1/2 inch or less.		X
	More than 1/2 inch.	X	
NOTE:	A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more consecutive skipped or runoff stitches occur.		
Raw edges (except where required)	More than 1/2 inch when securely caught in stitching.		X
NOTE:	Raw edges not securely caught in stitching shall be classified as open seams.		
Seams and stitch types	Wrong seam or stitch type.	X	
Stitch tension	Loose, resulting in a loose top or bobbin thread.		X
	Excessively tight, resulting in puckering of material.		X
Stitches per inch	One to two stitches less than minimum specified.		X
	Three or more stitches less than minimum specified.	X	
	One or more stitches in excess of maximum specified.		X
Stitching ends	Not secured as specified.		X
Thread breaks, skipped stitches, or run-offs	Not overstitched as specified.		X
NOTE:	Thread breaks, or two or more consecutive skipped or runoff stitches not overstitched shall be classified as open seams.		
Bartacks	Loose, stitching incomplete or broken.		X
	Any omitted.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Cleanness	Grease, oil, or dirt stains clearly noticeable.		X
	Thread ends not trimmed throughout as specified.		X
Components and assembly:			
General	Any component part omitted or not as specified or any operation omitted (unless otherwise classified herein).	X	
	Mend, darn or patch.	X	
	Needle chews on tape or webbing: - Up to and including 1/8 inch in length.		X
	- Over 1/8 inch in length.	X	
	Needle chews on cloth.	X	
Binding tape	Loosely applied but not exposing raw edge of material.		X
	Loosely applied exposing raw edge of material.	X	
Keeper retainer webbing	Attached with one row of stitching omitted.		X
	Attached with two or more rows of stitching omitted.	X	
Keeper with slide	Installed in reverse position.		X
Identification marking	Omitted, incorrect, illegible, misplaced, size of characters not as specified, or color of marking medium not as specified.		X

4.4.3.2 Dimensional examination. Examination shall be made for compliance with all dimensions shown on Drawing 2-2-29 which can be examined on the end item, including stitch margins and gauge, excluding reference dimensions. Any dimension exceeding the applicable tolerance shall constitute a defect.

4.4.3.3 Fit examination.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

Examine	Defect
Fit of first aid packets in case	Case too small, i.e., first aid packets fail to fit properly in case. Case body or flap too short, causing inability to secure the snap fastener.
NOTE:	Fit examination shall be performed with two Dressing, First Aid, Field, Individual Troop Camouflaged, FSN 6510-159-4883 and one package of Sodium Chloride - Sodium Bicarbonate Mixture, 4.5 grams, 2S., FSN 6505-663-2636, (see 6.3). The three items shall be evenly superimposed on each other and simultaneously inserted into the case without effort other than that necessary to overcome friction between the items and the case. The flap snap fastener shall be securely closed.

4.4.3.4 Inspection levels and AQLs. The inspection levels and AQLs expressed in defects per hundred units shall be as follows:

Examination	Inspection level	AQL
For defects applicable to 4.4.3.1, visual examination	II	2.5 Major 6.5 Total major and minor defects combined
For defects applicable to 4.4.3.2, dimensional examination	S-3	10.0 one class
For defects applicable to 4.4.3.3, fit examination	S-3	0.65 one class

* 4.4.4 Packaging inspection. An examination shall be made to determine that the preservation, packing and marking comply with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container packaged with the exception that it need not be closed. Examination of closure defects listed below shall be made on shipping containers fully packaged. The lot size shall be the number of containers in the inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing. Any component damaged affecting serviceability.
Workmanship	Inadequate application of components, such as incomplete closure of container flap, loose strapping, inadequate stapling. Bulged or distorted container.
Content	Number of cases per bundle is more or less than required. 1/ Number of bundles per container is more or less than required.

1/ Six bundles from each container in the sample shall be examined.

4.4.5 Examination for palletization. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the end item inspection lot. The inspection level shall be S-1 and the AQL shall be 6.5 defects per hundred units.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

5. PACKAGING

* 5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A. The flap of each case shall be fastened and the keeper closed. Ten cases shall be stacked one on top of another with the flaps alternated end for end facing downward, except the flap of the top case shall face upward. The bundle shall then be securely tied with cotton tape or twine.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

TABLE V. Examination of packaging

* 5.1.2 Commercial. The cases shall be preserved in accordance with MIL-STD-1188.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

* 5.2.1 Level A packing. Six hundred and forty cases, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Level A unit packs shall be packed flat, four in length, four in width, and four in depth within a shipping container. Inside dimensions of each shipping container shall approximate 21-1/2 inches in length, 18-1/2 inches in width, and 15 inches in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on the top and bottom with a sheet of 30 pound minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V and reinforced as specified in the appendix of the container specification, except the inspection shall be in accordance with 4.4.4.

* 5.2.2 Level B packing. Six hundred and forty cases, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, variety DW, class domestic, grade 275 of PPP-B-636. Level A unit packs shall be packed flat, four in length, four in width, and four in depth within a shipping container. Inside dimensions of each shipping container shall approximate 21-1/2 inches in length, 18-1/2 inches in width, and 15 inches in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on the top and bottom with a sheet of 30 pound minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. Each shipping container shall be closed in accordance with method II as specified in the appendix of the container specification, except the inspection shall be in accordance with 4.4.4.

* 5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s or V4s fiberboard box fabricated and closed in accordance with PPP-B-636, except the inspection shall be in accordance with 4.4.4.

* 5.2.3 Commercial packing. Cases, preserved as specified in 5.1 shall be packed in accordance with MIL-STD-1188.

5.3 Palletization. When specified (see 6.2), cases, packed as specified in 5.2, shall be palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

5.4 Marking. In addition to any special marking required by the contract, unit packs, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or MIL-STD-1188, as applicable. Each fourth unit pack shall have attached a manila colored paper shipping tag for the identification information.

6. NOTES

6.1 Intended use. The case is used to carry two camouflaged individual troop first aid dressing and a package of sodium chloride - sodium bicarbonate mixture, or an unmounted magnetic compass.

6.2 Ordering data. Procurements should specify the following:

(a) Title, number and date of this specification.
(b) When a first article sample is required (see 3.2, 4.3, and 6.4).
(c) Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
(d) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
(e) When palletization is required (see 5.3).

6.3 Samples. For access to samples and first aid items for performing fit examination (see 4.4.3.3), address the procuring activity issuing the invitation for bid.

6.4 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of DAR 7-104.55. The first article should be a preproduction sample. The first article should consist of one completed case. The contracting officer should include specific instructions in all procurement instruments, regarding arrangements for inspection and approval of the first article.

* 6.5 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.3).

* 6.6 International standardization agreements. Certain provisions of this specification are the subject of international standardization agreement number STANAG 2311. When amendment, revision, or cancellation of this specification is proposed which will effect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels including departmental standardization offices, if required.

* 6.7 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Navy - NU
Air Force - 11

Review activities:

Army - MD, ME
Air Force - 99
DLA - CT

User activity:

Navy - MC

Preparing activity:

Army - GL

Project No. 8465-0821

☆U.S. GOVERNMENT PRINTING OFFICE: 1981—703-023/1664

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-43745B Case, Field, First Aid Dressing-Unmounted MAgnetic Compass, LC-1

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1426 1 OCT 76

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Command
ATTN: DRDNA-ES
Natick, MA 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.