13 July 1972
SUPERSEDING
MIL-M-43719/2
15 October 1970

MILITARY SPECIFICATION SHEET

MARKING MATERIALS AND MARKERS, ADHESIVE, ELASTOMERIC, PIGMENTED; LEGENDS

The complete requirements for procuring legend markers described herein shall consist of this document and the issue in effect of MIL-M-43719.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

REQUIREMENTS

* Classification.- Legend markers shall be of the following types, as specified:

Style A - Cutout legend
Style B - Printed legend

* Materials.- Legend markers shall be made from marking material, liner, and when specified (see 6.2 of general specification), translucent transfer sheet, all conforming to requirements specified in MIL-M-43719. Ink(s) for type II markers shall be compatible with the specified marking material. When tested as in the general specification, the printed marking materials shall meet the performance requirements of the general specification.

Lettering.- Unless otherwise specified in the contract or order, the heights, dimensions, and configurations of the letters and numerals of the legend, and the spacing between letters, shall be as specified for Series C Alphabet, 1966 Edition, Standard Alphabets for Highway Signs, Bureau of Public Roads, U.S. Dept. of Commerce. One inch high letters and numerals shall be half-scale of the 2 inch size therein.

FSC 7690

Source: https://assist.dla.mil -- Downloaded: 20260-21T22:08Z
Check the source to verify that this is the current version before use.

Space between words.- The space between words, measured horizontally from the extreme right edge of the letter preceding the space to the extreme left edge of the letter following, shall generally be 75% of the letter height. This space may be reduced or increased where needed to obtain a more symmetrical appearance for easy and natural reading, for example, where an L is followed by a J, or where an H is followed by an I.

Construction.-

Style A.-

Cutout legend markers shall consist of a legend of letters or numerals or a combination thereof, cut from marking material, each letter and numeral mounted in line on a single, rectangular liner, and covered with a single, rectangular, translucent transfer sheet. All edges shall be cut smooth. The liner shall not be cut completely through at the outline of letters and numerals, nor shall it be cut so deep as to interfere with its ready removal from the marker or to result in distortion of the marker when removal is attempted.

Style B.-

Printed legend markers shall consist of a legend, instructions, notice or other written material printed on a sheet of marking material of specified dimensions, type, class, and color (see 6.2 of general specification). The written material shall have the content, arrangement, letter, size(s), and color as specified in the contract or order. After printing, the entire marker shall be given a clear overcoating to produce a final finish of uniform appearance and of the specified gloss (see Ordering data). When specified (see 6.2 of the general specification), the marker shall be covered on the face side with translucent transfer sheet.

Dimensions.- Shall be as follows:

(a) Letter height.- As specified in contract or order.

(b) Liner height.- (1) Letter height up to 2 inches plus 5/16 inch.
(2) Letter height over 2 inches plus 9/16 inch.

(c) Transfer sheet height.- Liner height minus 1/16 inch.

(d) Width of left and right margins.-

(1) 1/8 inch for legends up to 2 inches high.
(2) 1/4 inch for legends over 2 inches high.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:08Z
Check the source to verify that this is the current version before use.

(e) Top and bottom margins (letters on liner).- Equal.

(f) Alignment of liner and transfer sheet.- Edges of liner flush with edges of transfer sheet at top and sides. (Liner to protrude 1/16 inch at bottom edge.)

Alternate.- Legend markers which can not be adequately described through above requirements shall be constructed in accordance with drawing(s) to be furnished by the contracting officer.

List of legends.- Legends covered by this specification include, but are not limited to, the following:

U S ARMY	U S COAST GUARD
U S NAVY	U S MARINE CORPS
U S AIR FORCE	UNITED STATES ARMY
AMBULANCE	DEPARTMENT OF DEFENSE
FLAMMABLE	ARMY NATIONAL GUARD
FOR OFFICIAL USE ONLY	AIR NATIONAL GUARD
MAX SPEED	DEFENSE SUPPLY AGENCY
NO RIDERS	POLICE
NO SMOKING	ARMED FORCES POLICE
EMERGENCY DOOR	NO SMOKING WITHIN 50 FEET

Ordering data.- Procurement documents should specify the following in addition to the ordering data listed in the general specification:

(a) Construction style.

(b) Legend content (see list of legends).

(c) Size (height of lettering) (see lettering).

(d) Heights, dimensions, and configurations if other than Series C Alphabet.

(e) Drawing number, if required (see construction) (alternate).

(f) Degree of gloss after overcoating.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:08Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Navy - AS
Air Force - 84

Review activities:

Army - AT, AV, EL, MD
Navy - MC

User activities:

Army - ME, SM, WC

Preparing activity:

Army - GL

Project No. 7690-0042-2

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:08Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development
Laboratories
ATTN: DRDNA-ES (Mr. D. Luppino)
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:08Z
Check the source to verify that this is the current version before use.

of improper size, marking (exterior and omitted, incorrect, illegible

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*:
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 20261021T22:08Z
Check the source to verify that this is the current version before use.

ordance with load [illegible] shall be palletized on a 4-way entry pallet in acc