INCH-POUND

MIL-DTL-43719/2B
6 APRIL 2009
SUPERSEDING
MIL-M-43719/2A
13 July 1972

DETAIL SPECIFICATION SHEET

MARKING MATERIALS AND MARKERS, ADHESIVE, ELASTOMERIC, PIGMENTED; LEGENDS

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-43719.

REQUIREMENTS:

Classification. Legend markers shall be of the following style, as specified:

Style A - Cutout legend
Style B - Printed legend

Materials. Legend markers shall be made from marking material, liner, and when specified (see 6.2 of general specification), translucent transfer sheet, all conforming to requirements specified in MIL-DTL-43719. Ink(s) for type II markers shall be compatible with the specified marking material. When tested as in the general specification, the printed marking materials shall meet the performance requirements of the general specification.

Lettering. Unless otherwise specified in the contract or order, the heights, dimensions, and configurations of the letters and numerals of the legend, and the spacing between letters, shall be as specified for Series C Alphabet per Standard Highway Signs (SHS) 2004 Edition. One inch high letters and numerals shall be half-scale of the 2 inch size therein.

Space between words. The space between words, measured horizontally from the extreme right edge of the letter preceding the space to the extreme left edge of the letter following, shall generally be 75% of the letter height. This space may be reduced or increased where needed to obtain a more symmetrical appearance for easy and natural reading, for example, where an L is followed by a J, or where an H is followed by an I.

Construction.

Style A. Cutout legend markers shall consist of a legend of letters or numerals or a combination thereof, cut from marking material, each letter and numeral mounted in line on a single, rectangular liner, and covered with a single, rectangular, translucent transfer sheet. All edges shall be cut smooth. The liner shall not be cut completely through at the outline of letters and numerals, nor shall it be cut so deep as to interfere with its ready removal from the marker or to result in distortion of the marker when removal is attempted.

Style B. Printed legend markers shall consist of a legend, instructions, notice or other written material printed on a sheet of marking material of specified dimensions, type, class, and color (see 6.2 of general specification). The written material shall have the content, arrangement, letter, size(s), and color as specified in the contract or order. After printing, the entire marker shall be given a clear overcoating to produce a final finish of uniform appearance and of the specified gloss (see ordering data). When specified (see 6.2 of the general specification), the marker shall be covered on the face side with translucent transfer sheet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:08Z
Check the source to verify that this is the current version before use.

Dimensions. Shall be as follows:

(a) Letter height – As specified in contract or order.
(b) Liner height – (1) Letter height up to 2 inches plus 5/16 inch.
(2) Letter height over 2 inches plus 9/16 inch.
(c) Transfer sheet height – Liner height minus 1/16 inch.
(d) Width of left and right margin – (1) 1/8 inch for legends up to 2 inches high.
(2) 1/4 inch for legends over 2 inches high.
(e) Top and bottom margins (letters on liner) – Equal.
(f) Alignment of liner and transfer sheet – Edges of liner flush with edges of transfer sheet at top and sides. (Liner to protrude 1/16 inch at bottom edge.)

Alternate. Legend markers which can not be adequately described through above requirements shall be constructed in accordance with drawing(s) to be furnished by the contracting officer.

List of legends. Legends covered by this specification include, but are not limited to, the following:

U S ARMY	U S COAST GUARD
U S NAVY	U S MARINE CORPS
U S AIR FORCE	UNITED STATES ARMY
AMBULANCE	DEPARTMENT OF DEFENSE
FLAMMABLE	ARMY NATIONAL GUARD
FOR OFFICIAL USE ONLY	AIR NATIONAL GUARD
MAX SPEED	DEFENSE LOGISTIC AGENCY
NO RIDERS	POLICE
NO SMOKING	ARMED FORCES POLICE
EMERGENCY DOOR	NO SMOKING WITHIN 50 FEET

Ordering data. Procurement documents should specify the following in addition to the ordering data listed in the general specification:

(a) Construction style.
(b) Legend content (see list of legends).
(c) Size (height of lettering) (see lettering).
(d) Heights, dimensions, and configurations if other than Series C Alphabet.
(e) Drawing number, if required (see construction) (alternate).
(f) Degree of gross after overcoating.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:08Z
Check the source to verify that this is the current version before use.

Custodians:
Army – GL
Navy – SA
Air Force – 99

Preparing activity:
DLA – IS

(Project 7690-2009-003)

Review activities:
Army – AT, AV, CR, MD
Navy – MC
Air Force – 84

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil .

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:08Z
Check the source to verify that this is the current version before use.