MIL-D-43729A
3 June 1986
SUPERSEDING
MIL-D-43729
31 December 1970

MILITARY SPECIFICATION

DISPENSING UNIT, DETERGENT, AUTOMATIC, FOR COMMERCIAL DISHWASHING MACHINES

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers dispensing units for automatically controlling detergent concentration in wash tank water of commercial dishwashing machines.

1.2 Classification. Dispensers shall be of the following styles as specified (see 6.2).

Style 1 - Shore use
Style 2 - Shipboard use

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 7320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:10Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

P-D-1800	-	Dishwashing Compound, Machine (Granular, Bead or Flake)
00-D-431	-	Dishwashing Machines, Commercial (Rack Stationary)
00-D-1388	-	Dishwashing Machines, Commercial (Rackless Conveyor)
00-D-1390	-	Dishwashing Machines, Single Tank (Rack, Manual and Conveyor) and Double Tank (Rack, Conveyor), Commercial
PPP-B-566	-	Boxes, Folding, Paperboard
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-B-676	-	Boxes, Setup

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-130	-	Identification Marking of U.S. Military Property
MIL-STD-147	-	Palletized Unit Loads

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

NATIONAL SANITATION FOUNDATION (NSF)

Listing of Food Service Equipment

Standard No. 29 - Detergent and Chemical Feeders for Commercial Spray-Type Dishwashing Machines

(Application for copies should be addressed to the National Sanitation Foundation 3475 Plymouth Road, P.O. Box 1468. Ann Arbor, MI 48106.)

UNDERWRITERS LABORATORIES, INC. (UL)

Standard No. 921 - Commercial Electric Dishhwashers

(Application for copies should be addressed to Underwriters Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:10Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip
A 176 - Stainless and Heat-Resisting Chromium Steel Plate, Sheet, and Strip
D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for associated detail specifications, specification sheets, or MS standards), the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Standard product. The dispensers shall, as a minimum, be in accordance with the requirements of this document and shall be the manufacturer's standard commercial product with any added features needed to comply with the requirements of this document. Modifications to add features shall not incorporate different parts unless such parts are used on other current commercial models. Standard or modified commercial products furnished in accordance with this document shall be identifiable by all regular manufacturer's or commercial service organizations servicing the brand involved. Service organizations shall be capable of providing complete parts and repair services on models furnished to the Government consistent with their normal commercial practices.

3.2 Standard compliance. Unless otherwise specified herein, the dispensing units shall conform to the applicable requirements of UL Standard No. 921 and NSF Standard No. 29. Satisfactory evidence that these requirements have been met shall be submitted to the contracting officer or his authorized representative prior to the start of production (see 4.3).

3.3 Materials (see 6.4) and components. Materials and components shall be as specified herein. Materials not definitely specified shall be of the quality normally used by the manufacturer for dispensing units provided the completed item complies with all provisions of this document.

3.3.1 Stainless steel. Stainless steel shall conform to the chemical composition of any type steel in the 300 or 400 series as specified in ASTM Standard A 167 or ASTM Standard A 176, as applicable.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:10Z
Check the source to verify that this is the current version before use.

3.4 Design. The style 1 and style 2 dispensing units shall consist of an electrical control unit, a low voltage water inlet solenoid valve, detergent dispensing reservoir with syphon breaker, wash tank sensing electrodes, at least 6 feet of 1/4-inch copper tubing, and 30 feet of service wiring to form a complete dispensing system. Dispensing units shall be designed for dispensing dishwashing compound conforming to type I or type II, class 1 of P-D-1800. The units shall have an adjustable minimum range of 0.15 percent to 0.40 percent concentration by weight (see 4.4.1.2) and shall automatically feed and maintain a constant detergent concentration of the wash water (see 6.3) between 0.2 and 0.3 percent by weight when water temperature is between 150°F and 160°F (see 4.4.1.1). Automatic feeding shall be determined by conductance at tank electrodes to achieve proper concentration. A control unit shall operate a solenoid valve and shall have an "ON" - "OFF" switch and a light to indicate the unit is operating and a red signal light and buzzer to indicate detergent replenishment is necessary. All components of the control unit shall be accessible for repair or replacement. When the detergent concentration falls below the required setting, electric current at electrodes in the water tank shall cause a relay to operate a solenoid valve and allow water to enter the reservoir. When the desired concentration is attained, the unit shall cause the solenoid to close. The control unit shall be inclosed in a stainless steel or plastic housing. The reservoir shall have an overflow pipe to allow overflow of detergent solution to the washtank. The incoming water line and reservoir shall be designed so that the water completely dissolves the dishwashing compound and prevents "caking" of the the compound. The control unit shall be designed for mounting on a dishwashing machine or adjacent wall. Unless otherwise specified (see 6.2), the detergent dispensing reservoir and back syphoning breaker may be either wall or machine mounted independent of the location of the dispenser unit. In addition to the aforementioned requirements, style 2 dispensers shall operate at any 15 degree inclination from the vertical (see 4.4.1.3).

3.5 Construction.

3.5.1 Detergent reservoir. The reservoir shall be formed from stainless steel specified in 3.3.1 or polypropylene plastic.

3.5.2 Electrical characteristics. Unless otherwise specified (see 6.2), the dispensers shall be designed for operation on a nominal 120-volt, 60-hertz, 1-phase, electrical system. A transformer shall be provided to stepdown the service voltage to the voltage required for proper operation.

3.6 Data name plate. The dispensing unit shall be furnished with a data-name plate in accordance with the applicable requirements of MIL-STD-130 except the requirements for: (a) Methods of applying, (b) Identification tags, (c) Information not required, and (d) Optional marking information, shall not apply. The data name plate shall be made of minimum 20 gauge corrosion-resisting metal and shall be attached to the dispensing unit by rivets, by screws, or by welding in such a manner as to meet the applicable National Sanitation Foundation (NSF) sanitary requirements for this equipment. The

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:10Z
Check the source to verify that this is the current version before use.

plate shall contain the following information which shall be stamped, engraved, or applied by photosensitive means:

National Stock Number (NSN)
Procurement Instrument Identification Number
Specification Data (Document No. and style)
Manufacturer's Name, Address and Telephone Number
Supplier's Name, Address and Telephone Number (List only if different from Manufacturer)
Manufacturer's Model Number
Government Approved Manual Number (see 6.2)

Each plate shall be placed so that it is readily visible to the operator during normal operating use, and so as not to adversely affect the life and utility of the dispensing unit.

3.7 Finish. The dispensing components shall be finished in accordance with the manufacturer's standard commercial practice.

3.8 Operating instructions. Instructions indicating the proper operating procedures for using the dispensing unit shall be etched, stamped, or embossed on a brass or stainless metal or plastic plate and permanently attached to the control unit in a clearly visible location.

3.9 Workmanship. Dispensing units shall be finished with all burrs and rough edges removed. Welds shall be sound, smooth, and free from pits, fractures, burn-through, or fissures. Spot welds shall be free from pits and flashes. Bolt holes and rivet holes shall be accurately punched or drilled and shall have burrs removed. Washers or lockwashers shall be provided in accordance with standard commercial practice, and all bolts, nuts, and screws shall be drawn tight. Rivets shall be tightly driven and fully peened and shall completely fill the holes. Electrical wiring shall be provided with adequate slack to relieve strain and the wiring shall not be abraded, poorly joined, or loose at terminals.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements, specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:10Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirement in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for assuring that all specified dimensions have been met. When dimension cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

4.2 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.2.2 End item visual examination. The end item shall be examined for the defects listed in table I. The lot size shall be expressed in units of dispensers of one style only. The sample unit shall be one dispenser. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor
Construction and workmanship	Any component missing or not as specified	X	
	Any component fractured or malformed affecting usability	X	
	Any burr or rough edge	X	
	Functioning component that requires abnormal force to operate	X	
	Any adjustable assembly that cannot be adjusted to perform the function intended	X	
	Any component in control unit not accessible for replacement or repair	X	

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:10Z
Check the source to verify that this is the currentversion before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Welding	Any weld fractured, not sound, or contains fissures or burn through	X	
	Any weld not smooth or contains pits		X
	Spot weld contains flashes		X
Bolts, nuts, and screws	Stripped or fractured	X	
	Loose or not provided with lockwashers		X
Rivets	Loose, fractured, or not fully peened	X	
Electrical assemblies	Wiring cut, abraded, or loosely joined at terminals	X	
	Adequate slack not provided for wiring to relieve strain	X	
	Excessive insulation stripped from wire	X	
Data name plate	Omitted or not as specified		X
	Information incomplete or illegible		X
	Not located so as to be readily visible to the operator		X
Operating instructions	Missing	X	

4.2.3 End item testing. One dispenser from the lot shall be tested as specified in 4.4.1.1, 4.4.1.2 and 4.4.1.3, as applicable. Failure of any test shall be cause for rejection of the lot.

4.2.4 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Markings, exterior and interior	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or not as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:10Z
Check the source to verify that this is the current version before use.

Examine	Defect
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping or inadequate stapling. Bulged or distorted container.

4.2.5 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1, and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

4.3 Certification compliance examination. Certifications, certified test reports or listing marks for standards submitted in accordance with 3.2 shall be examined and validated as proof of compliance. Prior to Government approval of first shipment the contractor shall submit to the contracting officer or his authorized representative for approval, certification that the dispensers he proposes to furnish meet the applicable requirements of UL and NSF as follows:

4.3.1 Underwriters' Laboratories, Inc. (UL). Acceptable evidence of meeting the applicable requirements of the Underwriters' Laboratories Standard No. 921 shall be the UL label, a UL listing mark, or a certified test report from a recognized independent testing laboratory, acceptable to the Government, indicating that the dispensers have been tested and conform to the applicable requirements of UL Standard No. 921.

4.3.2 National Sanitation Foundation (NSF). Acceptable evidence of meeting the applicable requirements of the National Sanitation Foundation standard specified in 3.2 shall be one of the following:

a. A listing in the current edition of the National Sanitation Foundation "Listing of Food Service Equipment", and display of the NSF seal on the finished dispenser (see 3.2).

Source: https://assist.dla.mil -- Downloaded: 202640-21T22:10Z
Check the source to verify that this is the current version before use.

b. A certification for the dispenser issued by NSF under their special one-time contract evaluation/certification service (see 3.2).

c. A certified test report, acceptable to the contracting officer with the advice of the Army Surgeon General from an independent testing laboratory indicating that the dispensing units have been tested and conform to the specified NSF standard (see 3.2).

4.4 Methods of inspection.

4.4.1 Test preparation. Mount the dispenser reservoir and control unit on a dishwashing machine conforming to OO-D-431, OO-D-1388 or 00-D-1390, mount the electrodes in the water tank and make all necessary electrical and tubing connections between components. Provide a 1/4-inch fresh water line to provide 150° to 160°F water to the dispenser reservoir.

4.4.1.1 Operational test. Fill the dishwasher specified in 4.4.1 with clean 150° to 160°F water to the overflow level, as used in normal dishwashing operation. Turn off the water inlet valve. Turn on the dishwashing machine to circulate the water. Fill the detergent reservoir with the test detergent specified (see 4.4.1.1.2) to one-half capacity or as recommended by the manufacturer for normal operating conditions. Turn the dispensing unit on and allow it to feed until the buzzer and blinking lights go out, showing initial feeding has been completed. At this point remove a water sample and test for concentration using the concentration test kit (see 4.4.1.1.1). Record all readings taken during this test. Turn on the inlet valve and allow water to enter the wash tank at a rate of 2 quarts $\pm$ 1/2 pint per minute. Continue taking water samples and determine the detergent concentration and continue adjusting the control unit until a detergent concentration of 0.2 to 0.3 percent is reached. Leave the control setting at this point and allow the unit to cycle for at least 1 hour during which water samples shall be taken, tested and recorded for concentration every 10 minutes to determine if the dispenser is capable of maintaining the concentration required by 3.4. Inability of the dispensing unit to maintain the operational requirements in 3.4 or the presence of undissolved compound shall constitute failure of the test.

4.4.1.1.1 Test kit. For determining concentration, the following test apparatus and procedure shall be followed: Take a 10 $\pm$ 0.5 ml sample volume of wash water with detergent from the wash tank. Add two drops of methyl orange indicator solution. Titrate 0.5 N sulfuric acid (H_2SO4) drops from a standard medicine dropper until a pink end point from (orange to pink) is obtained. The following table may be used for determining concentrations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:10Z
Check the source to verify that this is the current version before use.

Percent concentration 1/	Drops 0.5 N sulfuric acid
0.10	4
0.15	5
0.20	7
0.30	9
0.40	12

1/ Interpolated readings may be made between these table readings.

4.4.1.1.2 Test detergent. The test detergent used for evaluating the detergent dispenser shall be formulated in the following manner.

Sodium tripolyphosphate, anhydrous	54 percent
Sodium metasilicate, anhydrous	24 percent
Sodium hydroxide, granular	16 percent
Sodium carbonate, anhydrous	6 percent
	100 percent

4.4.1.2 Adjustment range test. Adjust the control unit to its lowest position and take water samples to determine conformance with the lowest concentration required by 3.4 using the test kit and table described in 4.4.1.1.1. Repeat the procedures with the control adjusted to its highest concentration. Inability to maintain the concentration specified shall constitute failure of this test.

4.4.1.3 Shipboard use test. The reservoir shall be inclined at an angle of 15 degrees each side of the vertical in each of two vertical planes at right angles to each other and the dispenser shall be operated as specified in 4.4.1.1 in each plane and 4.4.1.2 to determine conformance with 3.4. Inability of the dispenser to maintain the desired concentration at 15 degree incline shall constitute failure of this test.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A. The components of the dispenser unit shall be unit packed in snug-fitting folding or set-up paperboard or fiberboard boxes conforming to variety 1 of PPP-B-566, variety 1 of PPP-B-676, or type CF, variety SW, or type SF, class domestic of PPP-B-636, respectively, except that the weight of contents of paperboard boxes shall not exceed 10 pounds. Components shall be cushioned as necessary, to prevent movement or damage while in transit. Closure shall be in accordance with the appendix of the applicable box specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:10Z
Check the source to verify that this is the current version before use.

5.1.2 Commercial. The dispensers shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. Each complete dispenser, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, V2s of PPP-B-636. Closure, waterproofing by means of tape, and reinforcing with flat strapping or tape banding, shall be in accordance with the appendix of PPP-B-636.

5.2.2 Level B packing. Each complete dispenser, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF, variety SW, or type SF, class domestic of PPP-B-636. Closure shall be in accordance with method II of the appendix of PPP-B-636.

5.2.2.1 Weather-resistant fiberboard container. When specified (see 6.2), the shipping container shall be of a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636.

5.2.3 Commercial. Dispensers preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), dispensers, packed as specified in 5.2, shall be palletized in accordance with load type Ia of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The dispensers are intended for use on single and multiple tank commercial dishwashing machines.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document
b. Style required (see 1.2).

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:10Z
Check the source to verify that this is the current version before use.

c. Location of detergent reservoir and back syphoning breaker, if other than specified (see 3.4).
d. Electrical characteristics, if other than specified (see 3.5.2).
e. Government approved manual number to be included in data name plate (see 3.6).
f. Selection of the applicable levels of preservation and packing (see 5.1 and 5.2).
g. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
h. When palletization is required (see 5.3).

6.3 Supplementary water supply. Dishwashing machines not provided with a supplementary water supply to the washtank will not permit proper operation of the dispenser. It is recommended that a hot water replenishing line to provide 1-gallon per minute be installed at time of dispenser installation.

6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this document (see 3.3).

6.5 Contract data requirements. Any requirements for equipment manuals for the item covered by this document should be included in DD form 1423 Contract Data Requirements list cited in the contract.

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - YD
Air Force - 99

Preparing activity:

Army - GL

Project No. 7320-0508

Review activities:

Army - MD, TS
Navy - MC, MS
Air Force - 84
DLA - GS

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:10Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:10Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-D-43729 A	DISPENSING UNIT, DETERGENT, AUTOMATIC, FOR COMMERCIAL DISHWASHING MACHINES

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP-1, Feb 86

Source: https://assist.dla.mil - Downloaded: 2026-10-21T22:10Z
Check the source to verify that this is the current version before use.