MIL-I-43746B
30 March 1988
SUPERSEDING
MIL-I-43746A
22 June 1976

MILITARY SPECIFICATION

INSECT NET, HAT, SUN, HOT WEATHER

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers an insect net made of nylon tricot netting. The insect net shall be of one type and size.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

V-T-285	-	Thread, Polyester
DDD-L-20	-	Label: For Clothing, Equipage, and Tentage, (General Use)
PPP-B-636	-	Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8415

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-L-35078 - Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For
MIL-C-43352 - Cloth, Netting, Nylon, Tulle Tricot

STANDARDS

FEDERAL

FED-STD-191 - Textile Test Methods
FED-STD-751 - Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads
MIL-STD-731 - Quality of Wood Members for Containers and Pallets

(Copies of drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Copies should be obtained from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187).

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

* 2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Guide sample. Samples, when furnished, are solely for guidance and information to the contractor (see 6.3). Variations from this document may appear in the sample in which case the document shall govern.

3.2 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.4).

* 3.3 Materials. (See 6.5)

3.3.1 Netting. The material for the insect net shall be nylon tricot netting conforming to class 2 of MIL-C-43352, color Dark Green 323.

3.3.2 Braid, nylon, elastic. The nylon elastic braid for the insect net shall be flat, 3/16 ± 1/32 inch wide, dyed Olive Green 106. The braid shall be braided using 210 denier nylon, on 17 carriers, one end per carrier with not less than 96 picks, braiding one over-one under. There shall be 8 strands of 70 gage compound natural rubber, synthetic rubber, or a mixture of both.

3.3.2.1 Colorfastness. The dyed braid shall show fastness to laundering and light equal to or better than the standard sample. When no standard sample is available, the dyed braid shall show "good" fastness to laundering and light.

3.3.3 Thread. The thread for all stitching shall be polyester, type I, class 1, subclass A, size A of V-T-285.

3.3.3.1 Color and colorfastness. The thread shall be dyed Olive Drab, S-1, C.A. 66022 and shall show fastness to laundering and light equal to or better than the standard sample.

3.3.4 Identification label. The insect net shall have an identification label conforming to type VI, class 4 of DDD-L-20 except that the size is not applicable. Colorfastness requirements shall not apply.

3.4 Design. The insect net is made of one piece of netting with elastic braid inserted in the top and bottom hems. Two loops made of elastic braid are attached at the bottom hem.

3.5 Pattern. Standard patterns that include seam allowances will be furnished by the Government. The standard patterns are provided as a guide for cutting the contractors working pattern and shall not be altered in any way. The working patterns shall be identical to the Government patterns.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

3.5.1 Pattern parts. The insect net shall be cut from the material specified in accordance with the pattern part indicated below:

Material	Pattern nomenclature	Cut part
Nylon tricot netting	Insect net	1

3.6 Construction. The construction shall conform to the requirements specified in table I and herein.

* 3.6.1 Stitches, seams, and stitching. All stitches, seams, and stitching shall conform to FED-STD-751. The type of seam, stitching, and stitches per inch shall be as specified in table I. Seam allowances shall be maintained with seams sewn so that no raw edges, run-offs, pleats, puckers, or open seams occur. When two or more methods of seams or stitches are given for the same operation, any one may be used. Where stitch type 401 is used, the chain or underside of the stitch shall be on the inside of the insect net.

* 3.6.1.1 Type 301 stitching. Ends of all stitching shall be backstitched or overstitched not less than 1/2 inch except where ends are turned under or caught in other seams or stitching. Thread tensions shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread or excessively tight stitching resulting in puckering of the materials sewn. The lock shall be embedded in the materials sewn.

* 3.6.1.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during stitching, the stitching shall be repaired by restarting the stitching a minimum of 1/2 inch back of the end of the stitching. 1/

b. Thread breaks or two or more consecutive skipped or run-off stitches noted during end item inspection shall be repaired by overstitching. The stitching shall start a minimum of 1/2 inch in back of the defective area and continue a minimum of 1/2 inch beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching without damaging the materials and restitching in the required manner. 1/

1/ When making the above repairs, the ends of the stitching are not required to be backstitched.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

* 3.6.1.2 Type 401 stitching. Thread tension shall be maintained so that there will be no loose stitching. All repairs shall be in accordance with 3.6.1.1.1a and 3.6.1.1.1.b except substitute 3/4 inch for 1/2 inch wherever 1/2 inch appears. Type 301 stitching may be used for repairing type 401 stitching.

3.6.1.3 Type 101 button tack stitching. Type 101 stitching shall have at least two ties per tack. Button tacks shall be free of loose stitching.

3.6.2 Thread ends. All thread ends shall be trimmed to a length of not more than 1/4 inch.

3.6.3 Repairs. Except as otherwise specified herein, repairs are not allowed to be made to the insect net.

3.7 Manufacturing operations requirements. The insect net shall be manufactured in accordance with the operation requirements specified in table I. The contractor is not required to follow the exact sequence of operations listed, unless otherwise specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

TABLE I. Manufacturing operations requirements

No.	Requirements	Stitch type	Seam and stitching type	Stitches per inch	Thread: Needle	Thread: Bobbin or Looper
1.	Cutting.					
	a. Cut the net along the width or length of the material and in strict accordance with pattern furnished.					
	b. Cut elastic braid for top and bottom hems and loops with a heated blade to fuse ends of braids and in the following lengths:					
	(1) Cut braid for top and bottom hems 21 ± 1/2 inches long.					
	(2) Cut braid for loops 5 ± 1/2 inches long. Braid may be folded to form loop and both ends cut and fused simultaneously, fusing ends together.					
2.	Replacement of defective components.					
	During the spreading, cutting, and manufacturing process, components having material defects or damages that are classified as defects in 4.4.2 shall be removed from production and replaced with non-defective and properly matched components.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

TABLE I. Manufacturing operations requirements - Continued

No.	Requirements	Stitch type	Seam and stitching type	Stitches per inch	Thread: Needle	Thread: Bobbin or Looper
3.	Make insect net.					
	a. Join ends (shortest sides) of netting by superimposing the edges evenly on each other within 1/16 inch and stitching 3/8 to 1/2 inch from edges of netting.	301 or 401	SSa-1	10-14	A A	A A
	b. Overlap the ends of the elastic braid for top and bottom hems 3/4 to 1 inch and button tack ends together across full width of braid in approximate center of overlap, with two adjacent button-hole tacks.	101		14-18 per tack	A	
	c. Turn back the top and bottom edges of the insect net 3/8 to 5/8 inch with the elastic braid inserted within. Stitch through netting only 1/4 to 3/8 inch from outer edge at each end of insect net around the entire periphery except at both ends leave a 3/8 to 1/2 inch opening located not less than 1/2 inch from the end joining seam. During the sewing operation the elastic braid shall be stretched so that the netting is not puckered. The identification label shall be caught in the stitching a minimum of 1/8 inch in either the top or bottom hem.	301	EFa-1	10-14	A	A
	d. When the two elastic loops are not formed by fusing the ends together, form each loop by folding the elastic evenly in half within 1/8 inch and button tack the two ends together. Locate button tack 1/4 ± 1/8 inch from ends of loop.	101		14-18 per tack	A	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

TABLE I. Manufacturing operations requirements - Continued

No.	Requirements	Stitch type	Seam and stitching type	Stitches per inch	Thread Needle	Thread Bobbin or Looper
3.	Make insect net. - continued					
	e. With insect net laying flat, position netting so that joining seam is on bottom and approximately centered. With the fullness of the netting evenly distributed along the elastic braid at the bottom hem (curved edge) of the insect net, mark two locations on bottom hem at front of insect net with the marks 6 ± 1/4 inches apart and centered between the joining seam on the back of the insect net. Position the two loops on the marks with the loops projecting perpendicularly beyond the edge of the insect net and the opposite ends projecting 1/4 to 3/8 inch beyond the edge of the net. Button tack each loop to insect net with two adjacent tacks with the tacks passing through the elastic braid in the hem.	101		14-18 per tack	A	
	f. Turn insect net right side out. Note: When the insect net is right side out, the cut edges of the netting at the joining seam and the top and bottom hems shall be on the inside and also the cut ends of the two loops shall be on the inside.					
4.	Clean net.					
	Remove all spots, stains, and cut ends of thread.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

3.8 Measurements. The finished measurements of the insect net shall conform to table II.

TABLE II. Finished measurements (in inches)

Length (relaxed) 1/	1/2 top (elastic relaxed) 2/	1/2 bottom (elastic relaxed) 3/
16-1/2 ±1/2	10 ±1/2	9-1/4 ±1/2

1/ Measure from top to bottom along the joining seam.

2/ Measure across top edge from folded edge to folded edge.

3/ Measure across bottom edge from folded edge to folded edge.

3.9 Workmanship. The finished insect net shall conform to the quality of product established by this document and the occurence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

* 4.1.1 Responsiblity for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirement in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

* 4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for assuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

4.1.3 Certificates of compliance. When certificates of compliance are submitted, the Government reserves the right to inspect such items to determine the validity of the certification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.2 and 4.4.3. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document. In addition, the elastic nylon braid shall be tested for the characteristics listed in table III. The lot size shall be expressed in units of yards of braid. The sample unit shall be 3 yards of braid. The sample size for the designated lot size shall be as shown below. There shall be no evidence of failure of any sample unit to meet the requirements specified.

Lot size	Sample size
800 or less	2
801 up to and including 22,000	3
22,001 and over	5

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

TABLE III. Elastic braid tests

Component	Characteristic	Requirement paragraph	Test method	Number of determinations per sample unit	Results reported as
Braid, nylon elastic	Material identification	3.3.2	1/		
	Width	3.3.2	5020 2/		
	Yarn denier	3.3.2	1/		
	Number of carriers	3.3.2	Count	1	To nearest whole number
	Number of picks	3.3.2	Count	1	To nearest whole number
	Weave	3.3.2	Visual	1	Pass or fail
	Number of strands of rubber	3.3.2	Count	1	Pass or fail
	Gage of rubber	3.3.2	1/	1	To nearest 0.001 inch or number of strands side by side, actual count 3/
	Color	3.3.2	Visual	1	Pass or fail
	Colorfastness to:				
	- laundering	3.3.2.1	5610 2/		
	- light	3.3.2.1	5660 2/		

1/ Unless otherwise specified, a certificate of compliance shall be submitted and will be acceptable for the stated requirement.

2/ Test method indicated shall be in accordance with FED-STD-191. All test reports shall contain the individual values utilized in expressing the final results.

3/ Measure prior to fabrication into finished braid.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

* 4.4.2 End item visual examination. The end item shall be examined for the defects listed in table IV. The lot size shall be expressed in units of insect nets. The sample unit shall be one insect net. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 10.0 for total (major and minor combined) defects.

TABLE IV. End item visual defects

Examine	Defect	Classification	
		Major	Minor
Cloth, netting	Any cut, tear, or hole	X	
Braid, elastic	Any cut or abraded area	X	
Seams and stitchings:			
Open seams	Up to and including 1/2 inch		X
	More than 1/2 inch	X	
NOTE:	A seam shall be classified as an open seam when one or more stitches joining a seam are broken, or when two or more consecutive skipped or run-off stitches occur.		
Seam or stitch type	Incorrect seam or stitch type	X	
Stitch tension	Loose tension, resulting in a loose top or bobbin thread		X
	Excessively tight tension, resulting in puckering of material		X
Stitches per inch	One or two stitches less than minimum specified		X
	Three or more stitches less than minimum specified	X	
	Two or more stitches in excess of maximum specified		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

TABLE IV. End item visual defects - Continued

Examine	Defect	Classification	
		Major	Minor
Stitching ends (on stitch type 301)	Not secured as specified		X
Thread breaks, skipped or run-off stitches (on types 301 and 401 stitching)	Thread breaks or two or more consecutive skipped or run-off stitches overstitched less than specified amount in each direction beyond the defective stitching area		X
	NOTE: Thread breaks or two or more consecutive skipped or run-off stitches not overstitched shall be classified as open seams.		
Button tack	Loose stitching		X
	Any omitted	X	
Elastic braid loops	Any omitted	X	
	Any attached on top hem of net in lieu of bottom	X	
	Any attached on back of net in lieu of front, i.e., loops are spaced between joining seam	X	
	Attached on outside surface of net in lieu of inside		X
	Button tacks do not pass through elastic braid in hem	X	
	On bottom hem fullness of netting not evenly distributed		X
Components and assembly	Netting not cut in accordance with specified directional lines	X	
	Elastic braid in hems caught in stitching for forming hem	X	
	Any mend, darn, patch, or other unauthorized repair	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

TABLE IV. End item visual defects - Continued

Examine	Defect	Classification	
		Major	Minor
Cleanness	Grease or oil stains clearly noticeable; thread ends not removed or not trimmed throughout as specified		X
Identification label	Omitted, incorrect, illegible, or not attached as specified		X

* 4.4.3 End item dimensional examination. The end items shall be examined for the dimensions specified in table II. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of insect nets. The sample unit shall be one insect net. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundreds units, shall be 4.0.

* 4.4.4 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling Bulged or distorted container Polyethylene bag heat sealed seam open, noncontinuous, or crooked

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

Content	Number of insect nets per unit pack is more or less than specified 1/

1/ For this defect one shipping container in the sample shall be examined.

* 4.4.5 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A. Each insect net shall be laid out flat. Fifty insect nets shall be neatly stacked one on top of another and then inserted in a snug-fitting clear polyethylene film bag of 0.00125 inch thickness (± 25 percent tolerance). The bag shall be formed with heat sealed seams that are straight, continuous, and parallel to each other and to the formed edges of the bag. The final closure of the bag shall be heat sealed with the heat seal made as close as possible to the open end. Prior to or during the closure operation, excess air within the bag shall be expelled.

* 5.1.2 Commercial. Insect nets shall be preserved in accordance with ASTM D 3951.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

* 5.2.1 Level A packing. Five hundred insect nets, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each fiberboard shipping container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Level A unit packs shall be packed flat, two in length, one in width, and five in depth within a shipping container. Inside dimensions of the shipping container shall approximate 24-1/2 inches in length, 16-1/2 inches in width, and 15 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V and reinforced as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.4. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

* 5.2.2 Level B packing. Five hundred insect nets, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a liner conforming to type CF, class domestic, variety SW, grade 275 of PPP-B-636. Level A unit packs shall be packed flat, two in length, one in width, and five in depth within a shipping container. Inside dimensions of the shipping container shall approximate 24-1/2 inches in length, 16-1/2 inches in width, and 15 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.4.

5.2.2.1 Weather-resistant fiberboard container. When specified (see 6.2), the shipping container shall be grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.4.

* 5.2.3 Commercial. Insect nets, preserved as specified in 5.1, shall be packaged in accordance with ASTM D 3951.

* 5.3 Palletization. When specified (see 6.2), insect nets, packed as specified in 5.2.2 and 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet pattern shall be number 3 in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course.

* 5.4 Marking. In addition to any special marking required by the contract or purchase order, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

5.4.1 Polyethylene bagged unit packs. Polyethylene bagged unit packs shall have the required identification information listed below legibly printed or stamped in black directly on the bag across the center face or on a white paper label inserted within the bag so as to permit ready identification. The bag or label shall only indicate the following information:

STOCK NUMBER
ITEM DESCRIPTION
QUANTITY

6. NOTES

6.1 Intended use. The insect net is intended for use in tropical and semi-tropical areas with Hat, Sun, Hot Weather.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required (see 3.2, 4.3, and 6.4).
c. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
d. Type and class of unit load required (see 5.2.1).
e. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
f. When palletization is required (see 5.3).

6.3 Sample and shade samples. For access to samples of the net and shade samples of the materials, address the contracting activity issuing the invitation for bids.

6.4 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

6.5 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this document (see 3.3).

* 6.6 Subject term (key words) listing.

Hat
Hot weather
Insect net
Protective clothing

6.7 Changes from previous issue. The margins of this document are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content, as written, irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Air Force - 99

Review activities:

Army - MD
Air Force - 82
DLA - CT

User activity:

Air Force - 45

Preparing activity:

Army - GL

Project No. 8415-0608

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-I-43746B	Insect Net, Hat, Sun, Hot Weather

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:12Z
Check the source to verify that this is the current version before use.