INCH-POUND

MIL-P-43740C(GL)
4 November 1991
SUPERSEDING
MIL-P-43740B(GL)
23 May 1978

MILITARY SPECIFICATION

PERSONNEL IDENTIFICATION BAND KIT WITH COMPONENTS AND CASE

This specification is approved for use by Natick Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type and size of personnel identification band kit with components and case.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

PPP-B-636 - Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be sent to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5019 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8465

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:11Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-L-35078 - Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads
MIL-STD-731 - Quality of Wood Members for Containers and Pallets
MIL-STD-810 - Environmental Test Methods and Engineering Guidelines

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

5-7-141 - Kit, Personnel Identification Band; Assembly Complete
5-7-142 - Kit, Personnel identification Band; Marking Case, Assembly and Sections
5-7-143 - Kit, Personnel Identification Band; Marking Case Details
5-7-144 - Kit, Personnel Identification Band; Details
5-7-145 - Kit, Personnel Identification Band

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-UX, Natick, MA 01760-5017.)

2.2 Non-Government publications. The following documents form a part of this document to extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:11Z
Check the source to verify that this is the current version before use.

of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 570 - Water Absorption of Plastics
D 638 - Tensile Properties of Plastics
D 648 - Deflection Temperature of Plastics Under Flexural Load
D 789 - Nylon Injection Molding and Extrusion Materials
D 790 - Flexural Properties of Plastics
D 792 - Specific Gravity and Density of Plastics by Displacement
D 3951 - Standard Practice for Commercial Packing

(Applications for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Alternate components. Components offered as equivalent to components specified hereinafter on the referenced drawings as specific manufacturer's part numbers or equal, shall be functionally equal to and of equal or better quality than the manufacturer's part numbers identified. The incorporation and inclusion of such a component in the design of the specified end product shall not require modification or change to any other specified component, and shall not reduce ease of maintenance to it or any other component, unless such modification or change is specifically approved by the contracting officer. Prior to manufacture of the preproduction first article, or if none is required prior to commencing production, the contractor shall submit, for the contracting officer's approval, a list identifying each proposed alternate component, together with proof that each listed component complies with requirements specified herein. The contracting officer, at his option, may require a physical sample of the proposed substitution. Approval of the submitted listing, together with necessary supporting date, authorizes the commencement of first article or production manufacture, as applicable, and does not relieve the contractor of the responsibility that these components perform in accordance with specified requirements when incorporated into the end product.

3.3 Components of personnel identification band kit. The components of the kit shall conform to the quantities specified in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:11Z
Check the source to verify that this is the current version before use.

TABLE I. Components of one kit

Component	Quantity
Carrying case, fiberglass	1
Roll of name slips (550 slips per roll)	1
Identification bands	500
Instruction sheet (see figure 1)	1
Check list (see figure 2)	1
Case, vinyl coated cloth (for marking assembly	1
Rivets, blind	500
Hand rivet guns	2
Ball point pens, black	5
Markers, felt tip (colors as specified on Drawing 5-7-142)	16
Scissors	1
Pliers, diagonal cutting	1

3.3.1 Replacement components packet. The replacement component package shall consist of:

ITEM	QUANTITY
Name Slips	550
Rivets	500
Identification bands	500

The items of the Replacement components packet shall conform to the design details, materials, dimensions, and requirements stated herein (see 5.1.1).

3.4 Materials. The materials used shall conform to the applicable referenced specifications, standards, drawings, and requirements specified herein. Where materials are not definitely specified, they shall be of the quality and type normally used by the contractor provided the completed item complies with all provisions of this specification. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.4.1 Nylon. Nylon for the identification band, when tested as specified in 4.4.1.1, shall meet the following requirements (see 6.4):

Property	Requirement
Water absorption, maximum	3.5 percent
Tensile strength at yield, minimum	7000 psi
Elongation at fail, minimum	250 percent
Deflection temperature at 66 psi, minimum	320°F

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:11Z
Check the source to verify that this is the current version before use.

Property	Requirement
Moisture content, maximum	0.3 percent
Flexural strength at yield, minimum	7000 psi
Specific gravity	1.13 ± 0.01

3.5 Design and construction. The personnel identification band kit, with components and case, shall conform to the design details, materials, and dimensions shown on Drawings 5-7-141, 5-7-142, 5-7-143, 5-7-144 and 5-7-145 and to the requirements specified herein. The mold to be used in the fabrication of the identification band shall be provided by the contractor.

3.5.1 Flap assemblies and flap retainer. Flap assemblies and flap retainer shall be riveted to the case as shown on Drawing 5-7-141.

3.5.2 Machine stitching. The stitching shall have from six to eight stitches to the inch and shall be type 301 conforming to FED-STD-751. Thread breaks in stitching shall be overstitched not less than 1 inch at each break. Stitching ends shall be overstitched not less than 1 inch except where ends are turned under in a hem or are held down by other stitching. Where two or more skipped stitches occur consecutively, they shall be overstitched not less than 1 inch.

3.5.3 Assembly instruction and list of components sheets. The instruction sheet for assembly and application of the personnel identification band, and the check list of components as shown on figures 1 and 2 shall each be printed on an 8 inch by 10-1/2 inch sheet of paper with waterproof ink. The characters shall be 10 point bold face. The sheets shall be securely attached in the locations shown on Drawing 5-7-141. The instructions and list of components shall be legible.

3.5.4 Carrying case. The carrying case shall be as shown on Drawing 5-7-141. The carrying case shall be free from evidence of water penetration when tested as specified in 4.4.1.3.

3.5.5 Finish.

3.5.5.1 Carrying case and components. The carrying case and the components shall be finished in accordance with the manufacturer's current commercial practice.

3.5.6 Marking. The letters "U.S." in characters 1 inch high shall be marked in a visible area on the inside of the carrying case.

3.5.7 Workmanship. All surfaces of the finished personnel identification kit carrying case and components shall be free of burrs, slivers, and rough and sharp edges. Components shall not be broken, cracked, split, or malformed. Cloth components shall be free of holes, cuts, or tears. Tapes

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:11Z
Check the source to verify that this is the currentversion before use.

shall not have frayed or scalloped edges. Thread tensions shall be maintained so that there will be no loose stitching, and seam allowances shall be maintained with seams properly sewed so that no runoffs or open seams will result. Care shall be taken in sewing to see that no needle chews occur. All thread ends shall be trimmed to 1/2 inch or less. Rivet head of item 8 of Drawing 5-7-141 shall be drawn up tightly, i.e., free from looseness. Rivet shall be properly peened on washer, i.e., cannot be removed by hand. The end items shall conform to the quality of product established by this specification and the occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.1.3 Certificates of compliance. When certificates of compliance are submitted, the Government reserves the right to inspect such items to determine the validity of the certification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:11Z
Check the source to verify that this is the current version before use.

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.2. Any nonconformance shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.1.1 Component and material certification. A certificate of compliance may be acceptable as evidence that the components listed below conform to the specified requirements when tested by the specified methods.

Component	Requirement	Paragraph	Test method
Nylon	Water absorption	3.4.1	ASTM D 570
	Tensile strength at yield	3.4.1	ASTM D 638
	Elongation at fail	3.4.1	ASTM D 638
	Deflection temp. at 66 psi	3.4.1	ASTM D 648
	Moisture content	3.4.1	ASTM D 789
	Flexural strength at yield	3.4.1	ASTM D 790
	Specific gravity	3.4.1	ASTM D 792
Rivet gun	Design and working duration	Drawing 5-7-142	-----

4.4.1.2 Carrying case operation testing. The carrying case shall be examined for opening and secure closing of the lid. The sample unit shall be one carrying case. The lid on each case in the sample shall be opened and closed three times. Any case requiring manipulative force to open or fully close the lid shall fail this examination and the lot represented by the sample. The inspection level for this examination shall be S-4.

4.4.1.3 Carrying case leakage testing. After the "A" and "B" flap assemblies have been assembled to the carrying case with rivets and washers (see Drawing 5-7-141), the carrying cases shall be tested as specified in 4.5.1 and 4.5.2 for conformance to the requirement in 3.5.4. The lots shall consist of all carrying cases with "A" and "B" flap assemblies attached with units and washers. The sample units shall be one carrying case with "A" and "B" flap assemblies attached with units and washers. The inspection level shall be I. Any failure will be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:11Z
Check the source to verify that this is the current version before use.

4.4.2 End item visual examination. The personal identification band kits shall be examined for the defects listed in table II. The lot size shall be expressed in units of kits. The sample unit shall be one kit. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0 for major defects and 10.0 for total (major and minor combined) defects.

TABLE II. End item visual defects

Examine	Defect	Classification Major	Minor
Finish	Any carrying case not finished in accordance with manufacturer's commercial practice	101	
	Any component not finished		201
Construction, assembly and workmanship	Washer inserted into identification band is not an interference fit		202
	Burrs, slivers, rough or sharp edges	102	
	Components not type, size, or shape specified	103	
	Component missing	104	
	Component broken, cracked, split, or malformed	105	
	Component in wrong location		203
	Quantity of component less than specified		204
Attachment of rivets on carrying case	Any rivet missing	106	
	Rivet not properly peened on washer, i.e. can be removed by hand	107	
	Rivet head not drawn up tightly, i.e. is loose		205
Fabric	Any hole, cut, or tear	108	
Tape	Edge frayed or scalloped		206
Seams and stitching	Open seams:		
	- for more than 1/4 inch but not more than 1/2 inch		207
	- for more than 1/2 inch	109	
	Thread break overstitched less than 1 inch		208

NOTE: Thread breaks not overstitched shall be classified as open seams.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:11Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Seams and stitching (cont'd)	Skipped stitches overstitched less than 1 inch		209
	NOTE: Skipped stitches not overstitched shall be classified as open seams.		
	Needle chews resulting in cut, tear, or hole		210
	One or more required rows of stitching omitted	110	
Stitching ends	Overstitched less than 1 inch (except where ends are turned under in a hem or are held down by other stitching		211
Stitch type	Wrong stitch type	111	
Stitch tension	Loose, resulting in exposed bobbin or top thread for more than 2 inches		212
	Tight, as evidenced by puckering of fabric for more than 2 inches	112	
Stitches per inch	Less than minimum specified:		
	- one stitch		213
	- two or more stitches	113	
	More than maximum specified:		
	- one stitch		214
	- two or more stitches	114	
Ball-point pens	Do not write or do not write clearly on name slips without running or smearing		215
Name slip	Smearing, running, or fading when written on with ball-point pen, felt pen, or pencil or when typewritten on	115	
Instruction sheet and check list	Missing, illegible, or not as specified	116	
Marking	Missing, illegible, incorrect, or in wrong location		216

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:11Z
Check the source to verify that this is the current version before use.

4.4.3 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Markings (exterior and unit packs)	Omitted; incorrect; illegible; incomplete; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged or not as specified
Workmanship	Inadequate application of components such as incomplete closure of flaps Bulged or distorted container Open or noncontinuous heat sealed seam Incorrectly fabricated polyethylene bag Closure of the polyethylene bag not accomplished by use of a twist tie (paper or plastic coated soft steel wire)
Contents	Number of components in each kit is more or less than specified Number of kits per container is more than required Number of name slips or number of rivets per polyethylene bag not as specified

4.4.4 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Load not bonded with required straps as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:11Z
Check the source to verify that this is the current version before use.

4.5 Methods of inspection.

4.5.1 Rain. Rain test shall conform to procedure I of method 506 of MIL-STD-810.

4.5.2 Leakage. Leakage test shall conform to procedure No. 1 of method 512 of MIL-STD-810 except as follows:

a. The temperature of the test condition need not apply.
b. The bottom of the carrying case having the rivets and washers need not be submerged more than 4 inches.

5. PACKAGING

5.1 Preservation. Preservation shall be level A, or Commercial, as specified (see 6.2).

5.1.1 Level A. Each roll of 550 name slips and each unit of 500 rivets shall be separately packaged in clear polyethylene film bags having minimum film thickness of 0.003 inch. The bags shall be closed with a twist tie. All components of the kit shall then be placed in their appropriate positions within the carrying case as shown in Drawings 5-7-141 and 5-7-142. The carrying case shall be closed and secured with the two locking fasteners provided on the carrying case. Each kit, preserved as specified in 5.1, shall be blocked and cushioned to prevent damage. Each replacement components packet consisting of 550 name slips, 500 rivets and 500 identification bands, preserved as specified in 5.1, shall be packed as one unit (see 3.3.1).

5.1.2 Commercial. Components shall be preserved in accordance with ASTM D-3951.

5.2 Packing. Packing shall be level A, B or Commercial, as specified (see 6.2).

5.2.1 Level A packing. Each kit or packet shall be packed in a shipping container. The shipping container shall be a fiberboard box conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each box shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Inside dimensions of the box for the kit shall be approximately 20-1/2 inches in length, 16-1/2 inches in width, and 11-1/4 inches in depth. Inside dimensions of the box for the packet shall be 18-1/2 inches in length, 16-1/2 inches in width, and 9 inches in depth. Each box shall be closed, waterproofed, and reinforced with strapping or tape banding in accordance with the appendix of PPP-B-636. Boxes shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:11Z
Check the source to verify that this is the current version before use.

5.2.2 Level B packing. Each kit or packet shall be packed in a shipping container. The shipping container shall be a fiberboard box conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each box shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Inside dimensions of the box for the kit shall be approximately 20-1/2 inches in length, 16-1/2 inches in width, and 11-1/4 inches in depth. Inside dimensions of the box for the packet shall be 18-1/2 inches in length, 16-1/2 inches in width, and 9 inches in depth. Each box shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.1 Weather-resistant shipping container. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix of PPP-B-636.

5.2.3 Commercial packing. Each kit or packet shall be packed in accordance with ASTM D-3951.

5.3 Palletization. When specified (see 6.2), kits or packets packed as specified in 5.2.2 or 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet types shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means C and D or film bonding means F or G. Pallet pattern shall be number 95 in accordance with the appendix of MIL-STD-147.

5.4 Marking. In addition to any special marking required by the contract or purchase order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D-3951, as applicable.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The personnel identification band kit with components and case is intended to be used by the military police units for the preparation and attachment of individual prisoner of war identification name bands, and in addition for use on U.S. Military prisoners, casualties, and civilian internees.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:11Z
Check the source to verify that this is the current version before use.

c. When first article is required (see 3.1, 4.3, and 6.3).
d. Levels of preservation and packing (see 5.1 and 5.2).
e. Type and class of unit load (see 5.2.1).
f. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209-4. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Source of supply. Fosta Nylon 567, supplied by Foster Grand Co., Inc., Leominster, MA 01453, meets the nylon requirements in 3.4.1. Any contractor's item which conforms to the specified requirements will be acceptable.

6.5 Subject term (key word) listing.

Casualty
Military police
Name tag
Name slip
Prisoner
Wristband

6.6 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:

Army - GL

Review activities:

Army - MD
DLA - CT

Preparing activity:

Army - GL

(Project 8465-A081)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:11Z
Check the source to verify that this is the current version before use.

DIRECTIONS FOR APPLYING IDENTIFICATION BAND TO WRIST

REMOVE MARKING CASE FROM CARRYING CASE, UNFOLD MAIN FLAP AND BOTH SIDE FLAPS. USE SURFACE BETWEEN SIDE FLAPS AS THE WORKING AREA.

INSERT RIVET (USUALLY STORED IN HOOK AND PILE POCKET OF MARKING CASE) IN RIVET GUN.

SELECT AN IDENTIFICATION BAND, PREBEND THE STRAP SECTION TO THE APPROXIMATE CONTOUR OF THE WRIST.

PRINT OR TYPE REQUIRED INFORMATION ON NAME SLIP. CLEAR PRECUT ROUND HOLE IN NAME SLIP BY PUSHING OUT MATERIAL. MARK COLOR CODE ON HOLE END OF NAME SLIP.

SLIDE NAME SLIP INTO BAND ENVELOPE UNTIL HOLE IN SLIP IS IN LINE WITH HOLE IN ENVELOPE. THE NAME SLIP WILL PROTRUDE 1/4 INCH (6 mm) FROM THE END OF THE BAND ENVELOPE.

PLACE BAND ON SUBJECTS WRIST, FOLD THE 1/4 INCH (6 mm) PROTRUSION OVER TOP OF ENVELOPE. INSERT BAND STRAP INTO ENVELOPE POCKET UNDER THE NAME SLIP WHILE FINGER PRESSURE IS APPLIED TO FOLDED PROTRUSION TO PREVENT CRUSHING OF NAME SLIP. BRING BAND TO A COMFORTABLE FIT WITH HOLES IN STRAP AND ENVELOPE IN LINE. PERSONAL JUDGEMENT MUST BE USED IN FITTING THE BAND TO ASSURE THAT THE BAND IS TIGHT ENOUGH TO PREVENT SLIPPING OVER THE HAND BUT LOOSE ENOUGH TO BE COMFORTABLE. AS A RULE IF THE BAND IS BROUGHT TO A SNUG FIT AND THEN BACKED OFF FROM ONE TO TWO HOLES THE FIT WILL BE SATISFACTORY.

USING RIVETER AS A GUIDE, INSERT RIVET IN ENVELOPE HOLE MAKING SURE THAT RIVET HEAD CONTACTS BAND ENVELOPE.

TRIM OFF EXCESS NAME SLIP PROTRUDING FROM BAND ENVELOPE WITH SCISSORS PROVIDED IN KIT.

NOTE: IN CASE OF UNUSUALLY SMALL WRIST, THE BAND MAY BE SHORTENED BY CUTTING OFF THE REQUIRED AMOUNT FROM THE END OF THE STRAP SECTION WITH THE DIAGONAL CUTTING PLIERS. DO NOT CUT OFF MORE THAN IS NECESSARY AS BAND STRAP IS DESIGNED TO EXERT PRESSURE ON NAME SLIP AND HOLD AGAINST WINDOW OF ENVELOPE. BAND STRAP MAY BE CUT OFF AT A 45 DEGREE ANGLE TO FACILITATE THREADING INTO ENVELOPE WHEN APPLYING TO WRIST. CUT BAND AT HOLE SECTION.

Figure 1 - Instruction Sheet

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:11Z
Check the source to verify that this is the currentversion before use.

CHECK LIST

PERSONNEL IDENTIFICATION BAND KIT

MARKING CASE	1
IDENTIFICATION BANDS 1/	500
RIVETS, Blind, 1/8 inch stainless steel, U.S. Machinery No. SSD43SSBS or equal 1/	500
RIVET GUN, HAND, NSN 5120-00-017-2849	2
SCISSORS, NSN 5110-00-255-0420	1
MARKERS, FELT TIP, Eberhard Faber #229-LF, or equal:	
Red	2
Black	2
Yellow	2
Purple	2
Green	2
Orange	2
Blue	2
Brown	2
PENS, BALL POINT, Black Ink, Bic M-19 or equal	5
INSTRUCTION SHEET	1
SAMPLE WRIST BAND, ASSEMBLED	1
PLIERS, DIAGONAL CUTTING, NSN 5110-00-222-2708	1
NAME SLIPS, Dupont, Tyvek, Style 1085, 2.7 oz. or equivalent 1/	550
CARRYING CASE, Fiberglass, Skydyne Inc. No. 92300 or equivalent	1

1/ Each replacement components packet consisting of 500 Name Slips, 500 Rivets and 500 Identification Bands may be ordered under NSN 8465-01-041-9816.

Figure 2 - Check List

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:11Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-P-43740C(GL)	1991 November 4

3. DOCUMENT TITLE

PERSONNEL IDENTIFICATION BAND KIT WITH COMPONENTS AND CASE

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON/DSN
U.S. Army Natick RD&E Center	508-651-4532	256-4532
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: STRNC-IRT Natick, MA 01760-5019	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 NATICK OP2, JUL 91 *Previous editions are obsolete.*

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:11Z
Check the source to verify that this is the current version before use.