MILITARY SPECIFICATION

MANUALS, TECHNICAL: WORK UNIT CODE (For Air Launched Missiles)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1. Scope. This specification prescribes the requirements for the preparation of work unit code manuals for air launched missiles.

1.2. Purpose. Under the Air Force Data Collection System, each maintenance action performed on Air Force equipment must be fully and accurately documented. The volume of data collected requires the use of automatic data processing techniques. The use of automatic data processing (ADP) equipment requires that the data input be coded in such a manner that it can be "read" by the data processing machines. Standard codes have been developed for recording the type of maintenance being performed, the action taken to correct a deficiency, when a deficiency was discovered, and the type of malfunction that occurred. Identification codes, called Work Unit Codes, are used to identify the specific assembly or part within an end item on which an action was performed. Each work unit code manual shall contain complete listings of all "Work Unit" (support general and equipment identification), "Unique Data Codes for MCSC Maintenance Cost System," "Type Maintenance," "Action Taken," "When Discovered," and "How Malfunctioned" codes applicable to the air launched missile and peculiar AGE covered by the manual.

2. APPLICABLE DOCUMENTS.

2.1. The following documents of the issue in effect on date of invitation for bids, or request for proposal, form a part of this specification to the extent prescribed herein:

SPECIFICATIONS

Military

MIL-M-38784	Manuals, Technical: General Requirements for Preparation of:
MIL-P-38790	Printing Production of Technical Manuals: General Requirements for:
MIL-B-83931	Binders, Flexible: Technical Manual

PUBLICATIONS

Air Force

AFM 66-1	Maintenance Management
AFM 300-4, Vol XI	Data Elements and Codes
AFR 205-1	Information Security Program
AFLCM 66-14	AF Technical Order System Data Operations

Source: https://assist.dla.mil -- Downloaded: 202610-21T15:27Z
Check the source to verify that this is the current version before use.

TECHNICAL ORDERS

00-5-1	Air Force Technical Order System
00-20-2 series	The Maintenance Data Collection System
00-25-06 series	Work Unit Code Manuals

(Current copies of documents required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1. Preparation. Manuals shall be supplied in the form (reproducible copy, negatives, punched cards, or printed copies) specified in the contract. MIL-P-38790 is applicable to negative and printed copies.

3.1.1. Mechanization. When punched cards or preparation of code manuals utilizing ADP procedures are specified, this shall be accomplished in accordance with the requirements of AFLCM 66-14, Chapter 8.

3.1.2. Binders. When the contract specifies that printed copies of the manuals shall be delivered in binders, such binders shall be in accordance with MIL-B-83931.

3.1.3. Functional System Concept. The functional system concept shall be used for equipment breakout except for peculiar AGE as noted below. A functional system shall consist of those units which make up a system without regard to whether the units are hydraulic, electronic, pneumatic, etc. The components which comprise a functional system shall be those components which contribute to the actual function or activation of the system. For example, the components which supply hydraulic or pneumatic source of power (and distribution) will be included under system 33, "Hydraulic-Pneumatic Power Supply and Distribution," where as a fuel control valve actuator, which is pneumatically operated, will be included under the propellant system, which is the functional system. Items of peculiar AGE will be work unit coded as individual end items, within the homogeneous groups of AGE as listed in figure 4, utilizing assembly and component breakout.

3.1.4. Level of detail for each functional system. (Reference 3.3.3.1 through 3.3.3.3.1 for levels of assembly.) The work unit codes for each functional system/homogeneous group shall cover each reparable item in the functional system/homogeneous group as specified by the applicable source document. Work unit codes shall also be assigned to nonreparable components if they are known or suspected to be vital to successful system operation or to be significant manhour consumers. These items shall have a work unit code assigned in order to report those critical "on-equipment" actions for reliability and maintainability evaluation purposes. In some cases it may be necessary to arbitrarily assign "interface" type items of equipment to a functional system. This type of problem will arise in cases of interface connectors, tubing, couplings, wire, etc. Those decisions will be made after primary consideration is given to the maintenance responsibilities and training of the technicians who are required to maintain the interface items of equipment. For example, if a piece of tubing with a regulator attached makes the interface between the missile pneumatic and engine systems, and the engine technician is responsible for adjustments and maintenance of the regulator, then the tubing and associated regulator will be assigned to the engine functional subsystem.

3.1.5. Source Data. Systems engineering data (i.e., engineering analysis data, equipment maintenance analysis data, and contract end item detail specification) shall be used as source data for work unit code assignment. Maximum correlation between the component content of a contract end item and the assignment and grouping of work unit codes is desirable. When available concurrently with the code manual preparation, Illustrated Parts Breakdown Technical Manual shall be used as source data in determining level of assembly.

Source: https://assist.dla.mil -- Downloaded: 202610-21T15:27Z
Check the source to verify that this is the current version before use.

3.2. MANUAL CONSTRUCTION.

3.2.1. Mission, Design and Series (MDS). Work unit code manuals shall be prepared for each basic mission and design missile. Code manuals may be prepared by individual missile series if specified by the procuring activity. This will require that the AFLC Air Logistics Center System Manager (SM) assure that an equipment classification code is assigned for that specific mission, design and series in TO 00-20-2, Attachment 2. Work unit code manuals shall be prepared in two sections for each missile as follows: (However, each section may be a separate manual upon approval of the procuring agency.)

3.2.1.1. Section I. The first section shall be developed in accordance with the functional system concept to include work unit codes for all airborne equipment. This section will be utilized by maintenance missile personnel to record maintenance tasks accomplished directly on the missile, or on missile components or equipment undergoing repair, servicing, testing, calibration or bench check in specialized shops.

3.2.1.2. Section II. The second section shall be developed in accordance with the AGE homogenous grouping concept to include work unit codes for aerospace ground equipment (AGE) peculiar to the equipment contained in Section I. This section will be utilized by maintenance personnel to record maintenance tasks accomplished directly on end items of AGE, or on AGE components or equipment undergoing repair, servicing, testing, calibration or bench check in specialized shops. AGE equipment included in this section shall be that which was specifically designed for, or is peculiar to, the MDS missile covered by the manual. AGE that is commonly used in the Air Force will be included in the TO 00-25-06 series work unit code manuals.

3.2.2. Preliminary and formal manual size. The page size of preliminary manuals shall be determined by the procuring activity. Formal manuals shall be prepared in 4 by 8 inch size in accordance with MIL-M-38784.

3.2.3. Style of type. Each line entry with a zero in the fifth character of the work unit code shall be in uppercase type. Each line entry with other than a zero in the fifth character of the work unit code shall be in lowercase type with the first letter of each word in uppercase. In the event that automatic data processing equipment is utilized for preparation of reproducible copy, uppercase (machine printout) type will be utilized exclusively.

3.2.4. Columnar arrangement. All work unit code manuals will be in single column format. There shall be a spaced separation between work unit code line entries (excluding support general codes) in uppercase type form the preceding line. The code definition (nomenclature) for the third, fourth, and fifth positions of the work unit code shall be indented a space to the right. For example, the code definition for BA100 shall be indented to the right of the code definition of BA000. In the event that automatic data processing equipment is utilized for preparation of reproducible copy, the spacing and indentures will be in accordance with the requirements of AFLCM 66-14, Chapter 8.

3.2.5. Page numbering. Pages containing work unit codes shall be numbered in the lower-outer corner of each page by the work unit code system (or homogeneous group) number and consecutive page number. For example: the first page of the support general codes shall be 01-001, and the eleventh page of inertial guidance systems codes shall be 62-011. NOTE: Support General Codes 01000, 02000, 05000, 06000, 07000, and 09000 will be listed on page 01-001 thru 01- appropriate page numbers required. Codes 03XXX and 04XXX will be listed on separate pages utilizing page numbers 03- appropriate page sequence number and 04- appropriate page sequence number, respectively. Unique Data Codes for MCS (Maintenance Cost System) though not support general codes, will be listed in the support general codes portion of the manual and numbered 05-001.

3.2.6. Contents. The contents of the work unit code manuals will vary depending on the concept approved by the procuring agency. The contents and arrangements of the work unit code manuals for the different concepts shall be as follows:

Source: https://assist.dla.mil -- Downloaded: 202610-21T15:27Z
Check the source to verify that this is the current version before use.

3.2.6.1. Sectionalized manual concept.

Title page

List of Effective Pages

Table of Contents

Preface

Section I

Type Maintenance Codes (missile and engine codes, when applicable, shall be separate lists)

Action Taken Codes

When Discovered Codes

How Malfunctioned Codes (Alphabetic Sequence)

How Malfunctioned Codes (Numeric Sequence)

Work Unit Codes - Support General (AGE and missile codes shall be separate lists)

Unique Data Codes for MCS (Maintenance Cost System)

Work Unit Codes - Equipment Identification (Missile codes only)

Section II

Introduction (see figure 5)

Work Unit Codes - Equipment Identification (AGE codes only)

3.2.6.2. Segregated manual concept.

3.2.6.2.1. For missile only.

Title page

List of Effective Pages

Table of Contents

Preface

Type Maintenance Codes (missile and engine codes, when applicable, shall be separate lists)

Action Taken Codes

When Discovered Codes

How Malfunctioned Codes (Alphabetic Sequence)

How Malfunctioned Codes (Numeric Sequence)

Work Unit Codes - Support General

Unique Data Codes for MCS (Maintenance Cost System)

Work Unit Codes - Equipment Identification

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

3.2.6.2.2. For missile peculiar AGE only.

Title Page

List of Effective Pages

Table of Contents

Preface

Type Maintenance Codes

Action Taken Codes

When Discovered Codes

How Malfunctioned Codes (Alphabetic Sequence)

How Malfunctioned Codes (Numeric Sequence)

Work Unit Codes - Support General

Unique Data Codes for MCS (Maintenance Cost System)

Work Unit Codes - Equipment Identification

3.2.6.3. Title Page. A title page shall be prepared in accordance with the requirements of MIL-M-38784. An effectivity date statement will be included on the title page above the authority notice for each new code manual, similar to the following: "The effectivity date of this publication is 1 December 1974. Codes in this publication shall not be used prior to that date." All subsequent work unit code manual changes, supplements or revisions that contain a change to a work unit code from one nomenclature to another shall contain an effectivity date statement on the title page. The effectivity date will be established by the Air Force activity responsible for the management of the work unit code manual and provided to the contractor. The effectivity date shall be a minimum of 30 days subsequent to the actual distribution date. All effectivity dates shall be the first day of the month.

3.2.6.4. List of effective pages. A list of effective pages shall be prepared in accordance with the requirements of MIL-M-38784.

3.2.6.5. Table of contents. The table of contents shall list the code manual contents in the order shown in 3.2.6.1 and 3.2.6.2, together with the appropriate page reference. The cover page and the list of effective pages shall not be included in the Table of Contents. The work unit code listing shall be comprised of the first two characters of the support general and equipment system or the homogeneous group codes, and the title or description of each code listed. (End item work unit codes are authorized in the description for homogeneously grouped items to aid in the location of the item within the code manual.) Example:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

TABLE OF CONTENTS

Code	Page No.
Preface	II-001
Type Maintenance Codes	III-001
Action Taken Codes	IV-001
When Discovered Codes	V-001
How Malfunctioned Codes (Alphabetic Sequence)	VI-001
How Malfunctioned Codes (Numeric Sequence)	VII-001
Missile Support General Codes	
01 Thru 09 (except 03 & 04) Support General Codes	01-001
03 Look Phase of Scheduled Inspections	03-001
04 Special Inspections	04-001
Unique Data Codes for MCS (Maintenance Cost System)	05-001
Missile Basic	
11 Airframe	11-001
13 Wing and Finfold	13-001
Propulsion	
25 Solid Rocket	25-001
etc	

3.2.6.6. Preface. The preface shall be as outlined in figure 2.

3.2.6.7. Type Maintenance, Action Taken, When Discovered and How Malfunctioned Codes. These codes are assigned and controlled through the medium of AFM 300-4, Volume XI. No changes or additions shall be made to these codes without prior approval in accordance with the requirements of AFM 300-4, Volume XI. The procuring activity is responsible for selection of codes from AFM 300-4, Volume XI, and assuring proper entries in the work unit code manual in accordance with this specification. The selected codes will be appended to the contractual or work statement at time of contract award.

3.2.6.7.1. Type Maintenance Code. This code consists of one alphabetic character and identifies the type of work performed; i.e., scheduled or unscheduled maintenance. This list shall include only those codes that are applicable to the work unit manual. Engine shop work type maintenance codes for removed engines will be listed in applicable work unit code manuals. (Reference AFM 300-4, Volume XI, ADE MA-358). The following note will be included in all work unit code manuals following the type maintenance codes for the basic type of equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

NOTE

See TO 00-25-06-2-1 for off-equipment shop type maintenance codes.

3.2.6.7.2. Action Taken Code. This code consists of one alphabetic or numeric character and identifies what work was done; i.e., the action taken. Collectively, the work unit code and the action taken code idneity a "unit of work" as defined in TO 00-20-2. Example: Work Unit Code 25130 Igniter Assembly, Action Taken Code R - Remove and Replace. The complete list of Action Taken Codes shall be included in the code manual. (Reference AFM 300-4, Volume XI.)

3.2.6.7.3. When Discovered Code. This code consists of one alphabetic or numeric character and identifies when a defect was doscovered; i.e., during a periodic inspection, during countdown, etc. Only that portion of the When Discovered Code definition that applies to the missile and/or AGE shall be included in the code manual. (Reference AFM 300-4, Volume XI, ADE AC-780.)

3.2.6.7.4. How Malfunctioned Code. This code consists of three numeric characters and is used to identify how the equipment malfunctioned; i.e., was it shorted; cracked; corroded; etc. The How Malfunctioned Codes shall be listed in both alphabetic and numeric sequence, and shall contain only those codes that are applicable to the code manual. Example: Codes applicable to reciprocating engines will not be listed in TO 21M-AGM28A-06-1. (Reference AFM 300-4, Volume XI, ADE HO-920.)

3.2.6.8. Work Unit Code - Support General. A list of Support General Codes for missiles and their peculiar AGE equipment is included in figure 3. Support General Codes that do not apply to the equipment listed in the code manual shall be omitted. Support General Codes 03000 and 04000 shall not be included in the code manuals adjacent to the titles for look phase of scheduled or special inspections.

3.2.6.8.1. Unique Data Codes for MCS. A list of Unique Data Codes for MCS is included in figure 3. These codes shall be included in the work unit code manuals following the last page of support general codes. They will be printed on one page and numbered 05-001.

3.2.6.9. Work Unit Code - Equipment Identification. This is a five position code which identifies the major system/homogeneous group, subsystem (or end item of AGE), subassembly and component that required maintenance. The first two positions of the work unit codes (designating the system or homogeneous group) are standard throughout the USAF and are included in figure 4. The third and fourth characters include subassembly (or ancillary system), or major assembly as applicable, and identify the first and second levels of assembly below the system (excepting peculiar AGE, in which case the third character will identify the end item and the fourth character will identify the assembly.) The fifth position of the work unit code includes reparable components and identifies the lowest level of assembly below the major system/end item.

3.2.6.9.1. System code definition. The use of the terms "System" or "Major System" within the work unit code structure are synonymous and apply to functional systems. These terms should not be construed as including or pertaining to a complete weapon or space "system." An assembled listing of all applicable system codes and their related equipment will portray the make-up of a missile or space system. See figure 4.

3.3. WORK UNIT CODE APPLICATION AND CONSTRUCTION.

3.3.1. Application of work unit codes. The primary purpose of work unit codes is to identify the item on which work was accomplished, and the relationship of this item within a functional system. Work unit codes shall not be assigned to locations or general terms. For instance, station numbers, geographic locations and terms such as mechanical components or miscellaneous equipment may be used as titles to aid in locating work unit codes within the code manual, but these titles shall not have work unit codes assigned. Work unit codes should not be assigned to common hardware or soft-goods, such as nuts, bolts, washers, clamps, seals, gaskets and O-rings. Work on these type items is normally reported against the coded assembly to which they attach.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

3.3.1.1. Reserving codes for future use. It is essential that expansion capability be designed into each code manual in the third, fourth and fifth positions of the work unit codes to assure that new codes can be assigned for future modifications or additions of equipment. For example, one series of missile is delivered with one type of first stage skirt insulation. A block of these missiles are subsequently modified for a different type of insulation. Both types of insulation can be coded in a single manual if expansion room is available, without recoding the original insulation. If adequate expansion capability was designed into the original codes, this equipment can be added without disturbing the original codes. Minimum code changes are essential to prevent loss of previously compiled maintenance data.

3.3.1.2. Reuse of codes. When existing work unit codes are deleted from a manual, they normally will not be reassigned for a minimum of ninety days following their deletion, nor without prior approval of the procuring activity. If there is no other code or code sequence that can be used, work unit codes may be reassigned by the procuring activity without waiting ninety days.

3.3.1.3. System code/homogeneous group code page entries. When a change occurs in the first or second position of the work unit code (system/homogeneous group code), the next entry shall begin on a new right hand page. For example: following completion of code assignments for BA000, code BB000 assignments will be made on a new right hand page. A change from BE000 to CA000 will also require entry on a new right hand page. Exception: Support General Codes 01000, 02000, 05000, 06000, 07000, and 09000 will be listed in numerical sequence under the heading of Support General Codes.

3.3.1.4. Nomenclature. Each work unit code in the equipment identification listing shall reflect adequate information to properly identify all levels of assembly, and shall include the basic noun for each individual item that is coded. If official military type nomenclature has been assigned, it shall be used for identification. Part numbers are to be utilized solely for explosive items and are not to identify nonexplosive items except as noted by 3.3.3.4. Approved abbreviations may be used when necessary.

3.3.2. Alphabetic and numeric characters. Uppercase letters Z through Z (excluding I and O) and numerics 0 through 9 shall be utilized for work unit code assignments as specified in subsequent paragraphs. The letters I and O shall not be utilized in any work unit code in order to prevent confusion with numerics one and zero.

3.3.3. Work unit code construction. (Refer to 3.2.6.9 for levels of assembly.)

3.3.3.1. First level of assembly code construction. Alphabetic and numeric characters shall be used as the third character of the work unit code to designate first level of assembly below major system. Thirty-three (33) separate levels may be identified in this manner. For example:

33000 - SYSTEM

33A00 - FIRST LEVEL OF ASSEMBLY
thru
33Z00
then
33100 - FIRST LEVEL OF ASSEMBLY
thru
33900

3.3.3.2. Second level of assembly. Alphabetic and numeric characters shall be used as the fourth character of the work unit code to designate second level of assembly below major system. Thirty-three separate levels may be identified in this manner. For example:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

33000 - SYSTEM

33A00 - FIRST LEVEL OF ASSEMBLY

33AA0 - SECOND LEVEL OF ASSEMBLY
thru
33AZ0
then
33A10 - SECOND LEVEL OF ASSEMBLY
thru
33A90

3.3.3.3. Third level of assembly code construction. Alphabetic and numeric characters shall be used as the fifth character of the work unit code to designated third level of assembly below major system. Thirty-two levels may be identified in this manner. The numbers "99" are used in the fourth and fifth positions to indicate Not Otherwise Coded (NOC). For example:

33000 - SYSTEM

33A00 - FIRST LEVEL OF ASSEMBLY

33AA0 - SECOND LEVEL OF ASSEMBLY
33AAA - Third Level of Assembly
thru
33AAZ
then
33AA1 - Third Level of Assembly
thru
33AA8

33A99 - NOC (First Level of Assembly)

NOTE: Numerics may be assigned initially in the third, fourth, and fifth positions of the work unit codes when there is positive assurance that the numeric coding capacity will not be exceeded during initial code assignment, or by future equipment additions or modifications.

3.3.3.3.1. Homogeneously grouped code construction. Exception to the above work unit codes construction will be taken when utilizing homogeneous grouping (for peculiar AGE equipment). The first two characters will identify the homogeneous group, the third character will identify the end item, the fourth character will identify the first level of assembly and the fifth character will identify the lowest level of assembly. For example:

CA000 - HOMOGENEOUS GROUP

CAA00 - END ITEM

CAAA0 - FIRST LEVEL OF ASSEMBLY
CAAAA - Lowest Level of Assembly
thru
CAAA8 - Lowest Level of Assembly

CAA99 - NOC (End item)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

3.3.3.3.2. Use of "99 - Not Otherwise Coded." The number 9 is used in the fourth and fifth characters of the work unit code, followed by the abbreviation "NOC," which stands for "Not Otherwise Coded." This code is used to provide a work unit code for components that do not have specific codes assigned. NOC codes will relate to the first level of assembly when the first level of assembly is the third character of the work unit code. When the third character is the end item (homogeneous group), the NOC code will relate to the end item rather than the first level of assembly. The "99 NOC" code will appear as the last entry under the last component in the first level of assembly (or end item for homogeneous groups) breakout. When continuations are used as outlined in 3.3.3.6, Code "99 NOC" shall only appear in the last group of codes. There shall be a spaced separation between the last component of the first level of assembly/end item and the NOC code for that first level of assembly/end item to provide easy recognition of the NOC code. NOTE: The numbers 99 shall not be used in the fourth and fifth positions of the work unit code to identify any specific type of equipment.

3.3.3.4. Multiple items serving a single system/homogeneously grouped end item. Identical components within a system/end item performing peculiar functions shall have individual work unit code assignments for each peculiar function/application. For example, a pressurization control unit (PCU) in a system may contain four identical controllers but each controller has a different usage (pressure setting) in the PCU. In this case, each controller will have a unique work unit code assigned. Items installed in multiples within a functional system/homogeneously grouped end item which perform within the same function/application parameters, except for location, will normally have a single code assigned. For instance, only one code should be assigned for items having left hand and right hand application even though they have different part numbers. The procuring activity may grant exceptions to this requirement for items that have high failure rates or warrant detailed reporting for analysis purposes. If exceptions are granted when the nomenclatures of the items will reflect part number references to distinguish between the like items. This shall be done on an exception basis and shall not be a common practice.

3.3.3.5. Items serving multiple systems/homogeneous grouped end items. When a single component functionally services two or more major systems, end items, or lower levels of assembly, only one work unit code shall appear in only one of the system/homogeneous grouped end item listings. However, the item shall be listed (by identical nomenclature only) in the remaining applicable system(s)/homogeneously grouped end item(s) with a reference to the previously assigned work unit code; e.g., "Manifold Sequence Valve (Reference 33FAA)." The work unit code column for such items will be left blank.

3.3.3.6. Coding capability. The construction of work unit codes provides a capability to designate thrity-three first level assemblies (for other than homogeneously grouped items) and thirty-two third or lowest level assemblies. If equipment breakout exceeds these capabilities, it will be necessary to continue the listing with the next available code. For example:

33AA0 - DUAL PUMPING UNIT

33AA8 - Controller

DUA PUMPING UNIT (CONT)

33ABA - Controller Modulator

33A99 _ NOC

Note the change in the fourth character of the work unit code.

3.4. Code arrangement and special procedures.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

3.4.1. Work unit code column heading. The first line entry at the top of each work unit code column shall be the type of equipment (see figure 4) to which the work unit codes apply. For example:

11000 - AIRFRAME

* * * *

25000 - SOLID ROCKET

* * * *

RA000 - GUIDED MISSILE TEST SET

3.4.2. New page entries. When work unit codes for a major system/end item or lower level of assembly are carried over to a new page, the first work unit code entry on the new page shall be (1) the system (or end item for AGE) code and title; (2) following that line entry shall be the work unit code and title of the second level of assembly (or the first level of assembly for homogeneously grouped end items) followed by the abbreviation for continued, in parentheses. Example, assuming that the last code of the preceding page is 62AA4 Guard-Filter:

62000 -	INERTIAL GUIDANCE	(System)
62AA0 -	CHASSIS ASSY (CONT)	(Second level assy)
62AA5 -	Spring-Lock	(Third level assy)

3.4.3. End item identification. Each end item of equipment in the AGE portion of the work unit code manual shall be identified by an "AT"@ sign between the work unit code and its nomenclature. This is intended to aid maintenance technicians in identifying what equipment should be entered in the "end item work unit code" block of the maintenance forms.

3.4.4. Time change item and configured article identification. An asterisk shall be placed between the work unit code and its definition (nomenclature) for each time change, time significant or serially controlled item, which shall be identified and provided by the procuring activity. The abbreviation TCI shall be entered in the parentheses following the definition (nomenclature) for time change items to differentiate between these items and time significant or serially controlled items. (Reference paragraph 2a of figure 2.)

3.4.5. Mobile Training Sets (MTS) and Resident Training Equipment (RTE). Maintenance on MTS and RTE is recorded by utilizing the operational equipment work unit code manuals. When specified by the procuring activity, items peculiar to the training equipment (not utilized in the operational equipment of the same type) shall be coded in the applicable operational equipment work unit code manual. The abbreviation MTS or RTE, as applicable, shall be entered in parentheses for these items following the code definition. Codes for peculiar training equipment shall be restricted to items on which it is essential to collect maintenance data, such as a motor to simulate actuation or actuating devices necessary to simulate functions. Such items shall be coded at the end of the applicable system codes following the operational equipment with adequate code spacing to permit expansion of operational equipment codes. The following sentence shall be added to the end of paragraph 2.a of the work unit code manual preface when the preceding coding procedure is used: "The abbreviation (MTS or RTE, as applicable) identifies training equipment (Mobile Training Sets or Resident Training Equipment) peculiar items included in this work unit code manual for recording purposes."

3.4.6. Real Property Installed Equipment (RPIE). Work unit codes for RPIE shall be furnished by the applicable SM through the procuring activity, if required.

3.4.7. Standardization. When similar systems and components are used in two different series of the same mission and design missile, such as the AIM-4A and AIM-4F, the first three characters of the work unit code shall remain the same in both manuals. To the maximum degree practicable, the fourth and fifth characters of the work unit codes shall also be the same.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS.

4.1. General. The requirements of MIL-M-38784 and MIL-P-38790 are applicable.

4.2. Validation. The contractor shall certify that information provided in the manual accurately and completely reflects the composition of the system in its latest Air Force approved configuration and as set forth in the source documentation used to develop the manual. Completed validation shall be a condition of Air Force acceptance for each manual prepared under this specification.

4.3. Verification. At the option of the procuring activity, a requirement for verification of work unit code manuals may be a condition of the contractual work statement. If verification is required, it shall be accomplished in accordance with a plan developed jointly by the procuring activity and the contractor. The procuring activity shall ensure that work unit code manual information and end item configuration information are completely compatible.

5. PREPARATION FOR DELIVERY.

5.1. The requirements of MIL-M-38784 and MIL-P-38790 are applicable.

6. NOTES.

6.1. Intended use. Refer to 1.2.

6.2. Ordering data. Procurement documents should specify:

a. Title, number and date of this specification.

b. Form in which data is to be supplied. (3.1)

c. Binder requirements. (3.1.2)

d. Individual missile series coverage. (3.2.1)

e. Sectionalization. (3.2.6)

f. Segregation. (3.2.6.2)

g. Size of preliminary manuals. (3.2.2)

h. Selected codes. (3.2.6.7)

i. Part number identification (3.3.1.4)

j. Peculiar training equipment application (3.4.5)

k. Verification. (4.3)

6.3. Identification of changes. The margins of this specification have not been marked to identify changes because the changes are fairly extensive. Bidders and contractors are cautioned to evaluate the requirements of this specification based on the entire contents.

Custodian:

Air Force - 16

Review Activities:

Air Force - 01, 10, 11, 70

Preparing Activity:

Air Force - 16

Project No:

TMSS F410

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

MISSILE

WORK UNIT CODE		TO 21M-AIM9B-06
65000	GUIDANCE SYSTEM, TARGET SEEKING (IR)	
65A00	GUIDANCE AND CONTROL SECTION	
65AJO	GUIDANCE AND CONTROL SUBASSEMBLY	
65AJA	Wiring Harness	
65AJB	Gas Grain Generator	
65AJC	Canards	
65AJD	Back Plate Wiring Harness	
65A99	NOC	65-001

AGE

WORK UNIT CODE		TO 21M-AIM9B-06
RA000	GUIDED MISSILE TEST SET, MK-342 MOD O	
RAA00	ELECTRONIC DRIVE UNIT	
RAAA0	CASE	
RAAAA	Latch	
RAAAB	Handle	
RAAAC	Relief Valve	
TAACO	POWER SUPPLY	
TAACA	Plate	
RAACB	Capacitor	
RAACC	Resistor	
RAACD	Diode	
RAACE	Transistor	
RAA99	NOC	
		RA-001

FIGURE 1 (SHEET 1 of 1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

PREFACE

1. GENERAL

The complete details on use of codes printed in this manual are prescribed in AFM 66-1 and TO 00-20-2 series technical orders.

2. USE OF CODES.

It is necessary to use codes for recording maintenance actions in order to convert this information into language for translation by accounting machines and computers. The maintenance forms are sent to Data Automation and the information recorded on them is punched into accounting machine cards. These cards are then mechanically processed periodically to produce reports for use in the management function, such as determining deficient materiel, facilities or procedures. It is very important that all codes entered in the maintenance forms be accurate and clearly written so the keypunch operators can read and enter them in the punched cards correctly. The reports produced are significant only if the codes are accurate.

a. Work Unit Code. This code consists of five alphabetic and/or numeric characters and is used to identify the system, subsystem, and component which was worked on. The symbol NOC is the abbreviation for Not Otherwise Coded. Code "99," NOC should only be used when an item does not have a specific work unit assigned. An AFTO Form 22 will be submitted when a "99" NOC code is used due to lack of a work unit code for a reparable item. Items identified by an asterisk between the work unit code and the code definition are time significant, serially controlled or time change items. Time Change Items are further identified by the abbreviation (TCI) following the work unit code definition. Items identified by an asterisk require special consideration when completing maintenance documents. Tires and wheels that are identified by an asterisk require the same type of recording as time change items. (Refer to TO 00-20-2-2.)

b. MCS Code. This code consists of five alphabetic or numeric characters and is used to identify direct labor manhours expended in other than direct labor; i.e., Alert Duty, Detail, Leave, Training, etc.

c. Type Maintenance Code. This code consists of one alphabetic character and identifies the type of maintenance being performed; i.e., scheduled or nonscheduled maintenance, etc.

d. Action Taken Code. This code consists of one alphabetic or numeric character and identifies what work was done; i.e., the action taken.

NOTE

Collectively the Work Unit Code and the Action Taken Code identify a "unit of work" as defined in AFM 66-1.

e. When Discovered Code. This code consists of one alphabetic or numeric character and is used to describe at what time a discrepancy was discovered.

f. How Malfunctioned Code. This code consists of three numeric characters and is used to describe the equipment malfunction.

3. SECURITY

When maintenance is being performed on classified equipment, the listing of a work unit code could possibly lead to a breach of security, such as betraying mission capability. Extreme caution should be exercised, and if any question exists, it will be resolved according to AFR 205-1 and other applicable directives.

FIGURE 2 (SHEET 1 of 2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

4. CHANGES TO CODES.

a. The codes in this manual are standard throughout the Air Force and will only be revised by official publication. Recommended changes to this manual regarding its use, format, procedures, or the Type Maintenance, Action Taken, When Discovered, How Malfunctioned, or Support General Codes will be submitted through command channels in accordance with TO 00-5-1.

b. Recommended changes to Work Unit Codes or equipment listings in this manual shall be submitted on AFTO Form 22, in accordance with TO 00-5-1 to the following address:

NOTE

The procuring activity shall specify the symbol of the office responsible for this manual and the applicable addresses.

NOTE

The following sentences shall be added to paragraph 2.a of the Preface for each code manual prepared in accordance with the sectionalized manual concept (Reference 3.2.6.1).

This manual has been prepared in two sections; Section I containing work unit codes for the weapon system. Section II contains work unit codes for AGE. The Type Maintenance, Action Taken, When Discovered, How Malfunctioned, and Support General Codes are contained in Section I of this manual.

Aerospace Ground Equipment (AGE) which is normally construed as end items of AGE in accordance with the definition in Section VI of TO 00-20-2 are identified with an "at" @ sign between the work unit code and its definition. This intended to be a guide for filling out maintenance source documents.

FIGURE 2 (SHEET 2 of 2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

AIR LAUNCHED MISSILES SUPPORT GENERAL CODES

NOTE: Support general codes are for recording production credit of repetitive tasks of a general nature, and shall not be used for recording malfunctions, repair, NRTS, or condemnation actions. The multitude of tasks which must be accomplished preclude listing them all in the support general task lists provided. This is not intended to restrict documentation of tasks. All support general work must be identified to the most appropriate code.

01000	GROUND HANDLING, SERVICING AND RELATED TASKS
	Servicing
	AGE Operation. Fire Guard, Assisting Ground Crews, etc
	Handling and Moving
	Depressurizing (unscheduled)
02000	Equipment Cleaning
	Cleaning and Washing
	Cleaning and Treating Equipment to Prevent Corrosion
	Frost, Snow and Ice Removal
	Decontamination
05000	Preservation, Depreservation and Storage of Equipment
06000	ARming, Disarming and Ground Safety
07000	Preparation and Maintenance of Records. (This code will be used to record direct labor expended in the preparation and/or maintenance of status and historical forms. This excludes initiation and completion of production documentation forms.)
09000	Shop Support General Code
	Fabricate (includes bending, cutting, forming, casting, molding, machining, soldering, assembly, local manufacture, etc) not done as part of a fix on a specific job.
	Painting (includes stenciling, lettering, installing decals, instrument range marking, etc)
	Engine and/or Power Pack Buildup or Teardown
	Wheel and Tire Buildup or Teardown
	Reclamation

FIGURE 3 (SHEET 1 of 6)

Source: https://assist.dla.mil -- Downloaded: 202610-21T15:27Z
Check the source to verify that this is the current version before use.

AIR LAUNCHED MISSILE
SUPPORT GENERAL CODES
for
LOOK PHASE OF SCHEDULED AND SPECIAL INSPECTIONS

"LOOK" PHASE OF SCHEDULED INSPECTIONS

CODE	DESCRIPTION
03100	Preflight/Daily Inspection
03110	Preflight
03120	Daily
03200	Postflight/Down Load Inspection
03210	Postflight
03220	Down Load
03300	Storage Inspection (Live)
03310	7 Day
03320	30 Day
03330	90 Day
03340	180 Day
03350	270 Day
03360	360 Day/Annual
03400	Storage Inspection (Dead)
03410	7 Day
03420	30 Day
03500	Periodic Inspection
03510	30 Day
03530	90 Day
03550	180 Day
03570	270 Day
03590	360 Day
03595	540 Day
03596	720 Day/2 Year

FIGURE 3 (SHEET 2 of 6)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

SPECIAL INSPECTIONS

CODE	DESCRIPTION
04100	Missile and Pylon
04110	Hard Landing
0411D	Oil Sampling for Spectrometric Analysis
04120	Calendar
04130	Modification
04140	Excessive G Loading
04141	Corrosion Control
04150	Transfer
04160	Non-Tactical Instrumentation
04170	Cold Weather
04180	Combined Systems Checkout
04270	Partial Combined Systems CHeckout
04280	Checks Requiring Special CHeckout Equipment
04310	Receiving Inspection
04311	Uncrating
04313	Stray Voltage Check
04314	Blown Fuze/Squib or Parameter Activated
04315	Purging
04316	Assembly
04317	Disassembly
04320	Hangfire
04321	Misfire
04322	30 Day on Aircraft
04323	10 Captive Flights
04324	Moisture
04325	Desiccant Container
04326	Dust Cover Plug
04327	DPM-14 Checkout
04330	Extreme Temperature
04340	Load/Unload

FIGURE 3 (SHEET 3 of 6)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

CODE	DESCRIPTION
04341	Whenever Sealing Sleeve is Removed
04342	Abort
04343	When Chassis #5 or Frequency Converter is Replaced
04344	Whenever Warhead Safe Arm Device or Fuze is Removed from Missile
04345	Whenever Rocket Motor is Removed from Missile
04346	Whenever Powerplant is Removed from Missile
04347	Whenever Access Covers are Removed from WSEM or Missile
04348	Incident/Accident
04349	When Hydraulic or Electrical Connections are Disconnected
04350	Whenever Branched Warhead Harness has been Installed for 24 Months
04351	Whenever Guidance Unit is Removed from Missile
04352	When the Warhead is to be Removed from the Missile
04353	When Warhead is Handled
04354	When Control Surfaces, Servopositioner, Wing or Cowling is Removed or Installed
04355	When Fuze Antenna is being Installed
04356	When Missile or Missile Components are Stored in Shipping/Storage Containers
04358	Evidence of Tampering
04359	Whenever Radioactive Atmosphere has been Encountered
04360	Wing/Rolleron and Fin Check
04361	When Guidance Unit is Exposed to Sunlight
04362	Whenever Forward Body Section Displays a Dent or Deterioration
04363	Holding Area
04364	Return to Holding Area
04365	Physical Shock
04366	Transfer from Container to MHU-12 Trainer
04370	After 20 WSEM Flights
04371	Whenever Engine Exhaust Gas Temperature Exceeds Limits
04372	First Run after Engine Change
04373	Whenever Emergency Engine Shutdown Occurs
04400 thru 04425	Droppage Inspections (These codes will be assigned as required starting with code 04400.)

FIGURE 3 (SHEET 4 of 6)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

CODE	DESCRIPTION
04610	Non-Destructive Testing (All Types)
04620	Analysis of Oil Samples
04630	Research and Development of New or Revised Non-Destructive Inspection Techniques.
04999	Special Inspections Not Otherwise Coded

AIR LAUNCHED MISSILE AGE
SUPPORT GENERAL CODES
For
LOOK PHASE OF SCHEDULED AND SPECIAL INSPECTIONS

"LOOK" PHASE OF SCHEDULED INSPECTIONS

CODE	DESCRIPTION
03A00	Preflight/Daily Inspection
03B00	Postflight
03D00	Storage
03E00	Periodic
03E20	14 Day
03E30	30 Day
03E40	60 Day
03E50	180 Day
03E60	170 Day
03600	Replacement

SPECIAL INSPECTIONS

CODE	DESCRIPTION
04A20	Calendar
04A30	Modification
04A41	Corrosion Control
04A50	Transfer
04B80	Checks Requiring Special Checkout Equipment
04C30	Dessicant Check
04E20	Moisture
04E30	Loading Inspection
04E40	Incident/Accident
04E80	Droppage

FIGURE 3 (SHEET 5 of 6)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

CODE	DESCRIPTION
0411D	Oil Sampling for Spectrometric Analysis
04113	Functional Check
04610	Non-Destructive Testing (All Types)
04630	Research and Development of New or Revised Non-Destructive Inspection Techniques
04999	Special Inspection Not Otherwise Coded

UNIQUE DATA CODES FOR MCS
(Maintenance Cost System)

DATA CODE	DESCRIPTION
ALTØØ	Alert Duty. All manhours expended while waiting for alert aerospace vehicles to takeoff or land, such as strategic, defense, tactical, standing or for crash alert, or for alert missiles when no work is being accomplished. Not to be used for standby, awaiting work assignments, lag, or other delays, or when direct productive effort is being expended.
CMPØØ	Compensatory Time for Overtime. All direct assigned manhours excused from normal duty as a result of previously expended overtime manhours.
DTLØØ	Detail, Squadron or Base Duties. Manhours expended by direct labor personnel (labor code 100) performing on-base duties such as CQ, policing, building maintenance, driver, dining hall, parade, commanders call, general military training, nontechnical training, etc.
LVEØØ	Leave. Manhours excused from duty, pass, or official leave, military, medical or sick leave.
TRNØØ	Maintenance Training. Manhours expended in OJT, formal and informal maintenance technical training.

NOTE: These codes are to be used to account for manhour expenditures of personnel with an assigned "direct" labor code when performing one of the above functions. Documentation guidance for AFTO Form 349 entries is contained in 00-20-2 Series Technical Orders.

FIGURE 3 (SHEET 6 of 6)

Source: https://assist.dla.mil -- Downloaded: 202640-21T15:27Z
Check the source to verify that this is the current version before use.

SYSTEM CODES (MISSILE)

MISSILE BASIC	
11	Airframe
13	Wing and Finfold
19	Pylon
PROPULSION	
23	Gas Turbine Engine
24	Liquid Rocket
25	Solid Rocket
MISSILE SUPPORT SYSTEMS	
31	Air Conditioning (including Atmospheric and Environmental Control)
32	Pressurization (When Separate from Air Conditioning)
33	Hydraulic Pneumatic Power Supply and Distribution
34	Electric Power Supply and Distribution
35	Electrical Distribution (Wiring Harness)
36	Component Cooling
37	Gas Driven Turbine (Mark 4 Power Plant)
39	Miscellaneous
ARAMENT AND EXPLOSIVE DEVICES	
41	Warhead
43	Destruct
44	Arming and Fuxing
45	Separation
47	Flares
FLIGHT CONTROLS	
52	Flight Controls
55	Auto Pilot
56	Flight Reference
GUIDANCE	
61	Command
62	Inertial
63	Integrated Guidance and Flight Controls

FIGURE 4 (SHEET 1 OF 3)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

GUIDANCE (continued)	
64	T.V. Guidance
65	Target Seeking (IR)
67	Tracking (Radar)
PROPELLANT	
73	Air Breathing Engine Fuel
75	Chamical
COMMUNICATIONS AND DATA HANDLING	
91	Telemetering
92	Bomb Damage Assessment
93	Instrumentation
95	Airborne Cooperational Equipment
96	Data Recording and Retrieval
97	Simulation
98	Reconnaissance

AGE SYSTEMS

AA THRU AZ	*
BA THRU BZ	Launcher
CA THRU CZ	Servicing Equipment
DA THRU DZ	Combined Servicing and Handling Equipment
EA THRU EZ	*
FA THRU FZ	Handling Equipment
HA THRU HZ	Environmental Control
JA THRU JZ	Electrical Generation and Distribution
KA THRU KZ	Propellant Loading and Storage
LA THRU LZ	*
MA THRU MZ	Guidance and Instrumentation
NA THRU MZ	Launch Control
PA THRU PZ	*
QA THRU QZ	Communications
RA THRU RZ	Missile Test Equipment
SA THRU SZ	Systems Test Equipment

FIGURE 4 (SHEET 2 OF 3)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

AGE SYSTEMS (continued)

TA THRU TZ	Training and Equipment
UA THRU UZ	Checkout Equipment
VA THRU VZ	*
WA THRU WM	Weapon System Evaluator Missile (WSEM)
WN THRU WZ	Mission Simulator
XA THRU XZ	*
YA THRU YZ	*
ZA THRU ZZ	Miscellaneous

NOTE

* These codes are unassigned. Their utilization will require prior approval of the procuring activity.

FIGURE 4 (SHEET 3 OF 3)

Source: https://assist.dla.mil -- Downloaded: 202610-21T15:27Z
Check the source to verify that this is the current version before use.

SECTION II

INTRODUCTION

This section of the manual contains work unit codes for Aerospace Ground Equipment (AGE) that was specifically designed for, or is peculiar to, the missile/missiles covered in Section I of this manual. This portion of the manual will be utilized by maintenance personnel to record maintenance tasks accomplished directly on the end items of AGE, or on AGE components, or equipment undergoing repair, servicing, testing, calibration or bench check in specialized shops. The Type Maintenance, Action Taken, When Discovered, How Malfunctioned, and Support General codes are contained in Section I of this manual. Common AGE work unit codes are contained in TO 00-25-06 series work unit code manuals.

FIGURE 5 (SHEET 1 OF 1)

Source: https://assist.dla.mil -- Downloaded: 202610-21T15:27Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval No. 22-R255

INSTRUCTIONS. The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost at a minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers, vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE: Manuals, Technical: Work Unit Code MTL-M-38783A(USAF) (For Air Launched Missiles)

NAME OF ORGANIZATION AND ADDRESS	CONTRACT NUMBER
	MATERIAL PROCURED UNDER A ☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO (If "Yes", in what way?)

4. REMARKS

SUBMITTED BY (Printed or typed name and address - Optional)	TELEPHONE NO
	DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE AIR FORCE

UNITED STATES AIR FORCE
OFFICIAL BUSINESS

AFLC (MMOMP)
WRIGHT-PATTERSON AFB, OH 45433

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.