MILITARY SPECIFICATION
MANUALS, TECHNICAL: WORK UNIT CODE (FOR TRAINING EQUIPMENT)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification prescribes the requirements for the preparation of work unit code manuals for training equipment, excluding mobile training sets (MTS) and resident training equipment (RTE), the requirements for which are included in the applicable weapon system specification.

1.2 Purpose. Under the USAF Maintenance Data Collection (MDC) System, each maintenance action performed on Air Force equipment must be fully and accurately documented. The volume of data collected requires the use of automatic data processing techniques. The use of automatic data processing (ADP) equipment requires coding of the data that is input to the MDC system. This permits the information to be "read" by the data processing machines. Standard codes have been developed for use in recording to identify the type of maintenance being performed, the action taken to correct a deficiency, when a deficiency was discovered, and the type of malfunction that occurred. Item identification codes, called work unit codes, are used to identify the specific assembly or part within an end item on which an action was performed. Work unit codes are also assigned for certain support actions that are general in nature and are referred to as Support General Codes. Each work unit code manual shall contain complete listings of all "Work Unit" (support general and equipment identification), "Type Maintenance", "Action Taken", "When Discovered", and "How Malfunctioned" codes applicable to the training equipment that is covered by the manual.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposal; form a part of this specification to the extent prescribed herein.

SPECIFICATIONS

Military

MIL-M-38784	Manuals, Technical, General Requirements for:
MIL-P-38790	Printing Production of Technical Manuals: General Requirements for:
MIL-B-83931	Binders, Flexible: Technical Manual

PUBLICATIONS

Air Force

AFR 205-1	Information Security Program
AFM 66-1	Maintenance Management
AFM 300-4 Volume XI	Data Elements and Codes
AFLCM 66-14	AF Technical Order System Data Operations

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

Technical Orders

00-5-1	Air Force Technical Order System
00-20-1	Preventive Maintenance Program, General Requirements and Procedures
00-20-2 Series	The Maintenance Data Collection System

(Current copies of documents required by contractors in connections with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Preparation. Manuals shall be supplied in the form (reproducible copy, negatives, punches cards, or printed copies) specified in the contract. MIL-P-38790 is applicable to negative and printed copies.

3.1.1 Mechanization. When punched cards or preparation of code manuals utilizing ADP procedures are specified, this shall be accomplished in accordance with the requirements of AFLCM 66-14.

3.1.2 Binders. When the contract specifies that printed copies of the manuals shall be delivered in binders, such binders shall be in accordance with MIL-B-83931.

3.1.3 End item of equipment. An end item of equipment shall be construed as that designation of training equipment to which all major assemblies, sub-assemblies, and components comprise and which may not be considered as part of a higher level of assembly.

3.1.4 Functional work unit code concept. Training equipment will be work unit coded as individual end items of equipment utilizing major assembly, sub-assembly, and component functional concept relationship. This functional concept shall permit the identification of components to the next higher level of assembly by work unit code assignment. For example, the AN/APQ-T10 radar trainer has a printed circuit board wich is part of a 150 volt power supply. The power supply, in turn is part of the No. 3 power distribution group. This power distribution unit, in conjunction with other major assemblies, comprises the NA/APQ-T10.

3.1.5 Level of detail for each end item. The work unit codes for each major assembly, sub-assembly, and component shall cover each reparable item as specified by the applicable source document. Work unit codes shall also be assigned to non-reparable items, if they are known or suspected to be vital to successful equipment operation. For example, certain pressure switches, timers and controllers may be non-reparable items which require "on-equipment" servicing or adjustment to maintain the reliability of the equipment end item. These items shall have a work unit code assigned in order to report critical "on-equipment" actions for reliability and maintainability evaluation purposes. Coding non-reparable components shall be done on an exception basis and not as a common practice.

3.1.6 Source data. Systems engineering data (i.e., engineering analysis data, equipment maintenance analysis data, and contract end item detail specifications) and graphic illustrations shall be used as source data for work unit code assignments. Maximum correlation between the component parts and sub-assemblies that make up a contract end item, and the assignment and grouping of work unit codes is desirable. When available concurrently with the code manual preparation, Illustrated Parts Breakdown Technical Manuals shall be used as source data in determining level of assembly.

3.1.7 Trainer application. Class II trainers, mobile training sets and resident training equipment shall not be coded in the training equipment work unit code manuals. Class III training equipment does not require detailed work unit codes; one code is presently assigned for recording production credit on Class III trainers. The criteria for establishing work unit codes for Class I training equipment is as

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

follows: there must be five or more trainers in the inventory, or five or more trainers programmed for the inventory within the next fiscal year from time of determination. They shall be of sufficient cost or complexity to warrant detailed data analysis. This determination will not be predicated on cost alone. Reference TO 00-20-1 which defines Class I, II and III trainers.

3.2 Manual construction.

3.2.1 Preliminary and formal manual size. The page size of preliminary manuals shall be determined by the procuring activity. Formal manuals shall be prepared in 8½ x 10 3/4 inch size in accordance with MIL-M-38784.

3.2.2 Style of type. Each line entry with a zero in the fifth character of the work unit code shall be in uppercase type. Each line entry with other than a zero in the fifth character of the work unit code shall be in lowercase type with the first letter of each word in upper case (reference Figure 1). In the event that automatic data processing equipment is utilized for preparation of reproducible copy, uppercase (machine printout) type will be utilized exclusively.

3.2.3 Columnar arrangement. All training equipment work unit code manuals shall be in double column format. There will be a spaced separation between work unit code line entries (excluding support general codes) in uppercase type from the preceding line. The code definition (nomenclature) for the third, fourth and fifth positions of the work unit code shall be indented two spaces to the right. For example, the code definition for BA100 shall be indented to the right of the code definition for BA000. In the event that automatic data processing equipment is utilized for preparation of reproducible copy, the spacing and indentures will be in accordance with the requirements of AFLCM 66-14, Chapter 8.

3.2.4 Page numbering. Pages containing work unit codes shall be numbered in the lower-outer corner of each page by the first two characters of the end item work unit code and consecutive page number. For example, the first page of the support general codes shall be 01-001, and the eleventh page of the AN/APQ-T10 radar trainer shall be GD-011.

NOTE: Support General Codes 01000, 02000, 05000, 06000, 07000, and 09000 shall be listed on one page utilizing page number 01-001. Codes 03XXX and 04XXX shall be listed on separate pages utilizing page numbers 03-appropriate page sequence number and 04-appropriate page sequence number, respectively.

The Preface, Type Maintenance Codes, Action Taken Codes, etc, will be identified by roman numeral and consecutive page number. In the event that automatic data processing equipment is utilized for preparation of reproducible copy, page numbering will be accomplished with the requirements of AFLCM 66-14, Chapter 8.

3.2.5 Contents. Work unit code manuals shall be comprised of the following, arranged in the order indicated:

Cover Page (formerly called Title Page)
List of Effective Pages
Table of Contents
Preface
Type Maintenance Codes
Action Taken Codes
When Discovered Codes
How Malfunctioned Codes (Alphabetic Sequence)
How Malfunctioned Codes (Numeric Sequence)
Work Unit Codes - Support General
Work Unit Codes - Equipment Identification

3.2.5.1 Cover page. A cover page shall be prepared in accordance with the requirements of MIL-M-38784. An effectivity date statement will be included on the cover page above the authority notice for each new code manual, similar to the following, "The effectivity date of this publication is 1 December 1975. Codes in

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

this publication shall not be used prior to that date." All subsequent work unit code manual changes, supplements or revisions that contain a change to a work unit code assignment or description shall contain an effectivity date statement on the cover page. The effectivity date will be established by the Air Force activity responsible for management of the work unit code manual and provided to the contractor. The effectivity date shall be a minimum of 30 days subsequent to the actual distribution date. All effectivity dates shall be the first day of the month.

3.2.5.2 List of effective pages. A list of effective pages shall be prepared in accordance with the requirements of MIL-M-38784.

3.2.5.3 Table of contents. The table of contents shall list the code manual contents in the order shown in 3.2.5, in conjunction with the appropriate page reference. The cover page and list of effective pages shall not be included in the Table of Contents. The work unit code listing shall be comprised of the first two characters of the support general and equipment end item, and the title or narrative description of each code listed.

Example:

TABLE OF CONTENTS

Code		Page No.
	Preface	II-001
	Type Maintenance Codes	III-001
	Action Taken Codes	IV-001
	When Discovered Codes	V-001
	How Malfunctioned Codes (Alphabetic Sequence)	VI-001
	How Malfunctioned Codes (Numeric Sequence)	VII-001
	Support General Codes	
01 Thru 09 (except 03 & 04)	Support General Codes	01-001
03	Look Phase of Scheduled Inspections	03-001
04	Look Phase of Special Inspections	04-001
	Equipment Identification Codes	
KD	AN/GPS-T4 Radar Signal Simulator	KD-001
KE	AN/GPN-T2A Radar Signal Simulator	KE-001
KM	AN/GLA-18 ECM Simulator	KM-001
etc		

3.2.5.4 Preface. The preface shall be as outlined in Figure 2.

3.2.5.5 Type Maintenance, Action Taken, When Discovered, and How Malfunctioned Codes. These codes are assigned and controlled through the medium of AFM 300-4, Volume XI. No changes or additions shall be made to these codes without prior approval in accordance with the requirements of AFM 300-4, Volume XI. The procuring activity is responsible for selection of codes from AFM 300-4, Volume XI, and for assuring proper entires in the work unit code manual in accordance with this specification. The selected codes will be appended to the contract or work statement at time of contract award.

3.2.5.5.1 Type Maintenance Code. This code consists of one alphabetic character and identifies the type of work performed, i.e., scheduled or unscheduled maintenance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

This list shall include only those codes that are applicable to the equipment in the work unit code manual. (Reference AFM 300-4, ADE MA-358-XI). The following notice shall be included in all work unit code manuals following the type maintenance codes for the basic type of equipment.

NOTE:

Refer to TO 00-25-06-2-1 for off-equipment shop type maintenance codes.

3.2.5.5.2 Action Taken Code. This code consists of one character and identifies what work was done, i.e., the action taken. Collectively the work unit code and the action taken code identify a "unit of work" as defined in TO 00-20-2. Example: Work Unit Code JDABC Cathode Ray Tube, Action Taken Code "R" (Remove and Replace). The complete list of action taken codes shall be included in the code manual. (Reference AFM 300-4, ADE AC-780-XI.)

3.2.5.5.3 When Discovered Code. This code consists of one alphabetic character and identifies when a defect was discovered, i.e., during equipment operation, scheduled calibration, etc. Only those When Discovered Codes that apply to training equipment shall be included in the code manual. (Reference AFM 300-4, ADE WH-180-XI.)

3.2.5.5.4 How Malfunctioned Code. This code consists of three numeric characters and is used to identify how the equipment malfunctioned, i.e., was it shorted, cracked, corroded, etc. The How Malfunctioned Codes shall be listed in both alphabetic and numeric sequence, and shall contain only those codes that are applicable to the equipment covered by the manual. (Reference AFM 300-4, HO-902-XI.)

3.2.5.6 Work Unit Code - Support General. A listing of Support General Codes for training equipment is included in Figure 3. Any changes or additions to support general code assignments reflected in Figure 3 must be approved, in writing, by HQ AFLC/MMOM. Support General Codes that do not apply to the equipment listed in the code manual shall be omitted. Support General Codes 03000 and 04000 shall not be included in the code manuals adjacent to the titles for look phase of scheduled or special inspections.

3.2.5.7 Work Unit Code - Equipment Identification. This is a five position code which identifies the end item, major assembly, sub-assembly, or component that required maintenance. The first two positions of the work unit codes will be assigned and controlled by the procuring activity to identify the end item of training equipment. The third and fourth characters include major assemblies and sub-assemblies, and identify first and second levels of assembly. The fifth position of the work unit code includes reparable/recoverable components and identifies the lowest level of assembly below the end item.

3.3. Work unit code application and construction.

3.3.1 Application of work unit codes. The primary purpose of work unit codes is to identify the item on which work was accomplished, and the relationship of this item within an end item, a major assembly, sub-assembly, component, etc. Work unit codes shall not be assigned to locations or general terms. For instance, station numbers, geographic locations and terms such as mechanical components or miscellaneous equipment may be used as titles to aid in locating work unit codes within the code manual, but these titles shall not have work unit codes assigned. Work unit codes should not be assigned to common hardware or softgoods, such as nuts, bolts, washers, clamps, seals, packing and O-rings. Work on these type items is normally reported against the coded assembly to which the item is attached.

3.3.1.1 Reserving codes for future use. It is essential that expansion capability be designed into each code manual in the third, fourth, and fifth positions of the work unit codes to assure that new codes can be assigned for future modifications or additions of equipment. If adequate expansion capability was designed into the original codes, new equipment can be added without disturbing the originial codes. Minimum code changes are essential to prevent loss of identity for previously complied maintenance data.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

3.3.1.2 Re-use of codes. When existing work unit codes are deleted from a manual, they normally will not be reassigned for a minimum of ninety days following their deletion, or without prior approval of the procuring activity. If there is no other code or code sequence that can be used, work unit codes may be reassigned by the procuring activity without waiting ninety days.

3.3.1.3 End item code page entries. When a change occurs in the first or second position of the work unit code (end item code), the next entry shall begin on a new right hand page. For example: Following completion of code assignments for KB000, KC000 assignments will be made on a new right hand page. A change from code GZ000 to HA000 will also require entry on a new right hand page. Exception: Support General Codes 01000, 02000, 05000, 06000, 07000, and 09000 will be listed in numerical sequence on one page under the heading of Support General Codes.

3.3.1.4 Nomenclature. The end item and each item listed in the work unit code breakout shall be fully identified. If official military type nomenclature has been assigned, it shall be used for identification. Part numbers shall not be included except as identified in 3.3.2.7. If manufacturer's identification data must be used, it shall include as a minimum, the model or type number, a descriptive noun, and the manufacturer's name. Approved abbreviations may be used when necessary.

3.3.2 Work unit code construction. (Ref to 3.2.5.7 for levels of assembly and Figure 1 for example of work unit code assignments)

3.3.2.1 Alphabetic and numeric characters. Uppercase letters A through Z (Excluding I and O) and numbers 0 through 9 shall be utilized for work unit code assignments as specified in subsequent paragraphs. The letters I and O shall not be assigned in any work unit code in order to prevent confusion with the numbers one and zero.

3.3.2.2 End item code construction. The first two characters of the work unit code are alphabetic and identify the end item of equipment. These characters are assigned and controlled by the procuring activity. No deviations are authorized without prior approval by Ogden Air Logistics Center/MMST.

3.3.2.3 First level of assembly. Alphabetic and numeric characters shall be used as the third character of the work unit code to designate the first level of assembly below the end item. Thrity-three separate levels may be identified in this manner. For example:

AA000 - END ITEM

AAA00 - FIRST LEVEL OF ASSEMBLY
thru
AAZ00

then
AA100 - FIRST LEVEL OF ASSEMBLY
thru
AA900

3.3.2.4 Second level of assembly. Alphabetic and numeric characters shall be used as the forth character of the work unit code to designate second level of assembly below the end item. Thirty-three separate levels may be identified in this manner. For example:

AA000 - END ITEM

AAA00 - FIRST LEVEL OF ASSEMBLY

AAAA0 - SECOND LEVEL OF ASSEMBLY
thru
AAAZ0

then
AAA10 - SECOND LEVEL OF ASSEMBLY
thru
AAA90

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

3.3.2.5 Third level of assembly. Alphabetic and numeric characters shall be used as the fifth character of the work unit code to designate the third or lowest level of assembly below the end item. Thirty-two levels may be identified in this manner. The numbers "99" NOC are used in the fourth and fifth positions to indicate Not Otherwise Coded (NOC). For example:

AAOOO - END ITEM

AAAOO - FIRST LEVEL OF ASSEMBLY

AAAAO - SECOND LEVEL OF ASSEMBLY
AAAAA - Third or Lowest Level of Assembly
thru
AAAAZ
then
AAAA1 - Third or Lowest Level of Assembly
thru
AAAA8

AAAA9 - NOC (First level of assembly)

NOTE: Numerical characters may be assigned initially in the third, fourth, and fifth positions of the work unit codes when there is positive assurance that the numerical coding capacity will not be exceeded during the initial code assignment, or by future equipment additions or modifications.

3.3.2.6 Use of "99" - Not Otherwise Coded". The number 9 is used in the fourth and fifth positions of the work unit code, followed by the abbreviation "NOC", which stands for "Not Otherwise Coded". This code is used to provide a work unit code for reparable or recoverable items that do not have specific codes assigned. NOC codes will relate to the first level of assembly (the third character of the work unit code). When continuations are used as outlined in 3.3.2.9, Code "99 NOC" shall only appear in the last group of codes. There shall be a spaced separation between the last component of the first level of assembly and the NOC code for that first level of assembly to provide easy recognition of the NOC code. NOTE: The numbers 99 shall not be used in the fourth and fifth positions of the work unit code to identify any specific type of equipment.

3.3.2.7 Multiple items serving a single end item. Identical components within an end item, performing peculiar functions, shall have individual work unit code assignments for each peculiar function/application. For example, a pressurization control unit (PCU) in an end item may contain four identical controllers but each controller has a different usage (pressure setting) in the PCU. In this case, each controller will have a unique work unit code assigned and each will be further identified by its part number in the nomenclature. Items installed in multiples within an end item which perform within the same function/application parameters, except for location, will normally have a single code assigned. For instance, only one code should be assigned for items having left hand and right hand application even though they have part numbers. The procuring activity may grant waivers to this requirement for items that have high failure rates or warrant detailed reporting for analysis purposes. This shall be doen on an exception basis only and shall not be a common practice.

3.3.2.8 Items serving multiple assemblies. When a single component functionally services two or more assemblies/or lower levels of assembly, only one work unit code shall appear in only one of the assembly listings. However, the item shall be listed (by identical nomenclature only) in the remaining applicable assemblies with a reference to the previously assigned work unit code, e.g., "Hydraulic Pressure Servo (reference AXHFS)". The work unit code column for such items will be left blank.

3.3.2.9 Coding capability. The construction of work unit codes provides a capability to designate thirty-three first level assemblies, thirty-three second level assemblies, and thirty-two third or lowest level assemblies. If equipment breakout exceeds these capabilities, it will be necessary to continue the listing with the next available code. For example:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

APNYO GROUND APPROACH RECORDER
APNY8 Motor

GROUND APPROACH RECORDER (CONT)
APNZA Gear Assembly

APN99 NOC

Note the change in the fourth character of the work unit code.

3.4 Code arrangement and special procedures.

3.4.1 Work unit code column heading. The first line entry at the top of each work unit code column on the left hand side of each page shall be the type of equipment to which the work unit codes apply. For example:

AJOOO A/F 37A-T2A FLIGHT SIMULATOR, C-130B

* * * * * *

KKOOO AIR TRAFFIC CONTROL TRAINING SET, AN/GPN-T3

3.4.2 New page entries. When work unit codes for an end item are carried over to a new page, the first work unit code entry on the new page shall be (1) the end item code and title; (2) following that line entry shall be the work unit code and title of the second level of assembly (fourth character of the work unit code) followed by the abbreviation for continued in parentheses. Code assignments for the third level of assembly (fifth character of the work unit code) can then resume. Example, assuming that the last code of the preceding page is APNDQ Oil Temp Indicator:

APOOO C-141A SIMULATOR, A/F 37A-T24A (End Item)

APNDO FLIGHT ENGINEER PANEL (CONT) (Second level assy)
APNDR Fuel Pressure Indicator (Third level assy)

3.4.3 Time change article identification. An asterisk shall be placed between the work unit code and its definition (nomenclature) for each time change or time significant item, which shall be identified and provided by the procuring activity. The abbreviation TCI shall be entered in parenthesis following the definition (nomenclature) for time change items to differentiate between these items and time significant items. (Reference paragraph 2.a of Figure 2).

4. QUALITY ASSURANCE PROVISIONS.

4.1 General. The requirements of MIL-M-38784 and MIL-P-38790 are applicable.

4.2 Validation. The contractor shall certify that information provided in the manual accurately and completely reflects the composition of the training item is its latest Air Force approved configuration and as set forth in the source documentation used to develop the manual. Completed validation and certification shall be a condition of Air Force acceptance for each manual prepared under this specification.

4.3 Verification. At the option of the procuring activity, a requirement for verification of work unit code manuals may be a condition of the contractual work statement. If verification is required, it shall be accomplished in accordance with a plan developed jointly by the procuring activity and the contractor. The procuring activity shall ensure that work unit code manual information and end item configuration information are completely compatible.

5. PREPARATION FOR DELIVERY.

5.1 The requirements of MIL-M-38784 and MIL-P-38790 are applicable.

6. NOTES.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

6.1 Intended use. Refer to 1.2.

6.2 Ordering data. Procurement documents should specify:

a. Title, number, and date of this specification.

b. Form in which data is to be supplied. (3.1)

c. Mechanization requirements. (3.1.2)

d. Binder requirements. (3.1.2)

e. Trainer application. (3.1.7)

f. Size of preliminary manuals. (3.2.1)

g. Selected codes. (3.2.5.5 and 3.2.5.6)

h. End item code assignment. (3.3.2.2)

i. Verification requirements. (4.3)

Custodian:

Air Force 16

Reviewer:

Air Force 01, 11, 70

Preparing Activity:

Air Force 16

Project No. TMSS-F387

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

WORK UNIT CODE	
APOOO	C-141A SIMULATOR, A/F 37A-T24A
APAOO	OPERATOR'S CONSOLE
APABO	RECORDER
APABA	Head Assy
APABB	Capstan Assy
APABC	Clutch Assy
APABD	Speed Change Assy
APABE	Drive Motor Assy
APABF	Drive Motor Fan
APACO	ICE SYSTEM
APACA	Instructor's Ice Control
APACB	Motor Amplifier
APACC	Summing Amplifier
APACD	Input Assembly
APA99	NOC

AP-001

FIGURE 1 (SHEET 1 of 1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

PREFACE

1. GENERAL.

The complete details on use of codes printed in this manual are prescribed in AFM 66-1 and TO 00-20-2 series.

2. USE OF CODES.

It is necessary to use codes for recording maintenance actions in order to convert this information into language for translation by accounting machines and computers. The maintenance forms are sent to Data Automation and the information recorded on them is punched into accounting machine cards. These cards are then mechanically processed periodically to produce reports for use in the management function, such as determining deficient materiel, facilities, or procedures. It is very important that all codes entered in the maintenance forms be accurate and clearly written so the keypunch operators can read and enter them in the punched cards correctly. The reports produced are significant only if the codes are accurate.

a. Work Unit Code. This code consists of five alphabetic and/or numeric characters and is used to identify the end item, major assembly, sub-assembly, and component which was worked on. The symbol NOC is the abbreviation for Not Otherwise Coded. Code "99", NOC should only be used when an item does not have a specific work unit code assigned. An AFTO Form 22 (Technical Order System Publication Improvement Report and Reply) will be submitted when a "99" NOC code is used due to lack of a work unit code for reparable item. Items identified by an asterisk between the work unit code and the code definition are time significatn or time change items. Time change items are further identified by the abbreviation (TCI) following the work unit code definition. Items identified by an asterisk require special consideration when completing maintenance documents. (Refer to TO 00-20-2-7 for trainers and simulatros; or TO 00-20-2-8 for ground CEM training equipment except simulators.)

b. Type Maintenance Code. This code consists of one alphabetic character and identifies the type of maintenance being performed, i.e., scheduled or unscheduled maintenance, etc.

c. Action Taken Code. This code consists of one alphabetic or numeric character and identifies what work was done, i.e., the action taken.

d. When Discovered Code. This code consists of one alphabetic character and is used to describe at what time a discrepancy or maintenance requirement was discovered.

e. How Malfunctioned Code. This code consists of three numeric characters and is used to describe the equipment malfunction.

3. SECURITY

When maintenance is being performed on classified equipment, the listing of a work unit code or nomenclature could possibly lead to a breach of security, such as betraying mission capability. Extreme caution should be exercised, and if any questions exists, they will be resolved according to AFR 205-1 and other applicable directives.

FIGURE 2 (SHEET 1 OF 2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

4. SCOPE.

a. Due to the number of training devices of various types, separate manuals in the TO 43-1-06 series are prepared by groups as follows:

TO 43-1-06-2	Flight Simulators, Cockpit Procedure Trainers, Instrument Flying Trainers, and Navigation Trainers.
TO 43-1-06-3	Radio and Radar Training Equipment (Including fire control, bombing-navigation, and electronic warfare).
TO 43-1-06-4	Missile Training Equipment.
TO 43-1-06-5	Armament Trainers, Physiological Trainers, Miscellaneous Trainers and Classroom Aids.

b. Training equipment which is installed on aircraft (target towing equipment, radar scorers) or connected into the missile system, and maintained by the using activity will be coded in the applicable weapon system work unit code manual.

c. Obsolescent and limited quantity training equipment is listed in a separate section in the back of each manual under Miscellaneous Trainer Codes. These codes will be used to code all training equipment not otherwise coded.

d. The following general equipment identification codes are common to all training equipment and shall be included as the last section in each training equipment work unit code manual.

Class I and III Training Equipment

ZYA00	Class I Training Equipment Not Otherwise Coded.
ZY200	Class III Training Equipment Not Otherwise Coded.

The work unit code ZY000 is not an authorized code and shall not be used for documenting maintenance performed on Class I or III training equipment.

5. CHANGES TO CODES.

a. The codes in this manual are standard throughout the Air Force and will be revised only by an offical published change. Recommended changes to this manual regarding its use, format, procedures, or the Type Maintenance, Action Taken, When Discovered, How Malfunctioned, or Support General Codes will be submitted through command channels in accordance with TO 00-5-1.

b. Recommended changes to Work Unit Codes or equipment listings in this manual shall be submitted on an AFTO Form 22, in accordance with TO 00-5-1, to the following address:

NOTE

The procuring activity shall specify the symbol of the office responsible for this manual and the applicable addresses.

FIGURE 2 (SHEET 2 OF 2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

SUPPORT GENERAL CODES
(Except "Look" Phase of Scheduled and Special Inspections)

NOTE: Support General Codes are for recording direct labor only, and shall not be used for recording indirect work on functions such as shop cleaning, training, grass mowing and reclamation.

01000	Ground Handling, Servicing and Related Tasks. Includes installation or removal of training maps, charts, films, batteries; oxygen system servicing; disassembly and assembly required for movement of equipment, etc.
02000	Washing, Cleaning, Corrosion Prevention Treatment and Decontamination.
05000	Preservation and Depreservation of Equipment. Includes work incident to Training equipment storage and removal from storage.
06000	Arming, Disarming and Ground Safety. Includes seat and explosive device arming/disarming; battery connect/ disconnect; charging of fire extinguishers, etc.
07000	Preparation and Maintenance of Records and Publications. Includes direct labor expended by maintenance personnel in the preparation and/or maintenance of records.
09000	Shop Support Functions, Fabrication, Painting, Equipment Build-up or Tear-down, Test Stand Operation, In-shop Item Inspection (excluding bench check), and Related Shop Tasks not Involving Repairs, NRTS or Condemnation Actions.

FIGURE 3 (SHEET 1 OF 3)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

SUPPORT GENERAL CODES

"LOOK" PHASE OF SCHEDULED INSPECTIONS (Includes all work such as greasing, etc, included on the work cards, minor fixes, such as tightening clamps and connections, and unbuttoning and buttoning up the trainer.)

CODE	DESCRIPTION
03100	Daily Inspection.
03200	Periodic Inspection.

FIGURE 3 (SHEET 2 OF 3)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

SUPPORT GENERAL CODES

"LOOK" PHASE OF SPECIAL INSPECTIONS (Includes all work, such as greasing, etc, included on the work cards; minor fixes, such as tightening clamps and connections, and unbuttoning and buttoning the trainer.)

CODE	DESCRIPTION
04100	Special Modification Inspection
04199	Special Inspections Not Otherwise Coded
04200	Unscheduled Periodic Inspection
04610	Non-Destructive Testing (All Types)
04630	Research and Development of New or Revised Non-Destructive Inspection Techniques

☆U.S. GOVERNMENT PRINTING OFFICE: 1975-603-128/1118

FIGURE 3 (SHEET 3 OF 3)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

FOLD

Department of The Air Force
POSTAGE AND FEES PAID

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

AFLC (MMOMP)
Wright-Patterson Air Force Base
Ohio 45433

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE: MIL-M-38786A(USAF) Manuals, Technical: Work Unit Code (For Training Equipment)

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:27Z
Check the source to verify that this is the current version before use.