MIL-M-38788A(USAF)
15 April 1975

Supersedes
MIL-M-38788 (USAF)
29 March 1968

MILITARY SPECIFICATION

MANUALS, TECHNICAL: WORK UNIT CODES (FOR COMMON AND PECULIAR AEROSPACE GROUND EQUIPMENT)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE.

1.1. Scope. This specification prescribes the requirements for the preparation of work unit code manuals for all Aerospace Ground Equipment (AGE) both common and peculiar, except Precision Measurement Equipment.

1.2. Purpose. Under the USAF Maintenance Data Collection (MDC) System, each maintenance action performed on Air Force equipment must be fully and accurately documented. The volume of data collected requires the use of automatic data processing (ADP) techniques. The use of automatic data processing equipment requires coding of the data that is input to the MDC system. This permits the information to be "read" by the data processing machines. Standard codes have been developed for use in recording to identify the type of maintenance being performed, the action taken to correct a deficiency, when a deficiency was discovered, and the type of malfunction that occurred. Equipment identification codes, called Work Unit Codes, are used to identify the specific assembly or part within an end item on which action was performed. Work unit codes are also assigned for certain support actions that are general in nature and are referred to as Support General Codes. Each work unit code manual shall contain complete listings of all "Work Unit" (support general and equipment identification), "Unique Data Codes for MCS (Maintenance Cost System)", "Type Maintenance", "Action Taken", "When Discovered", and "How Malfunctioned" codes applicable to Aerospace Ground Equipment (AGE) that is covered by the manual.

2. APPLICABLE DOCUMENTS.

2.1. The following documents of the issue in effect on date of invitation for bids, or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-M-38784	Manuals, Technical, General Requirements for:
MIL-P-38790	Printing Production of Technical Manuals: General Requirements for:
MIL-B-83931	Binders, Flexible: Technical Manual

PUBLICATIONS

AFR 205-1	Information Security Program
AFM 66-1	Maintenance Management
AFM 300-5, Vol XI	Data Elements and Codes
AFLCM 66-14	AF Technical Order System Data Operations

TECHNICAL ORDERS

00-5-1	Air Force Technical Order System

Source: https://assist.dla.mil -- Downloaded: 202610-21T15:28Z
Check the source to verify that this is the current version before use.

00-20-2 series	The Maintenance Data Collection System
00-20-1	Preventive Maintenance Program, General Requirements and Procedures

(Current copies of documents required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1. Preparation. Manuals shall be [illegible] negatives, punched cards, or printed copies) specified in the contract. MIL-P-38790 is applicable to negative and printed copies.

3.1.1. Mechanization. When punched cards or preparation of code manuals utilizing ADP procedures are specified, this shall be accomplished in accordance with the requirements of AFLCM 66-14, Chapter 8.

3.1.2. Binders. When the contract specifies that printed copies of the manuals shall be delivered in binders, such binders shall be in accordance with MIL-B-83931.

3.1.3. Level of Detail. The work unit codes shall cover each reparable item as specified by the applicable source document. Work unit codes shall also be assigned to nonreparable components if they are known or suspected to be vital to successful system operation. These items shall have a work unit code assigned in order to report those critical "on-equipment" actions for reliability and maintainability evaluation purposes. Coding nonreparable components shall be done on an exception basis and shall not be a common practice.

3.1.4. Source Data. Systems engineering data (i.e., engineering analysis data, equipment maintenance analysis data, and contract end item detail specifications) shall be used as source data for work unit code assignment. Maximum correlation between the component content of a contract end item and the assignment and grouping of work unit codes is desirable. When available concurrently with the code manual preparation, Illustrated Parts Breakdown Technical Manuals shall be used as source data in determining level of assembly.

3.2. Manual Construction.

3.2.1. Preliminary and formal manual size. The page size of preliminary manuals shall be determined by the procuring activity. Formal manuals shall be prepared in 8-1/4 by 10-3/4 in size in accordance with MIL-M-38784.

3.2.2. Style of type. Each line entry with a zero in the fifth character of the work unit code shall be in uppercase type. Each line entry with other than a zero in the fifth character of the work unit code shall be in lowercase type with the first letter of each word in uppercase. In the event that automatic data processing equipment is utilized for preparation of reproducible copy, uppercase (machine printout) type will be utilized exclusively.

3.2.3. Columnar arrangement. Work unit code manuals prepared under this military specification shall be in double column format. There will be a double spaced separation between work unit code line entries (excluding support general codes) in uppercase type from the preceding line. The code definition (nomenclature) for the third, fourth and fifth positions of the work unit code shall be indented two spaces to the right. For example, the code definition for BAAA0 shall be indented to the right of the code definition for BAA00. In the event that automatic data processing equipment is utilized for preparation of reproducible copy, the spacing and indentures will be in accordance with the requirements of AFLCM 66-14, Chapter 8.

3.2.4. Page numbering. Pages containing work unit codes shall be numbered in the lower-outer corner of each page by the work unit code system number and consecutive page number. For example: The first page of the support general codes shall be 01-001, and the ninth page of the computer test station system codes shall be FA-009. Note: Support General Codes 01000, 02000, 05000, 06000, 07000 and 09000 will be listed on page 01-001 through 01- appropriate page number sequence. Codes 03XXX and 04XXX shall be listed on separate pages utilizing page numbers 03-appropriate page

Source: https://assist.dla.mil -- Downloaded: 202640-21T15:28Z
Check the source to verify that this is the currenversion before use.

sequence number and 04-appropriate page sequence number, respectively. The Preface, Type Maintenance Codes, Action Taken Codes, etc, will be identified by roman numeral and consecutive page number. For MCS page numbering see paragraph 3.2.5.6.1. In the event that automatic data processing equipment is utilized for preparation of reproducible copy, page numbering will be accomplished in accordance with the requirements of AFLCM 66-14, Chapter 8.

3.2.5. Contents. The contents of the work unit code manuals shall be comprised of the following, arranged in the order indicated:

Title Page

List of Effective Pages

Table of Contents

Preface

Type Maintenance Codes

Action Taken Codes

When Discovered Codes

How Malfunctioned Codes (Alphabetic Sequence)

How Malfunctioned Codes (Numeric Sequence)

Work Unit Codes - Support General

Unique Data Codes for MCS (Maintenance Cost System)

Work Unit Codes - Equipment Identification

3.2.5.1. Title Page. A title page shall be prepared in accordance with the requirements of MIL-M-38784. An effectivity date statement will be included on the title page above the authority notice for each new code manual, similar to the following: "The effectivity date of this publication is 1 December 1974. Codes in this publication shall not be used prior to that date." All subsequent work unit code manual changes, supplements or revisions that contain a change to a work unit code from one nomenclature to another shall contain an effectivity date statement on the title page. The effectivity date will be established by the Air Force activity responsible for the management of the work unit code manual and provided to the contractor. The effectivity date shall be a minimum of 30 days subsequent to the actual distribution date. All effectivity dates shall be the first day of the month.

3.2.5.2. List of effective pages. A list of effective pages shall be prepared in accordance with the requirementsof MIL-M-38784.

3.2.5.3. Table of contents. The table of contents shall list the code manual contents in the order shown in 3.2.5. together with the appropriate page reference. The title page and the list of effective pages shall not be included in the Table of Contents. The work unit code listing shall be comprised of the first two characters of the support general or equipment identification codes, and the title or narrative description of each code listed.

3.2.5.4. Preface. The preface shall be as outlined in figure 2.

3.2.5.5. Type Maintenance, Action Taken, When Discovered, and How Malfunctioned Codes. These codes are assigned and controlled through the medium of AFM 300-4, Volume XI. No changes or additions shall be made to these codes without prior approval in accordance with the requirements of AFM 300-4, Volume XI, and assuring proper entries in the work unit code manual in accordance with this specification. The selected codes will be appended to the contract or work statement at time of contract award.

Source: https://assist.dla.mil -- Downloaded: 202610-21T15:28Z
Check the source to verify that this is the current version before use.

3.2.5.5.1. Type Maintenance Code. This code consists of one alphabetic character and identifies the type of work performed, i.e., scheduled or unscheduled maintenance. This list shall include only those codes that are applicable to the equipment in the work unit code manual. (Reference AFM 300-4, Volume XI, ADE MA-358.) The following note shall be included in all work unit code manuals following the type maintenance codes for the basic type of equipment.

NOTE:

Refer to TO 00-25-06-2-1 for off-equipment shop type maintenance codes.

3.2.5.5.2. Action Taken Code. This code consists of an alphabetic or numeric character and identifies what work was done, i.e., the action taken. Collectively, the work unit code and the action taken code identify a "unit of work" as defined in TO 00-20-2. Example: Work Unit Code ABA22 Converter, Action Taken Code R - Remove and Replace. The complete list of action taken codes shall be included in the code manual. (Reference AFM 300-4, Volume XI, ADE AC-780.)

3.2.5.5.3. When Discovered Code. This code consists of an alphabetic or numeric character and identifies when a defect was discovered, i.e., during a daily inspection, scheduled inspection, etc. Only that portion of the When Discovered Code definition that applies to AGE shall be included in the code manual. (Reference AFM 300-4, Volume XI, ADE WH-180.)

3.2.5.5.4. How Malfunctioned Code. This code consists of three numeric characters and is used to identify how the equipment malfunctioned, i.e., was it shorted, cracked, corroded, etc. The How Malfunctioned Codes shall be listed in both alphabetic and numeric sequence, and shall contain only those codes that are applicable to the code manual. (Reference AFM 300-4, Volume XI, ADE HO-920.)

3.2.5.6. Work Unit Code - Support General. A listing of Support General Codes for AGE is included in Figure 1. Support General Codes that do not apply to the equipment listed in the code manual shall be omitted. Support General Codes 03000 and 04000 shall not be included in the code manuals adjacent to the titles for look phase of scheduled or special inspections.

3.2.5.6.1. Unique Data Codes for MCS. A list of Unique Data Codes for MCS is included in Figure 1. These codes shall be included in the work unit code manual following the last page of support general codes. They will be printed on one page and numbered 05-001.

3.2.5.7. Work Unit Code - Equipment Identification. This is a five-character code which identifies the end item, subsystem and component that required maintenance. The first three characters of the work unit code include the end item, and identify the first level of assembly. The fourth character includes the subsystem, ancillary system or a major assembly (as applicable) and the second level of assembly. The fifth character of the work unit code includes reparable components and identifies the lowest level of assembly below the end item.

NOTE:

For aircraft peculiar AGE reference 3.3.3.4.1.

3.3 Work Unit Code application and construction.

3.3.1. Application of work unit codes. The primary purpose of work unit codes is to identify the item on which work was accomplished, and the relationship of this item within an end item. Work unit codes shall not be assigned to locations or general terms. For instance, geographic locations and terms such as mechanical components or miscellaneous equipment may be used as titles to aid in locating work unit codes within the code manual, but these titles shall not have work unit codes assigned. Work unit codes should not be assigned to common hardware or soft-goods, such as nuts, bolts, washers, clamps, seals, packing and O-rings. Work on these type items is normally reported against the coded assembly to which they attach.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:28Z
Check the source to verify that this is the current version before use.

3.3.1.1. Reserving codes for future use. It is essential that expansion capability be designed into each code manual in the fourth and fifth positions of the work unit codes to assure that new codes can be assigned for future modifications or additions of equipment. Minimum code changes are essential to prevent loss of previously compiled maintenance data.

3.3.1.2. Reuse of codes. When existing work unit codes are deleted from a manual, they normally will not be reassigned for a minimum of ninety days following their deletion, nor without prior approval of the procuring activity. If there is no other code or code sequence that can be used, work unit codes may be reassigned by the procuring activity without waiting ninety days.

3.3.1.3. Page entries. When a change occurs in the first or second position of the work unit code the next entry shall begin on a new right hand page. For example: following completion of code assignments for BA000, code BB000 assignments will be made on a new right hand page. A change from BZ000 to CA000 will also require entry on a new right hand page. Exception: Support General Codes as outlined in 3.2.4.

3.3.1.4. Nomenclature. Each work unit code in the equipment identification listing shall reflect adequate information to properly identify all levels of assembly, and shall include the basic noun for each individual item that is coded. If official military type nomenclature has been assigned, it shall be used for identification. Part numbers are to be utilized solely for explosive items and are not to identify nonexplosive items except as noted by 3.3.3.5. Approved abbreviations may be used when necessary.

3.3.2. Alphabetic and numeric characters. Uppercase letters A through Z (excluding I and O) and numerics Ø through 9 shall be utilized for work unit code assignments as specified in subsequent paragraphs. The letters I and O shall not be utilized in any work unit code in order to prevent confusion with numerics one and zero.

3.3.3. Work unit code construction. (Refer to 3.2.5.7. for levels of assembly.)

3.3.3.1. End item code construction. The first three characters of the work unit code identify the end item of equipment. These characters are preselected and are controlled by the procuring activity.

3.3.3.2. First level of assembly. Alphabetic and numeric characters shall be used as the third character of the work unit code to designate the first level of assembly which is the end item. Thirty-three separate levels may be identified in this manner. For example:

```
CEA00   FIRST LEVEL OF ASSEMBLY
 thru
CEZ00
 then
CE100   FIRST LEVEL OF ASSEMBLY
 thru
CE900
```

3.3.3.3. Second level of assembly. Alphabetic and numeric characters shall be used as the fourth character of the work unit code to designate the second level of assembly of the end item. Thirty-three separate levels may be identified in this manner. For example:

```
CEA00   FIRST LEVEL OF ASSEMBLY

CEAA0     SECOND LEVEL OF ASSEMBLY
 thru
CEAZ0
 then
CEA10     SECOND LEVEL OF ASSEMBLY
 thru
CEA90
```


Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:28Z
Check the source to verify that this is the current version before use.

3.3.3.4. Third level of assembly. Alphabetic and numeric characters shall be used as the fifth character of the work unit code to designate third or lowest level of assembly below the end item. Thirty-two levels may be identified in this manner. The numbers "99" are used in the fourth and fifth positions to indicate Not Otherwise Coded (NOC). For example:

```
CEA00   FIRST LEVEL OF ASSEMBLY

CEAA0      SECOND LEVEL OF ASSEMBLY

CEAAA         Third or Lowest Level of Assembly
 thru
CEAAZ
 then
CEAA1         Third or Lowest Level of Assembly
 thru
CEAA8

CEA99   NOC (First level of assembly)
```

NOTE:

Numerics may be assigned initially in the third, fourth and fifth positions of the work unit codes when there is a positive assurance that the numeric coding capacity will not be exceeded during the initial code assignment, or by future equipment additions or modifications.

3.3.3.4.1. Homogeneously grouped code construction. Exception to the above work unit code construction will be taken when utilizing homogeneous grouping, (for aircraft peculiar AGE equipment). The first two characters will identify the homogeneous group, the third character will identify the end item, the fourth character will identify the first level of assembly and fifth character will identify the lowest level of assembly. For example:

```
CA000   HOMOGENEOUS GROUP

CAA00      END ITEM

CAAA0         FIRST LEVEL OF ASSEMBLY
CAAAA            Lowest Level of Assembly
 thru
CAAA8            Lowest Level of Assembly

CAA99   NOC (End item)
```

3.3.3.4.2. Use of "99" - Not Otherwise Coded. The number 9 is used in the fourth and fifth characters of the work unit code, followed by the abbreviation "NOC", which stands for "Not Otherwise Coded." This code is used to provide a work unit code for components that do not have specific codes assigned. NOC codes will relate to the end item or first level of assembly. The "99 NOC" code will appear as the last entry under the last component in the first level of assembly or end item breakout. When continuations are used, Code "99 NOC" shall only appear in the last group of codes. There shall be a spaced separation between the last component and the NOC code to provide easy recognition of the NOC code.

NOTE:

The numbers 99 shall not be used in the fourth and fifth positions of the work unit code to identify any specific type of equipment.

3.3.3.5. Multiple items serving a single function. Identical components within an end item performing peculiar functions shall have individual work unit code assignments for each peculiar function/application. For example, a pressurization control unit (PCU) in an end item may contain four identical controllers but each controller has a different usage (pressure setting) in the PCU. In this case, each controller will have a unique work unit code assigned. Items installed in multiples within an end item which perform within the same function/application parameters, except for

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:28Z
Check the source to verify that this is the current version before use.

location will normally have a single code assigned. For instance, only one code should be assigned for items having left hand and right hand application even though they have different part numbers. The procuring activity may grant exceptions to this requirement for items that have high failure rates or warrant detailed reporting for analysis purposes. If exceptions are granted then the nomenclatures of the items will reflect part number references to distinguish between the like items. This shall be done on an exception basis and shall not be a common practice.

3.3.3.6. Coding capability. The construction of work unit codes provides a capability to designate thirty-three first level assemblies or end items, thirty-three second level assemblies(for other than homogeneously grouped items) and thirty-two third or lowest level assemblies. If equipment breakout exceeds these capabilities, it will be necessary to continue the listing with the next available code. For example:

```
BBAA0   DUAL PUMPING UNIT

BBAA8    Controller

        DUAL PUMPTING UNIT (CONT)

BBABA    Controller Modulator

BBA99   NOC
```

Note the change in the fourth character of the work unit code.

3.4. Code arrangement and special procedures.

3.4.1. Work unit code column heading. The first line entry at the top of each work unit code column shall be the type of equipment to which the work unit codes apply. For example:

```
ABA00   LOAD BANK F-106/MA-1
*         *          *        *
BEA00   TEST STAND, ASTRO TRACKER
*         *          *        *
FAA00   COMPUTER TEST STATION
```

3.4.2. New page entries. When work unit codes for an end item or lower level of assembly are carried over to a new page, the first work unit code entry on the new page shall be (1) the end item code and title; (2) following that line entry shall be the work unit code and title for the second level of assembly (first level for homogeneously grouped end itmes) followed by the abbreviation for continued, in parentheses. Example, assuming that the last code of the preceding page is FABTX Circuit Card Assy:

```
FAA00  COMPUTER TEST STSTION          (End Item)

FABT0   ANALYZER SAMPLING (CONT)      (Second Level Assy)
FABTY    Circuit Card Assy            (Third Level Assy)
```

3.4.3. End item identification. Each end item of equipment in the AGE work unit code manual shall be identified by an "at" @ sign between the work unit code and its nomenclature. This is intended to aid maintenance technicians in identifying what equipment should be entered in the "end item work unit code" block of the maintenance forms.

3.4.4. Time change item and configured article identification. An asterisk shall be placed between the work unit code and its definition (nomenclature) for each time change, time significant or serially controlled item, which shall be identified and provided by the procuring activity. The abbreviation TCI shall be entered in the parentheses following the definition (nomenclature) for time change items to differentiate between these items and time significant or serially controlled items. (Reference paragraph 2.a of Figure 2.)

Source: https://assist.dla.mil -- Downloaded: 202610-21T15:28Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS.

4.1. General. The requirements of MIL-M-38784 and MIL-P-38790 are applicable.

4.2. Validation. The contractor shall certify that information provided in the manual accurately and completely reflects the composition of the system in its latest Air Force approved configuration and as set forth in the source documentation used to develop the manual. Completed validation and certification shall be a condition of Air Force acceptance for each manual prepared under this specification.

4.3. Verification. At the option of the procuring activity, a requirement for verification of work unit code manuals may be a condition of the contractual work statement. If verification is required, it shall be accomplished in accordance with a plan developed jointly by the procuring activity and the contractor. The procuring activity shall ensure that work unit code manual information and end item configuration information are completely compatible.

5. PREPARATION FOR DELIVERY.

5.1. The requirements of MIL-M-38784 and MIL-P-38790 are applicable.

6. NOTES

6.1. Intended use. Refer to 1.2.

6.2. Ordering data. Procurement documents should specify:

a. Title, number and date of this specification.

b. Form in which data is to be supplied. (3.1)

c. Binder Requirements. (3.1.2)

d. Size of preliminary manuals. (3.2.1)

e. Selected codes. (3.2.5.5 and 3.2.5.6)

f. Part number identification. (3.3.1.4)

g. Verification requirements. (4.3)

6.3. Identification of changes. The margins of this specification have not been marked to identify changes because the changes are fairly extensive. Bidders and contractors are cautioned to evaluate the requirements of this specification based on the entire contents.

Custodian:

Air Force-16

Preparing Activity:

Air Force-16

Review Activities:

Air Force-01,11,70

Project No:

TMSS F411

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:28Z
Check the source to verify that this is the current version before use.

AGE SUPPORT GENERAL CODES

NOTE: Support general codes are for recording production credit of repetative tasks of a general nature, and shall not be used for recording malfunctions, repair, NRTS, or condemnation actions. The multitude of tasks which must be accomplished preclude listing them all in the support general task lists provided. This is not intended to restrict documentation of tasks. All support general work must be identified to the most appropriate code.

01000 GROUND HANDLING, SERVICING AND RELATED TASKS

Ground Handling (includes movement or repositioning of AGE).

Assisting Ground Crews

AGE Operation

Fire Guard

SERVICING

ADI Injuection, Fuel, Oil, Air, Hydraulic, Water, CO^2

Anti Freeze, Oxygen, Nitrogen

Refrigerant

Freon

Lubrication (when not part of an inspection)

02000 EQUIPMENT CLEANING

Includes washing, decontamination, snow, frost and ice removal, wiping, polishing, cleaning and treating of equipment to prevent corrosion.

05000 Preservation, Depreservation, Storage and climatization of equipment.

06000 Ground Safety

07000 Preparation and Maintenance of Records. This code will be used by maintenance personnel to record only the direct labor expended in preparation and/or maintenance of status and historical forms. This excludes initiation and completion of production documentation forms.

09000 SHOP SUPPORT GENERAL CODES

Fabricate (includes bending, cutting, forming, casting, holding, machining, soldering, assembly, local manufacture, etc) not done as part of a fix on a specific job.

Engine/or Power Pack Buildup or Teardown.

Engine Operation - Test Stand (includes installation of engines in test stand).

Cleaning and/or servicing (includes recharging, sandblast, degreasing, preparation for an/or removal from storage or shipment, etc.

Painting (includes stenciling, lettering, installing decals, instrument rnage marking, etc).

FIGURE 1 (SHEET 1 OF 3)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:28Z
Check the source to verify that this is the current version before use.

AGE SUPPORT GENERAL CODES
FOR
LOOK PHASE OF SCHEDULED AND SPECIAL INSPECTIONS

"LOOK" PHASE OF SCHEDULED INSPECTIONS

Code	Description
03111	Service Inspection
03112	Acceptance
03113	Incoming (Entering shop)
03114	Periodic
03115	Final (Leaving shop)

SPECIAL INSPECTIONS

Code	Description
0411C	Hydraulic System Contamination Check
0411D	Oil Sampling for Spectrometric Analysis
04111	Special Modification Inspection
04112	Hydrostatic (Includes Inspection, Weighing and Servicing)
04113	Functional/Operational Check
04114	Special Inspection - General Requirements
04115	Special Inspection - Special Event Inspection Requirement
04117	Battery Capacity/Specific Gravity Check
04119	Corrosion Control Inspection (Use if Accomplished Separately from a Scheduled Inspection)
04610	Non-Destructive Testing (All Types)
04620	Analysis of Oil Samples
04630	Research and Development of New or Revised Non-Destructive Inspection Techniques
04919	Special Inspection Not Otherwise Coded

FIGURE 1 (SHEET 2 OF 3)

Source: https://assist.dla.mil -- Downloaded: 202610-21T15:28Z
Check the source to verify that this is the current version before use.

UNIQUE DATA CODES FOR MCS
(Maintenance Cost System)

Data Code	Description
ALTØØ	Alert Duty. All manhours expended while waiting for alert aerospace vehicles to takeoff or land, such as strategic, defense, tactical, standing by for crash alert, or for alert missiles when no work is being accomplished. Not to be used for standby, awaiting work assignments, lag, or other delays, or when direct productive effort is being expended.
CMPØØ	Compensatory Time for Overtime. All direct assigned manhours excused from normal duty as a result of previously expended overtime manhours.
DTLØØ	Detail, Squadron or Base Duties. Manhours expended by direct labor personnel (labor code 100) performing on-base duties such as CQ, policing, building maintenance, driver, dining hall, parade, commanders call, general military training, nontechnical training, etc.
LVEØØ	Leave. Manhours excused from duty, pass, or official leave, military, medical or sick leave.
TRNØØ	Maintenance Training. Manhours expended in OJT, formal and informal maintenance technical training.

NOTE: These codes are to be used to account for manhour expenditures of personnel with an assigned "direct" labor code when performing one of the above functions. Documentation guidance for AFTO Form 349 entries is contained in 00-20-2 Series Technical Orders.

FIGURE 1 (SHEET 3 OF 3)

Source: https://assist.dla.mil -- Downloaded: 202640-21T15:28Z
Check the source to verify that this is the current version before use.

PREFACE

1. GENERAL.

The complete details on use of codes printed in this manual are prescribed in AFM 66-1 and TO 00-20-2 series technical orders.

2. USE OF CODES.

It is necessary to use codes for recording maintenance actions in order to convert this information into language for translation by accounting machine and computers. The maintenance forms are sent to Data Automation and the information recorded on them is punched into accounting machine cards. These cards are then mechanically processed periodically to produce reports for use in the management function, such as determining deficient materiel, facilities or procedures. It is very important that all codes entered in the maintenance forms be accurate and clearly written so the keypunch operators can read and enter them in the punched cards correctly. The reports produced are significant only if the codes are accurate.

a. Work Unit Code. This code consists of five alphabetic and/or numeric characters and is used to identify the system (or end item), assembly, and component which was worked on. The symbol NOC is the abbreviation for Not Otherwise Coded. Code "99", NOC should only be used when an item does not have a specific work unit code assigned. An AFTO Form 22 will be submitted when a "99" NOC code is used due to lack of a work unit code for a reparable item. Items identified by an asterisk between the work unit code and the code definition are time significant, serially controlled or time change items. Time change items are further identified by the abbreviation (TCI) following the work unit code definition. Items identified by an asterisk require special consideration when completing maintenance documents.

b. MCS Code. This code consists of five alphabetic or numeric characters and is used to identify direct labor manhours expended in other than direct labor, i.e., Alert Duty, Detail, Leave, Training, etc.

c. Type Maintenance Code. This code consists of one alphabetic character and identifies the type of maintenance being performed, i.e., scheduled or unscheduled maintenance, etc.

d. Action Taken Code. This code consists of one alphabetic or numeric character and identifies what work was done, i.e., the action taken.

NOTE:

Collectively the Work Unit Code and the Action Taken Code identify a "unit of work" as defined in TO 00-20-2.

e. When Discovered Code. This code consists of one alphabetic or numeric character and is used to identify at what time a discrepancy or maintenance requirement was discovered.

f. How Malfunctioned Code. This code consists of three numeric characters and is used to describe the equipment malfunction.

3. SECURITY.

When maintenance is being performed on classified equipment, the listing of a work unit code or equipment classification code and nomenclature could possible lead to a breach of security, such as betraying mission capability. Extreme caution should be exercised, and if any question exists, it will be resolved according to AFR 205-1 and other applicable directives.

4. CHANGES TO CODES.

a. The codes in this manual are standard throughout the Air Force and will

FIGURE 2 (SHEET 1 OF 2)

Source: https://assist.dla.mil -- Downloaded: 202640-21T15:28Z
Check the source to verify that this is the current version before use.

only be revised by official publication. Recommended changes to this manual regarding its use, format, procedures, or the Type Maintenance, Action Taken, When Discovered, How Malfunctioned, or Support General Codes will be submitted through command channels in accordance with TO 00-5-1.

b. Recommended changes to Work Unit Codes or equipment listings in this manual shall be submitted on an AFTO Form 22, in accordance with TO 00-5-1, to the following address:

NOTE:

The procuring activity shall specify the symbol of the office responsible for this manual and the applicable address.

Aerospace Ground Equipment (AGE) which is normally construed as end items of AGE, in accordance with the definition in Section VI of TO 00-20-1, are identified with an "at" @ sign between the work unit code and its definition. This is intended to be a guide for filling out maintenance source documents.

FIGURE 2 (SHEET 2 OF 2)

Source: https://assist.dla.mil -- Downloaded: 202640-21T15:28Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:28Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE AIR FORCE

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 73236 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE AIR FORCE

AFLC/MMAPD
Wright-Patterson AFB, OH 45433-5001

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:28Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:28Z
Check the source to verify that this is the current version before use.