MIL-I-83245(USAF)
AMENDMENT 4
27 Mar 86

SUPERSEDING
AMENDMENT 3
8 JUNE 1978

MILIITARY SPECIFICATION

INDICATOR SET, OIL PRESSURE A/A24J-17

This amendment forms a part of MIL-I-83245(USAF), dated 6 November 1979, and is approved for use within the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 1.1 Add title "Scope".

* Delete "2.1" and add: " 2.1 Government documents".

* Add:

"2.1.1 Specification standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specification and Standards (DODISS) and supplement thereto, cited in the solicitation."

* Under SPECIFICATION, Federal add: "PPP-B-601 Boxes, Wood, Cleated Plywood" and "PPP-B-636 Box, Shipping, Fiberboard".

Under SPECIFICATION, Military delete: "MIL-C-675 Coating of Glass Optical Elements (Anti-reflection)" and add:
"MIL-P-116 Preservation-Packaging, Methods of
MIL-C-14806 Coating, Reflection Reducing, for Instrument Cover Glasses and Lighting Wedges
MIL-C-81704 Glass Aircraft Instrument, Lighting Wedge and Cover".

* Under STANDARDS, Military delete: "MIL-STD-100" and add: "DOD-STD-100". Also add "MIL-STD-129 Marking For Shipment and Storage".

* Add boxed paragraph to bottom center of page.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Oklahoma City Air Logistics Center/MMEDO, Tinker AFB OK 73145-5990 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

PAGE 2

Paragraph 2.1 Under STANDARDS; Military delete: "MIL-STD-785 Reliability Program for Systems and Equipment Development and Production".

AMSC N/A FSC 6620

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:42Z
Check the source to verify that this is the current version before use.

Paragraph 2.1 Under STANDARDS, Military add: "MIL-STD-794 Parts and Equipment, Procedures for Packing and Packaging of".

* Add:

"2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation."

ASTM-D-3951-82 Packaging, Commercial - 29 January 1982.

(Application for copies should be addressed to: ASTM, 1916 Race St, Philadelphia PA 19103.)

(Nongonvernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)"

* Add:

"3.4.2.1 Recovered materials. Recovered materials shall be used to the maximum extent possible without jeopardizing the end of the item."

PAGE 3

Paragraph 3.5.1.1: Delete.

PAGE 4

3.5.2.6.2 Add new paragraph.

"3.5.2.6.2 Damping fluid. The transmitter shall not contain silicone oil."

PAGE 9

Paragraph 3.5.3.5: Delete and substitute:

"3.5.3.5 Cover glass. The cover glass shall be in accordance with MIL-G-81704."

Paragraph 3.5.3.5.1: Delete and substitute:

"3.5.3.5.1 Reflection glass surfaces. All reflecting glass surfaces shall be provided with a reflection reducing coating which meets the requirements of MIL-C-14806 in addition to withstanding the environmental conditions specified herein."

PAGE 14

* 3.7 Line 3 delete MIL-STD-100 and add: "DOD-STD-100".

PAGE 19

Source: https://assist.dla.mil -- Downloaded: 202610-23T07:42Z
Check the source to verify that this is the currentversion before use.

Paragraph 4.6.1.3 c: Delete and substitute:

"c. A vacuum of 14.0 ± .5 PSI shall be applied to the P_2 (low pressure) port of the transmitter. A pressure shall be applied to the P_1 (high pressure) port which shall exceed that applied to the P_2 port by each of the test points listed in Table I and a scale error and friction test performed. The scale error and friction errors shall not exceed the values specified in Tables I and II."

PAGE 20

4.6.1.7 Line 2 delete "(b)" and add: "(b.1)".

PAGE 22

* 4.6.2.6 Delete first sentence and add: "The indicator shall be subjected to a vibration test in accordance with MIL-STD-810, Method 514, equipment category b.1, along a curve parallel to curve B of figure 514.2-2".

PAGE 23

* 4.6.2.13 In first sentence delete: "MIL-STD-810, Method 504, procedure II" and add: "MIL-STD-810, Method 504.1, procedure I".

PAGE 24

4.6.2.17 Line 2 delete: "509" and add: "509.1".

* 4.6.3 Delete: "MIL-STD-781, Test Plan I" and add: "MIL-STD-781 Test Plan IC".

* 4.6.3.1 Line 11 delete: "Test Level J of MIL-STD-781" and add: "Paragraph 4.6.3.1.1".

* Add:

"4.6.3.1.1 Vibration. The vibration shall be 2.2G ± 10% peak acceleration value at any nonresonant frequency between 20 and 60 cps measured at the mounting points of the equipment. (Equipment designed for use on Navy ships shall be at vibrated 1G ± 10%. If the equipment is designed to meet a vibration requirement less severe than the level specified as a design requirement.) The duration of vibration shall be at least 10 minutes during each hour of equipment operating time. When the equipment being tested contains circuit boards or cards, vibration shall be normal to the plane of the majority of the cards. Otherwise, the direction vibration is not critical. This vibration requirement may be met by mounting the equipment solidly, (that is, without the equipment shock vibration mounts) to a strong flat plate which is supported by vibration isolators. The desired amplitude and frequency may be obtained by a simple vibration machine with an asymetric weight on a shaft attached to the plate and driven by a suitable motor. It is recommended that the vibration equipment be checked for proper operation each 24 hours of operation, and that the vibration transducer be "on" and monitored continuously during vibration."

Add:

"4.7 Inspection and test. Inspection and test of methods of preservation and packaging shall be accomplished in accordance with section 4 of MIL-P-116 to insure compliance with section 5 of this specification."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:42Z
Check the source to verify that this is the current version before use.

be accomplished in accordance with section 4 of MIL-P-116 to insure compliance with section 5 of this specification."

* Delete section 5 and add:

"5 PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be level A, C, or Industrial, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Cleaning. Indicator set, oil pressure components shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying. Indicator set, oil pressure components shall be dried in accordance with process D-4 of MIl-P-116.

5.1.1.4 Unit packaging. Unless otherwise specified by the contracting activity, each indicator set, oil pressure component shall be packaged in quantity unit packs of one each in accordance with Method 1C1 of MIL-P-116. Overboxed completed pack in PPP-B-636 container. Apply sufficient cushioning material between bag and unit container of a type, density, and thickness to insure shock transmission does not exceed peak values in Gs established for the components when completed packs are subjected to the rough handling drop tests of MIL-P-116.

5.1.2 Level C. Indicator set components shall be clean, dry, and individually packaged in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from supply source to the first receiving activity.

5.1.3 Industrial. The industrial preservation of indicator set components shall be in accordance with ASTM-D-3951-82.

5.2 Packing. Packing shall be level A, B, C, or Industrial as specified (see 6.2).

5.2.1 Level A. Indicator set components packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-601, Styles A or B, class overseas, unless otherwise specified by the contracting activity. Insofar as practical, exterior shipping container shall be of uniform shape, size, minimum tare and cube consistent with the protection required.

5.2.2 Level B. Indicator set components packaged as specified in 5.1.1 shall be packed in shipping container conforming to PPP-B-636, class weather-resistant, unless otherwise specified by the contracting activity. Other requirements as specified in 5.2.1 apply.

5.2.3 Level C. Packing shall be applied which affords adequate protection during domestic shipment from the supply source to the first receiving activity for immediate use. This level shall conform to applicable carrier rules and regulations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:42Z
Check the source to verify that this is the current version before use.

5.2.4 Industrial. The packaged components shall be packed in accordance with ASTM-D-3951-82.

5.3 Marking. In addition to any other markings required by the contract or order (see 6.2), interior and exterior containers shall be marked in accordance with MIL-STD-129."

Delete paragraph "6.3" and add:

" 6.3 The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to irrespective of the marginal notations and relationship to the last previous amendment."

Custodian:
Air Force - 99

Preparing Activity:
Air Force - 71

Project Number:
6620 - F379

Source: https://assist.dla.mil -- Downloaded: 202610-23T07:42Z
Check the source to verify that this is the current version before use.