MILITARY SPECIFICATION
INDICATOR, TEMPERATURE, THERMOCOUPLE
HERMETICALLY SEALED, GENERAL SPECIFICATION FOR

This amendment forms a part of Military Specification MIL-I-83262B(USAF) dated 25 May 1977.

PAGE 2

2.1 Under STANDARDS, MILITARY: Delete "MIL-STD-471 Maintainability Demonstration".

PAGE 6

3.11.2, 3.11.2.1 and 3.11.2.2: Delete and substitute:

"3.11.2 Prime standard. The internal lighting of production indicators shall be comparable to and shall balance in brightness and color with a prime standard indicator. The prime standard shall be either an actual indicator conforming to the requirements of this specification or a lighted model. The prime standard shall be used as the reference for acceptance of all production indicators.

3.11.2.1 Prime standard recertification. All representative areas of the face of the prime standard indicator shall be measured for brightness and color as specified in the applicable lighting specification. Each area shall be measured at a sufficient number of locations to obtain data representative of each area including the brightest and dimmest portions of the indicator display. The prime standard indicator shall be measured periodically (at least every 50 hours of operation or every 120 days, whichever occurs first) to determine the magnitude of any brightness or color change. The data and, if required by the qualifying activity, the prime standard shall be submitted for evaluation and reapproval or correction action, or both.

3.11.2.2 Visual comparison. The lighting level of the production indicator under test shall fall within the limits of the prime standard when energized at the voltage levels specified in 4.6.36.1."

PAGE 11

4.5.1 i: Change to read:

"i. Individual tests of MIL-L-25467 or MIL-L-27160, as applicable, and the visual comparison tests (4.6.36)."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:43Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:43Z
Check the source to verify that this is the current version before use.

PAGE 13

4.5.2.1 c and d: Delete. Add: "Vibration (4.6.14)."

4.5.2.2 g: Delete.

PAGE 17

4.6.13 lines 8 and 9: Change to read: "The scale error test specified in 4.6.4 shall then be conducted."

PAGE 23

4.6.31 and 4.6.32: Delete.

PAGE 24

4.6.35: Delete.

4.6.36 through 4.6.36.2.3: Delete and substitute:

"4.6.36 Visual comparison. The following tests shall be conducted during the individual production quality conformance testing. The tests shall be conducted by qualified personnel only after they have been previously tested for normal color vision and passed and have become dark adapted prior to performing any visual comparison tests. The prime standard and the indicator under test shall be placed side-by-side at eye level in completely dark surroundings and viewed at a distance of approximately 2.5 feet in a sighting cone 45° from the normal to the surface of the cover glass. All areas of the indicator including markings, pointers, flags, et cetera, shall be compared when viewed from any position within the sighting cone.

4.6.36.1 Brightness. With 2.50± 0.01V applied to the indicator under test and 2.40 and 2.60V applied consecutively to the lighting terminals of the standard, like areas of the test indicator and standard shall be compared such as: pointers, command bars, alarm flags, numerals, indicia, markings, et cetera for brightness. The two instruments shall also be compared for lighting uniformity. The brightness of the production unit at 2.50V shall fall within the brightness levels of the prime standard when set at 2.40 and 2.60V. If the brightness levels do not meet this criteria in any individual area or the relative uniformity of lighting of the indicator and prime standard are different, the questionable areas of the production units shall be measured with a photometer in accordance with MIL-L-25467 or MIL-L-27160, as applicable. If the production units fail this photometric test, they shall be rejected and returned for rework. Qualification units shall

Source: https://assist.dla.mil -- Downloaded: 202610-23T07:43Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:43Z
Check the source to verify that this is the current version before use.

not be tested by use of the prime standard. The qualification units must be photometrically measured in accordance with the applicable lighting specification.

4.6.36.2 Color. A color comparison test shall be conducted with 4.50V applied to both the production indicator and the prime standard. The two indicators shall appear identical in color. Questionable areas of the production units shall be measured in accordance with MIL-L-25467 or MIL-L-27160."

Custodian:
Air Force - 11

Reviewer activity:
Air Force - 99

Preparing activity:
Air Force - 11

(Project 6685-F598)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:43Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:43Z
Check the source to verify that this is the current version before use.