[INCH-POUND]
A-A-2957
November 21, 1995
SUPERSEDING
V-M-81F
April 22, 1975
Amendment 1
May 6, 1976

COMMERCIAL ITEM DESCRIPTION

MATTRESS, BED, FELT

The General Services Administration has authorized the use of this commercial item description for all federal agencies, in lieu of V-M-81F

1 SCOPE AND CLASSIFICATION

1.1 Scope This commercial item description covers flame resistant, reversible, box edged, laminated felt mattresses intended for use by civil and military agencies of the Government.

2 CLASSIFICATION

2.1 Classification The mattresses shall be of the style and size, as specified (see 7.3)

Style A - Flame resistant cotton ticking
Style B - Flame resistant, vinyl coated, cotton ticking

Size - The size shall be as shown in Table I

3 SALIENT CHARACTERISTICS

3.1 Standard commercial product. The felt mattresses covered by this commercial item description shall be the manufacturer's standard commercial product except for any changes necessary to conform to this commercial item description Materials not specified shall be the quality used in commercial practice

3.2 Finished mattress dimensions. The finished length and width of the mattress shall be as shown in Table I The depth of the mattress shall be 4 inches (10 cm) All dimensional tolerances shall be minus 0 and plus 0.5 inch (1.3 cm).

Beneficial comments, recommendations, additions, deletions, clarifications, etc and any data which may improve this document should be sent to General Services Administration, Engineering Group (7FXEE), 819 Taylor St , Fort Worth, TX 76102.

Distribution Statement A Approved for public release, distribution is unlimited

FSC 7210

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

Table 1 Finished mattress dimensions

Size	Length	Width
1	72 5 in (184 cm)	26 in (66 cm)
2	74 in (188 cm)	28 in (71 cm)
3	75 in (190 cm)	36 in (91 cm)
4	75 in (190 cm)	38 in (97 cm)
5	76 in (193 cm)	25 in (64 cm)
6	76 in (193 cm)	31 in (79 cm)
7	76 in (193 cm)	34 in (86 cm)
8	77 in (196 cm	28 in (71 cm)
9	78 in (198 cm)	31 in (79 cm)
10	78 in (198 cm)	36 in (91 cm)
11	79 in (201 cm)	26 in (66 cm)
12	80 in (203 cm)	36 in (91 cm)
13	80 in (203 cm)	38 in (97 cm)

3 3 Materials

3 3 1 Felt The felt shall be made of 50 percent cotton and 50 percent cotton linters having a minimum of 10 percent boric acid treatment by weight compared to the weight of the cotton. The felt shall be clean, well garnetted, and produced in unbroken laminated sheets The use of oil in the fabrication of the felt shall not be permitted

The cotton shall be 7/8 inch (2.2 cm) (minimum) staple cotton and not lower in grade than the lowest grade in the white, spotted, or gray grades conforming to the standard of the United States Department of Agriculture Publication No C&MS-SRA-180 The use of reginned cotton will be permitted provided the grade of the reginned cotton is equivalent to the grade specified above Tinged or stained cotton shall not be permitted

The linters shall conform to grade 5, staple 5, of USDA Publication No C&MS-SRA-180

3 3 2 Ticking The ticking shall be cotton, shall be suitable for mattress covers, and shall have a durable, non-toxic flame resistant treatment The flame resistant ticking may be vinyl coated for liquid repellency

The cotton ticking shall be flame resistant treated twill fabric with a weight range of 6 5 oz/sq yd (170 g/sq m) to 8 5 oz/sq yd (283 g/sq m when tested in accordance with ASTM D 3776 The fabric shall have a minimum breaking strength of 95 lb (43 kg) in the warp direction and 50 lb (23 kg) in the filling direction when tested in accordance with ASTM D 1682.

The fabric shall have a colorfastness rating of 4 or higher to dry crocking and a rating of 3 or higher to wet crocking when tested in accordance with AATCC 8 The pH value of the ticking fabric shall be not less than 4 5 and not more than 8 0 when tested in accordance with FED-STD-191, Test Method 2811

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

3 4 Design and construction The design and construction of the mattress shall include all materials and processes necessary to produce a functional, durable, attractive finished mattress meeting the requirements stated herein and specified in the contract or order The four corners of the mattress shall be firm, well padded, and slightly rounded.

3 4 1 Cover construction The top and bottom panels of the mattress cover (ticking) shall each be cut in one piece without splices Stripes, when used, shall run lengthwise of the mattress The ticking for the side panel shall match the top and bottom sections of the mattress cover and shall be made of not more than four pieces of ticking with the ends spliced together and any pattern well matched. Any splice shall fall at the middle of a corner of the mattress

The edges of the cover and side panel ticking shall be joined within the fold of flame resistant or smoldering ignition resistant edge binding tape. The binding tape shall extend completely around both edges of the mattress. No more than 3 pieces of tape shall be used on each border edge, not including normal bias splicing.

3 4 2 Batting distribution The batting shall be distributed in unbroken laminated sheets of uniform weight and thickness

3 4 3 Mattress construction. The ticking cover and layers of batting shall be locked together and shall not shift when the finished mattress is used Innertufted mattresses may require the use of tufting support fabric to properly anchor the filling materials If tufting support fabric is used, the fabric shall be flame resistant cotton

3 5 Flammability. The mattress shall meet the following flammability requirements.

a) California Technical Bulletin #129, Flammability Test Procedure for Mattresses for Use in Public Buildings.

b) CFR 16, Subchapter D, Flammable Fabrics Act Regulations Part 1632, Standard for the Flammability of Mattresses and Mattress Pads (FF 4-72, Amended).

3 6 Labels Each mattress shall be labeled for fiber content according to the Rules and Regulations of the Textile Fiber Products Identification Act and shall conform to the legal requirements of the state of manufacture The label information may be combined when allowed by state law.

3 7 Workmanship. The mattress shall conform to the quality of product established by this commercial item description and shall function as a comfortable, durable, sleep mattress and shall be free of any defect affecting appearance, function, or serviceability.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

The finished mattress shall be flat, smooth, uniform, correct in all dimensions, clean, and odor free The ticking shall be free from holes, cuts, tears, weaving flaws, mends, soil, dirt, stains, thread pulls, and other fabric defects Seams shall be secure and shall not slip or pull out Seams shall be free from any needle chews, unsecured ends of stitching, loose or unclipped threads; raw edges, open seams, puckering, pleating, or twisting, loose or tight stitch tension, or unevenly spaced stitches Chain stitched seams shall be chained off leaving a 1/2 inch (1 3 cm) nominal length tail All seams shall be straight and uniform

The mattress construction shall be free from sagging appearance, unevenly distributed filling, clearly noticeable lumps, thin hollow places, corner(s) not firm, or box edge or corner having insufficient padding Top or bottom face-panel ticking shall not be spliced When applicable, stripes shall run lengthwise of the mattress and shall be properly matched

The box edge shall be firmly constructed and fabricated with no more than four pieces of ticking Any splice shall fall at the middle of a corner Box edges shall be sharply defined Binding tape shall extend completely around edge of mattress and no more than three pieces of binding tape shall be used on an edge The binding tape shall not be puckered, pleated, or twisted

When applicable, outer tufting shall appear on both sides of mattress Knots of tufting tape shall not appear above surface on either side of mattress Tufting spacing and depth shall be uniform and shall hold the mattress upholstery securely in position

3 8 Measurement system The values stated in inch-pound units are to be regarded as the standard. The metric values stated in parentheses are for information purposes only.

3 9 Metric products Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, providing they fall within the tolerances specified and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the specification preparing activity for changes to this document

3 10 Commercial item The use of the term "commercial item" in this document does not imply that any item or items offered are not required to conform with all requirements specified herein.

4 REGULATORY REQUIREMENTS

4 1 Regulatory requirements The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

accordance with paragraph 23 403 of the Federal Acquisition Regulation (FAR)

5 QUALITY ASSURANCE

5 1 Contractor certification The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this commercial item description and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract

6 PACKAGING

6 1 Packaging Preservation, packing, and marking shall be as specified in the contract or order.

6 2 Special marking The following marking shall appear on at least two side edges of each shipping container in letters not less than 1-1/2 inches (3 8 cm) in height

STOW FLAT - DO NOT STOW ON END OR SIDE

7 NOTES

7 - Part Identification Number (PIN) Mattresses conforming with this commercial item description shall be identified by a part number configuration consisting of identification of a portion of the CID number, style, and size. An example of a part number configuration is shown below. This part number numbering system is intended for identification and cross-indexing of the item within the federal cataloging system. The following part identification numbering procedure is for government purposes and does not constitute a requirement for the contractor

A-A-2957A1 EXAMPLE A-A-2957A1 = Style A, Size 1

_____ Style A or B (A = cotton ticking
B = vinyl coated ticking)

_____ Size 1 through 13

_____ General specification number

7 2 Referenced documents

Copies of AATCC standards and test methods are available from American Association of Textile Colorists and Chemists, P O. Box 12215, Research Triangle Park, NC 27709

Copies of ASTM standards are available from the American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

Copies of California Technical Bulletins are available from the State of California, Department of Consumer Affairs, Bureau of Home Furnishings and Thermal Insulation, 3485 Orange Grove Avenue, North Highlands, CA 95660-5595

Copies of the Code of Federal Regulations are available from the Superintendent of Documents, U S Government Printing Office, Washington, DC, 20402

Copies of Federal standards are available from the General Services Administration Specifications Section (3FBP-W), Specifications Unit, Suite 8100, 470 E L'Enfant Plaza, SW, Washington, DC 20407

Copies of USDA publications are available from USDA Publication Division, 14th Street and Independence Avenue SW, Room 103A, Washington, DC 20250

7 3 Ordering data Purchasers should select the preferred options permitted herein and include the following information in procurement documents (if applicable)

a Title, number, and date of this commercial item description
b Style and size of mattress required (see 2 1)
c Preservation, packing, and marking desired

7 4 National Stock Numbers (NSNs) The following is a list of NSNs which reference this commercial item description. The list may not include all possible NSNs associated with this document

National Stock Number	Style	Size	PIN
7210-00-139-6517	A	1	AA2957A1
7210-01-417-9696	B	2	AA2957B2
7210-01-417-9705	B	3	AA2957B3
7210-01-417-9707	B	4	AA2957B4
7210-01-417-9694	A	5	AA2957A5
7210-00-139-6555	A	6	AA2957A6
7210-01-417-9699	B	7	AA2957B7
7210-00-139-6536	A	8	AA2957A8
7210-01-417-9706	B	8	AA2957B8
7210-01-417-9700	B	9	AA2957B9
7210-00-205-3913	A	10	AA2957A10
7210-01-417-9697	B	10	AA2957B10
7210-01-417-9691	A	11	AA2957A11
7210-01-417-9701	B	11	AA2957B11
7210-01-417-9703	B	12	AA2957B12
7210-01-417-9693	A	13	AA2957A13

PREPARING ACTIVITY

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.