INCH-POUND

A-A-50042A
April 30, 1990
SUPERSEDING
A-A-50042
December 30, 1982

COMMERCIAL ITEM DESCRIPTION

OVENS, BAKING AND ROASTING, FORCED CONVECTION, GAS

The General Services Administration has authorized the use of this commercial item description as a replacement for Military Specification MIL-O-43679, which was cancelled.

1. CLASSIFICATION

1.1 Classification. This commercial item description covers two types of ovens as follows (see 5.2).

Type I - one oven compartment
Type II - two oven compartments

1.2 CID based part identification number (PIN). A document based PIN to identify types of items is included in section 5. This identification numbering procedure is for Government purposes and does not constitute a requirement for the contractor.

2. SALIENT CHARACTERISTICS

2.1 Description. The type II oven shall consist of two type I ovens stacked and secured. Each oven compartment shall operate independently. Oven exterior surfaces except the bottom and back shall be stainless steel. The oven compartment and door lining shall be stainless steel. Each oven compartment shall be equipped with removable stainless steel top, right-hand, left-hand, and bottom oven liner panels, five equally spaced shelves supported by removable shelf supports, two-speed oven blower, blower speed selector switch (low and high), flue riser, oven light, oven indicator light, a 5-hour oven timer with alarm, heating units, temperature controls, and burners "ON-OFF" control. The oven shelves shall be capable of supporting a load of 20 pounds per square foot. The oven without liner panels shall preheat from

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data which may improve this document should be sent by letter to: Commander, U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-ES, Natick, MA 01760-5014.

AMSC N/A FSC 7310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:38Z
Check the source to verify that this is the current version before use.

an ambient temperature of 70° to 400°F within 20 minutes. Oven doors shall be vertically split, side opening type, with heat-resisting viewing windows. When in fully opened position, doors shall open flush with interior oven sidewalls and shall not obstruct removal of the shelves. A handle shall be provided on each door or one handle to open and close the doors simultaneously. Each convection oven shall be provided with a latch, clip, or other means to hold the doors in the closed position. The type I oven shall be mounted on legs or mounted on an open or inclosed stainless steel stand. All ovens shall be equipped with stainless steel legs with leveling devices. The oven shall be equipped with an air baffle and vent operated from the control panel to control moisture in the baking chamber.

2.2 Dimensions. The ovens shall be within the dimensional limits shown in table I.

TABLE I. Dimensions (inches)

Measurements	Minimum	Maximum
Width overall	33	52
Depth overall	30	48
Height 1/ overall (excluding vent)		
Type I	26	63
Type II	52	78
Height 1/ to bottom deck		
Type I	26	38
Type II	11	19-3/4
Height 1/ to top deck (type II)	30	51-3/4
Compartment (inside usable)		
Width	27	30
Depth	20	30
Height	19-3/8	28

1/ Height from floor, including supporting legs and base.

2.3 Fuel system. The oven shall be designed to burn natural gas or liquified petroleum gas (LPG) with conversion kit. Each oven rating shall not exceed 120,000 BTU/hr. The ovens shall be equipped with an automatic pilot of the 100 percent shut-off type, pressure regulator and automatic gas ignition system. For main burners, the pilot shall automatically shut off the gas to all oven burners including oven pilot burners in the event that means of ignition become inoperative. An ANSI Z21.41 approved quick disconnect (socket and plug) and a 5-foot minimum flexible metal connector consisting of a male pipe thread fitting on one end and union with female thread on the opposite end conforming to ANSI Z21.45 shall be supplied with each oven.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

2.4 Thermostats. Each oven compartment shall have a manually operated thermostat to provide automatic heat control of the oven compartment. The activating components of the thermostats shall be protected against moisture, grease, and direct heat radiation. A temperature control dial marked from 150°F to not less than 500°F shall be provided.

2.5 Electrical characteristics. The electrical controls, lights, switches, and blower shall operate on a nominal 120 volt, 60 hertz, single phase power source or 220 volt, 50 Hertz, single phase power source when specified (see 5.2).

2.5.1 Oven blower. The oven blower motor shall be of the capacitor or split-phase type rated at a minimum of 1/3 horsepower (HP). The blower motor shall conform to NEMA MG-1, shall operate whenever the oven doors are closed, and shall sustain continuous operation at high and low setting.

2.5.2 Oven light. The oven light shall be controlled by a manual switch and by a door actuated switch. The oven light bulb shall be accessible for replacement without major disassembly of the oven.

2.5.3 Indicator light. A separate indicator or light that illuminates when the oven is operating and does not illuminate whenever proper temperature has been attained shall be provided.

2.5.4 Oven timer. A 0 to 5 hour oven timer installed on a control panel located on the front of the oven shall be provided. The oven timer shall be equipped with an alarm signal.

2.6 Standards of compliance. The ovens shall comply with the American National Standard Institute (ANSI) Standard No. Z83.12 and the National Sanitation Foundation (NSF) Standard No. 4.

2.7 Data name plate (Government unique requirement, see 5.4). The ovens shall be furnished with a data name plate in accordance with the applicable requirements of MIL-STD-130 except the requirements for: (a) Methods of applying; (b) Identification tags; (c) Information not required and (d) Optional marking information shall not apply. The data plate shall be made of minimum 20 gauge corrosion-resisting metal and attached to the oven by rivets, screws, or welding in such a manner as to meet the applicable National Sanitation Foundation sanitary requirements for this equipment. The plate shall contain the following information which shall be stamped, engraved, or applied by photosensitive means:

National Stock Number
Procurement Contract Number
Specification Data
Manufacturer's Name, Address and Telephone Number
Supplier's Name, Address and Telephone Number (List only if different from Manufacturer)
Manufacturer's Model Number
Government Approved Manual Number (When specified, see 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

Each plate shall be placed so that it is readily visible to the operator during normal operating use and so as to not adversely affect the life and utility of the oven.

3. QUALITY ASSURANCE

3.1 Certification. The contractor shall certify, and maintain substantiating evidence, that the product offered meets the salient characteristics and requirements of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3.2 Metric product. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of Federal Standard No. 376, and all other requirements of this CID are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable. The contracting officer has the option of accepting or rejecting the product.

3.3 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

4. PACKAGING

4.1 Packaging and packing. Packaging and packing shall be commercial or export as specified (see 5.2).

4.2 Commercial packaging and packing. Each oven shall be cleaned, preserved, packaged, and packed in accordance with ASTM D 3951.

4.3 Export packaging and packing.

4.3.1 Export packaging. When specified in the contract or purchase order, the oven shall be disassembled to the extent determined by the supplier to protect parts susceptible to damage during shipment and storage and for reduction of cubage. Parts removed shall be identified. The oven and parts shall be cleaned, preserved, and cushioned to afford protection against corrosion, deterioration, and physical damage during shipment and storage. Disassembled parts may be packaged in a class weather-resistant fiberboard box conforming to PPP-B-636 or placed within the oven or directly into the shipping container with the oven.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

4.3.2 Export packing. One oven shall be packed in a snug-fitting wood-cleated plywood box conforming to domestic type, style A or J, grade B, type 2 load of PPP-B-601 or nailed wood box conforming to class 1, style 2 or 4, grade B of PPP-B-621. The contents of the box shall be cushioned, blocked, and braced to prevent movement while the box is in transit. Each shipping container shall be closed and strapped in accordance with the appendix of PPP-B-601 or PPP-B-621, as applicable.

4.4 Marking. Marking of interior packages and shipping containers shall be in accordance with MIL-STD-129.

5. NOTES

5.1 Intended use. The baking and roasting gas convection ovens are intended for use in military dining facilities.

5.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Type required (see 1.1).
c. Electrical characteristics required (see 2.5).
d. The Government approved manual number to be included on the data name plate when manuals are purchased under the contract (see 2.7).
e. Selection of applicable packaging and packing (see 4.1).

5.3 Sources of documents.

5.3.1 Sources for nongovernment association documents.

ANSI Z21.41 - Quick-Disconnect Devices for Use With Gas Fuel
ANSI Z21.45 - Flexible Connectors of Other Than All Metal Construction for Gas Appliances
ANSI Z83.12 - Gas Food Service Equipment - for Baking and Roasting Ovens

All are available from:

American National Standards Institute (ANSI)
1430 Broadway
New York, NY 10018

NSF Standard No. 4 - Commercial Cooking and Hot Food Storage Equipment, is available from:

National Sanitation Foundation (NSF)
3475 Plymouth Road
P.O. Box 1468
Ann Arbor, MI 48106

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:38Z
Check the source to verify that this is the current version before use.

NEMA MG-1 - Motors and Generators, is available from:

National Electrical Manufacturers Association (NEMA)
2101 L Street, N.W.
Washington, DC 20037

ASTM D 3951 - Standard Practice for Commercial Packaging, is available from:


The American Society for Testing and Materials (ASTM)
1916 Race Street
Philadelphia, PA 19103-1187

5.3.2 Sources of governmental documents. Copies of Military and Federal documents are available from:

Standardization Documents Order Desk
Bldg. 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

5.4 Government unique requirements. Whenever "(Government unique requirements)" is included in the title of a paragraph under "salient characteristics," it is meant that the requirement is something that is not normally offered to the commercial marketplace by the manufacturer.

5.5 Part identification number (PIN). The PIN's to be used for items required by this CID are created as follows:



MILITARY INTERESTS:

Custodians

Army - GL
Navy - YD
Air Force - 99

Review activities

Army - MD
Navy - MC
Air Force - 84
DLA - GS

CIVIL AGENCY COORDINATING ACTIVITY:

GSA-FSS

PREPARING ACTIVITY:

Army - GL

Project 7310-0770

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.