MIL-C-1161E
20 October 1988
SUPERSEDING
MIL-C-1161D
15 May 1970

MILITARY SPECIFICATION

COLLAR, DOG, LEATHER

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers the requirements for one type of leather dog collar (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

A-A-203	- Paper, Kraft, Untreated
V-T-285	- Thread, Polyester
FF-R-556	- Rivet, Solid, Small; Rivet, Split, Small; Rivet, Tubular, Small; Flat Washer (Burr); and Cap, Rivet; General Purpose

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3770

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:44Z
Check the source to verify that this is the current version before use.

KK-L-201 - Leather, Cattlehide, Lace, and Cut Laces
QQ-P-416 - Plating, Cadmium (Electrodeposited)
PPP-B-636 - Boxes, Shipping, Fiberboard

MILITARY

MIL-L-35078 - Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams and Stitchings

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads
MIL-STD-731 - Quality of Wood Members for Containers and Pallets

(Copies of specifications, standards, and handbooks required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWING

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

2-4-62 - Collar, Dog, Leather; Assembly and Details

(Copies of drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:44Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 545 - Steel Wire, Carbon, Cold-Heading Quality, for Machine Screws

D 3951 - Standard Practice for Commercial Packaging

(Copies should be obtained from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Alternate components. Components offered as equivalent to components specified herein and on the referenced drawings as a specific manufacturer's part or model number, or equal, shall be functionally equal to the manufacturer's part or model number identified, and shall be of equal or better quality. The incorporation and inclusion of such a component in the end product shall not require modification or change to any other specified component, and shall not reduce ease of maintenance to it or any other component, unless such change is specifically approved by the contracting officer. Prior to manufacture of the preproduction sample, or if none, the initial production unit, the supplier shall submit for the contracting officer's approval, a list identifying each proposed alternate component, together with proof that each listed component complies with requirements above. The contracting officer, at his option, may require a physical sample of the proposed substitution. Approval of the submitted listing, together with necessary supporting data, authorizes commencement of manufacture of the preproduction sample or initial production unit, as applicable, but does not relieve the supplier of the responsibility that these components perform in accordance with specified requirements when incorporated into the end product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:44Z
Check the source to verify that this is the current version before use.

3.2 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.3).

3.3 Materials and components (see 6.5).

3.3.1 Leather. The leather shall be vegetable tanned or combination tanned with vegetable and alum or vegetable and chrome tanning agents. The color shall be natural as produced by the tanning agents. The leather shall be furnished in the form of backs. The leather shall meet the elongation and breaking force requirements of KK-L-201, except elongation shall be measured under a load of 140 pounds and breaking force value shall be not less than 210 pounds. The width and thickness shall be as specified on Drawing 2-4-62.

3.3.2 Thread, polyester. The thread for all stitching shall conform to type I or II, class 1, size No. 3 of V-T-285.

3.3.3 Gum, tragacanth. Tragacanth gum for burnishing edges of leather shall be natural and conform to commercial grade No. 3.

3.3.4 Ring, dee. The dee ring shall be steel wire, cadmium plated, size 1-1/4 inches, conforming to North and Judd Mfg. Co., No. 3250 or equal.

3.3.5 Buckle, end bar. The end bar buckle shall be steel wire, cadmium plated, size 1-1/4 inches conforming to North and Judd Mfg. Co., No. 999 or equal.

3.3.6 Rivets with caps. Tubular rivets shall conform to type XII, class 3, grade E, 9/64 inch nominal diameter, and caps shall conform to type II of FF-R-556, except that the rivets and caps shall be fabricated from carbon steel, annealed in process, grades 1006, 1008, 1010, or 1012 in accordance with ASTM A 545. Rivets and caps shall be given a cadmium plated finish in accordance with class 2, type II of QQ-P-416. The length of the rivets shall be sufficient to allow full spread and anchorage within the cap.

3.4 Construction. The construction shall conform to Drawing No. 2-4-62 and as specified herein.

3.4.1 Stitching, machine. All stitching shall conform to type 301, 5 to 7 stitches per inch of FED-STD-751.

3.5 Marking. The letters "U.S.," the manufacturer's name, and the year of manufacture shall be indented in the size characters and in the location shown on Drawing 2-4-62.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:44Z
Check the source to verify that this is the current version before use.

3.6 Setting of rivets. The cap and head shall be set tight against the leather surface and there shall be no exposed rivet ends. The shank of the tubular rivets shall be fully spread and anchored within the cap. Rivets shall be set straight and not embedded in the leather. Rivets shall not be reversed on the assembly.

3.8 Workmanship. The dog collars shall conform to the quality of product established by this document and the occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirement in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for assuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.3. The presence of any defect shall be cause for rejection of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:44Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.4.1.1 Leather examination. An examination shall be made to determine that the leather is backs and is natural color (see 3.3.1). Any nonconformance shall be considered a defect. The lot shall consist of all collars offered for inspection at one time. The sample unit shall be one collar. The inspection level shall be S-2 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0.

4.4.2 In-process examination. Examination shall be made to determine that edges of collar leather are made smooth by burnishing with a natural gum (see 3.3.3). Whenever nonconformance is noted, correction shall be made to the items affected and to the process.

4.4.3 End item visual examination. The end item shall be examined for the defects listed in table I. The lot size shall be expressed in units of dog collars. The sample unit shall be one collar. The inspection level shall be II and the AQL, expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor
Leather			
Quality	Any hole, except where specified	X	
	Any cut or rupture	X	
	Brandmark, grub hole, scar tissue, hip mark, brittle, or bony area	X	
	Abraded, scratched, or other grain damage		X
	Flanky, spongy, or stretchy leather	X	
	Fat wrinkles		X
Cleanness	Grease or oil stains		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:44Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Hardware	Any hardware component incorrect type or finish; broken or malformed; protective finish omitted or corroded	X	
	Any burr or sharp edge		X
Construction and workmanship			
Rivets	Not set tight, i.e, cap and head set off from leather surface	X	
	Cap loosely set, i.e., shank not fully spread and anchored within cap	X	
	Rivets not set straight causing one side of head or cap to be embedded in leather		X
	Reversed on assembly		X
Buckle	Not type or finish as specified	X	
	Body or tongue malformed, or bent out of shape	X	
	Not assembled to strap as specified	X	
Seams and stitching	Any row of stitching omitted	X	
	Less than five or more than seven stitches per inch		X
	Any open seam	X	
Stitching ends	Thread ends not pulled through to back of collar and heat sealed where required		X
Seam and stitch type	Not type specified	X	
Stitch tension	Loose, resulting in a loosely secured seam, or locks exposed on surface of leather	X	
	Tight, causing stitches to rupture leather	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:44Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Cleanness	Thread ends not heat sealed		X
Marking	Omitted, incomplete, incorrect, not legible, not specified size, not in proper location, or not accomplished as specified		X

4.4.4 End item dimensional examination. Examination shall be made of the collar to determine compliance with the dimensions annotated with an asterisk on Drawing 2-4-62. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of dog collars. The sample unit shall be one collar. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling Bulged or distorted container
Content	Number per container is more or less than required

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:44Z
Check the source to verify that this is the current version before use.

4.4.6 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A. Five collars, each with its dee ring folded back, shall be alternated end for end, stacked flat one on another, and securely tied at each end with cotton tape or twine to form a compact package measuring approximately 27 inches in length, 3-1/4 inches in width, and 2 inches in depth.

5.1.2 Commercial. Collars shall be preserved in accordance with ASTM D 3951.

5.2. Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

5.2.1 Level A packing. One hundred and sixty collars, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each shipping container shall be fitted with a taped liner conforming to type CF, class weather resistant, variety DW, grade V15c, of PPP-B-636. Level A unit packs shall be packed on their side one in length, eight in width, and four in depth within a shipping container. Inside dimensions of each shipping container shall be approximately 27-1/2 inches in length, 16-1/2 inches in width, and 13 inches in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to A-A-203. Each shipping container shall be closed, waterproofed, and reinforced with flat strapping or tape banding in accordance with the

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:44Z
Check the source to verify that this is the current version before use.

appendix of the container document except that the inspection shall be in accordance with 4.4.5. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. One hundred and sixty collars, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, type CF or SF, (variety SW), class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a taped liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Level A unit packs shall be packed on their side one in length, eight in width, and four in depth within a shipping container. Inside dimensions of each shipping container shall be approximately 27-1/2 inches in length, 16-1/2 inches in width, and 13 inches in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to A-A-203. Each shipping container shall be closed in accordance with method II, as specified in the appendix of the container document except that the inspection shall be in accordance with 4.4.5.

5.2.2.1 Weather-resistant fiberboard container. When specified (see 6.2), the shipping container shall be grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

5.2.3 Commercial packing. Collars, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), dog collars, packed as specified in 5.2.2 and 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet pattern shall be number 1 in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course.

5.4 Marking. In addition to any special marking required by the contract or purchase order, shipping containers shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The dog collar is intended for use at dog training centers and military bases. The collar is adjustable and is equipped with a ring for attachment of a leash.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:44Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required (see 3.2, 4.3, and 6.3).
c. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
d. Type and class of unit loads required (see 5.2.1).
e. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
f. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

6.4 Standard sample. For access to samples, address the contracting activity issuing the invitation for bids.

6.5 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this document (see 3.3).

6.6 Subject term (key word) listing.

Collar
Dog, collar
Leather collar

6.7 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Air Force - 99

Review activities:

Air Force - 84
DLA - CS

User activity:

Navy - MC

Preparing activity:

Army - GL

Project No. 3770-0133

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:44Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-1161E	Collar, Dog, Leather

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 1 Apr 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:44Z
Check the source to verify that this is the current version before use.