INCH-POUND
MIL-DTL-1183/6A
w/AMENDMENT 1
20 August 2019
SUPERSEDING
MIL-DTL-1183/6A
20 December 2016

DETAIL SPECIFICATION SHEET

FITTINGS, PIPE, CAST BRONZE, SILVER-BRAZING; Y-BRANCH, PIPE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-1183.

REQUIREMENTS:

1. Y-branch type. Regular Y-branches (see figure 1), except the 8-inch Y-branch, shall be Type A (streamlined interior). The 8-inch Y-branch is Type B (interior not streamlined).

2. Reducing Y-branch type. Reducing Y-branches (see figure 2) shall be Type B (interior not streamlined).




FIGURE 1. Y-branch.




FIGURE 2. Reducing Y-branch.

3. Identification of reducing Y-branch end sizes. In identifying reducing Y-branch end sizes, the largest run size is given first, then the size at the opposite end of the run, and last is the size of the outlet. A Y-branch with reducing outlet, as shown on figure 3, is identified as a 4- by 4- by 2-inch nominal pipe size reducing Y-branch. A Y-branch with reduced run and outlet, as specified on figure 4, is identified as a 3- by 2½- by 2-inch nominal pipe size reducing Y-branch.

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:48Z
Check the source to verify that this is the current version before use.




FIGURE 3. Reduced outlet.




FIGURE 4. Reduced run and outlet.

4. Center-to-end dimensions. The center-to-end dimensions for Y-branches and reducing Y-branches shall be as specified in table I. Regular Y-branches (same size on all ends) and reducing Y-branches have the same center-to-end dimensions when the regular Y-branch size is the same size as the largest run end of the reducing Y-branch.

TABLE I. Center-to-end dimensions, inches.

Nominal pipe size	Bushed from pipe size	Center-to-end	
		A	B
¼ (all ends)		0.43	1.07
⅜ x ⅜ x ¼		0.50	1.28
⅜ (all ends)		0.50	1.28
½ x ⅜ x ⅜		0.61	1.58
½ x ½ x ¼	½ x ½ x ⅜	0.61	1.58
½ x ½ x ⅜		0.61	1.58
½ (all ends)		0.61	1.58
¾ x ½ x ½		0.72	1.90
¾ x ½ x ¾		0.72	1.90
¾ x ¾ x ¼	¾ x ¾ x ½	0.72	1.90
¾ x ¾ x ⅜	¾ x ¾ x ½	0.72	1.90
¾ x ¾ x ½		0.72	1.90
¾ (all ends)		0.72	1.90
1 x ½ x 1		0.85	2.33
1 x ¾ x ¾		0.85	2.33
1 x 1 x ½		0.85	2.33
1 x 1 x ¾	1 x 1 x 1	0.85	2.33
1 (all ends)		0.85	2.33
1¼ x 1 x 1		1.02	2.83
1¼ x 1 x 1¼		1.02	2.83
1¼ x 1¼ x ½		1.02	2.83
1¼ x 1¼ x 1		1.02	2.83
1¼ (all ends)		1.02	2.83
1½ x ¾ x 1½		1.10	3.14

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:48Z
Check the source to verify that this is the current version before use.

TABLE I. Center-to-end dimensions, inches – Continued.

Nominal pipe size	Bushed from pipe size	Center-to-end	
		A	B
1½ x 1¼ x 1¼		1.10	3.14
1½ x 1½ x ½		1.10	3.14
1½ x 1½ x ¾	1½ x 1½ x 1	1.10	3.14
1½ x 1½ x 1		1.10	3.14
1½ x 1½ x 1¼		1.10	3.14
1½ (all ends)		1.10	3.14
2 x ¾ x ¾		1.24	3.76
2 x 1 x 2		1.24	3.76
2 x 1¼ x 1¼		1.24	3.76
2 x 1½ x 1½		1.24	3.76
2 x 1½ x 2		1.24	3.76
2 x 2 x 1		1.24	3.76
2 x 2 x 1¼	2 x 2 x 1½	1.24	3.76
2 x 2 x 1½		1.24	3.76
2 (all ends)		1.24	3.76
2½ x 2 x 2		1.52	4.73
2½ x 2 x 2½		1.52	4.73
2½ x 2½ x 1		1.52	4.73
2½ x 2-½ x 2		1.52	4.73
2½ (all ends)		1.52	4.73
3 x 1 x 3		1.71	5.55
3 x 2 x 3	3 x 2½ x 3	1.71	5.55
3 x 2½ x 2	3 x 2½ x 3	1.71	5.55
3 x 2½ x 3		1.71	5.55
3 x 3 x ¾		1.71	5.55
3 x 3 x 1½		1.71	5.55
3 x 3 x 2	3 x 3 x 2½	1.71	5.55
3 x 3 x 2½		1.71	5.55
3 (all ends)		1.71	5.55
3½ x 2½ x 3		1.85	6.25
3½ x 3 x 3		1.85	6.25
3½ x 3½ x 1		1.85	6.25
3½ x 3½ x 2½		1.85	6.25
3½ (all ends)		1.85	6.25
4 x 2 x 4		2.01	6.97
4 x 3 x 4	4 x 3½ x 4	2.01	6.97
4 x 3½ x 4		2.01	6.97
4 x 4 x 1½	4 x 4 x 2	2.01	6.97

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:48Z
Check the source to verify that this is the current version before use.

TABLE I. Center-to-end dimensions, inches – Continued.

Nominal pipe size	Bushed from pipe size	Center-to-end	
		A	B
4 x 4 x 2		2.01	6.97
4 x 4 x 2½		2.01	6.97
4 x 4 x 3	4 x 4 x 3½	2.01	6.97
4 x 4 x 3½		2.01	6.97
4 (all ends)		2.01	6.97
5 x 3 x 5	5 x 4 x 5	2.34	8.43
5 x 4 x 5		2.34	8.43
5 x 5 x 1¼	5 x 5 x 2	2.34	8.43
5 x 5 x 2		2.34	8.43
5 x 5 x 3		2.34	8.43
5 x 5 x 4		2.34	8.43
5 (all ends)		2.34	8.43
6 x 6 x 4		2.66	9.81
6 (all ends)		2.66	9.81
8 x 8 x 6	8 x 8 x 8	3.31	12.75
8 (all ends)		3.31	12.75

5. Specification sheet part number. The specification sheet part number is a definitive part number that is formed by combining the specification sheet code number (M1183/6 for MIL-DTL-1183/6) with a dash after it, the Y-branch style and pipe size code number, the brazing ring groove and code letter, and an optional dash and lead-free fitting identifier. Y-branches covered by this specification sheet shall be designated in the following form (see 6.2.b of MIL-DTL-1183):

M1183/6 – XX X - PW

Specification sheet code number

Y-branch style and pipe size code number (see requirement 6 herein)

Brazing ring groove and brazing ring code letter (see requirement 7 herein)

Lead-free fitting identifier (optional) (see 3.2 of MIL-DTL-1183)

6. Y-branch style and pipe size. The Y-branch style (Y-branch or reducing Y-branch) and nominal pipe size(s) are identified by two digits (see table II).

TABLE II. Code number to style and size.

Y-branch (Type A)	Reducing Y-branch (Type B)	Nominal pipe size (inches)
01		¼ (all ends)
	21	⅜ x ⅜ x ¼
02		⅜ (all ends)
	22	½ x ⅜ x ⅜

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:48Z
Check the source to verify that this is the current version before use.

TABLE II. Code number to style and size – Continued.

Y-branch (Type A)	Reducing Y-branch (Type B)	Nominal pipe size (inches)
	23	½ x ½ x ¼
	24	½ x ½ x ⅜
03		½ (all ends)
	25	¾ x ½ x ½
	26	¾ x ½ x ¾
	27	¾ x ¾ x ¼
	28	¾ x ¾ x ⅜
	29	¾ x ¾ x ½
04		¾ (all ends)
	30	1 x ½ x 1
	31	1 x ¾ x ¾
	32	1 x 1 x ½
	33	1 x 1 x ¾
05		1 (all ends)
	34	1¼ x 1 x 1
	35	1¼ x 1 x 1¼
	36	1¼ x 1¼ x ½
	37	1¼ x 1¼ x 1
06		1¼ (all ends)
	38	1½ x ¾ x 1½
	39	1½ x 1¼ x 1¼
	40	1½ x 1½ x ½
	41	1½ x 1½ x ¾
	42	1½ x 1½ x 1
	43	1½ x 1½ x 1¼
07		1½ (all ends)
	44	2 x ¾ x ¾
	45	2 x 1 x 2
	46	2 x 1¼ x 1¼
	47	2 x 1½ x 1½
	48	2 x 1½ x 2
	49	2 x 2 x 1
	50	2 x 2 x 1¼
	51	2 x 2 x 1½
08		2 (all ends)
	52	2½ x 2 x 2
	53	2½ x 2 x 2½
	54	2½ x 2½ x 1

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:48Z
Check the source to verify that this is the current version before use.

TABLE II. Code number to style and size – Continued.

Y-branch (Type A)	Reducing Y-branch (Type B)	Nominal pipe size (inches)
	55	2½ x 2½ x 2
09		2½ (all ends)
	56	3 x 1 x 3
	57	3 x 2 x 3
	58	3 x 2½ x 2
	59	3 x 2½ x 3
	60	3 x 3 x ¾
	61	3 x 3 x 1½
	62	3 x 3 x 2
	63	3 x 3 x 2½
10		3 (all ends)
	64	3½ x 2½ x 3
	65	3½ x 3 x 3
	66	3½ x 3½ x 1
	67	3½ x 3½ x 2½
11		3½ (all ends)
	68	4 x 2 x 4
	69	4 x 3 x 4
	70	4 x 3½ x 4
	71	4 x 4 x 1½
	72	4 x 4 x 2
	73	4 x 4 x 2½
	74	4 x 4 x 3
	75	4 x 4 x 3½
12		4 (all ends)
	76	5 x 3 x 5
	77	5 x 4 x 5
	78	5 x 5 x 1¼
	79	5 x 5 x 2
	80	5 x 5 x 3
	81	5 x 5 x 4
13		5 (all ends)
	82	6 x 6 x 4
14		6 (all ends)
	83	8 x 8 x 6
[1/] 15		8 (all ends)

NOTE:

[1/] 8-inch Y-branch is Type B (interior not streamlined).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:48Z
Check the source to verify that this is the current version before use.

7. Brazing ring groove and brazing ring. Face fed (no groove), grooved without brazing ring, grooved with brazing ring inserted in groove, grooved with brazing ring(s) separately packaged and attached to the Y-branch, or grooved with brazing ring(s) separately packaged and shipped with but not attached to the Y-branch socket ends are identified by a single letter (see table III).

TABLE III. Code letter to socket condition.

Code letter	Condition of socket
N	No groove (face fed)
G 1/	Grooved (no brazing ring)
R 1/	Grooved with brazing ring inserted
A 2/	Grooved with brazing ring separately packaged and attached
S 1/ 2/	Grooved with brazing ring separately packaged and shipped with

NOTES:

1/ No National Stock Number (NSN) shall be established or exist in the Federal Supply System for Y-branch with the code letter of G, R, or S.

2/ When the socket condition code letter is A or S, the brazing rings are not to be inserted in the grooves, but packaged separately. For condition code letter A, the packaged brazing ring shall be either included within each individual Y-branch package or physically attached to the Y-branch. For condition code letter S, the brazing ring shall be included within each individual Y-branch package.

AMENDMENT NOTATIONS. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

CONCLUDING MATERIAL

Custodians:
Army – CR4
Navy – SH

Preparing activity:
Navy – SH
(Project 4730-2019-026)

Review activity:
DLA – CC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:48Z
Check the source to verify that this is the current version before use.